


## .150 Grid-space Relays Type 3SBH (4PDT)

### Product Facts

- Low profile... only 0.32 inches high
- Long life version available
- Qualified to MIL-R-39016/14



This .150 four pole double throw Grid-space relay is the companion to the two pole 3SBC type shown on page 1-41. It also features the same .150 inch pin spacing that allows you to insert the relay with no intermediate pin spreaders. There is adequate clearance for conductors to reach all pins. It is a very compact 4 pole double throw 2 ampere relay.

### Electrical Characteristics

#### Contact Ratings

DC resistive — 2 amps at 28 volts  
DC inductive — 0.5 amps at 28 volts, 200 mH  
AC resistive — 0.5 amps at 115 volts, 400 or 60 Hz (enclosure isolated from ground, or enclosure and movable contact at same potential)  
AC — 0.125 amps at 115 volts (enclosure at line potential with respect to movable contact)  
Low-level — low-level operation at 50 millivolts, 30 µA, 33 ohm miss level

#### Contact Resistance

0.050 ohms max.;  
0.150 ohms after life test

#### Life

100,000 operations at rated loads listed;  
1,000,000 operations at low-level loads

### Operating Characteristics

**Operate Time** — 4 ms max.

**Release Time** — 4 ms max.

**Contact Bounce** — 1.5 ms

#### Dielectric Strength

500 volts rms at sea level;  
350 volts rms at 70,000 feet

#### Insulation Resistance

1,000 megohms min. over temperature range

### Environmental Characteristics

**Vibration** — 30 G, to 3,000 Hz

**Shock** — 100 G at 11 ms

**Temperature** — -65°C to +125°C

See page 1-57 for Mounting Forms, Terminals and Circuit Diagrams.

## Coil Table (All Values DC)\* Type 3SBH, 4 Pole Relay—250 mW Sensitivity: (Code 1)

Coil Code Letter	Coil Resistance at 25°C ohms	SENSITIVITY CODE: 1			
		Voltage Calibrated, Code: 5			
		Suggested Source Volts†	Maximum Operate Volts at 25°C	Release Voltage Range at 25°C	
				Max.	Min.
B	28 ± 10%	4.0 - 7.0	2.7	1.6	0.3
D	73 ± 10%	6.0 - 11.0	4.2	2.5	0.4
E	115 ± 10%	8.0 - 14.0	5.4	3.2	0.6
G	280 ± 10%	12 - 22.0	8.4	5.0	0.8
H	430 ± 10%	15 - 26.0	10.3	6.0	1.0
K	720 ± 10%	20 - 35.0	13.5	8.1	1.5
N	1040 ± 10%	26 - 46.0	17.5	10.5	1.9


\*Values listed are factory test and inspection values. User should allow for meter variations.

†Applicable over the operating temperature range in circulating air.

### Ordering Instructions

**Catalog-selected Relays:** The catalog number is derived by choosing the proper CODE for each of the six relay characteristics in the order in which the codes are listed.

**Example:** The relay selected in this example is a 4PDT .150-grid relay, voltage calibrated, end bracket mounting, 0.13 inch solder hook header, 720 ohms coil resistance, and 250 mW sensitivity. By choosing the proper code for each of these relay characteristics, the catalog number is identified as 3SBH5131K1. The letter R following sensitivity code indicates relay received 5000 operation miss-test. Ex. 3SBH5131K1R.




\* The part number example shown on this page is for catalog items. For a list of specific QPL part numbers, please see the index in Section 15.

## Four Pole, Electrically Held, 2 Amps and Less (Continued)

### .150 Grid-space Hybrid Relays Type 3SBH (4PDT)

#### Product Facts

- Low profile... only 0.32 inches high
- Long life version available
- Qualified to MIL-R-39016/53 & 54



The 4PDT .150 Grid-space hybrid relays are advanced designs of the standard high reliability 4PDT .150 Grid-space relays. In the single diode version, the relay coil-back electromotive force is suppressed to prevent circuit/component damage. With the dual diode version, a steering diode is added to the coil circuit, along with the suppression diode. This

steering diode prevents operation of the relay by reverse polarity voltages and protects the suppression diode. The single diode version is qualified to MIL-R-39016/53 and the dual diode is qualified to MIL-R-39016/54.

#### Electrical Characteristics

- Contact Ratings** —  
 DC resistive — 2 amps at 28 volts  
 DC inductive — 0.5 amps at 28 volts, 200 mH  
 AC resistive — 0.5 amps at 115 volts, 400 or 60 Hz (enclosure isolated from ground, or enclosure and movable contact at same potential)  
 AC — 0.125 amps at 115 volts (enclosure at line potential with respect to movable contact)  
 Low-level — 50 µA at 50mV
- Contact Resistance** —  
 0.050 ohms max.;  
 0.150 ohms after life test
- Life** — 100,000 operations at rated loads listed; 1,000,000 operations at low-level loads

#### Operating Characteristics

**Operate Time** — 4 ms max.

**Release Time** — 6 ms max.

**Contact Bounce** — 2.0 ms

#### Dielectric Strength (Note 1)

500 volts rms at sea level;

350 volts rms at 70,000 feet

#### Insulation Resistance (Note 1)

1,000 megohms min. over temperature range

#### Semiconductor Characteristics at 25°C

- Max. Negative Transient** — 1 volt  
**Breakdown Voltage** —  
 100 Vdc @ 10 µA min.  
**Max. Leakage Current** —  
 1 µA @ 50 Vdc

**Note 1:** Tests for dielectric withstanding voltage and insulation resistance should be made with "coil terminals" shorted together to avoid unnecessary electrical stress to semiconductor elements.

See page 1-57 for Mounting Forms, Terminals and Circuit Diagrams.

#### Coil Table (All Values DC)\* Type 3SBH, 4 Pole Relay — 250 mW Sensitivity: (Code 5 single diode, Code 6 dual diodes)

Single Diode		SENSITIVITY CODE: 5			
Coil Code Letter	Coil Resistance at 25C ohms	Suggested Source Volts†	Maximum Operate Volts at 25C	Voltage Calibrated, Code: 5	
				Max.	Min.
B	28 ± 10%	4.0- 7.0	2.7	1.6	0.3
D	73 ± 10%	6.0-11.0	4.2	2.5	0.4
E	115 ± 10%	8.0-14.0	5.4	3.2	0.6
G	280 ± 10%	12 -22.0	8.4	5.0	0.8
H	430 ± 10%	15 -26.0	10.3	6.0	1.0
K	720 ± 10%	20 -35.0	13.5	8.1	1.5
N	1040 ± 10%	26 -46.0	17.5	10.5	1.9
Dual Diode		SENSITIVITY CODE: 6			
B	28 ± 10%	4.0- 7.0	3.7	2.3	0.5
D	73 ± 10%	6.0-11.0	5.2	3.2	0.6
E	115 ± 10%	8.0-14.0	6.4	3.9	0.8
G	280 ± 10%	12.0-22.0	9.4	5.7	1.0
H	430 ± 10%	15 -26.0	11.3	6.7	1.2
K	720 ± 10%	20 -35.0	14.5	8.8	1.7
N	1040 ± 10%	26 -46.0	18.1	11.1	2.1

\*Values listed are factory test and inspection values. User should allow for meter variations.

†Applicable over the operating temperature range in circulating air.

**Mounting Forms (3SBH)**

(Vibration note with each form is acceleration from 55 to 3000 Hz)


**Header Types**

Type	Z Dimension	Header Code
Solder hook	0.13	1
Straight pin	0.12	8
Straight pin socket or PCB type)	0.19	4
Straight pin	0.25	5

**No Mount**


Mounting Code	Vibration*
00	30g

\*Assumes relay held securely by potting or other means.







**CODE: 1**

**CODES: 4, 5, 8**
**End Bracket**

Mounting Code	Vibration
13	30g


**All dimensions in inches**

TOLERANCES (Unless otherwise specified)	
Hundredths	±0.020
Thousands	±0.005


**Header and Connection Diagrams**
**CODE 1**
**4-Pole Terminal View**

**CODE 5**

**CODE 6**

**CODE 1**

**CODE 5 & 6**


Terminals .020 dia

**Ordering Instructions**

**Catalog-selected Relays:** The catalog number is derived by choosing the proper CODE for each of the six relay characteristics in the order in which the codes are listed.

**Example:** The relay selected in this example is a 4PDT .150-grid relay, voltage calibrated, end bracket mounting, 0.13 inch solder hook header, 720 ohms coil resistance, and 250 mW sensitivity. By choosing the proper code for each of these relay characteristics, the catalog number is identified as 3SBH5131K5. The letter R following sensitivity code indicates relay received 5000 operation miss-test. Ex. 3SBH5131K5R.



\* The part number example shown on this page is for catalog items. For a list of specific QPL part numbers, please see the index in Section 15.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

#### Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: [org@eplast1.ru](mailto:org@eplast1.ru)

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.