




Technical Data:
M12 TO RJ45 CAT6_A Cordset AWG26
straight blue inline 360° shielded.


Poles: 8
Max. Voltage: 48V
Max Current: 0,5A
Contact resistance: <5m Ohm
Insulation withstand: >100M Ohm
Protection M12 / RJ45: IP67 / IP20
Temperature range: -40°C to 70°C
Transmission characteristics (category): CAT6_A

Low-Halogen-Status according to IEC 60754-1/-2

Product Specification see: PS-120341-140

Packaging:
The cordsets delivered packed into Carton.


Connector pin assignment
Plug RJ45
DETAIL-2
SCALE 4:1



Wiring Scheme RJ45

- 1 white-orange
- 2 orange
- 3 white-green
- 4 blue
- 5 white-blue
- 6 green
- 7 white-brown
- 8 brown

Connector pin assignment
Plug M12
pin side view
DETAIL-1
SCALE 4:1





Wiring Scheme M12

- 1 white-orange
- 2 orange
- 3 white-green
- 4 green
- 5 white-brown
- 6 brown
- 7 white-blue
- 8 blue

Material Number	Length L [m]
1203410500	0,5
1203410501	1
1203410502	2
1203410503	3
1203410504	4
1203410505	5
1203410506	10
1203410507	15
1203410508	20
1203410509	30
1203410510	40
1203410511	23

POS	DESCRIPTION	MATERIAL	FINISH
01	COUPLING NUT	BRASS	NICKEL PLATED
02	INSERT	PA	BLACK
03	CONTACT	BRASS	GOLD OVER NICKEL
04	SHIELDING CROSS	ZINC DIE-CAST	NICKEL PLATED
05	SHIELDING SHELL	ZINC DIE-CAST	NICKEL PLATED
06	FERRULE	BRASS	NICKEL PLATED
07	TAPE	PA	AMBER
08	OVERMOULD	PUR	BLACK
09	CABLE	PUR	BLUE
10	PLUG RJ45	NA	BLACK



ENTER DESCRIPTION EC NO: IPG2015-0518 DRAWN: ZISMAYILOV 2014/09/29 CHKD: RSCHIEBER 2014/09/30 APPR: CUBIGER 2014/10/01			QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 1:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION ⊙ □							
				mm	INCH	DRAWN BY ZISMAYILOV	DATE 2011/11/15	TITLE CSE M12 CAT6A RJ45 8P XC MA STR PUR XM SHLD BU									
DESCRIPTION	4 PLACES	± ---	± ---	CHECKED BY RSCHIEBER	DATE 2012/06/12	DOCUMENT NO. SD-120341-140											
	3 PLACES	± ---	± ---	APPROVED BY AVOGT	DATE 2012/06/12					SHEET NO. 1 OF 1							
	2 PLACES	± 0.05	± ---	SEE TABLE										THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
	1 PLACE	± 0.30	± ---														
0 PLACE	± 0.50	± ---															
REV	ANGULAR ± 1 °		DRAFT WHERE APPLICABLE		SIZE A2												
			MUST REMAIN WITHIN DIMENSIONS														



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.