

# ALUMINUM ELECTROLYTIC CAPACITORS



**GU** series Snap-in Terminal Type, 105°C Standard



- Withstanding 3000 hours application of rated ripple current at 105°C.
- Compliant to the RoHS directive (2002/95/EC).




## Specifications

| Item                          | Performance Characteristics                                                                                                                                                                                                 |                                               |            |            |            |            |                |                    |             |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|------------|------------|------------|------------|----------------|--------------------|-------------|
| Category Temperature Range    | - 40 to + 105°C (16 to 250V) , - 25 to +105°C (315 to 450V)                                                                                                                                                                 |                                               |            |            |            |            |                |                    |             |
| Rated Voltage Range           | 16 to 450V                                                                                                                                                                                                                  |                                               |            |            |            |            |                |                    |             |
| Rated Capacitance Range       | 47 to 47000μF                                                                                                                                                                                                               |                                               |            |            |            |            |                |                    |             |
| Capacitance Tolerance         | ±20% at 120Hz, 20°C                                                                                                                                                                                                         |                                               |            |            |            |            |                |                    |             |
| Leakage Current               | $I \leq 3\sqrt{CV}(\mu A)$ (After 5 minutes' application of rated voltage) [C : Rated Capacitance (μF) V : Voltage (V)]                                                                                                     |                                               |            |            |            |            |                |                    |             |
| Tangent of loss angle (tan δ) | Measurement frequency : 120Hz at 20°C                                                                                                                                                                                       |                                               |            |            |            |            |                |                    |             |
|                               | Rated voltage(V)<br>tan δ (MAX.)                                                                                                                                                                                            | 16<br>0.50                                    | 25<br>0.40 | 35<br>0.35 | 50<br>0.30 | 63<br>0.25 | 80·100<br>0.20 | 160 to 420<br>0.15 | 450<br>0.20 |
| Stability at Low Temperature  | Measurement frequency : 120Hz                                                                                                                                                                                               |                                               |            |            |            |            |                |                    |             |
|                               | Rated voltage (V)                                                                                                                                                                                                           |                                               |            | 16 to 100  | 160 to 250 | 315 to 450 |                |                    |             |
|                               | Impedance ratio<br>ZT/Z20 (MAX.)                                                                                                                                                                                            | Z - 25°C/Z+20°C                               |            | 4          | 3          | 8          |                |                    |             |
| Endurance                     | The specifications listed at right shall be met when the capacitors are restored to 20°C after D.C. bias plus rated ripple current is applied for 3000 hours at 105°C, the peak voltage shall not exceed the rated voltage. |                                               |            |            |            |            |                |                    |             |
|                               | Capacitance change                                                                                                                                                                                                          | Within ±20% of the initial capacitance value  |            |            |            |            |                |                    |             |
|                               | tan δ                                                                                                                                                                                                                       | 200% or less than the initial specified value |            |            |            |            |                |                    |             |
| Shelf Life                    | After storing the capacitors under no load at 105°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the characteristic requirements listed at right.         |                                               |            |            |            |            |                |                    |             |
|                               | Capacitance change                                                                                                                                                                                                          | Within ±15% of the initial capacitance value  |            |            |            |            |                |                    |             |
|                               | tan δ                                                                                                                                                                                                                       | 150% or less than the initial specified value |            |            |            |            |                |                    |             |
| Leakage current               | Less than or equal to the initial specified value                                                                                                                                                                           |                                               |            |            |            |            |                |                    |             |
| Marking                       | Printed with white color letter on black sleeve.                                                                                                                                                                            |                                               |            |            |            |            |                |                    |             |

## Drawing



## Type numbering system (Example : 200V 680μF)



## Frequency coefficient of rated ripple current

| Coeff.      | Frequency (Hz) | 50   | 60   | 120  | 300  | 1k   | 10k  | 50k or more |
|-------------|----------------|------|------|------|------|------|------|-------------|
|             | 16 to 100V     | 0.88 | 0.90 | 1.00 | 1.07 | 1.15 | 1.15 | 1.15        |
| 160 to 250V | 0.81           | 0.85 | 1.00 | 1.17 | 1.32 | 1.45 | 1.50 |             |
| 315 to 450V | 0.77           | 0.82 | 1.00 | 1.16 | 1.30 | 1.41 | 1.43 |             |

Minimum order quantity : 50pcs.

● Dimension table in next page.

## ■Dimensions

| 16V (1C)  |               |                   |                      |              |
|-----------|---------------|-------------------|----------------------|--------------|
| Cap. (μF) | Size φD×L(mm) | Rated ripple (mA) | Leakage Current (mA) | Code         |
| 6800      | 22 × 25       | 1750              | 0.98                 | LGU1C682MELZ |
| 8200      | 22 × 30       | 2000              | 1.08                 | LGU1C822MELZ |
| 10000     | 22 × 30       | 2100              | 1.20                 | LGU1C103MELZ |
|           | 25 × 25       | 2050              | 1.20                 | LGU1C103MELA |
| 12000     | 22 × 35       | 2310              | 1.31                 | LGU1C123MELZ |
|           | 25 × 30       | 2300              | 1.31                 | LGU1C123MELA |
|           | 30 × 25       | 2380              | 1.31                 | LGU1C123MELB |
| 15000     | 22 × 40       | 2680              | 1.46                 | LGU1C153MELZ |
|           | 25 × 35       | 2680              | 1.46                 | LGU1C153MELA |
|           | 30 × 30       | 2570              | 1.46                 | LGU1C153MELB |
| 18000     | 22 × 45       | 2980              | 1.60                 | LGU1C183MELZ |
|           | 25 × 40       | 3160              | 1.60                 | LGU1C183MELA |
|           | 30 × 30       | 3000              | 1.60                 | LGU1C183MELB |
| 22000     | 25 × 45       | 3400              | 1.77                 | LGU1C223MELA |
|           | 30 × 35       | 3390              | 1.77                 | LGU1C223MELB |
|           | 35 × 30       | 3250              | 1.77                 | LGU1C223MELC |
| 27000     | 25 × 50       | 3850              | 1.97                 | LGU1C273MELA |
|           | 30 × 40       | 3830              | 1.97                 | LGU1C273MELB |
|           | 35 × 30       | 3740              | 1.97                 | LGU1C273MELC |
| 33000     | 30 × 45       | 4300              | 2.17                 | LGU1C333MELB |
|           | 35 × 35       | 4270              | 2.17                 | LGU1C333MELC |
| 39000     | 30 × 50       | 4810              | 2.36                 | LGU1C393MELB |
|           | 35 × 40       | 4800              | 2.36                 | LGU1C393MELC |
| 47000     | 35 × 45       | 5530              | 2.60                 | LGU1C473MELC |

| 25V (1E)  |               |                   |                      |              |
|-----------|---------------|-------------------|----------------------|--------------|
| Cap. (μF) | Size φD×L(mm) | Rated ripple (mA) | Leakage Current (mA) | Code         |
| 4700      | 22 × 25       | 1610              | 1.02                 | LGU1E472MELZ |
| 5600      | 22 × 30       | 1800              | 1.12                 | LGU1E562MELZ |
| 6800      | 22 × 30       | 1910              | 1.23                 | LGU1E682MELZ |
|           | 25 × 25       | 1910              | 1.23                 | LGU1E682MELA |
| 8200      | 22 × 35       | 2140              | 1.35                 | LGU1E822MELZ |
|           | 25 × 30       | 2340              | 1.35                 | LGU1E822MELA |
|           | 30 × 25       | 2250              | 1.35                 | LGU1E822MELB |
| 10000     | 22 × 40       | 2650              | 1.50                 | LGU1E103MELZ |
|           | 25 × 35       | 2610              | 1.50                 | LGU1E103MELA |
|           | 30 × 30       | 2610              | 1.50                 | LGU1E103MELB |
| 12000     | 22 × 45       | 2690              | 1.64                 | LGU1E123MELZ |
|           | 25 × 40       | 2810              | 1.64                 | LGU1E123MELA |
|           | 30 × 30       | 2740              | 1.64                 | LGU1E123MELB |
| 15000     | 25 × 45       | 3270              | 1.83                 | LGU1E153MELA |
|           | 30 × 35       | 3130              | 1.83                 | LGU1E153MELB |
|           | 35 × 30       | 3260              | 1.83                 | LGU1E153MELC |
| 18000     | 25 × 50       | 3540              | 2.01                 | LGU1E183MELA |
|           | 30 × 40       | 3560              | 2.01                 | LGU1E183MELB |
|           | 35 × 35       | 3840              | 2.01                 | LGU1E183MELC |
| 22000     | 30 × 45       | 4240              | 2.22                 | LGU1E223MELB |
|           | 35 × 35       | 3960              | 2.22                 | LGU1E223MELC |
| 27000     | 35 × 45       | 4750              | 2.46                 | LGU1E273MELC |
| 33000     | 35 × 50       | 5500              | 2.72                 | LGU1E333MELC |

| 35V (1V)  |               |                   |                      |              |
|-----------|---------------|-------------------|----------------------|--------------|
| Cap. (μF) | Size φD×L(mm) | Rated ripple (mA) | Leakage Current (mA) | Code         |
| 3300      | 22 × 25       | 1450              | 1.01                 | LGU1V332MELZ |
| 3900      | 22 × 30       | 1690              | 1.10                 | LGU1V392MELZ |
| 4700      | 22 × 35       | 2020              | 1.21                 | LGU1V472MELZ |
|           | 25 × 25       | 1780              | 1.21                 | LGU1V472MELA |
| 5600      | 22 × 35       | 2130              | 1.32                 | LGU1V562MELZ |
|           | 25 × 30       | 2040              | 1.32                 | LGU1V562MELA |
|           | 30 × 25       | 2120              | 1.32                 | LGU1V562MELB |
| 6800      | 22 × 40       | 2410              | 1.46                 | LGU1V682MELZ |
|           | 25 × 35       | 2310              | 1.46                 | LGU1V682MELA |
|           | 30 × 25       | 2310              | 1.46                 | LGU1V682MELB |
| 8200      | 22 × 50       | 2850              | 1.60                 | LGU1V822MELZ |
|           | 25 × 40       | 2730              | 1.60                 | LGU1V822MELA |
|           | 30 × 30       | 2750              | 1.60                 | LGU1V822MELB |
| 10000     | 25 × 45       | 3050              | 1.77                 | LGU1V103MELA |
|           | 30 × 35       | 3050              | 1.77                 | LGU1V103MELB |
|           | 25 × 50       | 3370              | 1.94                 | LGU1V123MELA |
| 12000     | 30 × 40       | 3280              | 1.94                 | LGU1V123MELB |
|           | 35 × 30       | 3200              | 1.94                 | LGU1V123MELC |
|           | 15000         | 30 × 45           | 3740                 | 2.17         |
| 35 × 35   |               | 3690              | 2.17                 | LGU1V153MELC |
| 18000     | 35 × 40       | 4370              | 2.38                 | LGU1V183MELC |
| 22000     | 35 × 50       | 4920              | 2.63                 | LGU1V223MELC |

| 50V (1H)  |               |                   |                      |              |
|-----------|---------------|-------------------|----------------------|--------------|
| Cap. (μF) | Size φD×L(mm) | Rated ripple (mA) | Leakage Current (mA) | Code         |
| 1800      | 22 × 25       | 1340              | 0.90                 | LGU1H182MELZ |
|           | 22 × 30       | 1700              | 1.10                 | LGU1H272MELZ |
| 2700      | 25 × 25       | 1700              | 1.10                 | LGU1H272MELA |
|           | 22 × 35       | 1980              | 1.21                 | LGU1H332MELZ |
| 3300      | 25 × 30       | 2000              | 1.21                 | LGU1H332MELA |
|           | 22 × 40       | 2250              | 1.32                 | LGU1H392MELZ |
| 3900      | 25 × 30       | 2280              | 1.32                 | LGU1H392MELA |
|           | 30 × 25       | 2220              | 1.32                 | LGU1H392MELB |
|           | 22 × 45       | 2560              | 1.45                 | LGU1H472MELZ |
| 4700      | 25 × 35       | 2610              | 1.45                 | LGU1H472MELA |
|           | 30 × 30       | 2580              | 1.45                 | LGU1H472MELB |
|           | 22 × 50       | 2890              | 1.58                 | LGU1H562MELZ |
| 5600      | 25 × 40       | 2810              | 1.58                 | LGU1H562MELA |
|           | 30 × 30       | 2950              | 1.58                 | LGU1H562MELB |
|           | 25 × 45       | 3370              | 1.74                 | LGU1H682MELA |
| 6800      | 30 × 35       | 3390              | 1.74                 | LGU1H682MELB |
|           | 35 × 30       | 3310              | 1.74                 | LGU1H682MELC |
|           | 30 × 40       | 3710              | 1.92                 | LGU1H822MELB |
| 8200      | 35 × 35       | 3660              | 1.92                 | LGU1H822MELC |
|           | 30 × 50       | 4090              | 2.12                 | LGU1H103MELB |
| 10000     | 35 × 40       | 4070              | 2.12                 | LGU1H103MELC |
|           | 35 × 45       | 4560              | 2.32                 | LGU1H123MELC |
| 15000     | 35 × 50       | 4770              | 2.59                 | LGU1H153MELC |

Rated ripple current (mArms) at 105°C 120Hz



## ■ Dimensions

| 63V (1J)  |                |                   |                      |              |
|-----------|----------------|-------------------|----------------------|--------------|
| Cap. (μF) | Size φD×L (mm) | Rated ripple (mA) | Leakage Current (mA) | Code         |
| 1200      | 22 × 25        | 1250              | 0.82                 | LGU1J122MELZ |
|           | 22 × 30        | 1470              | 0.92                 | LGU1J152MELZ |
| 1500      | 25 × 25        | 1440              | 0.92                 | LGU1J152MELA |
|           | 22 × 30        | 1580              | 1.01                 | LGU1J182MELZ |
| 1800      | 25 × 25        | 1520              | 1.01                 | LGU1J182MELA |
|           | 22 × 35        | 1820              | 1.11                 | LGU1J222MELZ |
| 2200      | 25 × 30        | 1750              | 1.11                 | LGU1J222MELA |
|           | 22 × 40        | 2070              | 1.23                 | LGU1J272MELZ |
| 2700      | 25 × 35        | 2110              | 1.23                 | LGU1J272MELA |
|           | 30 × 25        | 1930              | 1.23                 | LGU1J272MELB |
|           | 22 × 45        | 2330              | 1.36                 | LGU1J332MELZ |
| 3300      | 25 × 35        | 2270              | 1.36                 | LGU1J332MELA |
|           | 30 × 30        | 2240              | 1.36                 | LGU1J332MELB |
|           | 25 × 40        | 2540              | 1.48                 | LGU1J392MELA |
| 3900      | 30 × 35        | 2550              | 1.48                 | LGU1J392MELB |
|           | 25 × 50        | 2970              | 1.63                 | LGU1J472MELA |
| 4700      | 30 × 40        | 2900              | 1.63                 | LGU1J472MELB |
|           | 35 × 30        | 2830              | 1.63                 | LGU1J472MELC |
| 5600      | 30 × 40        | 3280              | 1.78                 | LGU1J562MELB |
|           | 35 × 35        | 3240              | 1.78                 | LGU1J562MELC |
| 6800      | 30 × 50        | 3730              | 1.96                 | LGU1J682MELB |
|           | 35 × 40        | 3710              | 1.96                 | LGU1J682MELC |
| 8200      | 35 × 45        | 4160              | 2.15                 | LGU1J822MELC |
| 10000     | 35 × 50        | 4690              | 2.38                 | LGU1J103MELC |

| 80V (1K)  |                |                   |                      |              |
|-----------|----------------|-------------------|----------------------|--------------|
| Cap. (μF) | Size φD×L (mm) | Rated ripple (mA) | Leakage Current (mA) | Code         |
| 820       | 22 × 25        | 1110              | 0.76                 | LGU1K821MELZ |
| 1000      | 22 × 25        | 1290              | 0.84                 | LGU1K102MELZ |
| 1200      | 22 × 30        | 1440              | 0.92                 | LGU1K122MELZ |
|           | 25 × 25        | 1390              | 0.92                 | LGU1K122MELA |
| 1500      | 22 × 30        | 1610              | 1.03                 | LGU1K152MELZ |
|           | 25 × 25        | 1620              | 1.03                 | LGU1K152MELA |
| 1800      | 22 × 35        | 1830              | 1.13                 | LGU1K182MELZ |
|           | 25 × 30        | 1860              | 1.13                 | LGU1K182MELA |
|           | 30 × 25        | 1810              | 1.13                 | LGU1K182MELB |
| 2200      | 22 × 40        | 2090              | 1.25                 | LGU1K222MELZ |
|           | 25 × 35        | 2010              | 1.25                 | LGU1K222MELA |
|           | 30 × 25        | 2100              | 1.25                 | LGU1K222MELB |
| 2700      | 25 × 40        | 2430              | 1.39                 | LGU1K272MELA |
|           | 30 × 30        | 2430              | 1.39                 | LGU1K272MELB |
| 3300      | 25 × 45        | 2760              | 1.54                 | LGU1K332MELA |
|           | 30 × 35        | 2780              | 1.54                 | LGU1K332MELB |
|           | 35 × 30        | 2710              | 1.54                 | LGU1K332MELC |
| 3900      | 25 × 50        | 2920              | 1.67                 | LGU1K392MELA |
|           | 30 × 40        | 3120              | 1.67                 | LGU1K392MELB |
|           | 35 × 30        | 3070              | 1.67                 | LGU1K392MELC |
| 4700      | 30 × 45        | 3520              | 1.83                 | LGU1K472MELB |
|           | 35 × 35        | 3500              | 1.83                 | LGU1K472MELC |
| 5600      | 30 × 50        | 3800              | 2.00                 | LGU1K562MELB |
|           | 35 × 40        | 3870              | 2.00                 | LGU1K562MELC |
| 6800      | 35 × 45        | 4190              | 2.21                 | LGU1K682MELC |

| 100V (2A) |                |                   |                      |              |
|-----------|----------------|-------------------|----------------------|--------------|
| Cap. (μF) | Size φD×L (mm) | Rated ripple (mA) | Leakage Current (mA) | Code         |
| 560       | 22 × 25        | 1070              | 0.70                 | LGU2A561MELZ |
| 820       | 22 × 30        | 1350              | 0.85                 | LGU2A821MELZ |
|           | 25 × 25        | 1350              | 0.85                 | LGU2A821MELA |
| 1000      | 22 × 30        | 1540              | 0.94                 | LGU2A102MELZ |
|           | 25 × 30        | 1560              | 0.94                 | LGU2A102MELA |
| 1200      | 22 × 40        | 1740              | 1.03                 | LGU2A122MELZ |
|           | 25 × 30        | 1760              | 1.03                 | LGU2A122MELA |
|           | 30 × 25        | 1710              | 1.03                 | LGU2A122MELB |
| 1500      | 22 × 45        | 1990              | 1.16                 | LGU2A152MELZ |
|           | 25 × 35        | 2030              | 1.16                 | LGU2A152MELA |
|           | 30 × 30        | 2000              | 1.16                 | LGU2A152MELB |
| 1800      | 25 × 40        | 2280              | 1.27                 | LGU2A182MELA |
|           | 30 × 35        | 2270              | 1.27                 | LGU2A182MELB |
| 2200      | 25 × 50        | 2570              | 1.40                 | LGU2A222MELA |
|           | 30 × 35        | 2590              | 1.40                 | LGU2A222MELB |
|           | 35 × 30        | 2520              | 1.40                 | LGU2A222MELC |
| 2700      | 30 × 45        | 2940              | 1.55                 | LGU2A272MELB |
|           | 35 × 35        | 2900              | 1.55                 | LGU2A272MELC |
| 3300      | 30 × 50        | 3320              | 1.72                 | LGU2A332MELB |
|           | 35 × 40        | 3310              | 1.72                 | LGU2A332MELC |
| 3900      | 35 × 45        | 3690              | 1.87                 | LGU2A392MELC |
| 4700      | 35 × 50        | 4140              | 2.05                 | LGU2A472MELC |

| 160V (2C) |                |                   |                      |              |
|-----------|----------------|-------------------|----------------------|--------------|
| Cap. (μF) | Size φD×L (mm) | Rated ripple (mA) | Leakage Current (mA) | Code         |
| 270       | 20 × 25        | 1100              | 0.62                 | LGU2C271MELY |
| 330       | 20 × 30        | 1200              | 0.68                 | LGU2C331MELY |
| 390       | 20 × 30        | 1300              | 0.74                 | LGU2C391MELY |
|           | 22 × 25        | 1300              | 0.74                 | LGU2C391MELZ |
| 470       | 20 × 35        | 1340              | 0.82                 | LGU2C471MELY |
|           | 22 × 30        | 1550              | 0.82                 | LGU2C471MELZ |
|           | 25 × 25        | 1550              | 0.82                 | LGU2C471MELA |
| 560       | 20 × 40        | 1500              | 0.89                 | LGU2C561MELY |
|           | 22 × 35        | 1670              | 0.89                 | LGU2C561MELZ |
|           | 25 × 30        | 1670              | 0.89                 | LGU2C561MELA |
|           | 30 × 25        | 1670              | 0.89                 | LGU2C561MELB |
| 680       | 20 × 45        | 1700              | 0.98                 | LGU2C681MELY |
|           | 22 × 40        | 1820              | 0.98                 | LGU2C681MELZ |
|           | 25 × 30        | 1820              | 0.98                 | LGU2C681MELA |
| 820       | 30 × 25        | 1820              | 0.98                 | LGU2C681MELB |
|           | 22 × 45        | 2040              | 1.08                 | LGU2C821MELZ |
|           | 25 × 35        | 2040              | 1.08                 | LGU2C821MELA |
| 1000      | 30 × 30        | 2040              | 1.08                 | LGU2C821MELB |
|           | 35 × 25        | 2040              | 1.08                 | LGU2C821MELC |
|           | 22 × 50        | 2250              | 1.20                 | LGU2C102MELZ |
|           | 25 × 40        | 2250              | 1.20                 | LGU2C102MELA |
| 1200      | 30 × 30        | 2250              | 1.20                 | LGU2C102MELB |
|           | 35 × 25        | 2250              | 1.20                 | LGU2C102MELC |
|           | 25 × 45        | 2490              | 1.31                 | LGU2C122MELA |
| 1500      | 30 × 35        | 2490              | 1.31                 | LGU2C122MELB |
|           | 35 × 30        | 2490              | 1.31                 | LGU2C122MELC |
| 1800      | 30 × 40        | 2840              | 1.46                 | LGU2C152MELB |
|           | 35 × 30        | 2840              | 1.46                 | LGU2C152MELC |
| 2200      | 30 × 45        | 3320              | 1.60                 | LGU2C182MELB |
|           | 35 × 35        | 3000              | 1.60                 | LGU2C182MELC |
| 2700      | 35 × 45        | 3500              | 1.77                 | LGU2C222MELC |
| 3300      | 35 × 50        | 4000              | 1.97                 | LGU2C272MELC |

Rated ripple current (mA<sub>rms</sub>) at 105°C 120Hz



## ■Dimensions

| 180V (2Z) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 220       | 20 × 25          | 1000                 | 0.59                    | LGU2Z221MELY |
| 270       | 20 × 30          | 1100                 | 0.66                    | LGU2Z271MELY |
| 330       | 20 × 30          | 1200                 | 0.73                    | LGU2Z331MELY |
|           | 22 × 25          | 1200                 | 0.73                    | LGU2Z331MELZ |
| 390       | 20 × 35          | 1300                 | 0.79                    | LGU2Z391MELY |
|           | 22 × 30          | 1350                 | 0.79                    | LGU2Z391MELZ |
|           | 25 × 25          | 1350                 | 0.79                    | LGU2Z391MELA |
| 470       | 20 × 40          | 1400                 | 0.87                    | LGU2Z471MELY |
|           | 22 × 35          | 1500                 | 0.87                    | LGU2Z471MELZ |
|           | 25 × 30          | 1500                 | 0.87                    | LGU2Z471MELA |
| 560       | 30 × 25          | 1500                 | 0.87                    | LGU2Z471MELB |
|           | 20 × 45          | 1550                 | 0.95                    | LGU2Z561MELY |
|           | 22 × 40          | 1670                 | 0.95                    | LGU2Z561MELZ |
|           | 25 × 30          | 1670                 | 0.95                    | LGU2Z561MELA |
| 680       | 30 × 25          | 1670                 | 0.95                    | LGU2Z561MELB |
|           | 22 × 45          | 1780                 | 1.04                    | LGU2Z681MELZ |
|           | 25 × 35          | 1780                 | 1.04                    | LGU2Z681MELA |
|           | 30 × 30          | 1780                 | 1.04                    | LGU2Z681MELB |
| 820       | 35 × 25          | 1780                 | 1.04                    | LGU2Z681MELC |
|           | 22 × 50          | 2040                 | 1.15                    | LGU2Z821MELZ |
|           | 25 × 40          | 2040                 | 1.15                    | LGU2Z821MELA |
|           | 30 × 30          | 2040                 | 1.15                    | LGU2Z821MELB |
| 1000      | 35 × 25          | 2040                 | 1.15                    | LGU2Z821MELC |
|           | 25 × 45          | 2300                 | 1.27                    | LGU2Z102MELA |
|           | 30 × 35          | 2300                 | 1.27                    | LGU2Z102MELB |
|           | 35 × 30          | 2300                 | 1.27                    | LGU2Z102MELC |
| 1200      | 25 × 50          | 2550                 | 1.39                    | LGU2Z122MELA |
|           | 30 × 40          | 2550                 | 1.39                    | LGU2Z122MELB |
|           | 35 × 30          | 2550                 | 1.39                    | LGU2Z122MELC |
| 1500      | 30 × 45          | 2900                 | 1.55                    | LGU2Z152MELB |
|           | 35 × 35          | 2900                 | 1.55                    | LGU2Z152MELC |
| 1800      | 35 × 45          | 3300                 | 1.70                    | LGU2Z182MELC |
| 2200      | 35 × 50          | 3650                 | 1.88                    | LGU2Z222MELC |

| 200V (2D) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 220       | 20 × 25          | 1000                 | 0.62                    | LGU2D221MELY |
| 270       | 20 × 30          | 1100                 | 0.69                    | LGU2D271MELY |
|           | 22 × 25          | 1100                 | 0.69                    | LGU2D271MELZ |
| 330       | 20 × 35          | 1200                 | 0.77                    | LGU2D331MELY |
|           | 22 × 30          | 1250                 | 0.77                    | LGU2D331MELZ |
|           | 25 × 25          | 1250                 | 0.77                    | LGU2D331MELA |
| 390       | 20 × 40          | 1310                 | 0.83                    | LGU2D391MELY |
|           | 22 × 30          | 1350                 | 0.83                    | LGU2D391MELZ |
|           | 25 × 25          | 1350                 | 0.83                    | LGU2D391MELA |
| 470       | 20 × 45          | 1450                 | 0.91                    | LGU2D471MELY |
|           | 22 × 35          | 1500                 | 0.91                    | LGU2D471MELZ |
|           | 25 × 30          | 1500                 | 0.91                    | LGU2D471MELA |
| 560       | 30 × 25          | 1500                 | 0.91                    | LGU2D471MELB |
|           | 20 × 50          | 1580                 | 1.00                    | LGU2D561MELY |
|           | 22 × 40          | 1670                 | 1.00                    | LGU2D561MELZ |
|           | 25 × 30          | 1670                 | 1.00                    | LGU2D561MELA |
| 680       | 30 × 25          | 1670                 | 1.00                    | LGU2D561MELB |
|           | 22 × 45          | 1780                 | 1.10                    | LGU2D681MELZ |
|           | 25 × 35          | 1780                 | 1.10                    | LGU2D681MELA |
|           | 30 × 30          | 1780                 | 1.10                    | LGU2D681MELB |
| 820       | 35 × 25          | 1780                 | 1.10                    | LGU2D681MELC |
|           | 25 × 45          | 2040                 | 1.21                    | LGU2D821MELA |
|           | 30 × 30          | 2040                 | 1.21                    | LGU2D821MELB |
|           | 35 × 25          | 2040                 | 1.21                    | LGU2D821MELC |
| 1000      | 25 × 50          | 2300                 | 1.34                    | LGU2D102MELA |
|           | 30 × 35          | 2300                 | 1.34                    | LGU2D102MELB |
|           | 35 × 30          | 2300                 | 1.34                    | LGU2D102MELC |
| 1200      | 30 × 40          | 2650                 | 1.46                    | LGU2D122MELB |
|           | 35 × 35          | 2650                 | 1.46                    | LGU2D122MELC |
|           | 30 × 50          | 3080                 | 1.64                    | LGU2D152MELB |
| 1500      | 35 × 40          | 3080                 | 1.64                    | LGU2D152MELC |
|           | 35 × 45          | 3480                 | 1.80                    | LGU2D182MELC |
| 2200      | 35 × 50          | 3780                 | 1.98                    | LGU2D222MELC |

| 220V (2P) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 180       | 20 × 25          | 900                  | 0.59                    | LGU2P181MELY |
| 220       | 20 × 30          | 1000                 | 0.66                    | LGU2P221MELY |
|           | 22 × 25          | 1000                 | 0.66                    | LGU2P221MELZ |
| 270       | 20 × 35          | 1150                 | 0.73                    | LGU2P271MELY |
|           | 22 × 30          | 1150                 | 0.73                    | LGU2P271MELZ |
| 330       | 20 × 40          | 1250                 | 0.80                    | LGU2P331MELY |
|           | 22 × 35          | 1250                 | 0.80                    | LGU2P331MELZ |
|           | 25 × 25          | 1250                 | 0.80                    | LGU2P331MELA |
| 390       | 20 × 45          | 1400                 | 0.87                    | LGU2P391MELY |
|           | 22 × 35          | 1400                 | 0.87                    | LGU2P391MELZ |
|           | 25 × 30          | 1400                 | 0.87                    | LGU2P391MELA |
| 470       | 20 × 50          | 1450                 | 0.96                    | LGU2P471MELY |
|           | 22 × 40          | 1450                 | 0.96                    | LGU2P471MELZ |
|           | 25 × 35          | 1450                 | 0.96                    | LGU2P471MELA |
|           | 30 × 25          | 1450                 | 0.96                    | LGU2P471MELB |
| 560       | 22 × 45          | 1700                 | 1.05                    | LGU2P561MELZ |
|           | 25 × 40          | 1700                 | 1.05                    | LGU2P561MELA |
|           | 30 × 30          | 1700                 | 1.05                    | LGU2P561MELB |
| 680       | 25 × 45          | 1780                 | 1.16                    | LGU2P681MELA |
|           | 30 × 35          | 1780                 | 1.16                    | LGU2P681MELB |
|           | 35 × 25          | 1780                 | 1.16                    | LGU2P681MELC |
| 820       | 25 × 50          | 2100                 | 1.27                    | LGU2P821MELA |
|           | 30 × 40          | 2100                 | 1.27                    | LGU2P821MELB |
|           | 35 × 30          | 2100                 | 1.27                    | LGU2P821MELC |
| 1000      | 30 × 45          | 2400                 | 1.40                    | LGU2P102MELB |
|           | 35 × 35          | 2400                 | 1.40                    | LGU2P102MELC |
| 1200      | 30 × 50          | 2600                 | 1.54                    | LGU2P122MELB |
|           | 35 × 40          | 2600                 | 1.54                    | LGU2P122MELC |
| 1500      | 35 × 45          | 3000                 | 1.72                    | LGU2P152MELC |

| 250V (2E) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 150       | 20 × 25          | 790                  | 0.58                    | LGU2E151MELY |
| 180       | 20 × 30          | 900                  | 0.63                    | LGU2E181MELY |
| 220       | 20 × 30          | 1000                 | 0.70                    | LGU2E221MELY |
|           | 22 × 25          | 1000                 | 0.70                    | LGU2E221MELZ |
| 270       | 20 × 35          | 1100                 | 0.77                    | LGU2E271MELY |
|           | 22 × 35          | 1180                 | 0.77                    | LGU2E271MELZ |
|           | 25 × 25          | 1180                 | 0.77                    | LGU2E271MELA |
| 330       | 20 × 40          | 1200                 | 0.86                    | LGU2E331MELY |
|           | 22 × 40          | 1300                 | 0.86                    | LGU2E331MELZ |
|           | 25 × 30          | 1300                 | 0.86                    | LGU2E331MELA |
|           | 30 × 25          | 1300                 | 0.86                    | LGU2E331MELB |
| 390       | 20 × 50          | 1450                 | 0.93                    | LGU2E391MELY |
|           | 22 × 45          | 1490                 | 0.93                    | LGU2E391MELZ |
|           | 25 × 35          | 1490                 | 0.93                    | LGU2E391MELA |
|           | 30 × 25          | 1490                 | 0.93                    | LGU2E391MELB |
| 470       | 22 × 50          | 1650                 | 1.02                    | LGU2E471MELZ |
|           | 25 × 40          | 1650                 | 1.02                    | LGU2E471MELA |
|           | 30 × 30          | 1650                 | 1.02                    | LGU2E471MELB |
|           | 35 × 25          | 1650                 | 1.02                    | LGU2E471MELC |
|           | 25 × 45          | 1800                 | 1.12                    | LGU2E561MELA |
| 560       | 30 × 35          | 1800                 | 1.12                    | LGU2E561MELB |
|           | 35 × 25          | 1800                 | 1.12                    | LGU2E561MELC |
|           | 25 × 50          | 2000                 | 1.23                    | LGU2E681MELA |
| 680       | 30 × 40          | 2000                 | 1.23                    | LGU2E681MELB |
|           | 35 × 30          | 2000                 | 1.23                    | LGU2E681MELC |
| 820       | 30 × 45          | 2300                 | 1.35                    | LGU2E821MELB |
|           | 35 × 35          | 2300                 | 1.35                    | LGU2E821MELC |
| 1000      | 30 × 50          | 2470                 | 1.50                    | LGU2E102MELB |
|           | 35 × 40          | 2470                 | 1.50                    | LGU2E102MELC |
| 1200      | 35 × 45          | 2600                 | 1.64                    | LGU2E122MELC |
| 1500      | 35 × 50          | 3000                 | 1.83                    | LGU2E152MELC |

Rated ripple current (mA<sub>rms</sub>) at 105°C 120Hz



## ■ Dimensions

| 315V (2F) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 82        | 20 × 25          | 640                  | 0.48                    | LGU2F820MELY |
| 100       | 20 × 30          | 690                  | 0.53                    | LGU2F101MELY |
| 120       | 20 × 30          | 750                  | 0.58                    | LGU2F121MELY |
|           | 22 × 25          | 750                  | 0.58                    | LGU2F121MELZ |
| 150       | 20 × 35          | 820                  | 0.65                    | LGU2F151MELY |
|           | 22 × 30          | 820                  | 0.65                    | LGU2F151MELZ |
|           | 25 × 25          | 820                  | 0.65                    | LGU2F151MELA |
| 180       | 20 × 40          | 900                  | 0.71                    | LGU2F181MELY |
|           | 22 × 35          | 920                  | 0.71                    | LGU2F181MELZ |
|           | 25 × 25          | 920                  | 0.71                    | LGU2F181MELA |
| 220       | 20 × 50          | 1000                 | 0.78                    | LGU2F221MELY |
|           | 22 × 40          | 1040                 | 0.78                    | LGU2F221MELZ |
|           | 25 × 30          | 1040                 | 0.78                    | LGU2F221MELA |
| 270       | 30 × 25          | 1040                 | 0.78                    | LGU2F221MELB |
|           | 22 × 45          | 1160                 | 0.87                    | LGU2F271MELZ |
|           | 25 × 35          | 1160                 | 0.87                    | LGU2F271MELA |
| 330       | 30 × 25          | 1160                 | 0.87                    | LGU2F271MELB |
|           | 22 × 50          | 1330                 | 0.96                    | LGU2F331MELZ |
|           | 25 × 40          | 1330                 | 0.96                    | LGU2F331MELA |
| 390       | 30 × 30          | 1330                 | 0.96                    | LGU2F331MELB |
|           | 35 × 25          | 1330                 | 0.96                    | LGU2F331MELC |
|           | 25 × 45          | 1470                 | 1.05                    | LGU2F391MELA |
| 470       | 30 × 35          | 1470                 | 1.05                    | LGU2F391MELB |
|           | 35 × 30          | 1470                 | 1.05                    | LGU2F391MELC |
|           | 25 × 50          | 1700                 | 1.15                    | LGU2F471MELA |
| 560       | 30 × 40          | 1700                 | 1.15                    | LGU2F471MELB |
|           | 35 × 30          | 1700                 | 1.15                    | LGU2F471MELC |
|           | 30 × 45          | 2050                 | 1.26                    | LGU2F561MELB |
| 680       | 35 × 35          | 2050                 | 1.26                    | LGU2F561MELC |
|           | 30 × 50          | 2170                 | 1.38                    | LGU2F681MELB |
| 820       | 35 × 40          | 2170                 | 1.38                    | LGU2F681MELC |
|           | 35 × 45          | 2200                 | 1.52                    | LGU2F821MELC |

| 400V (2G) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 56        | 20 × 25          | 510                  | 0.44                    | LGU2G560MELY |
| 68        | 20 × 30          | 560                  | 0.49                    | LGU2G680MELY |
| 82        | 20 × 30          | 640                  | 0.54                    | LGU2G820MELY |
|           | 22 × 25          | 640                  | 0.54                    | LGU2G820MELZ |
| 100       | 20 × 35          | 700                  | 0.60                    | LGU2G101MELY |
|           | 22 × 30          | 700                  | 0.60                    | LGU2G101MELZ |
|           | 25 × 25          | 700                  | 0.60                    | LGU2G101MELA |
| 120       | 20 × 40          | 750                  | 0.65                    | LGU2G121MELY |
|           | 22 × 35          | 750                  | 0.65                    | LGU2G121MELZ |
|           | 25 × 25          | 750                  | 0.65                    | LGU2G121MELA |
| 150       | 20 × 45          | 830                  | 0.73                    | LGU2G151MELY |
|           | 22 × 40          | 880                  | 0.73                    | LGU2G151MELZ |
|           | 25 × 30          | 880                  | 0.73                    | LGU2G151MELA |
|           | 30 × 25          | 880                  | 0.73                    | LGU2G151MELB |
|           | 22 × 45          | 980                  | 0.80                    | LGU2G181MELZ |
| 180       | 25 × 35          | 980                  | 0.80                    | LGU2G181MELA |
|           | 30 × 30          | 980                  | 0.80                    | LGU2G181MELB |
|           | 35 × 25          | 980                  | 0.80                    | LGU2G181MELC |
| 220       | 22 × 50          | 1100                 | 0.88                    | LGU2G221MELZ |
|           | 25 × 40          | 1100                 | 0.88                    | LGU2G221MELA |
|           | 30 × 30          | 1100                 | 0.88                    | LGU2G221MELB |
|           | 35 × 25          | 1100                 | 0.88                    | LGU2G221MELC |
| 270       | 25 × 45          | 1220                 | 0.98                    | LGU2G271MELA |
|           | 30 × 35          | 1220                 | 0.98                    | LGU2G271MELB |
|           | 35 × 30          | 1220                 | 0.98                    | LGU2G271MELC |
| 330       | 25 × 50          | 1440                 | 1.08                    | LGU2G331MELA |
|           | 30 × 40          | 1440                 | 1.08                    | LGU2G331MELB |
|           | 35 × 30          | 1440                 | 1.08                    | LGU2G331MELC |
| 390       | 30 × 45          | 1600                 | 1.18                    | LGU2G391MELB |
|           | 35 × 35          | 1600                 | 1.18                    | LGU2G391MELC |
| 470       | 30 × 50          | 1900                 | 1.30                    | LGU2G471MELB |
|           | 35 × 40          | 1900                 | 1.30                    | LGU2G471MELC |
| 560       | 35 × 45          | 2120                 | 1.41                    | LGU2G561MELC |

| 420V (W6) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 56        | 20 × 25          | 510                  | 0.46                    | LGUW6560MELY |
| 68        | 20 × 30          | 560                  | 0.50                    | LGUW6680MELY |
| 82        | 20 × 35          | 640                  | 0.55                    | LGUW6820MELY |
|           | 22 × 25          | 640                  | 0.55                    | LGUW6820MELZ |
| 100       | 20 × 35          | 700                  | 0.61                    | LGUW6101MELY |
|           | 22 × 30          | 700                  | 0.61                    | LGUW6101MELZ |
|           | 25 × 25          | 700                  | 0.61                    | LGUW6101MELA |
| 120       | 20 × 40          | 750                  | 0.67                    | LGUW6121MELY |
|           | 22 × 35          | 750                  | 0.67                    | LGUW6121MELZ |
|           | 25 × 30          | 750                  | 0.67                    | LGUW6121MELA |
| 150       | 20 × 50          | 880                  | 0.75                    | LGUW6151MELY |
|           | 22 × 40          | 880                  | 0.75                    | LGUW6151MELZ |
|           | 25 × 35          | 880                  | 0.75                    | LGUW6151MELA |
|           | 30 × 25          | 880                  | 0.75                    | LGUW6151MELB |
| 180       | 22 × 45          | 950                  | 0.82                    | LGUW6181MELZ |
|           | 25 × 35          | 950                  | 0.82                    | LGUW6181MELA |
|           | 30 × 30          | 950                  | 0.82                    | LGUW6181MELB |
| 220       | 22 × 50          | 1100                 | 0.91                    | LGUW6221MELZ |
|           | 25 × 45          | 1100                 | 0.91                    | LGUW6221MELA |
|           | 30 × 35          | 1100                 | 0.91                    | LGUW6221MELB |
|           | 35 × 25          | 1100                 | 0.91                    | LGUW6221MELC |
| 270       | 25 × 50          | 1220                 | 1.01                    | LGUW6271MELA |
|           | 30 × 40          | 1220                 | 1.01                    | LGUW6271MELB |
|           | 35 × 30          | 1220                 | 1.01                    | LGUW6271MELC |
| 330       | 30 × 45          | 1450                 | 1.11                    | LGUW6331MELB |
|           | 35 × 35          | 1450                 | 1.11                    | LGUW6331MELC |
| 390       | 30 × 50          | 1550                 | 1.21                    | LGUW6391MELB |
|           | 35 × 40          | 1550                 | 1.21                    | LGUW6391MELC |
| 470       | 35 × 45          | 1900                 | 1.33                    | LGUW6471MELC |
| 560       | 35 × 50          | 2150                 | 1.45                    | LGUW6561MELC |

| 450V (2W) |                  |                      |                         |              |
|-----------|------------------|----------------------|-------------------------|--------------|
| Cap.(μF)  | Size<br>φD×L(mm) | Rated ripple<br>(mA) | Leakage Current<br>(mA) | Code         |
| 47        | 20 × 25          | 390                  | 0.43                    | LGU2W470MELY |
| 56        | 20 × 30          | 510                  | 0.47                    | LGU2W560MELY |
| 68        | 20 × 35          | 560                  | 0.52                    | LGU2W680MELY |
|           | 20 × 35          | 640                  | 0.57                    | LGU2W820MELY |
| 82        | 22 × 30          | 640                  | 0.57                    | LGU2W820MELZ |
|           | 25 × 25          | 640                  | 0.57                    | LGU2W820MELA |
|           | 20 × 45          | 690                  | 0.63                    | LGU2W101MELY |
| 100       | 22 × 35          | 690                  | 0.63                    | LGU2W101MELZ |
|           | 25 × 30          | 690                  | 0.63                    | LGU2W101MELA |
|           | 20 × 50          | 750                  | 0.69                    | LGU2W121MELY |
| 120       | 22 × 40          | 800                  | 0.69                    | LGU2W121MELZ |
|           | 25 × 30          | 800                  | 0.69                    | LGU2W121MELA |
|           | 30 × 25          | 800                  | 0.69                    | LGU2W121MELB |
|           | 22 × 45          | 880                  | 0.77                    | LGU2W151MELZ |
| 150       | 25 × 35          | 880                  | 0.77                    | LGU2W151MELA |
|           | 30 × 30          | 880                  | 0.77                    | LGU2W151MELB |
|           | 22 × 50          | 1000                 | 0.85                    | LGU2W181MELZ |
| 180       | 25 × 40          | 1000                 | 0.85                    | LGU2W181MELA |
|           | 30 × 30          | 1000                 | 0.85                    | LGU2W181MELB |
|           | 25 × 45          | 1120                 | 0.94                    | LGU2W221MELA |
| 220       | 30 × 35          | 1120                 | 0.94                    | LGU2W221MELB |
|           | 35 × 30          | 1120                 | 0.94                    | LGU2W221MELC |
|           | 30 × 40          | 1280                 | 1.04                    | LGU2W271MELB |
| 270       | 35 × 35          | 1280                 | 1.04                    | LGU2W271MELC |
|           | 30 × 50          | 1450                 | 1.15                    | LGU2W331MELB |
| 330       | 35 × 40          | 1450                 | 1.15                    | LGU2W331MELC |
|           | 30 × 50          | 1500                 | 1.25                    | LGU2W391MELC |
| 470       | 35 × 50          | 1850                 | 1.37                    | LGU2W471MELC |

Rated ripple current (mArms) at 105°C 120Hz



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.