

# FDD6630A

## 30V N-Channel PowerTrench<sup>®</sup> MOSFET

### General Description



This N-Channel MOSFET has been designed specifically to improve the overall efficiency of DC/DC converters using either synchronous or conventional switching PWM controllers. It has been optimized for low gate charge, low  $R_{DS(ON)}$  and fast switching speed.

### Applications

- DC/DC converter
- Motor drives

### Features

- 21 A, 30 V  $R_{DS(ON)} = 35\text{ m}\Omega$  @  $V_{GS} = 10\text{ V}$   
 $R_{DS(ON)} = 50\text{ m}\Omega$  @  $V_{GS} = 4.5\text{ V}$
- Low gate charge (5nC typical)
- Fast switching
- High performance trench technology for extremely low  $R_{DS(ON)}$



### Absolute Maximum Ratings

$T_A = 25^\circ\text{C}$  unless otherwise noted

| Symbol         | Parameter                                        | Ratings         | Units            |
|----------------|--------------------------------------------------|-----------------|------------------|
| $V_{DSS}$      | Drain-Source Voltage                             | 30              | V                |
| $V_{GSS}$      | Gate-Source Voltage                              | $\pm 20$        | V                |
| $I_D$          | Drain Current – Continuous (Note 3)              | 21              | A                |
|                | – Pulsed (Note 1a)                               | 100             |                  |
| $P_D$          | Power Dissipation (Note 1)                       | 28              | W                |
|                |                                                  | 3.2             |                  |
|                |                                                  | 1.3             |                  |
| $T_J, T_{STG}$ | Operating and Storage Junction Temperature Range | $-55$ to $+175$ | $^\circ\text{C}$ |

### Thermal Characteristics

|                 |                                                   |     |                    |
|-----------------|---------------------------------------------------|-----|--------------------|
| $R_{\theta JC}$ | Thermal Resistance, Junction-to-Case (Note 1)     | 4.5 | $^\circ\text{C/W}$ |
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient (Note 1a) | 40  | $^\circ\text{C/W}$ |
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient (Note 1b) | 96  | $^\circ\text{C/W}$ |

### Package Marking and Ordering Information


| Device Marking | Device   | Reel Size | Tape width | Quantity   |
|----------------|----------|-----------|------------|------------|
| FDD6630A       | FDD6630A | 13"       | 16mm       | 2500 units |

**Electrical Characteristics** $T_A = 25^\circ\text{C}$  unless otherwise noted

| Symbol                                                 | Parameter                                             | Test Conditions                                                                                                                                                             | Min | Typ            | Max            | Units |
|--------------------------------------------------------|-------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----------------|----------------|-------|
| Drain-Source Avalanche Ratings (Note 2)                |                                                       |                                                                                                                                                                             |     |                |                |       |
| W <sub>DSS</sub>                                       | Drain-Source Avalanche Energy                         | Single Pulse, V <sub>DD</sub> = 15 V                                                                                                                                        |     |                | 55             | mJ    |
| I <sub>AR</sub>                                        | Drain-Source Avalanche Current                        |                                                                                                                                                                             |     |                | 7.6            | A     |
| Off Characteristics                                    |                                                       |                                                                                                                                                                             |     |                |                |       |
| BV <sub>DSS</sub>                                      | Drain-Source Breakdown Voltage                        | V <sub>GS</sub> = 0 V, I <sub>b</sub> = 250 μA                                                                                                                              | 30  |                |                | V     |
| $\frac{\Delta BV_{DSS}}{\Delta T_J}$                   | Breakdown Voltage Temperature Coefficient             | I <sub>b</sub> = 250 μA, Referenced to 25°C                                                                                                                                 |     | 23             |                | mV/°C |
| I <sub>BSS</sub>                                       | Zero Gate Voltage Drain Current                       | V <sub>DS</sub> = 24 V, V <sub>GS</sub> = 0 V                                                                                                                               |     |                | 1              | μA    |
| I <sub>GSSF</sub>                                      | Gate-Body Leakage, Forward                            | V <sub>GS</sub> = 20 V, V <sub>DS</sub> = 0 V                                                                                                                               |     |                | 100            | nA    |
| I <sub>GSSR</sub>                                      | Gate-Body Leakage, Reverse                            | V <sub>GS</sub> = -20 V, V <sub>DS</sub> = 0 V                                                                                                                              |     |                | -100           | nA    |
| On Characteristics (Note 2)                            |                                                       |                                                                                                                                                                             |     |                |                |       |
| V <sub>GS(th)</sub>                                    | Gate Threshold Voltage                                | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>b</sub> = 250 μA                                                                                                                 | 1   | 1.7            | 3              | V     |
| $\frac{\Delta V_{GS(th)}}{\Delta T_J}$                 | Gate Threshold Voltage Temperature Coefficient        | I <sub>b</sub> = 250 μA, Referenced to 25°C                                                                                                                                 |     | -4             |                | mV/°C |
| R <sub>DS(on)</sub>                                    | Static Drain-Source On-Resistance                     | V <sub>GS</sub> = 10 V, I <sub>b</sub> = 7.6 A<br>V <sub>GS</sub> = 4.5 V, I <sub>b</sub> = 6.3 A<br>V <sub>GS</sub> = 10 V, I <sub>b</sub> = 7.6 A, T <sub>J</sub> = 125°C |     | 28<br>40<br>44 | 35<br>50<br>58 | mΩ    |
| I <sub>b(on)</sub>                                     | On-State Drain Current                                | V <sub>GS</sub> = 10 V, V <sub>DS</sub> = 5 V                                                                                                                               | 20  |                |                | A     |
| g <sub>FS</sub>                                        | Forward Transconductance                              | V <sub>DS</sub> = 5 V, I <sub>b</sub> = 7.6 A                                                                                                                               |     | 13             |                | S     |
| Dynamic Characteristics                                |                                                       |                                                                                                                                                                             |     |                |                |       |
| C <sub>iss</sub>                                       | Input Capacitance                                     | V <sub>DS</sub> = 15 V, V <sub>GS</sub> = 0 V, f = 1.0 MHz                                                                                                                  |     | 462            |                | pF    |
| C <sub>oss</sub>                                       | Output Capacitance                                    |                                                                                                                                                                             |     | 113            |                | pF    |
| C <sub>rss</sub>                                       | Reverse Transfer Capacitance                          |                                                                                                                                                                             |     | 40             |                | pF    |
| Switching Characteristics (Note 2)                     |                                                       |                                                                                                                                                                             |     |                |                |       |
| t <sub>d(on)</sub>                                     | Turn-On Delay Time                                    | V <sub>DD</sub> = 15 V, I <sub>b</sub> = 1 A, V <sub>GS</sub> = 10 V, R <sub>GEN</sub> = 6 Ω                                                                                |     | 5              | 11             | ns    |
| t <sub>r</sub>                                         | Turn-On Rise Time                                     |                                                                                                                                                                             |     | 8              | 17             | ns    |
| t <sub>d(off)</sub>                                    | Turn-Off Delay Time                                   |                                                                                                                                                                             |     | 17             | 28             | ns    |
| t <sub>f</sub>                                         | Turn-Off Fall Time                                    |                                                                                                                                                                             |     | 13             | 24             | ns    |
| Q <sub>g</sub>                                         | Total Gate Charge                                     | V <sub>DS</sub> = 15 V, V <sub>GS</sub> = 5 V, I <sub>b</sub> = 7.6 A,                                                                                                      |     | 5              | 7              | nC    |
| Q <sub>gs</sub>                                        | Gate-Source Charge                                    |                                                                                                                                                                             |     | 2              |                | nC    |
| Q <sub>gd</sub>                                        | Gate-Drain Charge                                     |                                                                                                                                                                             |     | 1.4            |                | nC    |
| Drain-Source Diode Characteristics and Maximum Ratings |                                                       |                                                                                                                                                                             |     |                |                |       |
| I <sub>S</sub>                                         | Maximum Continuous Drain-Source Diode Forward Current |                                                                                                                                                                             |     |                | 2.7            | A     |
| V <sub>SD</sub>                                        | Drain-Source Diode Forward Voltage                    | V <sub>GS</sub> = 0 V, I <sub>S</sub> = 2.7 A (Note 2)                                                                                                                      |     | 0.8            | 1.2            | V     |

**Notes:**

1.  $R_{\theta JA}$  is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins.  $R_{\theta JC}$  is guaranteed by design while  $R_{\theta CA}$  is determined by the user's board design.



a)  $R_{\theta JA} = 40^\circ\text{C/W}$  when mounted on a  
1 in<sup>2</sup> pad of 2 oz copper



b)  $R_{\theta JA} = 96^\circ\text{C/W}$  when mounted  
on a minimum pad.

Scale 1 : 1 on letter size paper

2. Pulse Test: Pulse Width < 300 $\mu\text{s}$ , Duty Cycle < 2.0%

3. Maximum current is calculated as:
- $$\sqrt{\frac{P_D}{R_{DS(on)}}}$$
- where  $P_D$  is maximum power dissipation at  $T_C = 25^\circ\text{C}$  and  $R_{DS(on)}$  is at  $T_{J(max)}$  and  $V_{GS} = 10\text{ V}$ . Package current limitation is 21A

## Typical Characteristics




Figure 1. On-Region Characteristics.




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 3. On-Resistance Variation with Temperature.




Figure 4. On-Resistance Variation with Gate-to-Source Voltage.




Figure 5. Transfer Characteristics.




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature.

# Typical Characteristics




Figure 7. Gate Charge Characteristics.




Figure 8. Capacitance Characteristics.




Figure 9. Maximum Safe Operating Area.




Figure 10. Single Pulse Maximum Power Dissipation.




Figure 11. Transient Thermal Response Curve.

Thermal characterization performed using the conditions described in Note 1b.  
Transient thermal response will change depending on the circuit board design.

## TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

|                                                                                     |                                                                                   |                                                                                      |                                                                                     |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 2Cool™                                                                              | FPS™                                                                              | PDP SPM™                                                                             | The Power Franchise®                                                                |
| AccuPower™                                                                          | F-PFS™                                                                            | Power-SPM™                                                                           | the power®                                                                          |
| Auto-SPM™                                                                           | FRFET®                                                                            | PowerTrench®                                                                         | TinyBoost™                                                                          |
| AX-CAP™*                                                                            | Global Power Resource <sup>SM</sup>                                               | PowerXS™                                                                             | TinyBuck™                                                                           |
| BitSiC®                                                                             | Green FPS™                                                                        | Programmable Active Droop™                                                           | TinyCalc™                                                                           |
| Build it Now™                                                                       | Green FPS™ e-Series™                                                              | QFET®                                                                                | TinyLogic®                                                                          |
| CorePLUS™                                                                           | Gmax™                                                                             | QS™                                                                                  | TINYOPTO™                                                                           |
| CorePOWER™                                                                          | GTO™                                                                              | Quiet Series™                                                                        | TinyPower™                                                                          |
| CROSSVOLT™                                                                          | IntelliMAX™                                                                       | RapidConfigure™                                                                      | TinyPWM™                                                                            |
| CTL™                                                                                | ISOPLANAR™                                                                        |  ™  | TinyWire™                                                                           |
| Current Transfer Logic™                                                             | Marking Small Speakers Sound Louder and Better™                                   | Saving our world, 1mW/W/kW at a time™                                                | TranSiC®                                                                            |
| DEUXPEED®                                                                           | MegaBuck™                                                                         | SignalWise™                                                                          | TriFault Detect™                                                                    |
| Dual Cool™                                                                          | MICROCOUPLER™                                                                     | SmartMax™                                                                            | TRUECURRENT®*                                                                       |
| EcoSPARK®                                                                           | MicroFET™                                                                         | SMART START™                                                                         | µSerDes™                                                                            |
| EfficientMax™                                                                       | MicroPak™                                                                         | Solutions for Your Success™                                                          |  |
| ESBC™                                                                               | MicroPak2™                                                                        | SPM®                                                                                 | UHC®                                                                                |
|  ® | MillerDrive™                                                                      | STEALTH™                                                                             | Ultra FRFET™                                                                        |
| Fairchild®                                                                          | MotionMax™                                                                        | SuperFET®                                                                            | UniFET™                                                                             |
| Fairchild Semiconductor®                                                            | Motion-SPM™                                                                       | SuperSOT™-3                                                                          | VCX™                                                                                |
| FACT Quiet Series™                                                                  | mWSaver™                                                                          | SuperSOT™-6                                                                          | VisualMax™                                                                          |
| FACT®                                                                               | OptoHiT™                                                                          | SuperSOT™-8                                                                          | VoltagePlus™                                                                        |
| FAST®                                                                               | OPTOLOGIC®                                                                        | SupreMOS®                                                                            | XS™                                                                                 |
| FastvCore™                                                                          | OPTOPLANAR®                                                                       | SyncFET™                                                                             |                                                                                     |
| FETBench™                                                                           |  | Sync-Lock™                                                                           |                                                                                     |
| FlashWriter®*                                                                       |                                                                                   |  ®* |                                                                                     |

\*Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used here in:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, [www.fairchildsemi.com](http://www.fairchildsemi.com), under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufactures of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed application, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address and warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status        | Definition                                                                                                                                                                                          |
|--------------------------|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative / In Design | Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                       |
| Preliminary              | First Production      | Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production       | Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.                                               |
| Obsolete                 | Not In Production     | Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.                                                    |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.