



SEE SHEET 2 OF 2 FOR DASH NUMBERS AND NOTES

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN R.K. SEIFRIED/UTA 13JUL92	TE Connectivity
DIMENSIONS: INCHES		CHK B FLICKER 23OCT92	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME B FLICKER 23OCT92	PRODUCT SPEC
0 PLC	± -	APPLICATION SPEC	NAME
1 PLC	± -	SIZE	CAGE CODE
2 PLC	± -	WEIGHT	DRAWING NO
3 PLC	± .005	CUSTOMER DRAWING	RESTRICTED TO
4 PLC	± -	SCALE	4:1
ANGLES	± -	SHEET	1 OF 2
MATERIAL: HOUSING: PPA	FINISH: SEE TABLE	REV	U
COLOR: BLACK			
CONTACT: COPPER ALLOY			

- 1 .000030 GOLD IN LOCALIZED PLATE AREA, .000150 TIN-LEAD ON SOLDER TAILS ALL OVER .000050 NICKEL.
- 2 USE .0465±.0010 DRILLED HOLE (#56 DRILL) WITH .001 MIN COPPER.
- 3 CIRCUIT IDENTIFICATION FEATURE OMITTED ON 10 POSITION HEADER ASSEMBLIES.
- 4 DIMENSION APPLIES AT BASE OF SHROUD.
- 5 THE NOTED DIMENSIONS APPLY AT THE MATING FACE OF THE HOUSING.
- 6 ARE LOCATED THE SAME AS EXCEPT ON OPPOSITE SIDE OF HOUSING.
- 7 PADS ON THE OPPOSITE SIDE OF THE BOARD TO BE Ø.065 MINIMUM.
- 8 REFER TO NO. OF POSN. IN CHART FOR NUMBER OF SURFACES THAT ARE TO BE COPLALAR.
- 9 .000030 GOLD IN LOCALIZED PLATE AREA, .000150 TIN ON SOLDER TAILS, ALL OVER .000050 NICKEL.
- 10 NO CIRCUIT IDENTIFICATION FEATURE ON 10,12,20,24 AND 30 POSITION PARTS.
- 11 FINISH: .000001 MIN. GOLD GOLD PLATED AREA, .000150-.000250 MATTE TIN LEAD ON TIN PLATE AREA, UNDER PLATING SHOULD BE .000050-.000100 NICKEL ON ENTIRE CONTACT, GOLD AND TIN PLATING MAY NOT OVERLAP.
- 12 FINISH: .000001 MIN GOLD ON GOLD PLATED AREA, .000150-.000250 MATTE TIN ON TIN PLATE AREA, UNDERPLATING TO BE .000050-.000100 NICKEL ON ENTIRE CONTACT, GOLD AND TIN PLATING MAY NOT OVERLAP.
- 13 PRELIMINARY - NOT FOR PRODUCTION
- 14 OBSOLETE

	-	-	-	.000	.250	5	.430	12	13-8-104549-1
	-	.000	1.150	1.150	2.450	49	2.630	100	8-104549-0
	-	.000	.900	.900	1.950	39	2.130	80	13-7-104549-9
	-	.000	.650	.650	1.450	29	1.630	60	13-7-104549-8
	-	.025	.525	.525	1.200	24	1.380	50	13-7-104549-7
	-	-	.400	.400	.950	19	1.130	40	13-7-104549-6
	-	-	.275	.275	.700	14	.880	30	7-104549-5
	-	-	.225	.225	.600	12	.780	26	13-7-104549-4
	-	-	.200	.200	.550	11	.730	24	13-7-104549-3
	-	-	.150	.150	.450	9	.630	20	13-7-104549-2
	.494	-	-	.025	.200	4	-	10	13-7-104549-1
	-	-	-	.000	.250	5	.430	12	6-104549-1
	-	.000	1.150	1.150	2.450	49	2.630	100	6-104549-0
-	.000	.900	.900	1.950	39	2.130	80	5-104549-9	
-	.000	.650	.650	1.450	29	1.630	60	5-104549-8	
-	.025	.525	.525	1.200	24	1.380	50	5-104549-7	
-	-	.400	.400	.950	19	1.130	40	5-104549-6	
-	-	.275	.275	.700	14	.880	30	5-104549-5	
-	-	.225	.225	.600	12	.780	26	5-104549-4	
-	-	.200	.200	.550	11	.730	24	5-104549-3	
-	-	.150	.150	.450	9	.630	20	5-104549-2	
.494	-	-	.025	.200	4	-	10	5-104549-1	
FINISH	G	F	E	D	C	B	A	NO OF POSN	PART NUMBER

	-	-	-	.000	.250	5	.430	12	13-3-104549-1
	-	.000	1.150	1.150	2.450	49	2.630	100	13-3-104549-0
	-	.000	.900	.900	1.950	39	2.130	80	13-2-104549-9
	-	.000	.650	.650	1.450	29	1.630	60	13-2-104549-8
	-	.025	.525	.525	1.200	24	1.380	50	13-2-104549-7
	-	-	.400	.400	.950	19	1.130	40	13-2-104549-6
	-	-	.275	.275	.700	14	.880	30	13-2-104549-5
	-	-	.225	.225	.600	12	.780	26	13-2-104549-4
	-	-	.200	.200	.550	11	.730	24	13-2-104549-3
	-	-	.150	.150	.450	9	.630	20	13-2-104549-2
	.494	-	-	.025	.200	4	-	10	13-2-104549-1
	-	-	-	.000	.250	5	.430	12	1-104549-1
	-	.000	1.150	1.150	2.450	49	2.630	100	1-104549-0
-	.000	.900	.900	1.950	39	2.130	80	104549-9	
-	.000	.650	.650	1.450	29	1.630	60	104549-8	
-	.025	.525	.525	1.200	24	1.380	50	104549-7	
-	-	.400	.400	.950	19	1.130	40	104549-6	
-	-	.275	.275	.700	14	.880	30	104549-5	
-	-	.225	.225	.600	12	.780	26	104549-4	
-	-	.200	.200	.550	11	.730	24	104549-3	
-	-	.150	.150	.450	9	.630	20	104549-2	
.494	-	-	.025	.200	4	-	10	104549-1	
FINISH	G	F	E	D	C	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIN R.K. SEIFRIED/UTA 13JUL92
 CHK B FLICKER 23OCT92
 APVD B FLICKER 23OCT92

STE TE Connectivity

NAME: HEADER ASSEMBLY, W/SIDE & END LATCHES, VERTICAL, SHROUDED, DOUBLE ROW,SURFACE MOUNT, AMPMODU System 50, W/HOLDDOWNS

PRODUCT SPEC: -
 APPLICATION SPEC: -
 SIZE: A1
 CAGE CODE: 00779
 DRAWING NO: 104549

MATERIAL: HOUSING: PPA
 COLOR: BLACK
 CONTACT: COPPER ALLOY

FINISH: SEE TABLE

WEIGHT: -

CUSTOMER DRAWING

SCALE: 4:1 SHEET 2 OF 2 REV U



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.