

MultiMax-8G+



Today's flash memory market demands more than just production and testing tools. To meet those requirements on **MultiMax-8G+**, we do have adapters available, from factory stock, to use with Non-DIP devices, such as TSOP, SOP, QFP, PLCC, and BGA packages, allowing you to reduce your manufacturing time and cost. Therefore it is ideal for production lines, which need to program a full range of device types and packages. **MultiMax-8G+** is a new generation programming system to meet all the needs of today's most demanding programming centers.

PRODUCT HIGHLIGHTS

- Universal Device Programmer (Over 8000 selections)
- Works in 8-Sockets of Stand-Alone
- 1.25 Gbit for Standard Buffer Size
- High Speed : 2.5 Mbit / Sec
- Fast download data via USB 2.0

KEY FEATURES

- Operation
 - Stand-alone & Remote operation
- Number of supported devices
 - Over 8,000 devices
- Supported low-voltages
 - 1.8/ 2.0/ 2.7/ 3.0/ 3.3/ 5.0 Volt
- High-speed programming
 - Up to 2.5 Mbit/sec
- Pin-driver
 - 384 pin-driver (independent 48 pin full driving)
- Standard socket module
 - Universal 48-pin ZIF socket * 8 ea
- System clock speed
 - Max 66Mhz
- Control processor
 - 32 bit embedded RISC processor
- Display
 - Wide graphic back-lit LCD (40 words * 8 lines)
- Buffer memory capacity
 - 1.25 GBit
- Keyboard
 - 22 keys + independent Start key
- Data edit functions
 - Insert, Delete, Move, Copy, Fill, Clear, Search
- System control functions
 - Read, Program, Verify, Blank Check, Erase, Pgm, Seq, Cfg, Edit, Data, Check Sum, I/O

- Device control functions
 - Read, Program, Verify, Blank Check, Erase
- Auto Start Button Function
 - (E->B->P->V with one cycle operation)

PROGRAMMING SPEED


Device Name	Size(16bit)	Time(sec)
AT17LV010	1M	37.20
M27C512	512K	20.43
M27C1001	1M	16.78
M27C4001	4M	67.04
MX27C4096	4M	33.04
M27C801	8M	123.19
Intel 28F160C3T	16M NOR	22.96
Intel 28F320C3T	32M NOR	45.92
Intel 28F640J5	64M NOR	85.00
Intel 28F128J3A	128M NOR	170.00
Samsung KAB01D100M	192M NOR+NAND	169.07
Samsung K5D57298CM	256M NAND MCP	207.74
AM29LV61DH	64M NOR	115.30
K9K1G08U0M	1G NAND	775.10

* Time (sec) = Blank check + Program + Verify

DEVICES PROGRAMMED

- EPROM, EEPROM, NAND Flash / NOR Flash memory (up to 512Mbit), PLD
- FPGA, Serial PROM, Parallel PROM, CMOS PROM, Microcontrollers

MultiMax-8G+



PACKAGES SUPPORTED

- DIP, SDIP, PDIP, LCC, PLCC, QFP, TQFP, PQFP, VQFP, SOIC, SOP, PSOP, SON, TSOP, TSOP2, STSOP, TSSOP, SSOP, BGA, uBGA, FBGA, EBGA, CSP, SCSP, and more..

SUPPORTED FILE FORMATS

- Binary, ASCII, Intel Hex, Motorola S, Tektronix Hex, JEDEC and POF Files

SYSTEM REQUIREMENT

- TYPE: Pentium PC, Windows 2000 / XP
- Hard disk space : over 20Mbyte for software installation
- RAM size: over 256 Mbyte
- CD-ROM Drive
- I/O PORT: USB 2.0 & Serial ports

TECHNICAL SPECIFICATION

Dimension :

- Module : 15.5"(L) x 15.0"(W) x 5.0"(H)

Weight : 19 lbs

PC Host Interface for downloading data : USB 1.1 or 2.0

Built-in Socket : 48-pin Textool ZIF (300/600 mil) standard.

Input power : 110~230VAC, 50~60Hz

SAFETY STANDARD

- CE compliant

WARRANTY

- One year hardware warranty service in factory

STANDARD ACCESSORIES

- Power Cord
- USB Cable
- Software CD and User's Guide



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.