PCIE-Q870-i2

Full-size PICMG 1.3 CPU card supports LGA1150 Intel® Core™ i7/i5/i3, Pentium® and Celeron® CPU per Intel® Q87, DDR3, VGA, iDP, Dual PCIe GbE, SATA 6Gb/s, mSATA, PCIe Mini, RS-232, Audio, iRIS-2400 and RoHS

5 YEARS 5-YEAR SUPPLY GUARANTEE





New

iRIS-2400 Key Features

- IPMI 2.0 Based Management
- Cross OS Platform Support
- Hardware Health Monitor
- Event Log
- KVM over IP
- Notifications
- Virture Media Support
- Remote Power Control
- User Management
- Serial over LAN

Enhance component protection
Prevent the damage of bottom size components

IPMI 2.0 Compliant

One Key Recovery

TPM 1.2 Support

DDR3L 1600 | USB 3.0 | SATA 6Gb/s | Dual GbE | mSATA | iDP

Specifications

- CPU
  LGA1150 Intel® 4th generation Core™ i7/i5/i3, Pentium® or Celeron® processor supported
- System Chipset
  Intel® Q87
- Memory
  Four 240-pin 1600/1333MHz dual-channel DDR3 & DDR3L SDRAM unbuffered DIMMs support up to 32GB
- BIOS
  UEFI BIOS
- Graphics Engine
  Intel® HD Graphics Gen 7.5 supports DX11.1 and OpenCL 1.2, OpenGL 3.2
  Full MPEG2, VC1, AVC Decode
- Display Output
  VGA (up to 1920x1200 @ 60 Hz)
  iDP interface for HDMI, LVDS, VGA, DVI, DP (up to 3840x2160 @60 Hz)
- Ethernet
  LAN1: Intel® I217LM with Intel® AMT 9.0 support
  LAN2: Intel® I210-AT PCIe controller with NCSI support
- Super I/O
  Fintek F81866
- I/O Interface
  1 x 6-pin wafer for KB/MS 1 x LPT
  1 x RS-422/485 4 x RS-232
  1 x mSATA (colay SATA port 6) (support SATA 6GB/s signal only)
  4 x USB 3.0 (2 by rear IO, 2 by pin header)
  6 x SATA 6GB/s (RAID 0, 1, 5, 10 supported)
  8 x USB 2.0 (4 by pin header, 4 by backplane pin header)
- Front Panel
  1 x Front panel (Power LED, HDD LED, Speaker, Power Button, Reset Button)
- LAN LED
  2 x 2-pin headers for LAN1 Link LED, LAN2 Link LED
- Audio
  Supported by IEI AC-KIT-892HD Audio Kit
- TPM
  1 x TPM connector (2x10 pin)
- SMBus
  1 x 4-pin wafer
- I2C
  1 x 4-pin wafer
- Infrared Interface
  1 x 5-pin header
- iRIS Remote Management Module
  1 x iRIS-2400 slot
- Expansion
  PCIe signal and PCI signal via golden finger
  PCI signal by ITE 8892 (PCIe to PCI bridge)
  1 x Full-size PCIe Mini card slot (colay mSATA)
- Watchdog Timer
  Software programmable, support 1~255 sec. system reset
- Digital I/O
  8-bit digital I/O (4-bit input, 4-bit output)
- Fan Connector
  1 x 3-pin fan connector (system fan)
  1 x 4-pin smart fan connector (CPU fan)
- Power Supply
  5V/12V, AT/ATX support
- Power Consumption
  5V@3.55A, 12V@0.37A, Vcore_12V@7.61A, 3.3V@1.55A, 5VSB@0.13A
  (Intel® Core™ i7-4770K 3.90 GHz CPU with 16GB (4x4GB) 1333MHz DDR3 memory)
- Operating Temperature
  -20°C ~ 60°C
- Storage Temperature
  -30°C ~ 70°C
- Operating Humidity
  10% ~ 95%, non-condensing
- Dimensions
  338 mm x 126 mm
- Weight
  GW 1200g / NW: 420g

Features

- PICMG 1.3 full-size graphic grade solution
- LGA1150 Intel® 4th generation Core™ i7/i5/i3, Pentium® or Celeron® processor supported
- Four 240-pin 1600/1333MHz dual-channel DDR3 DIMMs support up to 32GB memory
- Supports dual independent display by VGA & iDP interface
- Supports PCIe Mini devices and mSATA via PCIe Mini socket
- Intel® PCIe GbE with Intel® AMT 9.0 support
- Supports RAID function via SATA 6Gb/s
- TPM V1.2 hardware security function supported by TPM module
- Stiffener bars
- IEI jumper-less function
- Support IPMI 2.0 via iRIS-2400 module

Packing List

1 x PCIE-Q870-i2 single board computer	
1 x Dual RS-232 cable (P/N: 19800-000051-RS)	
1 x USB 2.0 cable (P/N: 19800-003100-300-RS)	1 x QIG (Quick Installation Guide)
2 x SATA cable (P/N: 32000-062800-RS)	1 x Utility CD

Ordering Information

Part No.	Description
PCIE-Q870-i2-R10	Full-size PICMG 1.3 CPU card supports LGA1150 Intel® Core™ i7/i5/i3, Pentium® and Celeron® CPU per Intel® Q87, DDR3, VGA, iDP, Dual Intel® PCIe GbE, SATA 6Gb/s, mSATA, RS-232, PCIe Mini, Audio, iRIS-2400 and RoHS
iRIS-2400-R10	IPMI 2.0 adapter card with AST2400 BMC chip for DDR3 SO-DIMM socket interface
19800-000049-RS	LPT cable
19800-000075-RS	KB/MS cable with bracket
19800-010500-200-RS	USB 3.0 cable 457mm with bracket
32102-000100-200-RS	SATA power cable, MOLEX 5264-4P to SATA15P
32205-003800-300-RS	RS-422/485 cable, 200mm
AC-KIT-892HD-R10	7.1 channel HD Audio kit with Realtek ALC892 support dual audio streams
CF-1150SB-R11	Special cooler kit for LGA1150, high-performance compatible, 65W
CF-1150SC-R20	Special cooler kit for LGA115X, 1U chassis compatible, 65W, copper
CF-1150SE-R10	Special cooler kit for LGA115X, high-performance compatible, 95W, cooper
CF-1150SF-R10	Special cooler kit for LGA115X Intel® CPU, 107x70x35, 54W
DP-DP-R10	DisplayPort to DisplayPort converter board (for IEI iDP connector)
DP-DVI-R10	DisplayPort to DVI-D converter board (for IEI iDP connector)
DP-HDMI-R10	DisplayPort to HDMI converter board (for IEI iDP connector)
DP-LVDS-R10	DisplayPort to LVDS converter board (for IEI iDP connector)
DP-VGA-R10	DisplayPort to VGA converter board (for IEI iDP connector)
TPM-IN01-R11	20-pin Infineon TPM module, software management tool, firmware V3.17

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.

Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.