

## Features



- 2" x 3.5" x 1.3" Package, Ideal for 1U Applications
- 10-year life design with Premium E-Caps
- 65 Watts convection cooled
- Class I and Class II models
- Class B Conducted and Radiated EMI Performance
- BF Isolation Type Rated
- Designed to meet new IEC 60601-1-2 4<sup>th</sup> Edition EMC Requirements
- Approved to AAMI ES/CSA C22.2/EN/IEC60601-1, 3<sup>rd</sup> Edition
- 2 x MOPP Isolation
- Internal Temperature Monitor, DC – OK Signal, LED
- 3 Year Warranty

## Description

A superior performance 65 Watt AC to DC power supply designed for next generation medical applications. Feature rich and highly efficient, MB65 product family can easily fit in a 1U chassis and provides 65 Watts of convection power. Input & output and internal temperature monitoring/alarms are features of the MB65 family. All models are CE marked to low voltage directive and approved to AAMI ES/CSA C22.2 No./EN/IEC60601-1, 3<sup>rd</sup> edition. The design takes into consideration the pending international release of the new IEC 60601-1-2, 4<sup>th</sup> Edition EMC requirements. With low leakage current performance, the power supplies are BF rated.

## Model Selection

| Model Number | Class    | Volts | Output Current (Convection Cooled) | Efficiency <sup>1</sup> | Ripple & Noise <sup>2</sup> | Total Regulation | OVP Threshold |
|--------------|----------|-------|------------------------------------|-------------------------|-----------------------------|------------------|---------------|
| MB65S12K     | Class I  | 12V   | 5.4A                               | 88%                     | 0.5%                        | ±1%              | 17.3 ± 2.4V   |
| MB65S12C     | Class II | 12V   | 5.4A                               | 88%                     | 0.5%                        | ±1%              | 17.3 ± 2.4V   |
| MB65S15K     | Class I  | 15V   | 4.3A                               | 88%                     | 0.5%                        | ±1%              | 20.1 ± 2.4V   |
| MB65S15C     | Class II | 15V   | 4.3A                               | 88%                     | 0.5%                        | ±1%              | 20.1 ± 2.4V   |
| MB65S24K     | Class I  | 24V   | 2.7A                               | 89%                     | 0.5%                        | ±1%              | 29.3 ± 3.5V   |
| MB65S24C     | Class II | 24V   | 2.7A                               | 89%                     | 0.5%                        | ±1%              | 29.3 ± 3.5V   |
| MB65S48K     | Class I  | 48V   | 1.35A                              | 90%                     | 0.5%                        | ±1%              | 55.5 ± 4.5V   |
| MB65S48C     | Class II | 48V   | 1.35A                              | 90%                     | 0.5%                        | ±1%              | 55.5 ± 4.5V   |

Notes:

1) Efficiency, Typical at 115/230Vac, 25°C. See Charts below for load conditions.

2) Measured at 25C using 6 inch twisted pair wires with noise probe directly across output terminals, and load terminated with 0.1µF ceramic and 10µF low ESR capacitors.

3) Part number suffix to include "K" for Class-1 AC input, or "C" suffix for Class-2 AC Input

Consult Factory for following Models, availability may vary.

|          |          |     |      |     |      |      |             |
|----------|----------|-----|------|-----|------|------|-------------|
| MB65S18K | Class I  | 18V | 3.6A | 89% | 0.5% | ± 1% | 21.7 ± 2.5V |
| MB65S18C | Class II | 18V | 3.6A | 89% | 0.5% | ± 1% | 21.7 ± 2.5V |
| MB65S28K | Class I  | 28V | 2.3A | 89% | 0.5% | ± 1% | 35.2 ± 3.5V |
| MB65S28C | Class II | 28V | 2.3A | 89% | 0.5% | ± 1% | 35.2 ± 3.5V |
| MB65S32K | Class I  | 32V | 2.0A | 89% | 0.5% | ± 1% | 41.5 ± 4.5V |
| MB65S32C | Class II | 32V | 2.0A | 89% | 0.5% | ± 1% | 41.5 ± 4.5V |

## General Specifications

|  |   |   |   |
|--|---|---|---|
| <b>AC Input</b>                                  | 85-264Vac, single phase.<br>(Safety Approved to 90-264Vac).   | <b>Turn On Time</b>                               | <2 Seconds at 110Vac.   |
| <b>Input Current</b>                             | 1.5A at 110Vac, 1A at 240Vac  | <b>Rise Time</b>                                  | <30mS, 48V model: < 40mS  |
| <b>Inrush Current</b>                            | 40Arms Maximum within a half line cycle, cold start at 25C. See application note.   | <b>Hold-up Time</b>                               | 20mS min. from loss of AC input at 110 Vac, full load, 25°C.  |
| <b>I<sup>2</sup>T Characteristic</b>             | See Table below.  | <b>Over Load Protection (OCP)</b>                 | 115% - 200% of rated output current value. Hiccup Mode, Auto-recovery   |
| <b>Turn-On Input Voltage</b>                     | >75Vac ± 8Vac. Full spec performance at 85Vac.  | <b>Short Circuit Protection (SCP)</b>             | Short across the output terminals will not cause damage to the unit. Hiccup Mode , Auto-recovery  |
| <b>Turn-Off Input Voltage</b>                    | <63Vac ± 8Vac   | <b>Over Voltage Protection (OVP)</b>              | Latches off when output voltage is with range as shown in table. Requires AC Power cycle to reset   |
| <b>Input Fuses</b>                               | 3.15A, 250Vac, line and neutral inputs  | <b>Over Temperature Protection (OTP)</b>          | Power shuts down at temperature of 70°C (typical) at full load. Hiccup Mode , Auto-recovery   |
| <b>Earth Leakage Current</b>                     | <350 µA@264Vac, 60Hz input, NC  | <b>Output Reverse Voltage Protection</b>          | Outputs protected against momentary reverse current less than 20A peak for less than 10mS with 0.5A average. Sustained reverse current at high levels may damage unit.  |
| <b>Patient Leakage Current (Output to Earth)</b> | <4 mA@264Vac, 60Hz input, NC for BF rating  | <b>Isolation</b>                                  | Input-Output: 4500Vac, 2 x MOPP<br>Input-Ground: 1900Vac, 1 x MOPP<br>Output-Ground: 1900Vac, 1 x MOPP  |
| <b>Touch Current</b>                             | <90 µA@264Vac, 60 Hz input, NC, also suitable for BF rating<br><450 µA@264Vac, 60Hz input, SFC, also suitable for BF rating                                       | <b>Turn-On &amp; Operating Temperature</b>        | -20°C to +70°C.<br>Turn on Temperature = -40°C at >=120Vac, allowing [x] seconds for stabilization.<br>De-rated output power at 70°C = 45.5W  |
| <b>No Load Input Power</b>                       | <0.5W   | <b>Storage Temperature</b>                        | -40°C to +85°C  |
| <b>Efficiency</b>                                | 88% - 90% typical at 115/230Vac, 25°C. See chart for additional details   | <b>Altitude</b>                                   | Operating: -500m to 3000m<br>Non-operating: -500 to 40,000 feet   |
| <b>Output Power</b>                              | 65W continuous convection cooled, -20C to 50°C ambient. 85Vac to 264Vac. See chart for de-rating above 50°C.  | <b>Relative Humidity</b>                          | 5% to 95%, non-condensing   |
| <b>Transient Response</b>                        | 500µS typ. response time for return to within 0.5% of final value for a 50% load change, $\Delta i/\Delta t < 0.2A/\mu s$ . Max. volt. deviation is $\pm 3.5\%$ . | <b>Shock (IEC 60068-2-27)</b>                     | <u>Operating:</u> Half-sine shock waveform. Impact Acceleration: 20g, Pulse duration: 11mS.<br>Cycles: 3 times per axis in X,Y, Z direction<br><u>Non-Operating:</u> Half-sine shock waveform. Impact Acceleration: 100g, Pulse duration: 6mS<br>Cycles: 3 times per direction on 3 axes (X,Y, Z)   |
| <b>Ripple and Noise</b>                          | 0.5% pk-pk  | <b>Vibration (IEC 60068-2-6) (IEC 60068-2-64)</b> | <u>Operating:</u> Sinusoidal Frequency: 10-500Hz, Impact Acceleration: 1g, Sweep rate: 1 octave/min<br>Cycles: 10 times per axis in X, Y, Z direction<br><u>Random Vibration:</u><br><u>Operating:</u> 0.003g <sup>2</sup> /Hz, 1.224grms overall, 3 axes, 10 min per axis, 1-500Hz.<br><u>Non-Operating:</u> 0.02g <sup>2</sup> /Hz, 3.1grms overall, 3 axes, 1 hour per axis, 20-500 Hz |
| <b>Output Voltage</b>                            | 12V to 48Vdc. See models chart for part numbering.  | <b>MTBF</b>                                       | 564,500 hours (ave) @ 110Vac, 25°C, SR332 Issue 6.<br>Consult Factory @ 220Vac, 25°C, SR332 Issue 6.  |
| <b>Voltage Adjustability</b>                     | +/- 10%, 48V is +/- 5%  | <b>E-Cap Life</b>                                 | >10 Years in use condition of 40°C ambient, at 12h/day, 261 days/year. Additional information on other use profiles available on request.   |

## General Specifications (Continued)

|                             |  |                         |   |
|-----------------------------|--|-------------------------|---|
| <b>Overshoot</b>            | <2% overshoot at turn-on, <1% overshoot at turn-off, under all conditions. | <b>IPC 610</b>          | Class 2   |
| <b>HF Common Mode Noise</b> | 0.8 Vrms maximum (input class I)   | <b>Safety Standards</b> | IEC 60601-1, 3 <sup>rd</sup> Edition<br>ANSI/AAMI ES60601-1 (2008)<br>CAN/CSA – C22.2 No 60601-1 (2005)<br>DEMKO EN60601-1:2006<br>Designed to meet China Safety Doc. No. GB4943.1-2011 at 5Km, Tropical Standard at 40°C, 93% RH at 120 hours. |
| <b>Total Regulation</b>     | ±1.0 % for all models.   | <b>Weight</b>           | 140g, typical   |
| <b>Minimum Load</b>         | Not required.  | <b>Dimensions</b>       | W: 2.0" x L: 3.5" x H: 1.3"<br>W: 50.8mm x L: 88.9mm x H: 33.02mm   |

## Additional Outputs

|               |   |                        |   |
|---------------|---|------------------------|---|
| <b>DC OK:</b> | During normal operation, this signal is logic HIGH. Signal will go LOW for output less than 80% (typical) of nominal. Green LED will light on PCB top side during normal operation. | <b>PSU Temperature</b> | Provides resistive value indicating internal temperature of power supply. See Temp Sensor Conversion Table below. |
|---------------|---|------------------------|---|

## EMI/EMC Compliance

|  |  |
|--|--|
| <b>Conducted Emissions</b>   | <u>EN55011/22</u> : Class B, FCC Part 15. Class B: 6db margin typ, <b>Class 1</b> PSU configuration<br><u>EN55011/ 22</u> : Class B, FCC Part 15. Class B: 2db margin typ, <b>Class 2</b> PSU configuration  |
| <b>Radiated Emissions</b>  | <u>EN55011/22</u> : Class B, FCC Part 15. Class B: 3db margin typ, <b>Class 1</b> PSU configuration.<br><u>EN55011/22</u> : Class B, FCC Part 15. Class B: 3db margin typ, <b>Class 2</b> PSU configuration.   |
| <b>Harmonic Current Emissions</b>                                      | <u>IEC61000-3-2</u> : Class A  |
| <b>Voltage Fluctuations &amp; Flicker</b>                              | <u>IEC 61000-3-3</u>   |
| <b>Electro Static Discharge Immunity</b>                               | <u>IEC61000-4-2</u> : Level 4, 8kV Contact Discharge, 15kV air discharge, Criteria A. Also meets proposed IEC60601-1-2, 4 <sup>th</sup> edition, Table 4   |
| <b>Radiated RF EM Fields Susceptibility</b>                            | <u>IEC61000-4-3</u> : Level 3, 10V/m, Criteria A. 80MHz-1000 MHz and 3V/m 1.4Ghz to 2.7 GHz. 80% AM at 1kHz. Also meets proposed IEC60601-1-2, 4 <sup>th</sup> edition, Table 4  |
| <b>Proximity Fields from RF wireless communications Equipment</b>      | [ <u>IEC60601-1-2</u> : 4 <sup>th</sup> edition, Table 4]  |
| <b>Rated Power Frequency magnetic fields</b>                           | <u>IEC61000-4-8</u> : Level 5, 30A/m, 50/60 Hz   |
| <b>Low Frequency magnetic fields</b>                                   | [TBD]  |
| <b>Electrical Fast Transients /Bursts</b>                              | <u>IEC61000-4-4</u> : Level 3, 2KV, 100Khz rep rate, 40A (PS Output), Criteria A<br><u>IEC61000-4-4</u> : Level 3, 1kV, 20A, (Other Outputs), Criteria B<br>Also meets proposed IEC60601-1-2, 4th edition standard, Table 5 & 6.   |
| <b>Surges Line to Line (DM) and Line to Ground (CM)</b>                | <u>IEC61000-4-5</u> : Level 3, +/-1kV DM, +/-2kV CM, Criteria A<br>Also meets proposed IEC60601-1-2, 4th edition standard, Table 5.  |
| <b>Conducted Disturbances induced by RF Fields</b>                     | <u>IEC61000-4-6</u> : 3V/m & 10 V/m – 0.15 to 80Mhz and 10V/m in ISM and amateur radio bands between 0.15 MHz and 80 MHz, 80% AM at 1 KHz<br>Also meets proposed IEC60601-1-2, 4th edition standard, Table 5 & 6 & 8.  |
| <b>Rated Power Frequency Magnetic Fields Test</b>                      | <u>IEC61000-4-8</u> : Level 4 (30A/m), Criteria A<br>Also meets proposed IEC60601-1-2, 4 <sup>th</sup> edition standard, Table 4 enclosure port.   |
| <b>Voltage Dips</b>  | <u>IEC61000-4-11</u> : 100% dip for 10mS, at 0°, 45°, 90°, 135°, 180°, 225°, 270° and 315°, Criteria A; 60% dip for 100mS, Criteria B; 30% dip for 500mS (25/30 cycles) 1Ø, and 0° for 500mS, Criteria A. Also meets proposed IEC60601-1-2, 4 <sup>th</sup> edition standard, Table 5. |
| <b>Enclosure Port Immunity to RF wireless communications equipment</b> | <u>IEC61000-4-3</u>  |


**Notes:** Performance criteria are based on definitions contained in EN55024. Performance criteria are:

A – Normal performance during and after the test, B – Temporary degradation, self-recoverable, C – Temporary degradation, operator intervention required to recover the operation, D – Permanent damage may occur

## Isolation Specifications

| Parameter                      | Conditions/Description | Min  | Nom    | Max | Units |
|--------------------------------|------------------------|------|--------|-----|-------|
| Insulation Safety Rating       | Input/Ground           |      | 1 MOPP |     |       |
|                                | Input/Output           |      | 2 MOPP |     |       |
|                                | Output/Ground          |      | 1 MOPP |     |       |
| Electric Strength Test Voltage | Input/Ground           | 1900 |        |     | Vac   |
|                                | Input/Output           | 4500 | -      | -   | Vac   |
|                                | Output/Ground          | 1900 |        |     | Vac   |


## Mechanical Drawing



## Connector Information


| Input Connector<br>J1   | DC Output<br>Connector<br>J2                                 | Ground Connector<br>G1             | Signal Connector<br>J3   |
|---|--|------------------------------------|--|
| PIN 1) AC Line<br>PIN 2) Empty (removed)<br>PIN 3) AC Neutral | Pin 1) (+V1)<br>Pin 2) (+V1)<br>Pin 3) (RTN)<br>Pin 4) (RTN) | FG<br>0.187" Quick-<br>connect tab | PIN 1) RTN<br>PIN 2) DC_OK<br>Pin 3) TEMP SENSOR (+)<br>Pin 4) TEMP SENSOR (-) |
| <u>Mating Connector:</u>                                      | <u>Mating Connector:</u>                                     | <u>Mating Connector:</u>           | <u>Mating Connector:</u>   |
| Tyco/AMP 640250-3<br>Pins: 640252-2                           | Tyco/AMP 640250-4<br>Pins: 640252-2                          | Molex 01-90020005                  | Tyco/AMP 1375820-4<br>Pins: 1375819  |

### 1.DC-OK signal (J-3):



During normal operation, this signal is logic HIGH for output more than 85% (typical) of normal. Signal will go LOW for output less than 80% (typical) of normal. Green LED will light on PCB top side during normal operation.

### 2. Temperature sensor signal (J-3):




#### Internal Temperature Sensor Conversion Table

| Resistance Value across connector J3,<br>pins 3-4 | Internal<br>Temperature |
|---|-------------------------|
| 6,040K ohms                                       | -20°C                   |
| 3,227K ohms                                       | -10°C                   |
| 1,788K ohms                                       | 0°C                     |
| 1,025K ohms                                       | 10°C                    |
| 605.1K ohms                                       | 20°C                    |
| 367.6K ohms                                       | 30°C                    |
| 229.2K ohms                                       | 40°C                    |
| 146.4K ohms                                       | 50°C                    |
| 95.62K ohms                                       | 60°C                    |
| 63.80K ohms                                       | 70°C                    |
| 43.40K ohms                                       | 80°C                    |
| 30.07K ohms                                       | 90°C                    |
| 21.19K ohms                                       | 100°C                   |

**Notes:** 1) Tolerances: -20°C to 60°C: +/- 4°C; 70°C to 80°C: +/- 5°C; 90°C to 100°C: +/- 6°C.

### 3. Timing Sequence



### 4. Protection

All specifications apply over specified input voltage, output load, and temperature range, unless otherwise noted.

| Parameter                   | Conditions/Description                          | Min | Nom | Max    | Units   |
|-----------------------------|---|-----|-----|--------|---------|
| Input Fuses                 | Not user accessible                             |     |     |        |         |
| Input Transient Protection  | 2KV(CM) and 1KV(DM) surge                       |     |     | 2      | KV (CM) |
| Output                      | No-load and short circuit proof                 |     |     | Hiccup |         |
|                             | short circuit proof                             |     |     | Hiccup |         |
|                             | overload  |     |     | Hiccup |         |
| Oversvoltage Protection     | Latch style                                     |     |     | Latch  |         |
| Over temperature Protection | Automatic power shutdown at TA = 80 °C(typical) |     |     |        |         |


### 5. Inrush Current, peak ( $I^2T$ rating)

Measured at 264Vac, 50°C at 100% loading, 70°C at de-rated load condition

| Model     | 50°C - $I^2T$ rating<br>(A <sup>2</sup> Seconds, Typical) | 70°C - $I^2T$ rating<br>(A <sup>2</sup> Seconds, Typical) |
|-----------|---|---|
| 12V Model | 8.5   | 11.0  |
| 15V Model | 6.5   | 13.2  |
| 24V Model | 10.9  | 12.2  |
| 48V Model | 10.4  | 11.1  |


## 6. Characteristic Curves

### 6.1 Output vs. Temperature



65W convection cooled at -20°C to 50°C operating ambient temperature. De-rated output power to 45.5W at 70°C.

### 6.2 Efficiency vs. Loading at AC Input Voltages




High efficiency is achieved by using QR technology. Synchronous MOSFETs or ultra-fast diodes are used as rectifiers in MB65S family.


### 6.3 Efficiency vs. Loading

The charts below detail the MB65 efficiency vs input voltage and output loading conditions at 25°C, 50°C and 70°C under de-rated power.

**25°C ambient**




**50°C Ambient**




**70°C**

**Ambient**




### 6.4 Ripple & Noise

Measured using a scope probe socket with 0.1µF ceramic and a 10µF electrolytic capacitor connected in parallel across it. Bandwidth limit is 20MHz.




12V OUT, NO LOAD, 85VAC, 60HZ




12V OUT, FULL LOAD, 85VAC, 60HZ



### 6.4 Ripple & Noise (Cont'd)





12V OUT, NO LOAD, 264VAC, 50HZ



12V OUT, FULL LOAD, 264VAC, 50HZ

### 6.5 Output Transient Response

50% load step within the regulation limits of minimum and maximum load,  $di/dt < 0.2A/\mu\text{Sec}$ . Recovery time not specified as there are no lapse in regulation with a 50% Load Step. Maximum voltage deviation is 3.5%




5%~50% Load Transient (AC) at 25°C@115V


50%~100% Load Transient(AC) at 25°C@115V

## 6.6 Output Overload Characteristic

Supply protects itself against overload conditions. The Power Supply recovers from Overload Conditions without operator intervention.




12v out, 100Vac




12V out, 240Vac

## 6.7 Turn-On Time



12v out, FULL Load, 115Vac



12V out, Full Load, 230Vac

Data Sheet © 2014 SL Power Electronics Corp. The information and specifications contained herein are believed to be correct at the time of publication. However, SL Power accepts no responsibility for consequences arising from reproduction errors or inaccuracies. Specifications are subject to change without notice.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.