

PRESS-TO-TEST INDICATORS

MEET OR EXCEED REQUIREMENTS OF
MIL-L-7961B and MIL-L-3661

QPL APPROVAL: The products indicated have received
Department of Defense certification and are listed as QPL approved.

PROVIDE POSITIVE SAFETY FACTORS



Positive safety factors are provided by patented built-in Press-To-Test indicators. Lamps can be checked instantly without removing them from their assembly.

A slight pressure on the lens holder of the assembly breaks the normal circuit and makes a test circuit, informing the operator as follows:

1. If the lamp LIGHTS when pressed in, it is proven satisfactory.
2. If the lamp FAILS TO LIGHT when pressed in, it is defective and must be replaced from the front of the panel.

Release of finger pressure restores the lens holder to operating position.

Press-To-Switch (4 terminal assemblies) are available with all indicators in this catalog. They are useful for remote control applications, as they permit closing the circuit to any local or remote device.

Typical Press-To-Test (3 terminal) and Press-To-Switch (4 terminal) circuit drawings are illustrated below.

Sub-Miniature, Miniature and Large Press-To-Test Indicators are available for mounting in 15/32", 5/8" and 1" clearance holes respectively. Only typical incandescent assemblies are listed in this catalog. Data on other Press-To-Test assemblies will be furnished on request.

Hot-stamped or engraved legends can be supplied on flat lenses only. Additional information will be furnished on request.

Typical
3 Terminal
Press-To-Test
Circuit



Typical
4 Terminal
Press-To-Switch
Circuit



PATENTED SHUTTER DIMMING ACTION



Shutters open
Maximum full direct
light beam



Shutters adjusted
Adjustable direct
light beam



Shutters closed
Minimum indirect
"halo" light

The patented shutter-dimming device is available on most Press-To-Test indicators. By turning the knurled cap, the individual operator can regulate the brilliancy of the light from the indicator to suit his needs under varying light conditions.

Standard dimmer action is clockwise. Assemblies with counter-clockwise dimming action are available on special order.

LENS COLORS

| | |
|------------------|---------------------|
| 1-Red | 5-White translucent |
| 2-Green | 6-Light yellow |
| 3-Yellow (amber) | 7-Clear colorless |
| 4-Blue | |

The digit before the last dash in the part number designates the lens color. When color other than RED is desired, change this digit to a figure noted above. Example: 812-1030-0972-506 (green)

Sub-Miniature Incandescent PRESS-TO-TEST Indicators

MILITARY STANDARD DRAWING MS25041 – 1 to 11

For back of panel mounting in 15/32" clearance hole
Meet or exceed requirements of MIL-L-7961B and MIL-L-3661



See lamp ratings
on page J.

800 SERIES
801 SERIES
808 SERIES
809 SERIES

MATERIALS AND FINISHES

- **Mounting Bushing and Lens Holder:** Aluminum, black anodize finish.
- **Mounting and Flange Nuts:** Aluminum, black anodize finish.
- **Internal-tooth Lockwasher:** Phosphor bronze, white nickel finish.
- **Terminals:** Brass, hot tinned with elongated slot.

Lens cap assembly marking: "Dim" with an arrow is die-stamped and filled on all Dimmer lens cap assemblies. "Press-To-Test" marking is die-stamped and filled on all lens cap assemblies used with 3 terminal units only.

BASE PART NUMBERS

| Cap type | Transparent lens color | CAP PART NUMBERS for use with | |
|--|------------------------|-------------------------------|-----------------------|
| | | 3 terminal assemblies | 4 terminal assemblies |
| <p>mechanical shutter semi-blackout dimming</p> <p>801 series</p> <p>809 series</p> | Clear (Colorless) | 801-0337-500 | 809-0337-500 |
| | Red | 801-0331-500 | 809-0331-500 |
| | Green | 801-0332-500 | 809-0332-500 |
| | Yellow (Amber) | 801-0333-500 | 809-0333-500 |
| | Blue | 801-0334-500 | 809-0334-500 |
| <p>non-dimming</p> <p>800 series</p> <p>808 series</p> | Clear (Colorless) | 800-0337-500 | 808-0337-500 |
| | Red | 800-0331-500 | 808-0331-500 |
| | Green | 800-0332-500 | 808-0332-500 |
| | Yellow (Amber) | 800-0333-500 | 808-0333-500 |
| | Blue | 800-0334-500 | 808-0334-500 |



801-1030-0331-504
Dimming



800-1030-0331-504
Non-Dimming

QPL LISTED

3 Terminal Press-To-Test Assemblies



max. panel thickness 5/16"

800-1030-03-504

4 Terminal Press-To-Switch Assemblies



max. panel thickness 5/16"

808-1130-03-504

COMPLETE ASSEMBLY PART NUMBERS

| Part number | MS number |
|-------------------|------------|
| 801-1030-0337-504 | MS25041-1 |
| 801-1030-0331-504 | MS25041-2 |
| 801-1030-0332-504 | MS25041-3 |
| 801-1030-0333-504 | MS25041-4 |
| 801-1030-0334-504 | MS25041-10 |
| 800-1030-0337-504 | MS25041-5 |
| 800-1030-0331-504 | MS25041-6 |
| 800-1030-0332-504 | MS25041-7 |
| 800-1030-0333-504 | MS25041-8 |
| 800-1030-0334-504 | MS25041-11 |

| Part number |
|-------------------|
| 809-1130-0337-504 |
| 809-1130-0331-504 |
| 809-1130-0332-504 |
| 809-1130-0333-504 |
| 809-1130-0334-504 |
| 808-1130-0337-504 |
| 808-1130-0331-504 |
| 808-1130-0332-504 |
| 808-1130-0333-504 |
| 808-1130-0334-504 |

Part numbers shown in gray are normally in inventory at your Dialight Distributor.

Order complete with lamp to be assured of receiving the indicator light and correct lamp together for immediate use.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.