

SERIES 07
SERIES 2000
SPST and SPDT, 10 Amp

FEATURES

- Momentary Contact
- Extremely Fast Make-and-Break
- Audible Click
- 25,000 Cycles of Operation



DIMENSIONS In Inches (and millimeters)

SPDT Solder Lug Terminal
07-26*

Dimensions:
 A = .273 ± .020 (6,93 ± 0,51)
 B = .454 ± .015 (11,53 ± 0,38)
 C = .796 ± .015 (20,22 ± 0,38)
 D = .443 ± .015 (11,25 ± 0,38)

Other dimensions:
 .312 ± .005 (7,92 ± 0,13)
 KEYWAY .068 (1,72) WIDE
 15/32-32 UNS-2A THREAD
 HEX MOUNTING NUTS (2) .094 ± .010 (2,39 ± 0,25) THICK
 .562 ± .010 (14,27 ± 0,25) ACROSS FLATS
 .95 (24,13) MAX. OVER PIN HEADS
 .880 ± .010 DIA. (22,35 ± 0,25)

*PART NUMBER AND E.I.A. DATE CODE LABEL

SPST-Solder Lug Terminals

2201
2202
07-7
07-8

1.903 (48,34) REF.

Labels: LABEL*, .380 ± .015 (9,65 ± 0,38)

*PART NUMBER AND E.I.A. DATE CODE LABEL

All dimensions not shown are same as part no. 7-26.

SPST-Faston Terminals

07-21
07-22

1.910 (48,51) REF.




Labels: LABEL*, .387 ± .015 (9,83 ± 0,38)

*PART NUMBER AND E.I.A. DATE CODE LABEL

TERMINALS TO ACCOMMODATE 1/4 INCH PUSH-ON TERMINATION

All dimensions not shown are same as part no. 7-26.

CIRCUITRY



SPECIFICATIONS

Rating Criteria

Rated: To make and break 10 Amps at 115 Vac, or 5 Amps at 220 Vac resistive load for 25,000 operations
Contact Resistance: 25 milliohms or less on a new switch
Voltage Breakdown: 1,000 Vac between mutually insulated parts
Insulation Resistance: 1,000 megohms minimum

Operating Features

Total Button Travel: .065 (1,65) approximately
Overtravel: .008 (0,20) approximately
Actuating Force: 24 ounces approximately
Mounting Hole: 31/64" (12,30) inches
Terminal Type: Solder Lug/Faston
Operating Temperature: -40°C to +85°C

Available from your local Grayhill Distributor. For prices and discounts, contact a local Sales Office, an authorized local Distributor or Grayhill.

Materials and Finishes

Housing, Button and Internal Bridge: Thermoset plastic
Mounting Nuts, Bushings, and Internal Bracket: Brass, tin zinc
Fixed and Moving Contacts: Fine silver
Internal Spring, Link and Contact Carrier: Beryllium, copper
Cover-to-Base Mounting Pins: Brass
Faston Terminals: Brass, tin over nickel
Solder Lug Terminals: Brass, zinc trivalent chromate-plated

ACCESSORIES



ORDERING INFORMATION

*Part Number	Description		
	Circuitry	Button	Terminal
2201	SPST-N.O.	Red	Solder
07-7	SPST-N.O.	Black	Solder
07-21	SPST-N.O.	Red	Faston
2202	SPST-N.C.	Black	Solder
07-8	SPST-N.C.	Red	Solder
07-22	SPST-N.C.	Black	Faston
07-26 RED	SPDT-BBM	Red	Solder
07-26 BLK	SPDT-BBM	Black	Solder

Part Number	Accessory Description
07Z1047-1 BLK	Black Button Cap
07Z1047-2 RED	Red Button Cap
07C1040-1	Decorative Nut
10C1015-1	Button Guard



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.