

## Features


- IEC 61000-4-2 (ESD): Air  $\pm 20\text{kV}$ , Contact  $\pm 18\text{kV}$
- 4 Channels of ESD Protection
- Low Channel Input Capacitance of  $0.65\text{pF}$  Typical
- Typically Used at High Speed Ports such as USB 2.0, IEEE1394, Serial ATA, DVI, HDMI, PCI
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**

## Mechanical Data


- Case: SOT363
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Matte Tin Finish annealed over Alloy 42 leadframe (Lead Free Plating). Solderable per MIL-STD-202, Method 208 (e3)
- Weight: 0.006 grams (approximate)



Top View



Device Pinout



Device Schematic


## Ordering Information (Note 4)

Part Number	Case	Packaging
DT2636-04S-7	SOT363	3000/Tape & Reel

Notes:

1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
2. See [http://www.diodes.com/quality/lead\\_free.html](http://www.diodes.com/quality/lead_free.html) for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. For packaging details, go to our website at <http://www.diodes.com/products/packages.html>.

## Marking Information



BD4 = Product Type Marking Code  
 YM = Date Code Marking  
 Y = Year (ex: A = 2013)  
 M = Month (ex: 9 = September)

### Date Code Key

Year	2013	2014	2015	2016	2017	2018	2019					
Code	A	B	C	D	E	F	G					
Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

**Maximum Ratings (@ $T_A = +25^\circ\text{C}$ , unless otherwise specified)**

Characteristic	Symbol	Value	Unit	Conditions
Peak Pulse Current	$I_{PP}$	6.5	A	8/20 $\mu\text{s}$ , From CH to GND
Peak Pulse Current	$I_{PP}$	6.5	A	8/20 $\mu\text{s}$ , From GND to CH
Peak Pulse Power	$P_{PP}$	60	W	8/20 $\mu\text{s}$ , From CH to GND
ESD Protection – Contact Discharge	$V_{ESD\_Contact}$	$\pm 18$	kV	Standard IEC 61000-4-2
ESD Protection – Air Discharge	$V_{ESD\_Air}$	$\pm 20$	kV	Standard IEC 61000-4-2
Operating Temperature	$T_{OP}$	-55 to +85	$^\circ\text{C}$	—
Storage Temperature	$T_{STG}$	-55 to +150	$^\circ\text{C}$	—

**Thermal Characteristics**

Characteristic	Symbol	Value	Unit
Power Dissipation Typical (Note 5)	$P_D$	200	mW
Thermal Resistance, Junction to Ambient Typical (Note 5)	$R_{\theta JA}$	625	$^\circ\text{C}/\text{W}$

**Electrical Characteristics (@ $T_A = +25^\circ\text{C}$ , unless otherwise specified)**

Characteristic	Symbol	Min	Typ	Max	Unit	Test Conditions
Reverse Standoff Voltage	$V_{RWM}$	—	—	5.5	V	—
Channel Leakage Current (Note 6, 7)	$I_R$	—	1	10	nA	$V_R = 2.5\text{V}$
Reverse Breakdown Voltage	$V_{BR}$	7.0	—	9.5	V	$I_R = 1\text{mA}$ , from CH to GND
Clamping Voltage, Positive Transients	$V_{CL1}$	—	6.8	—	V	$I_{PP} = 1\text{A}$ , $t_p = 8/20\mu\text{s}$
Clamping Voltage, Positive Transients	$V_{CL1}$	—	9	—	V	$I_{PP} = 5\text{A}$ , $t_p = 8/20\mu\text{s}$
Clamping Voltage, Negative Transients	$V_{CL2}$	—	1.5	—	V	$I_{PP} = 1\text{A}$ , $t_p = 8/20\mu\text{s}$
Forward Voltage	$V_F$	—	0.7	—	V	$I_F = 1\text{mA}$ , GND to CH
Dynamic Resistance	$R_{\text{DIFF}}$	—	0.4	—	$\Omega$	$I_{PP} = 1\text{A}$ , $t_p = 8/20\mu\text{s}$ , CH to GND
Dynamic Resistance	$R_{\text{DIFF-R}}$	—	0.45	—	$\Omega$	TLP, 20A, $t_p = 100\text{ ns}$ , CH to GND
Dynamic Resistance	$R_{\text{DIFF-F}}$	—	0.2	—	$\Omega$	TLP, 20A, $t_p = 100\text{ ns}$ , GND to CH
CH to GND Capacitance	$C_{(\text{CH-GND})}$	—	0.75	—	pF	$V_{(\text{CH-GND})} = 0\text{V}$ , $f = 1\text{MHz}$
		—	0.65	0.9	pF	$V_{(\text{CH-GND})} = 2.5\text{V}$ , $f = 1\text{MHz}$
Delta $C_{\text{CH}}$	$C_{\text{CHMAX}} - C_{\text{CHMIN}}$	—	0.04	—	pF	$C_{\text{CHMAX}} - C_{\text{CHMIN}}$

Notes:

- 5. Device mounted on FR-4 PCB pad layout (2oz copper) as shown on Diodes, Inc. suggested pad layout AP02001, which can be found on our website at <http://www.diodes.com>.
- 6. Short duration pulse test used to minimize self-heating effect.
- 7. Measured from pin 1, 2, 4 and 5 to GND.




Figure 1 Pulse Derating Curve




Figure 2 BV, Trigger Voltage, Holding Voltage vs. Ambient Temperature




Figure 3 Clamping Voltage Characteristic




Figure 4 Waveform of Clamping Voltage, Current vs. Time (8/20μs, CH to V<sub>SS</sub>)




Figure 5 Input Capacitance vs. Input Voltage





Figure 6 Current vs. Voltage


## Package Outline Dimensions

Please see AP02002 at <http://www.diodes.com/datasheets/ap02002.pdf> for latest version.



## Suggested Pad Layout

Please see AP02001 at <http://www.diodes.com/datasheets/ap02001.pdf> for the latest version.



**IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

**LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

- A. Life support devices or systems are devices or systems which:
  1. are intended to implant into the body, or
  2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.
- B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2013, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

#### Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: [org@eplast1.ru](mailto:org@eplast1.ru)

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литер A.