

8787 Multi-Conductor - Special Audio, Communication and Instrumentation Cable



For more Information
please call

1-800-Belden1

**Description:**

24 and 22 AWG stranded (7x32 and 7x30) TC conductors, PVC insulation (22 AWG) / polyethylene insulation (24 AWG), cabled in quads, 24 AWG stranded TC drain wire, PVC jacket.

Physical Characteristics (Overall)**Conductor****AWG:**

# Conductors	AWG	Stranding	Conductor Material
8	24	7x32	TC - Tinned Copper
2	22	7x30	TC - Tinned Copper

Total Number of Conductors: 10

Insulation**Insulation Material:**

Insulation Material	Wall Thickness (in.)	AWG
PE - Polyethylene	.012	24
PVC - Polyvinyl Chloride	.015	22

Insulation Resistance: 100 Megaohms/1000 ft. @ 500 V DC

Inner Shield**Inner Shield Material:**

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil® (Z-Fold®)	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Material (Multi-AWG):

AWG	Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)	Description
24	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100	Over Quad
24	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100	Over Quad
22			Unshielded		Singles

Inner Shield Drain Wire AWG:

AWG
24

Inner Shield Drain Wire Stranding: 7x32

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

Inner Shield Waterblocking Tape: Gray, White, Blue, Green; Brown, Red, Yellow, Orange; White, Blue

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	.030

Overall Cable**Overall Cabling Color Code Chart:**

Number	Color	AWG	Group/Cond. Color
1	Red Quad	24	Red Quad
2	White	22	White
3	Green Quad	24	Green Quad
4	Blue	22	Blue

8787 Multi-Conductor - Special Audio, Communication and Instrumentation Cable

Overall Nominal Diameter: 0.290 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +80°C

Non-UL Temperature Rating: 80°C

Bulk Cable Weight: 45 lbs/1000 ft.

Max. Recommended Pulling Tension: 62.200 lbs.

Min. Bend Radius/Minor Axis: 3 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Flame Test

UL Flame Test: VW-1, UL1685 UL Loading

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)**Nom. Conductor DC Resistance:**

Description	DCR @ 20°C (Ohm/1000 ft)
24 AWG	23.9
22 AWG	15

Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
5

Max. Operating Voltage - Non-UL:

Voltage
350 V RMS

Max. Recommended Current:

Current
1.5 Amps per conductor @ 25°C (24 AWG); 2.0 Amps per conductor @ 25°C (22 AWG)

Notes (Overall)

Notes: Inner Beldfoil® shield over 24 AWG quads. Each quad wrapped in transparent polyester tape. Red Beldfoil® shield over one quad, Green Beldfoil® shield over the other. (2) quads and (2) unshielded conductors cabled.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8787 060U500	500 FT	24.000 LB	CHROME		2 #22, 8 #24 FS PVC
8787 060500	500 FT	24.000 LB	CHROME	C	2 #22, 8 #24 FS PVC

Notes:

C = CRATE REEL PUT-UP.

8787 Multi-Conductor - Special Audio, Communication and Instrumentation Cable

Revision Number: 1 Revision Date: 08-27-2012

© 2012 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.