
Rectifier diodes ultrafast, rugged

BYV79E series

FEATURES

- Low forward volt drop
- Fast switching
- Soft recovery characteristic
- Reverse surge capability
- High thermal cycling performance
- Low thermal resistance

SYMBOL



QUICK REFERENCE DATA

V_R = 150 V/ 200 V

$V_F \leq 0.9$ V

$I_{F(AV)}$ = 14 A

$I_{RRM} \leq 0.2$ A

$t_{rr} \leq 30$ ns

GENERAL DESCRIPTION


Ultra-fast, epitaxial rectifier diodes intended for use as output rectifiers in high frequency switched mode power supplies.

The BYV79E series is supplied in the conventional leaded SOD59 (TO220AC) package.

PINNING

PIN	DESCRIPTION
1	cathode
2	anode
tab	cathode

SOD59 (TO220AC)



LIMITING VALUES

Limiting values in accordance with the Absolute Maximum System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.		UNIT
		BYV79E		**-150**	**-200**	
V_{RRM}	Peak repetitive reverse voltage		-	150	200	V
V_{RWM}	Crest working reverse voltage		-	150	200	V
V_R	Continuous reverse voltage	$T_{mb} \leq 145$˚C	-	150	200	V
$I_{F(AV)}$	Average forward current[1]	square wave $\delta = 0.5$; $T_{mb} \leq 120$ ˚C	-	14		A
I_{FRM}	Repetitive peak forward current	t = 25 µs; $\delta = 0.5$; $T_{mb} \leq 120$ ˚C	-	28		A
I_{FSM}	Non-repetitive peak forward current	t = 10 ms	-	150		A
		t = 8.3 ms sinusoidal; with reapplied $V_{RWM(max)}$	-	160		A
I_{RRM}	Repetitive peak reverse current	t_p = 2 µs; $\delta = 0.001$	-	0.2		A
I_{RSM}	Non-repetitive peak reverse current	t_p = 100 µs	-	0.2		A
T_{stg}	Storage temperature		-40	150		˚C
T_j	Operating junction temperature		-	150		˚C

1. Neglecting switching and reverse current losses.

ESD LIMITING VALUE

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_C	Electrostatic discharge capacitor voltage	Human body model; C = 250 pF; R = 1.5 kΩ	-	8	kV

THERMAL RESISTANCES

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$R_{th\ j\text{-}mb}$	Thermal resistance junction to mounting base		-	-	2	K/W
$R_{th\ j\text{-}a}$	Thermal resistance junction to ambient	in free air	-	60	-	K/W

STATIC CHARACTERISTICS

T_j = 25 ˚C unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_F	Forward voltage	I_F = 14 A; T_j = 150˚C	-	0.83	0.90	V
		I_F = 14 A	-	0.95	1.05	V
		I_F = 50 A	-	1.2	1.4	V
I_R	Reverse current	$V_R = V_{RWM}$; T_j = 100 ˚C	-	0.5	1.3	mA
		$V_R = V_{RWM}$	-	5	50	µA
Q_s	Reverse recovery charge	I_F = 2 A; $V_R \geq$ 30 V; $-dI_F/dt$ = 20 A/µs	-	6	15	nC
t_{rr1}	Reverse recovery time	I_F = 1 A; $V_R \geq$ 30 V; $-dI_F/dt$ = 100 A/µs	-	20	30	ns
t_{rr2}	Reverse recovery time	I_F = 0.5 A to I_R = 1 A; I_{rec} = 0.25 A	-	13	22	ns
V_{fr}	Forward recovery voltage	I_F = 1 A; dI_F/dt = 10 A/µs	-	1	-	V




Fig.1. Definition of t_{rr1}, Q_s and I_{rrm}




Fig.2. Definition of V_{fr}




Fig.3. Circuit schematic for t_{rr2}




Fig.4. Definition of t_{rr2}




Fig.5. Maximum forward dissipation $P_F = f(I_{F(AV)})$; square current waveform where $I_{F(AV)} = I_{F(RMS)} \times \sqrt{D}$.




Fig.6. Maximum forward dissipation $P_F = f(I_{F(AV)})$; sinusoidal current waveform where a = form factor = $I_{F(RMS)} / I_{F(AV)}$.




Fig.7. Maximum t_{rr} at T_j = 25 ˚C.




Fig.10. Maximum Q_s at T_j = 25 ˚C.




Fig.8. Maximum I_{rrm} at T_j = 25 ˚C.




Fig.11. Transient thermal impedance; $Z_{th\ j\text{-}mb} = f(t_p)$.




Fig.9. Typical and maximum forward characteristic $I_F = f(V_F)$; parameter T_j

MECHANICAL DATA

Dimensions in mm

Net Mass: 2 g




Fig.12. SOD59 (TO220AC). pin 1 connected to mounting base.

Notes
1. Refer to mounting instructions for TO220 envelopes.
2. Epoxy meets UL94 V0 at 1/8".

DEFINITIONS

Data sheet status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	
© **Philips Electronics N.V. 1998**	
All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.	
The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.