

13

12

11

10

9

8

7

6

5

4

3

2

1

J

I

H

G

F

E

D

C

B

A

J

I

H

G

F

E

D

C

B

A

NOTES:

1) MATERIALS:

HOUSING- LCP, GLASS FILLED, 94V-0, BLACK.

TERMINALS- COPPER ALLOY

METAL PEGS- COPPER ALLOY

2) FINISH:

TERMINALS:

.000030/(0.00076) MINIMUM GOLD IN CONTACT AREA OVER

.000050/(0.00127) MINIMUM TIN IN TAIL AREA OVER

.000075/(0.00191) MINIMUM NICKEL UNDERPLATE OVERALL.





3) ASSEMBLY MATES WITH MOLEX P/N SDA-71661-****.

4) CONFORMS TO PRODUCT SPECIFICATION PS-71660.

△5 CENTER PEG IS ONLY ON 120 AND 130 CIRCUIT ASSEMBLIES.

△6 TAIL LENGTH ON FIRST MATE CONTACTS IS APPROXIMATELY
.010 INCH/0.25 MM SHORTER THAN THE TAIL LENGTH SPECIFIED.△7 CONNECTOR WILL ACCEPT MATING TO A P.C. BOARD WITH
A THICKNESS OF .062±.003.△8 FOUR DIGIT DATE CODE (WK YR), EXAMPLE => 26 96
LOCATED IN AREA INDICATED.

△9 SEE CHART FOR PACKAGING INFORMATION.

60 CIRCUIT ASSEMBLY SHOWN
SCALE 2:1

3	0
2	0
1	0
SHT	REV

UPDATE BORDER EC NO: UCP2007-0935 DRAWN BY: 2006/11/06 CHKD: MIBARRA 2006/11/06 APPR: SMILLER 2006/11/07 REV:			QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE 4:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	
		mm		INCH	DRAWN BY	DATE	SALES ASSEMBLY MOLEX EBBI 50D VERTICAL RECEPTACLE CONNECTOR				
		4 PLACES ± ---		± ---	RAN	6/15/92					
		3 PLACES ± ---		± .005	CHECKED BY	DATE	MOLEX INCORPORATED				
		2 PLACES ± 0.13		± .010	RAN	6/15/92					
		1 PLACE ± 0.25		± ---	APPROVED BY	DATE	SDA-71660-1***				
		ANGULAR ± 1/2°		CAB	6/15/92						
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO.		DOCUMENT NO.		SHEET NO.			
				SEE TABLE				1 OF 3			
				THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION							

12

11

10

9

8

7

6

5

4

3

2

1

13

12

11

10

9

8

7

6




5

4

3


2

1



SECTION X-X
SCALE - 8:1

RECOMMENDED PC BOARD LAYOUT COMPONENT SIDE



UPDATE BORDER EC NO: UCP2007-0935 DRWN: BARKER 2006/11/06 CHKD: MIBARRA 2006/11/06 APPR: SMILLER 2006/11/07	QUALITY SYMBOLS ▽=0 ▽=0	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION				
					IN/MM		4:1	INCH					
REV			DRAWN BY		DATE		TITLE						
			4 PLACES ± --- ± ---		RAN		6/15/92		SALES ASSEMBLY				
			3 PLACES ± --- ± .005		CHECKED BY		DATE		MOLEX EBBI 50D VERTICAL				
			2 PLACES ± 0.13 ± .010		RAN		6/15/92		RECEPTACLE				
			1 PLACE ± 0.25 ± ---		APPROVED BY		DATE		MOLEX MOLEX INCORPORATED				
			ANGULAR ± 1/2°		CAB		6/15/92		MOLEX INCORPORATED				
			DRAFT WHERE APPLICABLE		MATERIAL NO.		DOCUMENT NO.		SHEET NO.				
			MUST REMAIN		SEE CHART		SDA-71660-1***		2 OF 3				
			WITHIN DIMENSIONS		SIZE		C		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				

12

11

10

9

8

7

6


5

4

3

2

1



ENGINEERING NUMBER	EDP NUMBER	PACKAGING SPEC	CKT (*N*)	A	B	C	D	P	ADVANCED TERMINALS / CKTS SEE SECTION X-X *FMLB OPT*
SDA-7 I660- I030	0 I5-92- I030	PK-7 I660	30	.700 (17.78)	.918 (23.32)	1.199 (30.45)	1.092 (27.75)	.134 (3.40)	N/A
SDA-7 I660- I040	0 I5-92- I040	PK-7 I660	40	.950 (24.13)	1.168 (29.67)	1.449 (36.80)	1.342 (34.10)		
SDA-7 I660- I050	0 I5-92- I050	PK-7 I660	50	1.200 (30.48)	1.418 (36.02)	1.699 (43.15)	1.592 (40.45)		
SDA-7 I660- I060	0 I5-92- I060	PK-7 I660	60	1.450 (36.83)	1.668 (42.37)	1.949 (49.50)	1.842 (46.80)		
SDA-7 I660- I068	0 I5-92- I068	PK-7 I660	68	1.650 (41.91)	1.868 (47.45)	2.149 (54.58)	2.042 (51.88)		
SDA-7 I660- I080	0 I5-92- I080	PK-7 I660	80	1.950 (49.53)	2.168 (55.07)	2.449 (62.20)	2.342 (59.50)		
SDA-7 I660- I100	0 I5-92- I100	PK-7 I660	100	2.450 (62.23)	2.668 (67.77)	2.949 (74.90)	2.842 (72.20)		
SDA-7 I660- I120	0 I5-92- I120	PK-7 I660	120	2.950 (74.93)	3.168 (80.47)	3.449 (87.60)	3.342 (84.90)		
SDA-7 I660- I130	0 I5-92- I130	PK-7 I660	130	3.200 (81.28)	3.418 (86.82)	3.699 (93.95)	3.592 (91.25)	.110 (2.79)	N/A
SDA-7 I660- I330	0 I5-92- I430	PK-7 I660	30	.700 (17.78)	.918 (23.32)	1.199 (30.45)	1.092 (27.75)		
SDA-7 I660- I340	0 I5-92- I440	PK-7 I660	40	.950 (24.13)	1.168 (29.67)	1.449 (36.80)	1.342 (34.10)		
SDA-7 I660- I350	0 I5-92- I450	PK-7 I660	50	1.200 (30.48)	1.418 (36.02)	1.699 (43.15)	1.592 (40.45)		
SDA-7 I660- I360	0 I5-92- I460	PK-7 I660	60	1.450 (36.83)	1.668 (42.37)	1.949 (49.50)	1.842 (46.80)		
SDA-7 I660- I368	0 I5-92- I468	PK-7 I660	68	1.650 (41.91)	1.868 (47.45)	2.149 (54.58)	2.042 (51.88)		
SDA-7 I660- I380	0 I5-92- I480	PK-7 I660	80	1.950 (49.53)	2.168 (55.07)	2.449 (62.20)	2.342 (59.50)		
SDA-7 I660- I400	0 I5-92- I500	PK-7 I660	100	2.450 (62.23)	2.668 (67.77)	2.949 (74.90)	2.842 (72.20)		
SDA-7 I660- I40 I	0 I5-92- I50 I	PK-70873-08 I6	100	2.450 (62.23)	2.668 (67.77)	2.949 (74.90)	2.842 (72.20)	.134 (3.40)	2-4, 8-11, 14, 17, 20, 23, 26-29, 31, 32, 34, 36, 39, 42, 45, 48, 49
SDA-7 I660- I420	0 I5-92- I520	PK-7 I660	120	2.950 (74.93)	3.168 (80.47)	3.449 (87.60)	3.342 (84.90)		
SDA-7 I660- I430	0 I5-92- I530	PK-7 I660	130	3.200 (81.28)	3.418 (86.82)	3.699 (93.95)	3.592 (91.25)		
SDA-7 I660- I550	0 I5-92- I550	PK-7 I660	50	1.200 (30.48)	1.418 (36.02)	1.699 (43.15)	1.592 (40.45)		
SDA-7 I660- I630	7 I660 I630	PK-7 I660	30	.700 (17.78)	.918 (23.32)	1.199 (30.45)	1.092 (27.75)	.155 (3.94)	N/A
SDA-7 I660- I640	7 I660 I640	PK-7 I660	40	.950 (24.13)	1.168 (29.67)	1.449 (36.80)	1.342 (34.10)		
SDA-7 I660- I650	7 I660 I650	PK-7 I660	50	1.200 (30.48)	1.418 (36.02)	1.699 (43.15)	1.592 (40.45)		
SDA-7 I660- I660	7 I660 I660	PK-7 I660	60	1.450 (36.83)	1.668 (42.37)	1.949 (49.50)	1.842 (46.80)		
SDA-7 I660- I668	7 I660 I668	PK-7 I660	68	1.650 (41.91)	1.868 (47.45)	2.149 (54.58)	2.042 (51.88)		
SDA-7 I660- I680	7 I660 I680	PK-7 I660	80	1.950 (49.53)	2.168 (55.07)	2.449 (62.20)	2.342 (59.50)		
SDA-7 I660- I700	7 I660 I700	PK-7 I660	100	2.450 (62.23)	2.668 (67.77)	2.949 (74.90)	2.842 (72.20)		
SDA-7 I660- I720	7 I660 I720	PK-7 I660	120	2.950 (74.93)	3.168 (80.47)	3.449 (87.60)	3.342 (84.90)		
SDA-7 I660- I730	7 I660 I730	PK-7 I660	130	3.200 (81.28)	3.418 (86.82)	3.699 (93.95)	3.592 (91.25)		

UPDATE BORDER
EC NO: UCP2007-0935
DRAWN BY: 2006/11/06
CHKD: 2006/11/06
APPR: MILLER
REV

DESCRIPTION
2006/11/07

QUALITY SYMBOLS
▽=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)
mm INCH
4 PLACES ± --- ± ---
3 PLACES ± --- ± .005
2 PLACES ± 0.13 ± .010
1 PLACE ± 0.25 ± ---
ANGULAR ±1/2°

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

DIMENSION STYLE
IN/MM

DRAWN BY DATE
RAN 6/15/92

CHECKED BY DATE
RAN 6/15/92

APPROVED BY DATE
CAB 6/15/92

MATERIAL NO.

SIZE
C

SCALE
4:1

DESIGN UNITS
INCH

THIRD ANGLE PROJECTION

SALES ASSEMBLY
MOLEX EBBI 50D VERTICAL
RECEPTACLE

MOLEX INCORPORATED

SDA-71660-1****

SHEET NO.
3 OF 3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX
INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.