
# RoHS Pb HF UltraMOV™ Varistor Series



## Agency Approvals

| Agency | Agency File Number |
|---|---|
| | E320116 |
| | 116895 |
| | LR91788 |
| | 42201-006 |

## Description

The UltraMOV™ Metal Oxide Varistor Series is designed for applications requiring high peak surge current ratings and high energy absorption capability. UltraMOV™ varistors are primarily intended for use in AC Line Voltage applications such as Transient Voltage Surge Suppressors (TVSS), Uninterruptable Power Supplies (UPS), AC Power Taps, AC Power Meters, or other products that require voltage clamping of high transient surge currents from sources such as lightning, inductive load switching, or capacitor bank switching.

These devices are produced in radial lead package sizes of 7, 10, 14 and 20mm and offered in a variety of lead forms. UltraMOVs™ are manufactured with recognized epoxy encapsulation and are rated for ambient temperatures up to 85°C with no derating. This Series is LASER-branded and is supplied in bulk, ammo pack (fan-fold), or tape and reel packaging.

## Features

- Lead–free, Halogen-Free and RoHS compliant.
- High peak surge current rating ($I_{TM}$) up to 10kA, single 8 x 20 pulse, (20mm)
- Standard operating voltage range compatible with common AC line voltages (130 $V_{AC}$ to 625 $V_{AC}$)
- Characterized for maximum standby current (Leakage)
- Custom voltage types available
- Standard lead form and lead space options

ULTRAMOV™ Series

## Absolute Maximum Ratings

• For ratings of individual members of a series, see Device Ratings and Specifications chart

| Continuous | UltraMOV™ Series | Units |
|---|---|---|
| Steady State Applied Voltage: | | |
| DC Voltage Range ($V_{M(AC)RMS}$) | 130 to 625 | V |
| Transients: | | |
| Single-Pulse Peak Current ($I_{TM}$) 8x20μs Wave (See Figure 2) | 1,750 to 10,000 | A |
| Single-Pulse Energy Range ($W_{TM}$) 2ms Square Wave | 12.5 to 400 | J |
| Operating Ambient Temperature Range ($T_A$) | -55 to +85 | °C |
| Storage Temperature Range ($T_{STG}$) | -55 to +125 | °C |
| Temperature Coefficient ($a^V$) of Clamping Voltage ($V_C$) at Specified Test Current | <0.01 | %/°C |
| Hi-Pot Encapsulation (COATING Isolation Voltage Capability) | 2500 | V |
| COATING Insulation Resistance | 1000 | MΩ |

*CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.*

©2012 Littelfuse, Inc.
Specifications are subject to change without notice.
Please refer to www.littelfuse.com/series/tmov.html for current information.

## UltraMOV™ Series Ratings & Specifications

| Part Number | Branding | Maximum Rating (85°C) | | | | | Specifications (25°C) | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Continuous | | Transient | | | Varistor Voltage at 1mA DC Test Current | | Maximum Clamping Voltage 8 x 20μs | | Typical Capacitance |
| | | RMS Volts | DC Volts | Energy 2ms | Peak Current 8 x 20μs | | | | | | |
| | | $V_{M(AC)}$ | $V_{M(DC)}$ | $W_{TM}$ | $I_{TM}$ 1 x Pulse | $I_{TM}$ 2 x Pulse | $V_{NOM}$ Min | $V_{NOM}$ Max | $V_C$ | $I_{PK}$ | $f$ = 1MHz |
| | | (V) | (V) | (J) | (A) | (A) | (V) | (V) | (V) | (A) | (pF) |
| V07E130P | P7V130 | 130 | 170 | 12.5 | 1750 | 1200 | 184 | 226 | 340 | 10 | 180 |
| V10E130P | P10V130 | 130 | 170 | 25 | 3500 | 2500 | 184 | 226 | 340 | 25 | 450 |
| V14E130P | P14V130 | 130 | 170 | 50 | 6000 | 4500 | 184 | 226 | 340 | 50 | 1000 |
| V20E130P | P20V130 | 130 | 170 | 100 | 10000 | 6500 | 184 | 226 | 340 | 100 | 1900 |
| V07E140P | P7V140 | 140 | 180 | 13.5 | 1750 | 1200 | 200 | 240 | 360 | 10 | 160 |
| V10E140P | P10V140 | 140 | 180 | 27.5 | 3500 | 2500 | 200 | 240 | 360 | 25 | 400 |
| V14E140P | P14V140 | 140 | 180 | 55 | 6000 | 4500 | 200 | 240 | 360 | 50 | 900 |
| V20E140P | P20V140 | 140 | 180 | 110 | 10000 | 6500 | 200 | 240 | 360 | 100 | 1750 |
| V07E150P | P7V150 | 150 | 200 | 15 | 1750 | 1200 | 216 | 264 | 395 | 10 | 150 |
| V10E150P | P10V150 | 150 | 200 | 30 | 3500 | 2500 | 216 | 264 | 395 | 25 | 360 |
| V14E150P | P14V150 | 150 | 200 | 60 | 6000 | 4500 | 216 | 264 | 395 | 50 | 800 |
| V20E150P | P20V150 | 150 | 200 | 120 | 10000 | 6500 | 216 | 264 | 395 | 100 | 1600 |
| V07E175P | P7V175 | 175 | 225 | 17 | 1750 | 1200 | 243 | 297 | 455 | 10 | 130 |
| V10E175P | P10V175 | 175 | 225 | 35 | 3500 | 2500 | 243 | 297 | 455 | 25 | 350 |
| V14E175P | P14V175 | 175 | 225 | 70 | 6000 | 4500 | 243 | 297 | 455 | 50 | 700 |
| V20E175P | P20V175 | 175 | 225 | 135 | 10000 | 6500 | 243 | 297 | 455 | 100 | 1400 |
| V07E230P | P7V230 | 230 | 300 | 20 | 1750 | 1200 | 324 | 396 | 595 | 10 | 100 |
| V10E230P | P10V230 | 230 | 300 | 42 | 3500 | 2500 | 324 | 396 | 595 | 25 | 250 |
| V14E230P | P14V230 | 230 | 300 | 80 | 6000 | 4500 | 324 | 396 | 595 | 50 | 550 |
| V20E230P | P20V230 | 230 | 300 | 160 | 10000 | 6500 | 324 | 396 | 595 | 100 | 1100 |
| V07E250P | P7V250 | 250 | 320 | 25 | 1750 | 1200 | 351 | 429 | 650 | 10 | 90 |
| V10E250P | P10V250 | 250 | 320 | 50 | 3500 | 2500 | 351 | 429 | 650 | 25 | 220 |
| V14E250P | P14V250 | 250 | 320 | 100 | 6000 | 4500 | 351 | 429 | 650 | 50 | 500 |
| V20E250P | P20V250 | 250 | 320 | 170 | 10000 | 6500 | 351 | 429 | 650 | 100 | 1000 |
| V07E275P | P7V275 | 275 | 350 | 28 | 1750 | 1200 | 387 | 473 | 710 | 10 | 80 |
| V10E275P | P10V275 | 275 | 350 | 55 | 3500 | 2500 | 387 | 473 | 710 | 25 | 200 |
| V14E275P | P14V275 | 275 | 350 | 110 | 6000 | 4500 | 387 | 473 | 710 | 50 | 450 |
| V20E275P | P20V275 | 275 | 350 | 190 | 10000 | 6500 | 387 | 473 | 710 | 100 | 900 |
| V07E300P | P7V300 | 300 | 385 | 30 | 1750 | 1200 | 423 | 517 | 775 | 10 | 70 |
| V10E300P | P10V300 | 300 | 385 | 60 | 3500 | 2500 | 423 | 517 | 775 | 25 | 180 |
| V14E300P | P14V300 | 300 | 385 | 125 | 6000 | 4500 | 423 | 517 | 775 | 50 | 400 |
| V20E300P | P20V300 | 300 | 385 | 250 | 10000 | 6500 | 423 | 517 | 775 | 100 | 800 |
| V07E320P | P7V320 | 320 | 420 | 32 | 1750 | 1200 | 459 | 561 | 840 | 10 | 65 |
| V10E320P | P10V320 | 320 | 420 | 67 | 3500 | 2500 | 459 | 561 | 840 | 25 | 170 |
| V14E320P | P14V320 | 320 | 420 | 136 | 6000 | 4500 | 459 | 561 | 840 | 50 | 380 |
| V20E320P | P20V320 | 320 | 420 | 273 | 10000 | 6500 | 459 | 561 | 840 | 100 | 750 |
| V07E385P | P7V385 | 385 | 505 | 36 | 1750 | 1200 | 558 | 682 | 1025 | 10 | 60 |
| V10E385P | P10V385 | 385 | 505 | 75 | 3500 | 2500 | 558 | 682 | 1025 | 25 | 160 |
| V14E385P | P14V385 | 385 | 505 | 150 | 6000 | 4500 | 558 | 682 | 1025 | 50 | 360 |
| V20E385P | P20V385 | 385 | 505 | 300 | 10000 | 6500 | 558 | 682 | 1025 | 100 | 700 |
| V07E420P | P7V420 | 420 | 560 | 40 | 1750 | 1200 | 612 | 748 | 1120 | 10 | 55 |
| V10E420P | P10V420 | 420 | 560 | 80 | 3500 | 2500 | 612 | 748 | 1120 | 25 | 140 |
| V14E420P | P14V420 | 420 | 560 | 160 | 6000 | 4500 | 612 | 748 | 1120 | 50 | 300 |
| V20E420P | P20V420 | 420 | 560 | 320 | 10000 | 6500 | 612 | 748 | 1120 | 100 | 600 |
| V07E440P | P7V440 | 440 | 585 | 44 | 1750 | 1200 | 643 | 787 | 1180 | 10 | 50 |
| V10E440P | P10V440 | 440 | 585 | 85 | 3500 | 2500 | 643 | 787 | 1180 | 25 | 130 |
| V14E440P | P14V440 | 440 | 585 | 170 | 6000 | 4500 | 643 | 787 | 1180 | 50 | 260 |
| V20E440P | P20V440 | 440 | 585 | 340 | 10000 | 6500 | 643 | 787 | 1180 | 100 | 500 |
| V07E460P | P7V460 | 460 | 615 | 48 | 1750 | 1200 | 675 | 825 | 1240 | 10 | 45 |
| V10E460P | P10V460 | 460 | 615 | 90 | 3500 | 2500 | 675 | 825 | 1240 | 25 | 120 |



Revision: February 9, 2012

©2012 Littelfuse, Inc.
Specifications are subject to change without notice.
Please refer to www.littelfuse.com/series/tmov.html for current information.

## UltraMOV™ Series Ratings & Specifications (Continued...)

| Part Number | Branding | Maximum Rating (85°C) | | | | | Specifications (25°C) | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Continuous | | Transient | | | Varistor Voltage at 1mA DC Test Current | | Maximum Clamping Voltage 8 x 20μs | | Typical Capacitance |
| | | RMS Volts | DC Volts | Energy 2ms | Peak Current 8 x 20μs | | | | | | |
| | | $V_{M(AC)}$ | $V_{M(DC)}$ | $W_{TM}$ | $I_{TM}$ 1 x Pulse | $I_{TM}$ 2 x Pulse | $V_{NOM}$ Min | $V_{NOM}$ Max | $V_C$ | $I_{PK}$ | $f$ = 1MHz |
| | | (V) | (V) | (J) | (A) | (A) | (V) | (V) | (V) | (A) | (pF) |
| V14E460P | P14V460 | 460 | 615 | 180 | 6000 | 4500 | 675 | 825 | 1240 | 50 | 220 |
| V20E460P | P20V460 | 460 | 615 | 360 | 10000 | 6500 | 675 | 825 | 1240 | 100 | 400 |
| V07E510P | P7V510 | 510 | 670 | 52 | 1750 | 1200 | 738 | 902 | 1355 | 10 | 40 |
| V10E510P | P10V510 | 510 | 670 | 92 | 3500 | 2500 | 738 | 902 | 1355 | 25 | 110 |
| V14E510P | P14V510 | 510 | 670 | 185 | 6000 | 4500 | 738 | 902 | 1355 | 50 | 200 |
| V20E510P | P20V510 | 510 | 670 | 365 | 10000 | 6500 | 738 | 902 | 1355 | 100 | 350 |
| V10E550P | P10V550 | 550 | 745 | 95 | 3500 | 2500 | 819 | 1001 | 1500 | 25 | 100 |
| V14E550P | P14V550 | 550 | 745 | 190 | 6000 | 4500 | 819 | 1001 | 1500 | 50 | 180 |
| V20E550P | P20V550 | 550 | 745 | 370 | 10000 | 6500 | 819 | 1001 | 1500 | 100 | 300 |
| V10E625P | P10V625 | 625 | 825 | 100 | 3500 | 2500 | 900 | 1100 | 1650 | 25 | 90 |
| V14E625P | P14V625 | 625 | 825 | 200 | 6000 | 4500 | 900 | 1100 | 1650 | 50 | 160 |
| V20E625P | P20V625 | 625 | 825 | 400 | 10000 | 6500 | 900 | 1100 | 1650 | 100 | 250 |

NOTE: 1. Average power dissipation of transients should not exceed 0.25W, 0.4W, 0.6W and 1.0W for 7mm, 10mm, 14mm, and 20mm model sizes, respectively.

## Current Energy and Power Dissipation Ratings

Should transients occur in rapid succession, the average power dissipation is the energy (watt-seconds) per pulse times the number of pulses per second. The power so developed must be within the specifications shown on the Device Ratings and Specifications Table for the specific device. The operating values of a MOV need to be derated at high temperatures as shown above. Because varistors only dissipate a relatively small amount of average power they are not suitable for repetitive applications that involve substantial amounts of average power dissipation.

**Figure 1A - Power Derating for Epoxy Coated**






**Figure 1B - Power Derating for Phenolic Coated**




## Peak Pulse Current Test Waveform





Figure 2

$0_1$ = Virtual Origin of Wave
T = Time from 10% to 90% of Peak
$T_1$ = Rise Time = 1.25 x T
$T_2$ = Decay Time

**Example** - For an 8/20 μs Current Waveform:
8μs = $T_1$ = Rise Time
20μs = $T_2$ = Decay Time



©2012 Littelfuse, Inc.
Specifications are subject to change without notice.
Please refer to www.littelfuse.com/series/tmov.html for current information.

## Transient V-I Characteristics Curves

## Maximum Clamping Voltage for 7mm Parts

**V7E130(P)-V7E460(P)**





**Figure 3**

## Maximum Clamping Voltage for 10mm Parts

**V10E130(P)-V10E625(P)**





**Figure 4**

## Maximum Clamping Voltage for 14mm Parts

**V14E130(P) - V14E625(P)**





**Figure 5**



©2012 Littelfuse, Inc.

Revision: February 9, 2012

Specifications are subject to change without notice.
Please refer to www.littelfuse.com/series/tmov.html for current information.

## Transient V-I Characteristics Curves (Continued...)

## Maximum Clamping Voltage for 20mm Parts

**V20E130(P) - V20E625(P)**





**Figure 6**

## Pulse Rating Curves

## Repetitive Surge Capability for 7mm Parts

**V7E130(P) - V7E460(P)**





**Figure 7**

ULTRAMOV™ Series

©2012 Littelfuse, Inc.
Specifications are subject to change without notice.
Please refer to www.littelfuse.com/series/tmov.html for current information.

## Pulse Rating Curves (Continued...)

## Repetitive Surge Capability for 10mm Parts

**V10E130(P) - VIOE625(P)**





**Figure 8**

## Repetitive Surge Capability for 14mm Parts

**V14E130(P) -V14E625(P)**





**Figure 9**

## Repetitive Surge Capability for 20mm Parts

**V20E130(P) -V20E625(P)**





**Figure 10**



©2012 Littelfuse, Inc.
Specifications are subject to change without notice.
Please refer to www.littelfuse.com/series/tmov.html for current information.

## Wave Solder Profile

### Non Lead–free Profile





Figure 11

### Lead–free Profile





Figure 12

## Physical Specifications


| | |
|---|---|
| **Lead Material** | Tin–C oated Copper Wire |
| **Soldering Characteristics** | Solderability per MIL–STD–202, Method 208E |
| **Insulating Material** | Cured, flame retardant epoxy polymer meets UL94V–0 requirements |
| **Device Labeling** | Marked with LF, voltage, UL/CSA logos, and date code |

## Environmental Specifications

| | |
|---|---|
| **Operating/Storage Temperature** | -55°C to +85°C/-55°C to +125°C |
| **Humidity Aging** | +85°C, 85% RH, 1000 hours +/-10% typical voltage change |
| **Thermal Shock** | +85°C to -40°C 5 times +/-10% typical voltage change |
| **Solvent Resistance** | MIL–STD–202, Method 215F |
| **Moisture Sensitivity** | Level 1, J–STD–020C |

## Phenolic Coating Option -- UltraMOV™ Series Varistors for Hi-Temperature Operating Conditions:

- Phenolic Coated UltraMOV™ Series devices are available with improved maximum operating temperature 125°C.
- These devices also have improved temperature cycling performance capability.
- Ratings and Specifications are as per standard UltraMOV™ Series except Hi–Pot Encapsulation (Isolation Voltage Capability) = 500V.
- Phenolic Coating is HALOGEN FREE. To order: change 'E' (Epoxy coating) in part number to 'P' (Phenolic coating; e.g. V20P230)
- See Part Numbering System section of this series for more information.
- Contact factory for further details.
- Product marking:








©2012 Littelfuse, Inc.
Specifications are subject to change without notice.
Please refer to www.littelfuse.com/series/tmov.html for current information.

## Product Dimensions (mm)

**Lead form options L1 and L3**
(refer to table below)




**Lead form options L2 and L4**
(refer to table below)




*Seating plane interpretation per IEC-717
(not available on tape or ammo pack)

| Dimension | $V_{RMS}$ Voltage Model | 7mm Size | | 10mm Size | | 14mm Size | | 20mm Size | |
|---|---|---|---|---|---|---|---|---|---|
| | | Min. mm (in) | Max. mm (in) | Min. mm (in) | Max. mm (in) | Min. mm (in) | Max. mm (in) | Min. mm (in) | Max. mm (in) |
| **A** | 130-320 | - | 12 (0.472) | - | 16 (0.630) | - | 20 (0.787) | - | 26.5 (1.043) |
| | 385-625 | - | 13 (0.512) | - | 17 (0.689) | - | 20.5 (0.807) | - | 28 (1.102) |
| **ØD** | All | - | 9 (0.354) | - | 12.5 (0.492) | - | 17 (0.669) | - | 23 (0.906) |
| **e (Note 2)** | All | 4 (0.157) | 6 (0.236) | 6.5 (0.256) | 8.5 (0.335) | 6.5 (0.256) | 8.5 (0.335) | 9 (0.354) | 11 (0.433) |
| **$e_1$ (Note 3)** | 130-320 | 1.5 (0.059) | 3.5 (0.138) | 1.5 (0.059) | 3.5 (0.138) | 1.5 (0.059) | 3.5 (0.138) | 1.5 (0.059) | 3.5 (0.138) |
| | 385-625 | 2.5 (0.098) | 5.5 (0.217) | 2.5 (0.098) | 5.5 (0.217) | 2.5 (0.098) | 5.5 (0.217) | 2.5 (0.098) | 5.5 (0.217) |
| **E** | 130-320 | - | 5.6 (0.220) | - | 5.6 (0.220) | - | 5.6 (0.220) | - | 5.6 (0.220) |
| | 385-510 | - | 7.3 (0.287) | - | 7.3 (0.287) | - | 7.3 (0.287) | - | 7.3 (0.287) |
| | 550-625 | - | 8.3 (0.327) | - | 8.3 (0.327) | - | 8.3 (0.327) | - | -8.3 (0.327) |
| **Ø b** | All | 0.585 (0.023) | 0.685 (0.027) | 0.76 (0.030) | 0.86 (0.034) | 0.76 (0.030) | 0.86 (0.034) | 0.76 (0.030) (Note 2) | 0.86 (0.034) (Note 2) |
| **$A_{TRIM}$** | All | - | 15 (0.591) | - | 19.5 (0.768) | - | 22.5 (0.886) | - | 29.0 (1.142) |
| **L (L2)** | All | 25.4 (1.00) | - | 25.4 (1.00) | - | 25.4 (1.00) | - | 25.4 (1.00) | - |
| ***L (L4)** | All | 2.41 (0.095) | 4.69 (0.185) | 2.41 (0.095) | 4.69 (0.185) | 2.41 (0.095) | 4.69 (0.185) | 2.41 (0.095) | 4.69 (0.185) |

NOTES:
1. Measurements displayed in Millimeters (Inches in parentheses).
2. Standard lead space.
3. For in-line lead option L3, dimension $e_1$ is "zero". Straight lead form option L1 shown.


For information about bulk packaging quantities, please refer to the Ordering Notes section at the end of this document.


©2012 Littelfuse, Inc.
Specifications are subject to change without notice.
Please refer to www.littelfuse.com/series/tmov.html for current information.


## Tape Specifications for Reel and Ammo Pack Items (Refer to dimensions on following page)

### 7mm Devices


CRIMPED LEADS "L2"




INLINE LEADS "L3"





STRAIGHT LEADS "L1"





### 10, 14 and 20mm Devices


CRIMPED LEADS "L2"




INLINE LEADS "L3"




STRAIGHT LEADS "L1"




ULTRAMOV™ Series

©2012 Littelfuse, Inc.
Specifications are subject to change without notice.
Please refer to www.littelfuse.com/series/tmov.html for current information.

## Tape Specifications for Reel and Ammo Pack Items (Refer to drawings on previous page)


- Conforms to ANSI and EIA specifications.
- Can be supplied to IEC Publication 286-2.
- Radial devices on tape are offered with crimped leads, straight leads, or in-line leads. See Ordering Information.
- For 10mm devices 'P' (component pitch) is 12.7mm when 'F' (lead space) is 5mm.
- 7mm parts are available on tape and reel up to 460 VAC only
- 10mm parts are available on tape and reel up to 510 VAC only
- 14mm and 20mm parts are available on tape and reel up to 550 VAC only
- 7mm devices with 7.5mm lead spacing option will be taped at 25.4mm component pitch and 500 pieces per reel
- 10mm devices with 5.0mm lead spacing option will be taped at 12.7mm component pitch and 1000 pieces per reel

| Symbol | Description | Model Size | | | |
|---|---|---|---|---|---|
| | | 7mm | 10mm | 14mm | 20mm |
| $B_1$ | Component Top to Seating Plane | 15 Max | 19.5 Max | 22.5 Max | 29 Max |
| C | Crimp Length | 2.4 Typ | 2.6 Typ | 2.6 Typ | 2.6 Typ |
| P | Pitch of Component | 12.7 +/- 1.0 | 25.4 +/- 1.0 | 25.4 +/- 1.0 | 25.4 +/- 1.0 |
| $P_0$ | Feed Hole Pitch | 12.7 +/- 0.2 | 12.7 +/- 0.2 | 12.7 +/- 0.2 | 12.7 +/- 0.2 |
| $P_1$ | Feed Hole Center to Pitch | 3.85 +/- 0.7 | 8.85 +/- 0.7 | 8.85 +/- 0.7 | 7.70 +/- 0.7 |
| $P_2$ | Hole Center to Component Center | 6.35 +/- 0.7 | 12.7 +/- 0.7 | 12.7 +/- 0.7 | 12.7 +/- 0.7 |
| F | Lead to Lead Distance | 5.0 +/- 0.8 | 7.5 +/- 0.8 | 7.5 +/- 0.8 | 10.0 +/- 0.8 |
| Δh | Component Alignment | 2.0 Max | 2.0 Max | 2.0 Max | 2.0 Max |
| W | Tape Width | 18.0 +1.0 / -0.5 | 18.0 +1.0 / -0.52 | 18.0 +1.0 / -0.5 | 18.0 +1.0 / -0.5 |
| $W_0$ | Hold Down Tape Width | 12.0 +/- 0.3 | 12.0 +/- 0.3 | 12.0 +/- 0.3 | 12.0 +/- 0.3 |
| $W_1$ | Hole Position | 9.0 +0.75 / -0.50 | 9.0 +0.75 / - 0.50 | 9.0 +0.75 / 0.50 | 9.0 +0.75 / -0.50 |
| $W_2$ | Hold Down Tape Position | 0.5 Max | 0.5 Max | 0.5 Max | 0.5 Max |
| H | Height from Tape Center to Component Base | 18.0 +2.0 / -0.0 | 18.0 +2.0 / -0.0 | 18.0 +2.0 / -0.0 | 18.0 +2.0 / -0.0 |
| $H_0$ | Seating Plane Height | 16.0 +/- 0.5 | 16.0 +/- 0.5 | 16.0 +/- 0.5 | 16.0 +/- 0.5 |
| $H_1$ | Component Height | 32.0 Max | 36.0 Max | 40.0 Max | 46.5 Max |
| $D_0$ | Feed Hole Diameter | 4.0 +/- 0.2 | 4.0 +/- 0.2 | 4.0 +/- 0.2 | 4.0 +/- 0.2 |
| t | Total Tape Thickness | 0.7 +/- 0.2 | 0.7 +/- 0.2 | 0.7 +/- 0.2 | 0.7 +/- 0.2 |
| Δp | Component Alignment | 3° Max, 1.00mm | 3° Max, 1.00mm | 3° Max, 1.00mm | 3° Max, 1.00mm |

For information on tape and reel packaging quantities, please refer to the Ordering Notes section at the end of this document.


©2012 Littelfuse, Inc.
Specifications are subject to change without notice.
Please refer to www.littelfuse.com/series/tmov.html for current information.

## Part Numbering System




UltraMOV™ is a trademark of Littelfuse, Inc.

## Ordering Notes:

For standard parts, use the **BASE PART** designator only.

For parts with non-standard options (such as additional form, packaging and lead space options) use, **BASE PART** + **OPTION CODE**.

**OPTION CODE** items are subject to availability and minimum order requirements. Please contact a Littelfuse representative if you require additional information

### OPTION CODES:

**X2855:** Nickel Barrier COATED WIRE OPTION

All standard parts use Tin–coated Copper Wire Nickel Barrier Coated Wire is available as an option, consisting of Copper Wire with a flashing of Nickel followed by a top coating of Tin.

**To order:** append standard model **BASE PART** number with "X2855." Example:

| Standard Model | Order As |
|---|---|
| V18ZA40P | V18ZA40P**X2855** |

### PACKAGING:

Littelfuse UltraMOV™ varistors are shipped standard in bulk pack with straight leads and lead spacing outlined in the dimensions sections of this document. Contact a Littelfuse representative to discuss non-standard options.

### Standard Part Default Conditions

| Device Size | Part # | Lead Space | Packaging |
|---|---|---|---|
| 7mm | V07E– | 5.0-/+1 | Bulk |
| 10mm | V10E– | 7.5-/+1 | Bulk |
| 14mm | V14E– | 7.5-/+1 | Bulk |
| 20mm | V20E– | 10.0-/+1 | Bulk |

### Standard Bulk Pack Quantity

| Varistor Voltage | Standard Bulk Pack Quantity | | | |
|---|---|---|---|---|
| | Varistor Model Size | | | |
| | 7mm | 10mm | 14mm | 20mm |
| 130 – 275 | 1500 | 1000 | 700 | 500 |
| 300 – 460 | 1500 | 700 | 600 | 400 |
| 510 – 625 | 1500 | 700 | 500 | 400 |

### Tape & Reel Quantity

| Varistor Voltage | Shipping Quantity Per Reel | | | |
|---|---|---|---|---|
| | 7mm | 10mm | 14mm | 20mm |
| 130 – 275 | 1000 | 500 | 500 | 500 |
| 300 – 625 | 1000 | 500 | 400 | 400 |



©2012 Littelfuse, Inc.
Specifications are subject to change without notice.
Please refer to www.littelfuse.com/series/tmov.html for current information.


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.




**Как с нами связаться**

**Телефон:** 8 (812) 309 58 32 (многоканальный)
**Факс:** 8 (812) 320-02-42
**Электронная почта:** org@eplast1.ru
**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.