REVISIONS			
LTR	DESCRIPTION	DATE	APPROVED
N/C	INITIAL RELEASE PER DCR# T-24384	3/2/2000	M.HIGGY
A	REVISE PER DCR# T-29844	8/17/2001	M.HIGGY



PLUG ASSEMBLY

RECEPTACLE ASSEMBLY

NOTES: SEE SHEET 2.

If this document is printed it becomes uncontrolled.
Check with the web for latest revision.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. METRIC DIMENSIONS ARE IN BRACKETS.

DECIMALS
.XXX ±.005 { .13 mm }
.XX ±.02 { .5 mm }

ANGLES
.X ±

WEIGHT: 8

DRAWN	ZS.ORBAN	2/29/2000
CHECKED		
APPROVED		
APPROVED	M.HIGGY	3/2/2000
CAD NAME	T29844a,b,DWG	
THIRD ANGLE PROJECTION		

SPECIFICATION CONTROL DRAWING

tyco Electronics Raychem
WIRE AND HARNESSING PRODUCTS
307 CONSTITUTION DRIVE
MENLO PARK, CALIFORNIA 94025

TITLE

SHELL, PLUG OR RECEPTACLE, SPECIAL MARKING, 1" AND 2" WITH EARS, CADMIUM PLATED

SIZE	CODE IDENT. NO.	DWG. NO.	REV
C	06090	MTCCXX-YYYYYY-01 1	A

DO NOT SCALE THIS DRAWING | SHEET 1 OF 2

DWG NO. MTCCXX-YYYYYY-01 SHEET 1

If this document is printed it becomes uncontrolled.
Check with the web for latest revision.

NOTES:

1. PART NUMBER VARIABLES:



TABLE I	
PART NUMBER	WEIGHT MAXIMUM GRAMS
MTCC1R-YYYYYYY-01	27.3
MTCC1P-YYYYYYY-01	23.8
MTCC2R-YYYYYYY-01	38.3
MTCC2P-YYYYYYY-01	34.2

2. MATERIAL:

A) SHELL	ALUMINUM ALLOY PER QQ-A-591
B) RETENTION CLIP	COPPER ALLOY 172 PER QQ-C-533
C) ADAPTER SCREW OR CAP SCREW	STAINLESS STEEL PER QQ-S-763, 300 SERIES
D) ADAPTER NUT OR RETAINER BUSHING	STAINLESS STEEL PER QQ-S-763, 300 SERIES
E) PANEL OR LOCK WASHER	STAINLESS STEEL PER QQ-S-763 OR QQ-S-766, 300 SERIES
F) KEYING PIN	HIGH GRADE POLYARYLENE THERMOPLASTIC, MOLDED
G) KEY PINS INSERT	HIGH GRADE POLYARYLENE THERMOPLASTIC, MOLDED
H) CLAMP BAR	STAINLESS STEEL PER QQ-S-763, 300 SERIES
J) CLAMP INSERT	SILICONE ELASTOMER PER MIL-R-25988
K) CAPTIVE SCREW	STAINLESS STEEL PER QQ-S-763, 300 SERIES
L) RETAINING RING	COPPER ALLOY 172 PER QQ-C-533
M) DUST CUP	POLYETHYLENE LOW DENSITY PER L-P-390, COLOR RED.

3. FINISH: CADMIUM PLATED CONNECTORS

A) SHELL	CADMIUM PLATED PER QQ-P-416 OVER NICKEL UNDERPLATE
B) RETENTION CLIP	CADMIUM PLATED PER QQ-P-416
C) ADAPTER OR CAP SCREW	CADMIUM PLATED PER QQ-P-416
D) ADAPTER NUT OR RETAINER BUSHING	CADMIUM PLATED PER QQ-P-416
E) PANEL OR LOCK WASHER	CADMIUM PLATED PER QQ-P-416
F) CLAMP BAR	CADMIUM PLATED PER QQ-P-416
G) CAPTIVE SCREW	CADMIUM PLATED PER QQ-P-416
H) RETAINING RING	CADMIUM PLATED PER QQ-P-416

4. DUST CAP SUPPLIED WITH EACH PLUG OR RECEPTACLE.

5. APPROPRIATE PART NUMBER AND DATE CODE ARE STAMPED APPROXIMATELY AS SHOWN.

6. THESE PARTS MEET THE REQUIREMENTS OF RAYCHEM SPECIFICATION C-6111.

7. INDICATED PARTS ARE SHIPPED LOOSE.

8. SEE TABLE I, WEIGHTS ARE WITHOUT DUST CAP.

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.