

COMMON MODE CHOKE CATALOG
Suited for LAN and Telecom Applications



TABLE of CONTENTS


Common Mode Chokes for Datacom Applications

Surface Mount Common Mode Chokes2-6

Through Hole Common Mode Chokes7-12

SURFACE MOUNT COMMON MODE CHOKES

Suited for LAN and Telecom Applications



-  Reduces radiated EMI emissions
-  Filters common mode noise for EMI reduction
-  Common mode attenuation from 100 kHz to 1 GHz
-  Tape & Reel packaging available for surface mount parts*

Electrical Specifications @ 25°C

Part Number	No. of Ports	Primary Inductance OCL (μH MIN)	Common Mode Attenuation (db TYP)									DCR (Ω MAX)	Page Number Mech & Schem
			100 KHz	1 MHz	10 MHz	30 MHz	50 MHz	100 MHz	300 MHz	500 MHz	1 GHz		
PE-68624	2	47	11	27	40	44	42	36	26	17	—	0.40	2
PE-65855	2	4700	41	43	49	39	34	26	20	20	12	1.0	4
B2013	2	6300	46	47	43	32	25	29	21	14	16	1.0	3
B4003	2	4700	42	41	48	38	33	21	22	23	17	1.0	6
23Z87SM	3	69	9	24	31	30	29	27	21	16	—	0.20	4
PE-65857	4	22.5	7	20	30	37	38	34	24	13	—	0.22	4
PE-68627	4	24	8	21	32	36	37	36	30	20	—	0.25	4
T8003	4	33	9	13	32	32	30	27	16	17	13	0.20	6
23Z4000SMD	4	36	7	23	35	38	38	36	29	24	—	0.50	5
PE-65854	4	47	3	19	32	36	35	29	12	6	—	0.40	3
23Z104SM	4	68	8	22	28	28	27	25	20	15	—	0.20	5
PE-67540	4	100	14	33	44	48	49	44	34	29	20	0.60	4
PE-65853	4	4700	40	51	38	30	25	20	14	13	—	1.20	3
23Z106SM	6	68	8	22	29	30	30	29	24	19	—	0.20	5
PE-69011	8	36	8	24	36	39	35	29	18	11	—	0.35	3
23Z105SM	8	68	8	24	30	29	27	24	16	11	—	0.20	5
23Z109SM	10	7.5	4	9	20	25	26	24	16	11	—	0.20	5
T8008	16	47	7	27	40	44	42	36	26	—	—	0.40	6



* When ordering Tape & Reel packaging, add a "T" at the end of the part number (i.e. PE-65738T or 23Z106SMT).

NOTE: Additional common mode chokes are available. Please contact Applications Engineering.


Mechanical

Schematic

PE-68624



SUGGESTED PAD LAYOUT



PE-68624



Weight 0.17 grams
Tape & Reel 1500/reel
Tube 85/tube

SURFACE MOUNT COMMON MODE CHOKES


Suited for LAN and Telecom Applications



Mechanical

Schematic

PE-69011



Dimensions: Inches
mm


Unless otherwise specified,
all tolerances are $\pm .010$
0,25

Weight 0.83 grams


Tape & Reel 900/reel

Tube 40/tube

PE-69011



PE-65853



Dimensions: Inches
mm


Unless otherwise specified,
all tolerances are $\pm .010$
0,25

Weight 4.0 grams


Tape & Reel 150/reel

Tube 35/tube

PE-65853



B2013



Dimensions: Inches
mm

Unless otherwise specified,
all tolerances are $\pm .010$
0,25


Weight 9.5 grams

Tray 30/tray

B2013



PE-65854



Dimensions: Inches
mm


Unless otherwise specified,
all tolerances are $\pm .010$
0,25

Weight 0.3 grams

Tape & Reel 1500/reel

Tube 60/tube

PE-65854



Schematic

4XØ .046 $\pm .002 / - .000$
 $1,17 \pm .05 / - .00$
 CONTACT SURFACE

3
 .245 $\pm .002$
 6,22 $\pm .05$

2
 .345 $\pm .000 / - .010$
 8,76 $\pm .00 / - .0,25$

.300
 7,62

.400 $\pm .000 / - .010$
 10,16 $\pm .00 / - .0,25$

.250
 6,35
 MAX

$\frac{.004}{.010}$
 4 SURFACES

Weight 0.69 grams
Tape & Reel 800/reel
Tube 40 /tube

PE-65857, PE-67540

Top View:

- Pin 1 indicator: 1
- Pin 5 indicator: 5
- Pin 8 indicator: 8
- Pin 4 indicator: 4
- Dimensions: .030 / 0,76 (pin pitch), .600 / 15,30 MAX (package width), .475 / 12,10 MAX (package length), .400 / 10,20 (pin offset), .475 / 12,10 MAX (total length), .100 / 2,54 TYP (pin length), .300 / 7,62 (pin length)

Side View:

- Dimensions: .475 / 12,1 MAX (package height), .340 / 8,64 MAX (pin height), .100 / 2,54 (pin offset), .085 / 2,16 (pin offset), .010 / .020 / 0,25 / 0,51 (pin thickness)

SUGGESTED PAD LAYOUT:

- Dimensions: .120 / 3,05 (pad width), .050 / 1,27 TYP (pad width), .640 / 16,30 (pad offset), .400 / 10,20 (pad offset), .100 / 2,54 TYP (pad length), .300 / 7,62 (pad length), .040 / .050 / 1,01 / 1,27 (pad thickness)

Weight 2.0 grams
Tape & Reel 250/reel
Tube 40/tube

PE-68627

DATE CODE
COUNTRY OF
ORIGIN

SUGGESTED PAD LAYOUT

Dimensions (inches / millimeters):

- Top View:
 - Overall Width: .345 MAX / 8.76
 - Overall Height: .285 / 7.24
 - Pin 1 to Pin 8 Distance: .100 / 2.54
 - Pin 1 to Pin 5 Distance: .355 MAX / 9.02
- Side View:
 - Overall Height: .207 MAX / 5.26
- Suggested Pad Layout:
 - Pin 1 to Pin 8 Distance: .300 / 7.62
 - Pin 1 to Pin 5 Distance: .100 / 2.54
 - Pin 1 to Pin 8 Distance: .270 / 6.86
 - Pin 1 to Pin 8 Distance: .050 / 1.27
 - Pin 1 to Pin 8 Distance: .070 / 1.78

Weight 0.3 grams
Tape & Reel 1500/reel
Tube 55/tube

23Z87SM

23Z87SM
Date Code
Country of Origin

SUGGESTED PAD LAYOUT

Dimensions (inches):

- Top View:
 - Overall Width: 2.30 (5.84)
 - Overall Height: 2.15 (5.46)
 - Pin Spacing: .100 (2.54)
 - Pin Width: .050 (1.27)
 - Pin Pitch: .050 (1.27)
 - Pin Thickness: .005/.010 (0.13/0.25)
 - Pin Height: 2.60 (6.60)
 - Pin Spacing (Inner): .050 (1.27)
 - Pin Spacing (Outer): .050 (1.27)
 - Pin Thickness (Inner): .030 (0.76)
 - Pin Thickness (Outer): .080 (2.03)
 - Pin Thickness (Inner): .018 (0.46) TYP
- Side View:
 - Overall Width: 2.65 (6.73)
 - Overall Height: 2.15 (5.46)
 - Pin Spacing: .100 (2.54)
 - Pin Width: .050 (1.27)
 - Pin Pitch: .050 (1.27)
 - Pin Thickness: .005/.010 (0.13/0.25)
 - Pin Height: 2.60 (6.60)
 - Pin Spacing (Inner): .050 (1.27)
 - Pin Spacing (Outer): .050 (1.27)
 - Pin Thickness (Inner): .030 (0.76)
 - Pin Thickness (Outer): .080 (2.03)
 - Pin Thickness (Inner): .018 (0.46) TYP

Weight 0.5 grams
Tape & Reel 750/reel
Tube 100/tube

SURFACE MOUNT COMMON MODE CHOKES


Suited for LAN and Telecom Applications



Mechanical

Schematic

23Z104SM



Dimensions: Inches
mm


Unless otherwise specified,
all tolerances are $\pm .005$
0,13

Weight 0.5 grams


Tape & Reel 750/reel

Tube 100/tube

23Z104SM



23Z105SM, 23Z106SM



Dimensions: Inches
mm

Unless otherwise specified,
all tolerances are $\pm .005$
0,13


23Z105SM 23Z106SM

Weight 0.8 grams 1.0 grams


Tape & Reel 750/reel 750/reel

Tube 50/tube 50/tube


23Z105SM



23Z106SM



23Z109SM



Dimensions: Inches
mm


Unless otherwise specified,
all tolerances are $\pm .005$
0,13

Weight 1.3 grams


Tape & Reel 500/reel

Tube 38/tube

23Z109SM



23Z4000SMD



Dimensions: Inches
mm


Unless otherwise specified,
all tolerances are $\pm .005$
0,13

Weight 2.1 grams

Tape & Reel 350/reel

Tube 38/tube

23Z4000SMD



SURFACE MOUNT COMMON MODE CHOKES


Suited for LAN and Telecom Applications



Mechanical

Schematic

T8003



Dimensions: $\frac{\text{Inches}}{\text{mm}}$


Unless otherwise specified,
all tolerances are $\pm .005$
0,13

Weight 0.84 grams


Tape & Reel 750/reel

Tube 100/tube

T8003



T8055



Dimensions: $\frac{\text{Inches}}{\text{mm}}$


Unless otherwise specified,
all tolerances are $\pm .010$
0,25

Weight 0.2 grams


Tape & Reel 1750/reel

Tube 80/tube

T8055



B4003



Dimensions: $\frac{\text{Inches}}{\text{mm}}$


Unless otherwise specified,
all tolerances are $\pm .010$
0,25

Weight 1.0 grams


Tape & Reel 425/reel

Tube 50/tube

B4003



T8008



Dimensions: $\frac{\text{Inches}}{\text{mm}}$


Unless otherwise specified,
all tolerances are $\pm .010$
0,25

Weight 4.0 grams

Tape & Reel 250/reel

Tube 15/tube


T8008



NOTE: The common mode test circuit for surface mount is the same as for through hole and is on the back page.

THROUGH HOLE COMMON MODE CHOKES

Suited for LAN and Telecom Applications



-  Reduces radiated EMI emissions
-  Filters common mode noise for EMI reduction
-  Common mode attenuation from 100 kHz to 1 GHz
-  Tube packaging available for through hole parts



Electrical Specifications @ 25°C

Part Number	No. of Lines	Primary Inductance OCL (μH MIN)	Common Mode Attenuation (dB TYP)									DCR (Ω MAX)	Page Number Mech & Schem
			100 kHz	1 MHz	10 MHz	30 MHz	50 MHz	100 MHz	300 MHz	500 MHz	1 GHz		
PE-65944	2	24	1	14	28	32	33	28	13	5	—	0.30	8
PE-67531	2	140	14	34	45	49	50	47	38	32	25	0.60	9
B2005	2	9000	47	47	41	30	22	33	21	15	15	1.0	10
PE-65554	4	24	—	21	32	38	39	34	24	13	—	0.30	8
PE-68002	4	68	7	24	37	41	42	40	31	27	—	0.35	9
23Z104	4	85	8	23	29	29	28	25	17	11	—	0.20	10
PE-67539	4	140	14	33	44	48	48	43	33	28	19	0.60	9
PE-65542	4	1000	28	41	42	32	22	—	—	—	—	0.70	8
PT5039	4	3600	42	43	42	32	27	17	15	9	13	0.50	8
J0010D11	4	—	9	13	32	35	35	29	13	24	19	0.50	10
PE-65950	4	4700±30%	40	51	37	28	23	20	—	—	—	1.00	8
PE-65541	4	6000	44	54	33	32	29	—	—	—	—	1.40	8
PE-68613	4	3290	40	51	37	28	23	20	—	—	—	1.00	10

Mechanical

Schematic


PE-65541, PE-65542, PE-65950



Dimensions: Inches
mm
Unless otherwise specified,
all tolerances are ± .010
0,25

Weight 0.38 grams
Tube 35/tube

PE-65541 PE-65542 PE-65950



THROUGH HOLE COMMON MODE CHOKES


Suited for LAN and Telecom Applications



Mechanical

Schematic


PE-65554




Dimensions: $\frac{\text{Inches}}{\text{mm}}$
Unless otherwise specified,
all tolerances are $\pm \frac{.010}{0,25}$

Weight 2.5 grams
Tube 35/tube

PE-65554




PT5039




Dimensions: $\frac{\text{Inches}}{\text{mm}}$
Unless otherwise specified,
all tolerances are $\pm \frac{.010}{0,25}$

Weight 2.5 grams
Tube 35/tube

PT5039



PE-65944



Dimensions: $\frac{\text{Inches}}{\text{mm}}$
Unless otherwise specified,
all tolerances are $\pm \frac{.010}{0,25}$

Weight 1.07 grams
Tube 30/tube

PE-65944



THROUGH HOLE COMMON MODE CHOKES

Suited for LAN and Telecom Applications




Pulse
A TECHNITROL COMPANY

Mechanical

Schematic


PE-67539




Dimensions: $\frac{\text{Inches}}{\text{mm}}$
Unless otherwise specified,
all tolerances are $\pm \frac{.010}{0,25}$

Weight 2.4 grams
Tube 40/tube

PE-67539



PE-67531




Dimensions: $\frac{\text{Inches}}{\text{mm}}$
Unless otherwise specified,
all tolerances are $\pm \frac{.010}{0,25}$

Weight 0.76 grams
Tube 40/tube

PE-67531




PE-68002



Dimensions: $\frac{\text{Inches}}{\text{mm}}$
Unless otherwise specified,
all tolerances are $\pm \frac{.010}{0,25}$

Weight 1.4 grams
Tube 50/tube

PE-68002



THROUGH HOLE COMMON MODE CHOKES


Suited for LAN and Telecom Applications



Mechanical

Schematic

B2005




Dimensions: $\frac{\text{Inches}}{\text{mm}}$
Unless otherwise specified,
all tolerances are $\pm \frac{.005}{0,13}$

Weight 3.7 grams
Tube 40/tube

B2005




23Z104




Dimensions: $\frac{\text{Inches}}{\text{mm}}$
Unless otherwise specified,
all tolerances are $\pm \frac{.005}{0,13}$

Weight 1.0 grams
Tube 50/tube

23Z104




PE-68613



Dimensions: $\frac{\text{Inches}}{\text{mm}}$
Unless otherwise specified,
all tolerances are $\pm \frac{.005}{0,127}$

Weight 3.5 grams
Tube 40/tube

PE-68613




THROUGH HOLE COMMON MODE CHOKES


Suited for LAN and Telecom Applications



J0010D11 - Filtered Connector



Common Mode Test Circuit for Surface Mount and Through Hole



Test Notes:

1. Network analyzer calibrated to compensate for 50 Ω resistors.
2. All windings on a core are connected in parallel for the test.
3. For multi-core chokes, test data is for one core only. The windings on the other core(s) are left unconnected (i.e. open).

For More Information:

Pulse Worldwide Headquarters

12220 World Trade Dr.
San Diego, CA 92128
U.S.A.

www.pulseeng.com

Tel: 858 674 8100
Fax: 858 674 8262

Pulse Europe

Einsteinstrasse 1
D-71083 Herrenberg
Germany

Tel: 49 7032 7806 0
Fax: 49 7032 7806 135

Pulse China Headquarters

B402, Shenzhen Academy of
Aerospace Technology Bldg.
10th Kejinan Rd.
High-Tech Zone
Nanshan District
Shenzhen, PR China 518057

TEL: 86 755 33966678
FAX: 86 755 33966700

Pulse North China

Room 1503
XinYin Building
No. 888 YiShan Rd.
Shanghai 200233
China

Tel: 86 21 54643211/2
Fax: 86 21 54643210

Pulse South Asia

135 Joo Seng Rd.
#03-02
PM Industrial Bldg.
Singapore 368363

TEL: 65 6287 8998
FAX: 65 6280 0080

Pulse North Asia

No. 26, Kao Ching Rd.
Yang Mei Chen
Taoyuan Hsien
Taiwan
R. O. C.

Tel: 886 3 4643715
Fax: 886 3 4641911

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.

© Copyright, 2009. Pulse Engineering, Inc. All rights reserved.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.