


PRODUCT NUMBER	MATING CONTACT AREA PLATING PERFORMANCE	SHROUD TO USE FOR REAR-PLUG-UP APPLICATIONS	CONNECTOR SIZE	PIN FIELD DIM C	LENGTH DIM D	PRESS FIT TAIL PLATING
84881-101ZZZ	TELCORDIA CO	84818-101	1 MOD	10.00	11.88	STANDARD
84881-101ZZZLF		84818-101LF				LEAD FREE
84881-102ZZZ		84818-102	2 MOD	22.00	23.88	STANDARD
84881-102ZZZLF		84818-102LF				LEAD FREE
84881-103ZZZ		84818-103	3 MOD	34.00	35.88	STANDARD
84881-103ZZZLF		84818-103LF				LEAD FREE
84881-104ZZZ		84818-104	4 MOD	46.00	47.88	STANDARD
84881-104ZZZLF		84818-104LF				LEAD FREE
84881-501ZZZ	TELCORDIA UE	84818-101	1 MOD	10.00	11.88	STANDARD
84881-501ZZZLF		84818-101LF				LEAD FREE
84881-502ZZZ		84818-102	2 MOD	22.00	23.88	STANDARD
84881-502ZZZLF		84818-102LF				LEAD FREE
84881-503ZZZ		84818-103	3 MOD	34.00	35.88	STANDARD
84881-503ZZZLF		84818-103LF				LEAD FREE
84881-504ZZZ		84818-104	4 MOD	46.00	47.88	STANDARD
84881-504ZZZLF		84818-104LF				LEAD FREE










EYE OF NEEDLE
PRESS FIT SECTION



BABY-H
PRESS FIT SECTION

DETAIL A
SCALE 4:1
SEE NOTE 17

mat'l code	SEE NOTE 5			tolerances unless otherwise specified		
ltr	ecn no.	dr	date	linear	0.X ±0.3	
M	V06-0569	DCH	2006-06-12		0.XX ±0.13	
N	V07-0179	DCH	2007-04-18		.XXX ±.051	
P	V08-0029	HTB	2008-01-21	angles	0° ±2°	
R	V08-0131	LP	2008-03-24	dr	E. KROPER.	2001-01-23
-	-	-	-	engr	J. VOLSTORF	2001-01-23
K	V04-0399	DAI	2004-05-24	chr	J. VOLSTORF	2001-01-23
L	V05-0806	VS	2005-09-22	appd	J. VOLSTORF	2001-01-23

sheet	revision	R	R	R	R	R	R
index	sheet	1	2	3	4	5	6

CUSTOMER COPY

projection

MM

scale 1:1

www.fciconnect.com

title: VERTICAL SIGNAL HDR 5 ROW P.F. SPECIAL LOAD EXT.

product family: METRAL 1000 | code: 213

size: A | dwg no: 84881 | sheet: 1 of 6

cage code: 22526

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

REV E - 2006-04-18

Pro/E

PDM: Rev:R STATUS: Released Printed: May 13, 2011

PIN NO.	DIM A MATING LENGTH	DIM B TAIL LENGTH	PCB THICKNESS RANGE ACCOMMODATED BY PIN'S TAIL LENGTH				
			WHEN MATING TO A 84854 METRAL 1000 SERIES RECEPTACLE		WHEN MATING TO A 52062 METRAL 4000 SERIES RECEPTACLE		
			ROWS A,B,C,D,E	GROUND ROW	ROWS:A,B,D,E	ROW C	GROUND ROW
01*		4.30	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN
22		12.20	2.95 - 3.80	2.95 - 4.20	2.95 - 3.80	2.95 - 3.80	2.95 - 4.20
30		12.95	2.95 - 4.55	3.25 - 4.95	2.95 - 4.55	2.95 - 4.55	3.25 - 4.95
05		13.70	2.95 - 5.30	4.00 - 5.70	3.30 - 5.30	2.95 - 5.30	4.00 - 5.70
35	5.00	14.45	3.05 - 6.05	4.75 - 6.45	4.05 - 6.05	3.05 - 6.05	4.75 - 6.45
48		15.20	3.80 - 6.80	5.50 - 7.20	4.80 - 6.80	3.80 - 6.80	5.50 - 7.20
40		15.70	4.30 - 7.30	6.00 - 7.70	5.30 - 7.30	4.30 - 7.30	6.00 - 7.70
65		16.40	5.00 - 8.00	6.70 - 8.40	6.00 - 8.00	5.00 - 8.00	6.70 - 8.40
09		17.10	5.70 - 8.70	7.40 - 9.10	6.70 - 8.70	5.70 - 8.70	7.40 - 9.10
02*		4.30	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN
44		12.20	2.95 - 3.80	2.95 - 4.20	2.95 - 3.80	2.95 - 3.80	2.95 - 4.20
31		12.95	2.95 - 4.55	3.25 - 4.95	2.95 - 4.55	2.95 - 4.55	3.25 - 4.95
06		13.70	2.95 - 5.30	4.00 - 5.70	3.30 - 5.30	2.95 - 5.30	4.00 - 5.70
36	5.75	14.45	3.05 - 6.05	4.75 - 6.45	4.05 - 6.05	3.05 - 6.05	4.75 - 6.45
49		15.20	3.80 - 6.80	5.50 - 7.20	4.80 - 6.80	3.80 - 6.80	5.50 - 7.20
25		15.70	4.30 - 7.30	6.00 - 7.70	5.30 - 7.30	4.30 - 7.30	6.00 - 7.70
66		16.40	5.00 - 8.00	6.70 - 8.40	6.00 - 8.00	5.00 - 8.00	6.70 - 8.40
10		17.10	5.70 - 8.70	7.40 - 9.10	6.70 - 8.70	5.70 - 8.70	7.40 - 9.10
03*		4.30	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN
45		12.20	2.95 - 3.80	2.95 - 4.20	2.95 - 3.80	2.95 - 3.80	2.95 - 4.20
32		12.95	2.95 - 4.55	3.25 - 4.95	2.95 - 4.55	2.95 - 4.55	3.25 - 4.95
07		13.70	2.95 - 5.30	4.00 - 5.70	3.30 - 5.30	2.95 - 5.30	4.00 - 5.70
37	6.50	14.45	3.05 - 6.05	4.75 - 6.45	4.05 - 6.05	3.05 - 6.05	4.75 - 6.45
50		15.20	3.80 - 6.80	5.50 - 7.20	4.80 - 6.80	3.80 - 6.80	5.50 - 7.20
41		15.70	4.30 - 7.30	6.00 - 7.70	5.30 - 7.30	4.30 - 7.30	6.00 - 7.70
24		16.40	5.00 - 8.00	6.70 - 8.40	6.00 - 8.00	5.00 - 8.00	6.70 - 8.40
11		17.10	5.70 - 8.70	7.40 - 9.10	6.70 - 8.70	5.70 - 8.70	7.40 - 9.10

* STUB PINS - NO REAR PLUG-UP

** THE GREATEST RANGE OCCURS WHEN THE B DIMENSION OF PIN 'GND' IS ONE SIZE SHORTER THEN THE OTHER PINS.

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

mat'l code	SEE NOTE 5		
ltr	ecn no.	dr	date
R			

tolerances unless otherwise specified		
linear	0.X ±0.3	
	0.XX ±0.13	
	.XXX ±.051	
angles	0° ±2°	
dr	E. KROPER.	2001-01-23
engr	J. VOLSTORF	2001-01-23
chr	J. VOLSTORF	2001-01-23
appd	J. VOLSTORF	2001-01-23

CUSTOMER COPY

projection

MM

scale 1:1

www.fciconnect.com

title: VERTICAL SIGNAL HDR 5 ROW P.F. SPECIAL LOAD EXT.

product family: METRAL 1000 | code: 213

size: A | dwg no: 84881 | sheet: 2

sheet index	revision sheet																							

cage code 22526

Pro/E

REV E - 2006-04-18

PDM: Rev:R STATUS: Released Printed: May 13, 2011

PIN NO.	DIM A MATING LENGTH	DIM B TAIL LENGTH	PCB THICKNESS RANGE ACCOMMODATED BY PIN LENGTH				
			WHEN MATING TO A 84854 METRAL 1000 SERIES RECEPTACLE		WHEN MATING TO A 52062 METRAL 4000 SERIES RECEPTACLE		
			ROWS A,B,C,D,E	GROUND ROW	ROWS:A,B,D,E	ROW C	GROUND ROW
04*	7.25	4.30	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN
46		12.20	2.95 - 3.80	2.95 - 4.20	2.95 - 3.80	2.95 - 3.80	2.95 - 4.20
33		12.95	2.95 - 4.55	3.25 - 4.95	2.95 - 4.55	2.95 - 4.55	3.25 - 4.95
08		13.70	2.95 - 5.30	4.00 - 5.70	3.30 - 5.30	2.95 - 5.30	4.00 - 5.70
38		14.45	3.05 - 6.05	4.75 - 6.45	4.05 - 6.05	3.05 - 6.05	4.75 - 6.45
51		15.20	3.80 - 6.80	5.50 - 7.20	4.80 - 6.80	3.80 - 6.80	5.50 - 7.20
42		15.70	4.30 - 7.30	6.00 - 7.70	5.30 - 7.30	4.30 - 7.30	6.00 - 7.70
67		16.40	5.00 - 8.00	6.70 - 8.40	6.00 - 8.00	5.00 - 8.00	6.70 - 8.40
12		17.10	5.70 - 8.70	7.40 - 9.10	6.70 - 8.70	5.70 - 8.70	7.40 - 9.10
19*	8.00	4.30	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN
47		12.20	2.95 - 3.80	2.95 - 4.20	2.95 - 3.80	2.95 - 3.80	2.95 - 4.20
34		12.95	2.95 - 4.55	3.25 - 4.95	2.95 - 4.55	2.95 - 4.55	3.25 - 4.95
20		13.70	2.95 - 5.30	4.00 - 5.70	3.30 - 5.30	2.95 - 5.30	4.00 - 5.70
39		14.45	3.05 - 6.05	4.75 - 6.45	4.05 - 6.05	3.05 - 6.05	4.75 - 6.45
52		15.20	3.80 - 6.80	5.50 - 7.20	4.80 - 6.80	3.80 - 6.80	5.50 - 7.20
43		15.70	4.30 - 7.30	6.00 - 7.70	5.30 - 7.30	4.30 - 7.30	6.00 - 7.70
68		16.40	5.00 - 8.00	6.70 - 8.40	6.00 - 8.00	5.00 - 8.00	6.70 - 8.40
21		17.10	5.70 - 8.70	7.40 - 9.10	6.70 - 8.70	5.70 - 8.70	7.40 - 9.10

* STUB PINS - NO REAR PLUG-UP

** THE GREATEST RANGE OCCURS WHEN THE B DIMENSION OF PIN 'GND' IS ONE SIZE SHORTER THEN THE OTHER PINS.

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

mat'l code SEE NOTE 5				tolerances unless otherwise specified			CUSTOMER	FCI www.fciconnect.com
ltr	ecn no.	dr	date				COPY	
R				linear	0.X ±0.3		projection	title VERTICAL SIGNAL HDR 5 ROW P.F. SPECIAL LOAD EXT.
					0.XX ±0.13			
					.XXX ±.051			
				angles	0° ±2°			
				dr	E. KROPER.	2001-01-23	MM	product family METRAL 1000 code 213
				engr	J. VOLSTORF	2001-01-23		
				chr	J. VOLSTORF	2001-01-23	scale 1:1	size A dwg no 84881 sheet 3
				appd	J. VOLSTORF	2001-01-23		
sheet index	revision sheet							

cage code 22526


REV E - 2006-04-18

Pro/E


PDM: Rev:R STATUS: Released Printed: May 13, 2011

PRODUCT NUMBER
SEE SHEET 1

PRESS-FIT HOLES	OPTION 1
HOLE DIAMETER AFTER PLATING	∅0.65-0.80
DRILLED HOLE	∅0.81-0.86 (∅0.85 DRILL)
COPPER PLATING	0.025 MIN
SnPb PLATING	0.005-0.015




REAR PLUG-UP



STUB MOUNT

SEE PRINT 58351 FOR ADDITIONAL PCB INFORMATION.



SHOWN FROM HEADER SIDE OF CIRCUIT BOARD

mat'l code SEE NOTE 5				tolerances unless otherwise specified			CUSTOMER	FCI www.fciconnect.com
ltr	ecn no.	dr	date	linear	0.X ±0.3		COPY	
R					0.XX ±0.13		projection	title VERTICAL SIGNAL HDR 5 ROW P.F. SPECIAL LOAD EXT.
					.XXX ±.051			
				angles	0° ±2°			
				dr	E. KROPER.	2001-01-23	MM	product family METRAL 1000 code 213
				engr	J. VOLSTORF	2001-01-23		size A dwg no 84881 sheet 4
				chr	J. VOLSTORF	2001-01-23	scale 1:1	
				appd	J. VOLSTORF	2001-01-23		
sheet index	revision sheet							cage code 22526

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

REV E - 2006-04-18

Pro/E

PDM: Rev:R STATUS: Released Printed: May 13, 2011

SPECIAL LOAD PATTERNS

PRODUCT #	ROW	PIN CODES
84881-XYY001 SEE NOTE 16 LEAD FREE OPTION	E	01
	D	
	C	
	B	
	A	
	GND	
84881-XYY011 SEE NOTE 16 LEAD FREE OPTION	E	02
	D	
	C	
	B	
	A	
	GND	01
84881-XYY021 SEE NOTE 16 LEAD FREE OPTION	E	03
	D	
	C	
	B	
	A	
	GND	01
84881-XYY050 *RPU ** SEE NOTE 16 LEAD FREE OPTION	E	19
	D	
	C	
	B	
	A	
	GND	02

PCB THICKNESS RANGE FOR REAR PLUG-UP APPLICATIONS: 2.95 TO 3.80

* REAR PLUG-UP PART NUMBERS

** CANNOT BE MATED WITH METRAL 4000 RECEPTACLE.

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

mat'l code SEE NOTE 5				tolerances unless otherwise specified			CUSTOMER COPY
ltr	ecn no.	dr	date	linear	0.X ±0.3		
R					0.XX ±0.13		projection
					.XXX ±.051		
				angles	0° ±2°		
				dr	E. KROPER.	2001-01-23	MM
				engr	J. VOLSTORF	2001-01-23	
				chr	J. VOLSTORF	2001-01-23	scale 1:1
				appd	J. VOLSTORF	2001-01-23	
sheet index	revision sheet						

FCI www.fciconnect.com

title VERTICAL SIGNAL HDR 5 ROW P.F. SPECIAL LOAD EXT.

product family METRAL 1000 | code 213

size A | dwg no 84881 | sheet 5

cage code 22526

Pro/E

REV E - 2006-04-18

PDM: Rev:R STATUS: Released Printed: May 13, 2011

PRODUCT NUMBER
SEE SHEET 1

NOTES:

1. SEE APPLICATION SPECIFICATION GS-20-010 FOR INFORMATION ON AVAILABLE TOOLING, CIRCUIT BOARD DESIGN CONSIDERATIONS, REPAIR PROCEDURES AND PRODUCT OFFERINGS.

2. SEE FCI PUBLICATION 95051I-028 FOR "ELECTRICAL PERFORMANCE DATA FOR DIFFERENTIAL APPLICATIONS."

3. SEE FCI PUBLICATION 95051I-029 FOR "ELECTRICAL PERFORMANCE DATA FOR SINGLE-ENDED APPLICATION."

4. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS AND TOLERANCES ARE IN ACCORDANCE WITH ASME Y14.5M, 1994

5. HOUSING MATERIAL: LIQUID CRYSTAL POLYMER, 30% GLASS FILLED, FLAME RETARDANT PER UL 94-V0.
PIN MATERIAL: PHOSPHER BRONZE
GROUND SPRING MATERIAL: PHOSPHER BRONZE

6. PLATING INFORMATION: PLATING ON CONTACT AREA MEETS THE PERFORMANCE LEVELS AS SHOWN IN TABLE ON SHEET 1.
PLATING ON "LF" TAILS IS Sn, PLATING ON ALL OTHER TAILS IS SnPb.

7. DIMENSIONAL RESTRICTIONS OF PINS IN HEADERS.
FOR MATING WITH METRAL 1000 RECEPTACLES
DIM A : 5.00mm MIN, 8.00mm MAX FOR ROWS A-E
DIM A : 5.00mm MIN, 5.75mm MAX FOR ROW GND NEXT TO ROW A
DIM C : 5.00mm MIN, 8.00mm MAX FOR ROWS A-E
DIM C : 4.60mm MIN, 6.30mm MAX FOR ROW GND NEXT TO ROW A
FOR MATING WITH METRAL 4000 RECEPTACLES
DIM A : 5.00mm MIN, 6.50mm MAX FOR ROWS A, B, D & E
DIM A : 5.00mm MIN, 8.00mm MAX FOR ROW C
DIM A : 5.00mm MIN, 5.75mm MAX FOR ROW GND NEXT TO ROW A
DIM C : 5.00mm MIN, 7.00mm MAX FOR ROWS A, B, D & E
DIM C : 5.00mm MIN, 8.00mm MAX FOR ROW C
DIM C : 4.60mm MIN, 6.30mm MAX FOR ROW GND NEXT TO ROW A

8. THE MIN PCB THICKNESS FOR REAR PLUG-UP APPLICATIONS IS 2.9mm SINCE THE COMPLIANT SECTIONS OF THE GROUND SPRING OF THE HEADER DIRECTLY OPPOSE THE GROUND SPRING OF THE SHROUD. THE MIN PCB THICKNESS FOR FRONT PLUG-UP ONLY APPLICATIONS IS 1.6mm.

9. THESE HOLES ARE NEEDED FOR REAR PLUG-UP DESIGNS USING A SHROUD AND MAY BE OMITTED FOR FRONT PLUG-UP ONLY DESIGNS.

10. THE 'CONNECTOR OUTLINE' IS THE MIN OUTLINE REQUIRED. TO DETERMINE THE OUTLINE NECESSARY TO PERMIT THE VARIOUS TYPES OF REPAIR OPERATIONS, SEE APPLICATION SPECIFICATION GS-20-010.

11. CURRENT RATING : 1 AMP PER PIN

12. TEMPERATURE RANGE : -55°C TO +105°C

13. P/N 84881-XYYZZZLF



14. P/N 84881-X01ZZZ SHOWN.

15. PRODUCTS WHERE THE PART NUMBERS ENDS IN LF MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
ALL PRODUCTS WILL WITHSTAND EXPOSURE TO 260°C FOR 60 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.

16. FOR LEAD FREE PART NUMBERS ADD 'LF' SUFFIX.
EXAMPLE: 84881-XYYYLF

17. PIN TYPE IS AT THE MANUFACTURERS OPTION AND CAN BE EITHER BABY-H OR EYE OF THE NEEDLE STYLE

mat'l code SEE NOTE 5				tolerances unless otherwise specified			CUSTOMER	FCI www.fciconnect.com
ltr	ecn no.	dr	date	linear	0.X ±0.3		COPY	
R					0.XX ±0.13		projection	title VERTICAL SIGNAL HDR 5 ROW P.F. SPECIAL LOAD EXT.
					.XXX ±.051			
				angles	0° ±2°			
				dr	E. KROPER.	2001-01-23	MM	product family METRAL 1000 code 213
				engr	J. VOLSTORF	2001-01-23		
				chr	J. VOLSTORF	2001-01-23	scale 1:1	size A dwg no 84881 sheet 6
				appd	J. VOLSTORF	2001-01-23		
sheet index	revision sheet							cage code 22526

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

REV E - 2006-04-18

Pro/E

PDM: Rev:R STATUS: Released Printed: May 13, 2011


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.