


OptiMOS® P-Power-Transistor
Features

- dual P-Channel in SO8
- Qualified according JEDEC for target applications
- 150°C operating temperature
- Super Logic Level (2.5V rated)
- Pb-free plating; RoHS compliant
- Halogen-free according to IEC61249-2-21


Product Summary

| | | | |
|------------------|-----------------------|------|----|
| V_{DS} | | -20 | V |
| $R_{DS(on),max}$ | $V_{GS}=4.5\text{ V}$ | 45.0 | mΩ |
| | $V_{GS}=2.5\text{ V}$ | 70.0 | |
| I_D | | -5.7 | A |



| Type | Package | Marking | Lead free | Halogen free | Packing |
|-----------|----------|---------|-----------|--------------|---------|
| BSO207P H | PG-DSO-8 | 207P | Yes | Yes | dry |

Maximum ratings, at $T_j=25\text{ °C}$, unless otherwise specified

| Parameter | Symbol | Conditions | Value | | Unit |
|----------------------------------------|----------------|-----------------------------------------|-------------|--------------|------|
| | | | 10 secs | steady state | |
| Continuous drain current ¹⁾ | I_D | $V_{GS}=4.5\text{ V}, T_A=25\text{ °C}$ | -5.7 | -5.0 | A |
| | | $V_{GS}=4.5\text{ V}, T_A=70\text{ °C}$ | -4.6 | -4.0 | |
| | | $V_{GS}=2.5\text{ V}, T_A=25\text{ °C}$ | -4.5 | -4.0 | |
| | | $V_{GS}=2.5\text{ V}, T_A=70\text{ °C}$ | -3.6 | -3.2 | |
| Pulsed drain current ²⁾ | $I_{D,pulse}$ | $T_A=25\text{ °C}$ | -22.8 | | |
| Avalanche energy, single pulse | E_{AS} | $I_D=-5.7\text{ A}, R_{GS}=25\text{ Ω}$ | 44 | | mJ |
| Gate source voltage | V_{GS} | | ±12 | | V |
| Power dissipation ¹⁾ | P_{tot} | $T_A=25\text{ °C}$ | 2 | 1.6 | W |
| Operating and storage temperature | T_j, T_{stg} | | -55 ... 150 | | °C |
| ESD class | | JESD22-A114 HBM | 1A < 500V | | |
| Soldering temperature | | | 260 | | °C |
| IEC climatic category; DIN IEC 68-1 | | | 55/150/56 | | |

| Parameter | Symbol | Conditions | Values | | | Unit |
|------------------------------------------------|------------|----------------------------------------------------------------|--------|------|------|------|
| | | | min. | typ. | max. | |
| Thermal characteristics | | | | | | |
| Thermal resistance, junction - soldering point | R_{thJS} | | - | - | 35 | K/W |
| Thermal resistance, junction - ambient | R_{thJA} | minimal footprint, $t_p \leq 10$ s | - | - | 110 | |
| | | minimal footprint, steady state | - | - | 150 | |
| | | 6 cm ² cooling area ¹⁾ , $t_p \leq 10$ s | - | - | 62.5 | |
| | | 6 cm ² cooling area ¹⁾ , steady state | - | - | 80 | |

Electrical characteristics, at $T_j=25$ °C, unless otherwise specified

Static characteristics

| | | | | | | |
|----------------------------------|---------------|--------------------------------------------------|------|------|------|------------|
| Drain-source breakdown voltage | $V_{(BR)DSS}$ | $V_{GS}=0$ V, $I_D=-0.25$ mA | -20 | - | - | V |
| Gate threshold voltage | $V_{GS(th)}$ | $V_{DS}=V_{GS}$, $I_D=44$ μ A | -0.6 | -0.9 | -1.2 | |
| Zero gate voltage drain current | I_{DSS} | $V_{DS}=-20$ V, $V_{GS}=0$ V, $T_j=25$ °C | - | 0.1 | 1 | μ A |
| | | $V_{DS}=-20$ V, $V_{GS}=0$ V, $T_j=150$ °C | - | 10 | 100 | |
| Gate-source leakage current | I_{GSS} | $V_{GS}=-12$ V, $V_{DS}=0$ V | - | - | -100 | nA |
| Drain-source on-state resistance | $R_{DS(on)}$ | $V_{GS}=2.5$ V, $I_D=-4.5$ A | - | 44 | 70 | m Ω |
| | | $V_{GS}=4.5$ V, $I_D=-5.7$ A | - | 32 | 45 | |
| Gate resistance | R_G | | - | 7.7 | - | Ω |
| Transconductance | g_{fs} | $ V_{DS} > 2 I_D R_{DS(on)max}$, $I_D=-4.6$ A | 10 | 18 | - | S |

¹⁾ Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm² (one layer, 70 μ m thick) copper area for drain connection. PCB is vertical in still air.

²⁾ See figure 3 for more detailed information

³⁾ See figure 13 for more detailed information

| Parameter | Symbol | Conditions | Values | | | Unit |
|-----------|--------|------------|--------|------|------|------|
| | | | min. | typ. | max. | |

Dynamic characteristics

| | | | | | | |
|------------------------------|--------------|------------------------------------------------------------------------------------------|---|------|------|----|
| Input capacitance | C_{iss} | $V_{GS}=0\text{ V}, V_{DS}=15\text{ V},$ $f=1\text{ MHz}$ | - | 1100 | 1650 | pF |
| Output capacitance | C_{oss} | | - | 380 | 570 | |
| Reverse transfer capacitance | C_{rss} | | - | 310 | 465 | |
| Turn-on delay time | $t_{d(on)}$ | $V_{DD}=-10\text{ V},$ $V_{GS}=4.5\text{ V}, I_D=-5.7\text{ A},$ $R_G=1.6\ \Omega$ | - | 9 | 14 | ns |
| Rise time | t_r | | - | 22 | 33 | |
| Turn-off delay time | $t_{d(off)}$ | | - | 33 | 50 | |
| Fall time | t_f | | - | 35 | 53 | |

Gate Charge Characteristics⁴⁾

| | | | | | | |
|--------------------------|---------------|--------------------------------------------------------------------------------|---|------|------|----|
| Gate to source charge | Q_{gs} | $V_{DD}=-10\text{ V}, I_D=-5.7\text{ A},$ $V_{GS}=0\text{ to }4.5\text{ V}$ | - | -2 | -3 | nC |
| Gate charge at threshold | $Q_{g(th)}$ | | - | -2 | -3 | |
| Gate to drain charge | Q_{gd} | | - | -5 | -7 | |
| Switching charge | Q_{sw} | | - | -5 | -7 | |
| Gate charge total | Q_g | | - | -12 | -16 | |
| Gate plateau voltage | $V_{plateau}$ | | - | -1.7 | -2.5 | |
| Output charge | Q_{oss} | $V_{DD}=-10\text{ V}, V_{GS}=0\text{ V}$ | - | 7 | 9 | nC |


Reverse Diode

| | | | | | | |
|----------------------------------|---------------|---------------------------------------------------------------------------|---|-----|------|----|
| Diode continuous forward current | I_S | $T_A=25\text{ }^\circ\text{C}$ | - | - | -2.2 | A |
| Diode pulse current | $I_{S,pulse}$ | | - | - | -23 | |
| Diode forward voltage | V_{SD} | $V_{GS}=0\text{ V}, I_F=-5.7\text{ A},$ $T_j=25\text{ }^\circ\text{C}$ | - | - | -1.1 | V |
| Reverse recovery charge | Q_{rr} | $V_R=10\text{ V}, I_F=I_S,$ $di_F/dt=100\text{ A}/\mu\text{s}$ | - | 6.2 | - | nC |

⁴⁾ See figure 16 for gate charge parameter definition

1 Power dissipation


$P_{tot}=f(T_A); t_p \leq 10 \text{ s}$



2 Drain current

$I_D=f(T_A); t_p \leq 10 \text{ s}$


parameter: $V_{GS} = 4.5 \text{ V}$



3 Safe operating area

$I_D=f(V_{DS}); T_A=25 \text{ °C}^2; D=0$


parameter: t_p



4 Max. transient thermal impedance

$Z_{thJA}=f(t_p^2)$


parameter: $D=t_p/T$



5 Typ. output characteristics

$I_D = f(V_{DS}); T_j = 25\text{ }^\circ\text{C}$


parameter: V_{GS}



6 Typ. drain-source on resistance

$R_{DS(on)} = f(I_D); T_j = 25\text{ }^\circ\text{C}$


parameter: V_{GS}



7 Typ. transfer characteristics


$I_D = f(V_{GS}); |V_{DS}| > 2|I_D|R_{DS(on)max}$

parameter: T_j




8 Typ. forward transconductance

$g_{fs} = f(I_D); T_j = 25\text{ }^\circ\text{C}$




9 Drain-source on-state resistance

$R_{DS(on)} = f(T_j); I_D = -5.7 \text{ A}; V_{GS} = -4.5 \text{ V}$




10 Typ. gate threshold voltage

$V_{GS(th)} = f(T_j); V_{GS} = V_{DS}; I_D = -44 \mu\text{A}$



11 Typ. capacitances


$C = f(V_{DS}); V_{GS} = 0 \text{ V}; f = 1 \text{ MHz}$



12 Forward characteristics of reverse diode

$I_F = f(V_{SD})$


parameter: T_j



13 Avalanche characteristics

$I_{AS}=f(t_{AV}); R_{GS}=25 \Omega$


parameter: $T_{j(start)}$



14 Typ. gate charge


$V_{GS}=f(Q_{gate}); I_D=-5.7 A$ pulsed

parameter: V_{DD}




15 Drain-source breakdown voltage

$V_{BR(DSS)}=f(T_j); I_D=0.25 mA$




16 Gate charge waveforms



Package Outline

PG-DSO-8: Outline



1) DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS.

| DIM | MILLIMETERS | | INCHES | |
|----------------|-------------|------|--------|-------|
| | MIN | MAX | MIN | MAX |
| A | - | 1.75 | - | 0.069 |
| A1 | 0.10 | - | 0.004 | - |
| A2 | 1.25 | 1.65 | 0.049 | 0.065 |
| b | 0.35 | 0.51 | 0.014 | 0.020 |
| c | 0.17 | 0.25 | 0.007 | 0.010 |
| D | 4.80 | 5.00 | 0.189 | 0.197 |
| E | 5.80 | 6.20 | 0.228 | 0.244 |
| E1 | 3.80 | 4.00 | 0.150 | 0.157 |
| e | 1.27 | | 0.050 | |
| N | 8 | | 8 | |
| L | 0.39 | 0.89 | 0.015 | 0.035 |
| h | 0.23 | 0.50 | 0.009 | 0.020 |
| θ | 0° | 8° | 0° | 8° |
| θ ₁ | - | 19° | - | 19° |
| ccc | 0.10 | | 0.004 | |
| ddd | 0.25 | | 0.010 | |
| F1 | 5.59 | 5.79 | 0.220 | 0.228 |
| F2 | 0.55 | 0.75 | 0.022 | 0.030 |
| F3 | 1.21 | 1.41 | 0.048 | 0.056 |

DOCUMENT NO.
Z8B00003333

SCALE

EUROPEAN PROJECTION

ISSUE DATE
09.01.2008

REVISION
02

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2009 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.