


## IR Receiver Modules for Remote Control Systems



### DESIGN SUPPORT TOOLS

[click logo to get started](#)


### FEATURES

- Improved dark sensitivity
- Improved immunity against optical noise
- Very low supply current
- Photo detector and preamplifier in one package
- Internal filter for PCM frequency
- Low supply voltage: 2.0 V to 3.6 V
- Insensitive to supply voltage ripple and noise
- Material categorization:  
for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



### MECHANICAL DATA

1 = OUT, 2 = GND, 3 =  $V_S$ 

### DESCRIPTION

The TSOP98... series devices are the latest generation miniaturized IR receiver modules for infrared remote control systems. This series provides improvements in sensitivity to remote control signals in dark ambient as well as in sensitivity in the presence of optical disturbances e.g. from CFLs.

The devices contain a PIN diode and a preamplifier assembled on a lead frame. The epoxy package contains an IR filter. The demodulated output signal can be directly connected to a microprocessor for decoding.



The TSOP986.. series devices are designed to receive long burst codes (10 or more carrier cycles per burst). The third digit designates the AGC level (AGC6) and the last two digits designate the band-pass frequency (see table below). The higher the AGC, the better noise is suppressed, but the lower the code compatibility. AGC6 provides maximized noise suppression. Generally, we advise to select the highest AGC that satisfactorily receives the desired remote code.

These components have not been qualified to automotive specifications.

| PARTS TABLE       |        |                                                                                                                                                                                                                                                                       |
|-------------------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AGC               |        | MAXIMIZED NOISE SUPPRESSION (AGC6)                                                                                                                                                                                                                                    |
| Carrier frequency | 30 kHz | TSOP98630                                                                                                                                                                                                                                                             |
|                   | 33 kHz | TSOP98633                                                                                                                                                                                                                                                             |
|                   | 36 kHz | TSOP98636 <sup>(5)(6)</sup>                                                                                                                                                                                                                                           |
|                   | 38 kHz | TSOP98638 <sup>(3)(4)(11)</sup>                                                                                                                                                                                                                                       |
|                   | 40 kHz | TSOP98640                                                                                                                                                                                                                                                             |
|                   | 56 kHz | TSOP98656                                                                                                                                                                                                                                                             |
| Package           |        | Minicast                                                                                                                                                                                                                                                              |
| Pinning           |        | 1 = OUT, 2 = GND, 3 = $V_S$                                                                                                                                                                                                                                           |
| Dimensions (mm)   |        | 5.0 W x 6.95 H x 4.8 D                                                                                                                                                                                                                                                |
| Mounting          |        | Leaded                                                                                                                                                                                                                                                                |
| Application       |        | Remote control                                                                                                                                                                                                                                                        |
| Best choice for   |        | <sup>(1)</sup> Cisco <sup>(2)</sup> MCIR <sup>(3)</sup> Mitsubishi <sup>(4)</sup> NEC <sup>(5)</sup> Panasonic <sup>(6)</sup> RC-5 <sup>(7)</sup> RC-6 <sup>(8)</sup> RCA <sup>(9)</sup> r-step <sup>(10)</sup> Sejin 4PPM <sup>(11)</sup> Sharp <sup>(12)</sup> Sony |

### Notes

- 30 kHz and 33 kHz only available on written request
- See datasheet for TSOP982..., TSOP984.. for preferred devices for <sup>(1)(2)(7)(8)(9)(10)(12)</sup>

**BLOCK DIAGRAM**

**APPLICATION CIRCUIT**


$R_1$  and  $C_1$  recommended to reduce supply ripple for  $V_S < 2.2$  V

**ABSOLUTE MAXIMUM RATINGS**

| PARAMETER                   | TEST CONDITION                | SYMBOL    | VALUE                   | UNIT |
|-----------------------------|-------------------------------|-----------|-------------------------|------|
| Supply voltage              |                               | $V_S$     | -0.3 to +3.6            | V    |
| Supply current              |                               | $I_S$     | 3                       | mA   |
| Output voltage              |                               | $V_O$     | -0.3 to ( $V_S + 0.3$ ) | V    |
| Output current              |                               | $I_O$     | 5                       | mA   |
| Junction temperature        |                               | $T_j$     | 100                     | °C   |
| Storage temperature range   |                               | $T_{stg}$ | -25 to +85              | °C   |
| Operating temperature range |                               | $T_{amb}$ | -25 to +85              | °C   |
| Power consumption           | $T_{amb} \leq 85$ °C          | $P_{tot}$ | 10                      | mW   |
| Soldering temperature       | $t \leq 10$ s, 1 mm from case | $T_{sd}$  | 260                     | °C   |

**Note**

- Stresses beyond those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect the device reliability

**ELECTRICAL AND OPTICAL CHARACTERISTICS** ( $T_{amb} = 25$  °C, unless otherwise specified)

| PARAMETER             | TEST CONDITION                                                             | SYMBOL               | MIN. | TYP.     | MAX. | UNIT              |
|-----------------------|----------------------------------------------------------------------------|----------------------|------|----------|------|-------------------|
| Supply current        | $E_v = 0$ , $V_S = 3.3$ V                                                  | $I_{SD}$             | 0.25 | 0.37     | 0.45 | mA                |
|                       | $E_v = 40$ klx, sunlight                                                   | $I_{SH}$             | -    | 0.50     | -    | mA                |
| Supply voltage        |                                                                            | $V_S$                | 2.0  | -        | 3.6  | V                 |
| Transmission distance | $E_v = 0$ , test signal see Fig. 1, IR diode TSAL6200, $I_F = 50$ mA       | $d$                  | -    | 24       | -    | m                 |
| Output voltage low    | $I_{OSL} = 0.5$ mA, $E_e = 0.7$ mW/m <sup>2</sup> , test signal see Fig. 1 | $V_{OSL}$            | -    | -        | 100  | mV                |
| Minimum irradiance    | Test signal: NEC code                                                      | $E_{e \text{ min.}}$ | -    | 0.12     | 0.25 | mW/m <sup>2</sup> |
| Maximum irradiance    | $t_{pi} - 5/f_0 < t_{po} < t_{pi} + 6/f_0$ , test signal see Fig. 1        | $E_{e \text{ max.}}$ | 30   | -        | -    | W/m <sup>2</sup>  |
| Directivity           | Angle of half transmission distance                                        | $\phi_{1/2}$         | -    | $\pm 45$ | -    | deg               |


**TYPICAL CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)


Fig. 1 - Output Delay and Pulse-Width




Fig. 4 - Pulse-Width vs. Irradiance in Dark Ambient




Fig. 2 - Pulse-Width vs. Irradiance in Dark Ambient




Fig. 5 - Frequency Dependence of Responsivity




Fig. 3 - Test Signal




Fig. 6 - Sensitivity in Bright Ambient




Fig. 7 - Sensitivity vs. Supply Voltage Disturbances




Fig. 9 - Sensitivity vs. Ambient Temperature




Fig. 8 - Max. Envelope Duty Cycle vs. Burst Length




Fig. 10 - Relative Spectral Sensitivity vs. Wavelength




Fig. 11 - Horizontal and Vertical Directivity




Fig. 12 - Sensitivity vs. Supply Voltage

## SUITABLE DATA FORMAT

This series is designed to suppress spurious output pulses due to noise or disturbance signals. The devices can distinguish data signals from noise due to differences in frequency, burst length, and envelope duty cycle. The data signal should be close to the device's band-pass center frequency (e.g. 38 kHz) and fulfill the conditions in the table below.

When a data signal is applied to the product in the presence of a disturbance, the sensitivity of the receiver is automatically reduced by the AGC to insure that no spurious pulses are present at the receiver's output.

Some examples which are suppressed are:

- DC light (e.g. from tungsten bulbs sunlight)
- Continuous signals at any frequency
- Strongly or weakly modulated patterns from fluorescent lamps with electronic ballasts (see Fig. 13 or Fig. 14)




Fig. 13 - IR Disturbance from Fluorescent Lamp With Low Modulation




Fig. 14 - IR Disturbance from Fluorescent Lamp With High Modulation


|                                                    | <b>TSOP986..</b>    |
|----------------------------------------------------|---------------------|
| Minimum burst length                               | 10 cycles/burst     |
| Minimum gap time between bursts                    | ≥ 13 cycles         |
| Minimum idle period between data frames            | 12 ms               |
| RC-5 code                                          | Preferred           |
| RC-6 code                                          | Yes                 |
| NEC code                                           | Preferred           |
| r-step code 56 kHz                                 | Yes                 |
| Sony code                                          | No                  |
| RCA 56 kHz code                                    | Yes                 |
| Mitsubishi code 38 kHz                             | Preferred           |
| Suppression of interference from fluorescent lamps | Fig. 13 and Fig. 14 |

### Note

- For data formats with short bursts please see the datasheet for TSOP983..., TSOP985..



**PACKAGE DIMENSIONS** in millimeters





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.