



FLIR **DM90**

TRMS Multimeter with Type K Temperature

The DM90 is an affordable True RMS digital multimeter with a Type K Temperature function, an ideal tool for electricians, service technicians and HVAC professionals to have on the job. Equipped with rich features including LoZ, Variable Frequency Drive (VFD), and uA current measurement capability, the DM90 gives you trusted readings to troubleshoot and repair a wide range of electrical and electronic systems. The DM90 is shipped fully tested and calibrated, and with proper use, will provide years of reliable service.

Trusted readings

Verify problems with accurate readings

- Measures Voltage, Current, Frequency, Resistance, Continuity, Diode, Capacitance, and Temperature
- Features LoZ, VFD, uA measurement, Smart/Classic Diode modes
- Measures voltage up to 1000V AC/DC

Feature-rich DMM

An ideal tool to have in the field

- Powerful LED worklights eliminate need for flashlight in dim lighting
- Digital LCD display with bargraph, customizable, easy-to-use settings option menu, and on-screen programming menu navigation
- Min/Max/Avg, Peak Min/Max, Hold, Auto Hold, Auto Power Off with Disable
- Includes a built-in non-contact AC voltage detector

Built to last

Will provide years of reliable service

- Provides industry-leading Limited Lifetime Warranty
- Made tough for protection against splashing water (IP54 rating), and withstands a 3-meter drop



Troubleshoot Variable Frequency Drives using VFD mode



Includes Type K Thermocouple input for temperature measurements

Specifications

Measurements	
Maximum voltage	1000 V DC or 1000 V AC True RMS
Display count	6000
Frequency	100.00 Hz $\pm$ (0.1% + 2D) 1000.0 Hz $\pm$ (0.1% + 2D) 10.000 kHz $\pm$ (0.1% + 2D) 100.00 kHz $\pm$ (0.1% + 2D)
Resistance	600.0 Ω $\pm$ (0.9% + 5D) 6.000 k Ω $\pm$ (0.9% + 2D) 60.00 k Ω $\pm$ (0.9% + 2D) 600.0 k Ω $\pm$ (0.9% + 2D) 6.000 M Ω $\pm$ (0.9% + 2D) 50.00 M Ω $\pm$ (3.0% + 5D)
Continuity check	600.0 Ω $\pm$ (0.9% + 5D)
Diode test	1.500 $\pm$ (0.9% + 2D)
Capacitance	1000 nF $\pm$ (1.9% + 5D) 10.00 μ F $\pm$ (1.9% + 2D) 100.0 μ F $\pm$ (0.9% + 2D) 1.000 mF $\pm$ (0.9% + 2D) 10.00 mF $\pm$ (0.9% + 2D) 40.00 mF $\pm$ (2.0% + 20D)
Temperature, Type K thermocouple	-40 to 752.0°F DMM $\pm$ (1.0% + 5.4°F)/ IGM $\pm$ (1.0% + 9°F), -40 to 400.0°C DMM $\pm$ (1.0% + 3°C)/ IGM $\pm$ (1.0% + 5°C)
Measuring rate	3 samples per second
General Information	
Category rating	CAT IV - 600 V, CAT III - 1000 V
IP rating	IP54
Battery life	Alkaline ~110hrs, LithiumPolymer (Optional)~ 500hrs
Battery type	4x AAA (included)
Drop test	3M
Warranty	Limited lifetime warranty

What's In the Box	UPC
DM90 True RMS Multimeter with Type K Temperature	793950370841
TA84 Test Lead Storage/Tripod	793950377840
TA70 CAT IV Insulated Alligator Probes (Slip On)	793950377703
TA60 Thermocouple Adapter with Type K Probe	793950377604
Accessories Optional	UPC
TA72 Universal Flex Current Probe Accessory 25cm (10")	793950377727
TA74 Universal Flex Current Probe Accessory 45cm (18")	793950377741
TA04-KIT Lithium Polymer Rechargeable Battery Kit	793950377048
TA15 Soft Sided Carrying Case	793950377154
TA52 Magnet Mount	793950377529
TA50 Magnetic Hanging Strap	793950377505
TA42 Belt Clip	793950374207
TA10 Protective Case for FLIR DMMs	793950377109
TA10-F Protective Case for FLIR DMMs and TA7X	793950377208

Specifications are subject to change without notice. For the most up-to-date specifications, go to www.flir.com

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2017 FLIR Systems, Inc. All rights reserved. (Updated Jan 24) 17-0072



Optional TA7x Flex Current Probe adds 3000A AC current measurement capability



Built-in worklight eliminates the need for a flashlight



PORTLAND
Corporate Headquarters
FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
PH: +1 866.477.3687

NASHUA
FLIR Systems, Inc.
9 Townsend West
Nashua, NH 03063
PH: +1 866.477.3687

CANADA
FLIR Systems, Ltd.
920 Sheldon Court
Burlington, ON L7L 5K6
Canada
PH: +1 800.613.0507

LATIN AMERICA
FLIR Systems Brasil
Av. Antonio Bardella,
320 Sorocaba,
SP 18085-852
Brasil
PH: +55 15 3238 7080

CHINA
FLIR Systems Co., Ltd
Rm 1613-16, Tower II
Grand Central Plaza 1
38 Shatin Rural
Committee Rd.
Shatin, New Territories
Hong Kong
PH: +852 2792 8955

BELGIUM
FLIR Systems
Luxemburgstraat 2
2321 Meer
Belgium
PH: +32 (0) 3665 5100

UNITED KINGDOM
FLIR Systems UK
2 Kings Hill Ave., Kings Hill
West Malling, Kent
ME19 4AQ
United Kingdom
PH +44 (0)1732 220 011

www.flir.com
NASDAQ: FLIR



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.