



LVDS-DVI

18-bit LVDS to DVI converter board, resolution support up to 1366x768 (Support IEI Model Only)



Dimensions (Unit: mm)



Features

- ◆ Provide DVI option for dual display output
- ◆ Resolution supported: 1366x768, 1024x768, 800x600, 640x480
- ◆ 18 or 24-bit LVDS to DVI converter board

Supported Models

WSB-PV-D5251	PICOe-PV-D5251	PCISA-PV-D5251
KINO-PV-D5252	NOVA-PV-D5251	NANO-PV-D5251
NANO-PV-D5252	WAFFER-PV-D5252	

Packing List


1 x LVDS to DVI converter board	
1 x SMBus cable	1 x QIG

Ordering Information


LVDS-DVI-R10	18/24-bit LVDS to DVI converter board
32602-012200-100-RS	20-pin to 30-pin LVDS connecting cable for WAFFER-PV-D5252 only
32602-012300-100-RS	20-pin to 20-pin LVDS connecting cable

LVDS-VGA02

18-bit LVDS to VGA converter board, resolution support up to 1366x768 (Support IEI Model Only)



Dimensions (Unit: mm)



Features

- ◆ Provide VGA option for dual VGA display output
- ◆ Resolution supported: 1366x768, 1024x768, 800x600, 640x480
- ◆ 18 or 24-bit LVDS to VGA converter board

Supported Models

WSB-PV-D5251	PICOe-PV-D5251	PCISA-PV-D5251
KINO-PV-D5252	NOVA-PV-D5251	NANO-PV-D5251
NANO-PV-D5252	WAFFER-PV-D5252	

Packing List


1 x LVDS to VGA converter board	
1 x SMBus cable	1 x QIG

Ordering Information


LVDS-VGA02-R10	18/24-bit LVDS to VGA converter board
32602-012200-100-RS	20-pin to 30-pin LVDS connecting cable for WAFFER-PV-D5252 only
32602-012300-100-RS	20-pin to 20-pin LVDS connecting cable

LVDS-VGA-R10

Single-channel LVDS to VGA converter board (Support IEI Model Only)



Dimensions (Unit: mm)



Features

- ◆ Provide 2nd VGA option for dual VGA display
- ◆ Resolution adjust by BIOS: Support 1024x768, 800x600, 640x480
- ◆ 18-bit LVDS to VGA converter board

Packing List

1 x LVDS to VGA converter board	
1 x QIG	


Ordering Information

Part No.	Description
LVDS-VGA-R10	18-bit LVDS to VGA converter board
32600-112300-RS	30-pin LVDS connecting cable
32600-114400-RS	20-pin LVDS connecting cable


LVDS24-01

18-bit to 24-bit LVDS converter board

24-bit dual-channel output



Dimensions (Unit: mm)



Features

- ◆ Resolution supports up to 1280x1024
- ◆ Support below configuration:
 - » Single-channel 18-bit to single-channel 24-bit
 - » Single-channel 18-bit to dual-channel 24-bit
 - » Dual-channel 18-bit to dual-channel 24-bit

* Note: The module does not support dual-channel 18-bit to single-channel 24-bit conversion.

Packing List

1 x 18-bit to 24-bit LVDS converter board	
1 x Power cable (P/N: 32100-130300-RS)	
1 x QIG	



Power cable
P/N: 32100-130300-RS

Ordering Information

Part No.	Description
LVDS24-01-R10	18-bit to 24-bit LVDS converter board
32602-007900-100-RS	Single-channel 18-bit 20-pin to 24-bit LVDS 30-pin connection cable
32602-008000-100-RS	Dual-channel 18-bit 30-pin to 24-bit 30-pin LVDS connection cable



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.