



FCIconnect.com

Copyright FCI

PRODUCT NUMBER

5 4 2 0 2 - X X X X X - X X X LF

PLATING

S=15μ" [0.38μm]
ON CONTACT AREA
100μ" [2.5μm] TIN
ON TAIL (NOTE 13)

G=30μ" [0.76μm]
ON CONTACT AREA
100μ" [2.5μm] TIN
ON TAIL (NOTE 13)

T=100μ" [2.5μm] TIN
ON CONTACT AREA
AND ON TAIL (SEE NOTE 11)

F=2μ" [0.05μm] GOLD
ON CONTACT AREA
AND ON TAIL

LEAD FREE OPTION NOTE 9 & 10

POLARIZATION
NOTE 6

PACKAGING TYPE, NOTE 5

POSITIONS PER ROW
02 TO 20

LEAD STYLE	POST	TAIL OVERALL WIDTH	PCB LAYOUT
08 30	0.230/5.84 0.318/8.08	.290 ^{+0.015} _{-0.017} / 7.37 ^{+0.38} _{-0.43}	FIGURE 1
60	0.575/14.60	.374 ^{+0.015} _{-0.017} / 9.50 ^{+0.38} _{-0.43}	FIGURE 2

NOTES:

- ① HOUSING MAT'L: HIGH TEMPERATURE THERMOPLASTIC.
FLAME RETARDANT PER UL 94V-0
COLOR: BLACK
OR
MINERAL FILLED LCP FLAME RETARDANT
PER UL-94V-0. COLOR: BLACK.
- THESE PART NUMBERS WILL WITHSTAND EXPOSURE
TO 260 C PEAK TEMPERATURE FOR 20 SECONDS IN
WAVE SOLDER, INFRA-RED OR VAPOR PHASE SOLDER PROCESS.

- ② PIN MATERIAL: PHOSPHOR-BRONZE

- ③ TO DETERMINE DIMENSIONS:
N = NUMBER OF POSITIONS ROW.
EXAMPLE: 10 POS., N x .100/2.54=1.00/25.4

- ④ 2LBS/0.9KG MIN. PIN RETENTION IN EITHER DIRECTION.

- ⑤ PACKAGING: NONE =POLY BAGS WITHOUT PICKUP CAP.
T =TUBES (OMIT DASH IF NOT POLARIZED).

P =TUBES WITH PICKUP CAPS.

A =TAPE AND REEL WITH PICKUP CAPS.

C =CUSTOMIZED TAPE AND REEL WITH PICKUP CAPS.

D =TAPE AND REEL WITHOUT PICKUP CAPS.

S =SPECIAL REQUEST OF TAPE AND REEL WITH PICKUP CAPS.

M =TAPE AND REEL WITH PICKUP CAPS FOR SPECIAL CUSTOMER.

- ⑥ FOR POLARIZATION, SPECIFY POSITION NUMBER
(i.e. A03=ROW A POS. 3) TO OMIT PIN.
OMIT FROM PRODUCT NUMBER IF THIS FEATURE IS NOT APPLICABLE.
PRODUCT MANAGEMENT APPROVAL REQUIRED PRIOR TO RELEASE
OR SALE OF POLARIZED PRODUCTS.

7. UNDERPLATING: 50μ" /1.2μm Ni.

8. PIN TIPS ON Sn PLATED PRODUCT MAY HAVE BARE METAL ON TWO SIDES,
BOTH ENDS.



- ⑨ PART NUMBERS WITH "LF" SUFFIX AT THE END ARE LEAD FREE.

- ⑩ THESE PRODUCTS MEETS EUROPEAN UNION DIRECTIVES AND OTHER
COUNTRY REGULATION AS DESCRIBED IN GS-22-008.

- ⑪ "THIS PRODUCT HAS 100% PURE TIN PLATING IN THE INTERFACE AND
HAS NOT BEEN TESTED FOR WHISKER GROWTH IN ALL INTERCONNECT
ENVIRONMENTS."




12. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE
FOR 20 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW
OVEN. SEE APPLICATION NOTES/PROCEDURES IF THEY ARE AVAILABLE.

- ⑬ MAY BE EITHER GOLD OR GXT PLATED AT MANUFACTURER'S OPTION



mat'l. code SEE NOTES 1&2				surface ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection INCH/MM	product family BERGSTIK
ltr	ecn	no	dr	date	tolerances unless otherwise specified		title
W	EXL-N-12227	JZ		2012-07-15	angles linear	XXL01/XXL03	.100 UNSHROUDED HDR
X	ELX-N-14748	ZK		2013-05-14		XXX005/XXX013	DUAL ROW VERT. SMT.
Y	ELX-N-19883	JH		2015-01-15	0°±2°	XXX0020/XXX0051	scale 1:1
AA	ELX-N-21232	MZ		2015-06-25	dr	D.INGRAM 1999-05-17	dwg no
AB	ELX-N-22858	MZ		2015-12-22	enr	H.SUNDAY 1999-07-21	sheet 1 of 4
					chr	H.SUNDAY 1999-07-21	size
					appd	H.SUNDAY 1999-07-21	A3
sheet	revision	AB	AB	AB	AB		type
index	sheet	1	2	3	4		Product Customer Drawing

PRODUCT NUMBER
SEE SHEET 1



mat'l. code SEE NOTES 1&2	surface ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection INCH/MM	product family BERGSTIK
ltr AB	ecn no	dr date	tolerances unless otherwise specified angles linear 0°±2'	title .100 UNSHROUDED HDR DUAL ROW VERT. SMT.
			dr D.INGRAM 1999-05-17	dwg no 54202
			enr H.SUNDAY 1999-07-21	sheet 2 of 4 size A3
			chr H.SUNDAY 1999-07-21	type Product Customer Drawing
			appd H.SUNDAY 1999-07-21	
sheet index	revision sheet			



Copyright FCI



TAPE AND REEL PACKAGING

SIZE	LEAD STYLE 08 POST (0.230 [5.84])	LEAD STYLE 30 POST (0.318 [8.08])
2X2	YES	YES
2X3	YES	
2X4	YES	YES
2X5	YES	
2X6	YES	
2X7	YES	YES
2X8	YES	
2X9	YES	
2X10	YES	
2X11	YES	
2X12	YES	YES
2X13	YES	
2X14	YES	
2X15	YES	
2X16	YES	YES
2X17	YES	
2X18	YES	
2X19	YES	
2X20	YES	

Cross Reference

CORE RANGE	EXTENDED RANGE
54202-X08XXLF	95278-X01-XXLF
54202-X30XXLF	95278-X02-XXLF

TAPE AND REEL PACKAGING




CUSTOMIZED CARRIER TAPE
FOR 2x2,2x3,2x4,2x5 SIZE.
(SEE NOTE 5)

mat'l. code SEE NOTES 1&2	surface ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection INCH/MM	product family BERGSTIK
ltr AB	ecn no dr	date	tolerances unless otherwise specified linear .XX±.01/.XX±0.3 angular .XXX±.005/.XXX±0.13 0°±2' .XXX±.0020/.XXX±0.051	title .100 UNSHROUDED HDR DUAL ROW VERT. SMT.
dr D.INGRAM	enr H.SUNDAY	chr H.SUNDAY	appd H.SUNDAY	scale 1:1
sheet index	revision sheet			dwg no 54202
				sheet 3 of 4
				size A3
				type Product Customer Drawing




FCIconnect.com

Copyright FCI



54202-****SLF
SPECIAL REQUEST CARRIER TAPE
FOR 2x5 SIZE(SEE NOTES 5)



54202-****MLF
TAPE AND REEL WITH PICK UP
CAP FOR SPECIAL CUSTOMER
FOR 2x5 SIZE(SEE NOTES 5)

mat'l. code SEE NOTES 1&2					surface ISO 1302 ✓		tolerance ISO 406 ISO 1101		projection 		product family BERGSTIK				
ltr ecn no dr date					tolerances unless otherwise specified							title			
AB					angles		linear		INCH/MM		.100 UNSHROUDED HDR				
					0°±2°				scale 1:1		DUAL ROW VERT. SMT.				
					dr		D.INGRAM		1999-05-17		dwg no sheet 4 of 4 size				
					enrg		H.SUNDAY		1999-07-21		54202 A3				
					chr		H.SUNDAY		1999-07-21		type Product Customer Drawing				
					appd		H.SUNDAY		1999-07-21						
sheet index		revision sheet													



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.