GP2D020A120A

VDC	**1200**	**V**
Q_C	**86**	**nC**
I_F (T_C<135°C)	**20**	**A**

1200V SiC Schottky Diode

Amp+™ Features


- High surge current capable
- Zero reverse recovery current
- High bandwidth
- Fast, temperature-independent switching

Amp+™ Benefits

- Unipolar rectifier
- Zero switching loss
- Higher efficiency
- Smaller heat sink
- Parallel devices with thermal stability

Amp+™ Applications

- Motor drives
- Switch mode power supplies
- Power factor correction



Part #	Package	Marking
GP2D020A120A	TO-220-2L	GP2D020A120



Maximum Rating	Symbol	Conditions	Value	Unit
Continuous forward current	I_F	T_C=25 °C, T_j=175 °C	65	A
		T_C=125 °C, T_j=175 °C	36	
		T_C=150 °C, T_j=175 °C	24	
Surge non-repetitive forward current sine halfwave	$I_{F,SM}$	T_C=25 °C, t_p=8.3 ms	160	
		T_C=150 °C, t_p=8.3 ms	100	
Non-repetitive peak forward current	$I_{F,max}$	T_C=25 °C, t_p=10 µs	400	
i^2t value	$\int i^2dt$	T_C=25 °C, t_p=8.3 ms	106	A^2s
		T_C=150 °C, t_p=8.3 ms	42	
Repetitive peak reverse voltage	V_{RRM}	T_j=25 °C	1200	V
Diode *dv/dt* ruggedness	*dv/dt*	Turn-on slew rate, repetitive	50	V/ns
Power dissipation	P_{tot}	T_C=25 °C	357	W
Operating & storage temperature	T_J, $T_{storage}$	Continuous	-55…175	°C
Soldering temperature	T_{solder}	Wave soldering leads	260	°C
Mounting torque		M3 Screw	1	N-m

Electrical Characteristics, at T_j=25 °C, unless otherwise specified

Static Characteristics	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
DC blocking voltage	V_{DC}		1200	-	-	V
Diode forward voltage	V_F	I_F=20A, T_j=25 °C	-	1.6	1.8	
		I_F=20A, T_j=175 °C	-	2.2	2.7	
Reverse current	I_R	V_R=1,200V, T_j=25 °C	-	4.0	200	µA
		V_R=1,200V, T_j=175 °C	-	120	700	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
AC Characteristics						
Total capacitive charge	Q_C	V_R=1,200V, T_j=25 °C	-	86	-	nC
Switching time	t_C	di_F/dt=200 A/µs T_j=150 °C	-	-	<10	ns
Total capacitance	C	V_R=1 V, f=1 MHz	-	1270	-	pF
		V_R=600V, f=1 MHz	-	74	-	
		V_R=1,200V, f=1 MHz	-	72	-	
Thermal Characteristics						
Thermal resistance, junction-case	R_{thJC}	Package (flange) mount	-	0.42	-	°C/W

Typical Performance

Fig. 1 Forward Characteristics (parameterized on T_j)




Fig. 2 Reverse Characteristics (parameterized on Tj)




Fig. 3 Power Derating




Fig. 4 Current Derating




Fig. 5 Capacitance






Fig. 6 Recovery Charge



Package Dimensions

Package TO-220-2L



SYMBOL	MIN	NOM	MAX
A	4.30	4.50	4.70
A1	1.25	1.30	1.40
A2	2.20	2.40	2.60
b	0.70	0.80	0.90
b1	1.42	1.52	1.62
b2	1.17	1.27	1.37
c	0.45	0.50	0.60
D	15.50	15.70	15.90
D1	9.00	9.20	9.40
D2		(12.70)	
E	9.00	9.20	9.40
E1		(8.00)	
E2		(0.60)	
E3	9.70	9.90	10.10
e		2.54 BSC	
e1		5.08 BSC	
H1	6.30	6.50	6.70
L	12.88	13.08	13.28
L1		(3.00)	
L2	-	-	0.80
ΦP	3.50	3.60	3.70
Q	2.70	2.80	2.90

NOTE
1. THESE DIMENSIONS DO NOT INCLUDE PROTRUSIONS OF THE MOLD.
2. THE "( )" MARK IS THE REFERENCE
3. THE "L2" SYMBOL IS A PROTRUSION OF THE MOLD.

Note

RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented March, 2013. RoHS Declarations for this product can be obtained from the Product Documentation sections of www.gptechgroup.com.

REACh Compliance

REACh substances of high concern (SVHCs) information is available for this product. Since the European Chemi- cal Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future,please contact our office at GPTG Headquarters in Lake Forest, Californiato insure you get the most up-to-date REACh SVHC Declaration. REACh banned substance information (REACh Article 67) is also available upon request.

This product has not been designed or tested for use in, and is not intended for use in, applications implanted into the human body nor in applications in which failure of the product could lead to death, personal injury or property damage, including but not limited to equipment used in the operation of nuclear facilities, life-support machines, cardiac defibrillators or similar emergency medical equipment, aircraft navigation or communication or control systems, or air traffic control.

Global Power Technologies Group Inc., Reserves the right to make changes to the product specifications and data in this docum ent without notice.


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.