



PHANTOM[®] ANTENNA IS IDEAL FOR CELL, GSM, PCE, WIFI, 802.11 AND BLUETOOTH WIRELESS APPLICATIONS

Laird's unique patented Phantom[®] is a tough low-profile antenna for outdoor or indoor applications. Measuring only 2.7" tall, the Phantom 800 MHz to 5.8 GHz antenna models' revolutionary design features field diversity with both vertical and horizontal polarization components. This gives the antenna diversity, frequency agility, low visibility, wide bandwidth and a low angle radiation pattern that is superior to traditional gain antennas in most applications.

The industry standard NMO mounting socket mates with all Laird Technologies' magnetic, trunk lid, and hole mounts. A threaded permanent stud mount model is also available for vandal resistant mounting on brackets, panels, ceilings or any other kind of housing.

The Phantom[®] patented technology is beneficial when high performance is desired and extreme ruggedness and low profile is required.


FEATURES 

- True Field Diversity design ensures uninterrupted transmissions in urban canyons and rural drop off areas
- Phantom[®] outperforms a 3dB whip in many applications
- U.S. Patent Nos. 5,977,931 – 6,292,156 and 7,209,096


MARKETS

- Cell
- GSM and PCS
- WiFi
- 802.11
- Bluetooth wireless applications

ANTENNA PATTERNS



Elevation Pattern (Y, Z, or H-plane)



Azimuth Pattern (X,Y, or E-plane)

Americas: +1.847 839.6925
IAS-AmericasEastSales@lairdtech.com
Europe: +44.1628.858941
IAS-EUSales@lairdtech.com
Asia: IAS-AsiaSales@lairdtech.com

SPECIFICATIONS

| ELECTRICAL | |
|--|------------------------------|
| VSWR | < 2.1 |
| Nominal Gain | 3 dB-M.E.G. |
| Maximum Power | 100 W |
| Nominal Impedance | 50 Ω |
| Polarization | Vertical |
| Pattern | Omnidirectional |
| Half-Power Beamwidth (Elevation° x Azimuth°) | 130° x 360° |
| Coaxial Cable Length & Type | None |
| Terminations | NMO Socket or, type N-female |

MECHANICAL

| | |
|----------------------|--|
| Color | Black or White |
| Height (initially) | 2 ³ / ₄ " |
| Diameter | 1.438" |
| Weight | 0.173 lb |
| Material | ABS |
| Mounting Information | NMO (PN: MB8, MAB8) Sold Separately |
| Noise Suppressor | BlackHawk NS1535 1-35 VOLT, 15 Amp Noise Suppressor (Sold Separately) |

Permanent Mounting Option:

Please order by antenna model and insert letter "P" to indicate permanent mounting option (TRA8063P).

MODEL AND ORDERING INFORMATION

| MODEL | DESCRIPTION |
|-----------|---|
| TRA8063 | 806-870 MHz 3 dB-MEG Phantom [®] 3/4 NMO, White Radome |
| TRA8213 | 821-896 MHz 3 dB-MEG Phantom [®] 3/4 NMO, White Radome |
| TRA8903 | 890-960 MHz 3 dB-MEG Phantom [®] 3/4 NMO, White Radome |
| TRA9023 | 902-928 MHz 3 dB-MEG Phantom [®] 3/4 NMO, White Radome |
| TRA18503 | 1.85 - 1.99 GHz 3dB-MEG Phantom [®] 3/4 NMO, White Radome |
| TRA24003 | 2.4 – 2.5 GHz 3 dB-MEG Phantom [®] 3/4 NMO, White Radome |
| TRA58003 | 4.9 – 6.0 GHz 3 dB-MEG Phantom [®] 3/4 NMO, White Radome |
| TRADCAGP | G - Drop ceiling antenna adaptor for P-mount Phantom w/ 6"x6"x0.016" ground plane |
| Sealtube3 | Heat shrink tubing 3"x1"DIA install (use for jaw protector on installation wrench) |

Add "B" to model number for black radome. Example: TRAB8063

Add "P" to model number for Permanent Mount. Example: TRA8063P

ANT-DS-PHANTOM 800-5800 MHz 1214

All information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2014 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.