



# MMXZ5221B THRU MMXZ5259B

**200 mW**  
**Zener Diodes**  
**2.4 to 39 Volts**

## Features

- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Planar Die construction
- Zener Voltages from 2.4V - 39V and 200mW Power Dissipation
- Ideally Suited for Automated Assembly Processes

## Mechanical Data


- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Approx. Weight: 0.008 gram
- Mounting Position: Any
- Storage & Operating Junction Temperature: -55°C to +150°C

### Maximum Ratings @ 25°C Unless Otherwise Specified

|                                      |                   |     |       |
|--------------------------------------|-------------------|-----|-------|
| Forward Current                      | I <sub>F</sub>    | 100 | mA    |
| Maximum Forward Voltage              | V <sub>F</sub>    | 1.2 | V     |
| Power Dissipation (Notes A)          | P <sub>(AV)</sub> | 200 | mWatt |
| Peak Forward Surge Current (Notes B) | I <sub>FSM</sub>  | 2.0 | Amps  |

#### NOTES:

- A. Mounted on 5.0mm<sup>2</sup> (.013mm thick) land areas.  
 B. Measured on 8.3ms, single half sine-wave or equivalent square wave, duty cycle = 4 pulses per minute maximum.









# MMXZ5221B thru MMXZ5259B

## Electrical Characteristics @ 25°C Unless Otherwise Specified




| MCC PART NUMBER | Marking | NORMAL ZENER VOLTAGE | TEST CURRENT Izt | MAXIMUM ZENER IMPEDANCE 'B' SUFFIX ONLY |                  | MAXIMUM REVERSE LEAKAGE CURRENT |       | MAXIMUM ZENER VOLTAGE TEMP COEFFICIENT 'B' SUFFIX ONLY |
|-----------------|---------|----------------------|------------------|---|------------------|---------------------------------|-------|--|
|                 |         | Vz @ Izt             |                  | Zzt @ Izt                               | Zzk @ Izk=0.25mA | Ir @ Vr                         | %/°C  |  |
|                 |         | VOLTS                | mA               | OHMS                                    | OHMS             | uA                              | VOLTS |  |
| MMXZ5221B       | C1      | 2.4                  | 20               | 30                                      | 1200             | 100                             | 1.0   | -0.085   |
| MMXZ5222B       | C2      | 2.5                  | 20               | 30                                      | 1250             | 100                             | 1.0   | -0.085   |
| MMXZ5223B       | C3      | 2.7                  | 20               | 30                                      | 1300             | 75                              | 1.0   | -0.080   |
| MMXZ5225B       | C5      | 3.0                  | 20               | 29                                      | 1600             | 50                              | 1.0   | -0.075   |
| MMXZ5226B       | G1/D1   | 3.3                  | 20               | 28                                      | 1600             | 25                              | 1.0   | -0.070   |
| MMXZ5227B       | G2/D2   | 3.6                  | 20               | 24                                      | 1700             | 15                              | 1.0   | -0.065   |
| MMXZ5228B       | G3/D3   | 3.9                  | 20               | 23                                      | 1900             | 10                              | 1.0   | -0.060   |
| MMXZ5229B       | G4/D4   | 4.3                  | 20               | 22                                      | 2000             | 5.0                             | 1.0   | ±0.055   |
| MMXZ5230B       | G5/D5   | 4.7                  | 20               | 19                                      | 1900             | 5.0                             | 2.0   | ±0.030   |
| MMXZ5231B       | E1      | 5.1                  | 20               | 17                                      | 1600             | 5.0                             | 2.0   | ±0.030   |
| MMXZ5232B       | E2      | 5.6                  | 20               | 11                                      | 1600             | 5.0                             | 3.0   | +0.038   |
| MMXZ5234B       | E4      | 6.2                  | 20               | 7.0                                     | 1000             | 5.0                             | 4.0   | +0.045   |
| MMXZ5235B       | E5      | 6.8                  | 20               | 5.0                                     | 750              | 3.0                             | 5.0   | +0.050   |
| MMXZ5236B       | F1      | 7.5                  | 20               | 6.0                                     | 500              | 3.0                             | 6.0   | +0.058   |
| MMXZ5237B       | F2      | 8.2                  | 20               | 8.0                                     | 500              | 3.0                             | 6.5   | +0.062   |
| MMXZ5239B       | F4      | 9.1                  | 20               | 10                                      | 600              | 3.0                             | 7.0   | +0.068   |
| MMXZ5240B       | F5      | 10                   | 20               | 17                                      | 600              | 3.0                             | 8.0   | +0.075   |
| MMXZ5241B       | H1      | 11                   | 20               | 22                                      | 600              | 2.0                             | 8.4   | +0.076   |
| MMXZ5242B       | H2      | 12                   | 20               | 30                                      | 600              | 1.0                             | 9.1   | +0.077   |
| MMXZ5243B       | H3      | 13                   | 9.5              | 13                                      | 600              | 0.5                             | 9.9   | +0.079   |
| MMXZ5245B       | H5      | 15                   | 8.5              | 16                                      | 600              | 0.1                             | 11    | +0.082   |
| MMXZ5246B       | J1      | 16                   | 7.8              | 17                                      | 600              | 0.1                             | 12    | +0.083   |
| MMXZ5248B       | J3      | 18                   | 7.0              | 21                                      | 600              | 0.1                             | 14    | +0.085   |
| MMXZ5250B       | J5      | 20                   | 6.2              | 25                                      | 600              | 0.1                             | 15    | +0.086   |
| MMXZ5251B       | K1      | 22                   | 5.6              | 29                                      | 600              | 0.1                             | 17    | +0.087   |
| MMXZ5252B       | K2      | 24                   | 5.2              | 33                                      | 600              | 0.1                             | 18    | +0.088   |
| MMXZ5254B       | K4      | 27                   | 4.6              | 41                                      | 600              | 0.1                             | 21    | +0.090   |
| MMXZ5255B       | K5      | 28                   | 4.5              | 44                                      | 600              | 0.1                             | 21    | +0.091   |
| MMXZ5256B       | M1      | 30                   | 4.2              | 49                                      | 600              | 0.1                             | 23    | +0.091   |
| MMXZ5257B       | M2      | 33                   | 3.8              | 58                                      | 700              | 0.1                             | 25    | +0.092   |
| MMXZ5258B       | M3      | 36                   | 3.4              | 70                                      | 700              | 0.1                             | 27    | +0.093   |
| MMXZ5259B       | M4      | 39                   | 3.2              | 80                                      | 800              | 0.1                             | 30    | +0.094   |

NOTE:

1. Tolerance and Type Number Designation. The type numbers listed have a standard tolerance on the nominal zener voltage of ±5%.
2. Specials Available Include:
  - A. Nominal zener voltages between the voltages shown and tighter voltage tolerances.
  - B. Matched sets.
3. Zener Voltage (Vz) Measurement. Guarantees the zener voltage when measured at 90 seconds while maintaining the lead temperature (Tl) at 30°C, from the diode body.
4. Zener Impedance (Zz) Derivation. The zener impedance is derived from the 60 cycle ac voltage, which results when an AC current having an rms value equal to 10% of the dc zener current (Izt or Izk) is superimposed on Izt or Izk.
5. Surge Current (Ir) Non-Repetitive. The rating listed in the electrical characteristics table is maximum peak, non-repetitive, reverse surge current of 1/2 square wave or equivalent sine wave pulse of 1/120 second duration superimposed on the test current, Izt, per JEDEC registration; however, actual device capability is as described in Figure 5.



# MMXZ5221B thru MMXZ5259B





Micro Commercial Components

Ordering Information :

| Device         | Packing               |
|----------------|-----------------------|
| Part Number-TP | Tape&Reel: 3Kpcs/Reel |

**\*\*\*IMPORTANT NOTICE\*\*\***

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

**\*\*\*LIFE SUPPORT\*\*\***

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

**\*\*\*CUSTOMER AWARENESS\*\*\***

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.