

4		3		2		1																																																																																																																				
THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		LOC		DIST		REVISIONS																																																																																																																		
© COPYRIGHT - By -		ALL RIGHTS RESERVED.		G		14		P		LTR		DESCRIPTION		DATE		DWN		APVD																																																																																																								
										L2		REVISED PER ECO-11-004820		11MAR11		RK		HMR																																																																																																								
AMP WIRE RANGE 12-10 SOLID OR STRANDED UL E13288 LR7189 Certified 12-10 SOLID OR STRANDED 12-10 SOLID OR STRANDED 12-10 SOLID OR STRANDED SERRATIONS WIRE STOP INSULATION BODY AMP AMP AMP A 29.46 MAX [1.160] 1. WIRE INSUL DIA, 3.81-5.84 [.150-.230] <table><tr><td>-</td><td>-</td><td>-</td></tr><tr><td>25</td><td>LOOSE PIECE, BAG</td><td>8-34072-5</td></tr><tr><td>5</td><td>LOOSE PIECE, BLS</td><td>8-34072-4</td></tr><tr><td>100</td><td>LOOSE PIECE, BOX</td><td>8-34072-1</td></tr><tr><td>1500</td><td>ON TAPE, REEL</td><td>2-34072-2</td></tr><tr><td>500</td><td>LOOSE PIECE</td><td>34072</td></tr><tr><td>QTY</td><td>PACKAGE TYPE</td><td>PART NO</td></tr></table><table><tr><td colspan="2">AMP INCORPORATED CUSTOMER SERVICE SYSTEM</td><td colspan="2">MAX RECOMMENDED OPERATING TEMPERATURE: 90° C [194° F]</td><td colspan="2">THIS DRAWING IS A CONTROLLED DOCUMENT.</td><td colspan="2">DWN M ELLIS 19JUL95</td><td colspan="4" rowspan="2"> TE TE Connectivity </td></tr><tr><td colspan="2">FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS</td><td colspan="2">PRODUCT INFORMATION CENTER 1-800-522-6752</td><td colspan="2">DIMENSIONS: mm [INCHES]</td><td colspan="2">TOLERANCES UNLESS OTHERWISE SPECIFIED:</td><td colspan="2">CHK C PRESNELL 19JUL95</td></tr><tr><td colspan="2">FOR APPLICATION TOOLING INFORMATION</td><td colspan="2">TOOLING ASSISTANCE CENTER 1-800-722-1111</td><td colspan="2">VOLTAGE RATING: 600V MAX 1000V (FIXTURES OR SIGNS)</td><td colspan="2"> </td><td colspan="2">APVD S BORTNER 19JUL95</td><td colspan="4" rowspan="2">NAME SPLICE, BUTT, PLASTI-GRIP™ WIRE SIZE,12-10 AWG</td></tr><tr><td colspan="2">FOR ORDER ENTRY</td><td colspan="2">1-800-526-5142</td><td colspan="2">CIRCULAR MIL AREA: 2.62mm²-6.64mm² [5180-13100]</td><td colspan="2">MATERIAL BODY, CU ASTM B 152 SLV, PVC, COLOR, YELLO</td><td colspan="2">PRODUCT SPEC UL486A</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">FINISH TIN PLATE PER MIL-T-10727</td><td colspan="2">APPLICATION SPEC -</td><td colspan="2">SIZE A3</td><td colspan="2">CAGE CODE 00779</td><td colspan="2">DRAWING NO C-34072</td><td colspan="2">RESTRICTED TO -</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">WEIGHT -</td><td colspan="2">CUSTOMER DRAWING</td><td colspan="2">SCALE 4:1</td><td colspan="2">SHEET 1 OF 1</td><td colspan="2">REV L2</td></tr></table>																				-	-	-	25	LOOSE PIECE, BAG	8-34072-5	5	LOOSE PIECE, BLS	8-34072-4	100	LOOSE PIECE, BOX	8-34072-1	1500	ON TAPE, REEL	2-34072-2	500	LOOSE PIECE	34072	QTY	PACKAGE TYPE	PART NO	AMP INCORPORATED CUSTOMER SERVICE SYSTEM		MAX RECOMMENDED OPERATING TEMPERATURE: 90° C [194° F]		THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN M ELLIS 19JUL95		TE TE Connectivity				FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS		PRODUCT INFORMATION CENTER 1-800-522-6752		DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		CHK C PRESNELL 19JUL95		FOR APPLICATION TOOLING INFORMATION		TOOLING ASSISTANCE CENTER 1-800-722-1111		VOLTAGE RATING: 600V MAX 1000V (FIXTURES OR SIGNS)				APVD S BORTNER 19JUL95		NAME SPLICE, BUTT, PLASTI-GRIP™ WIRE SIZE,12-10 AWG				FOR ORDER ENTRY		1-800-526-5142		CIRCULAR MIL AREA: 2.62mm²-6.64mm² [5180-13100]		MATERIAL BODY, CU ASTM B 152 SLV, PVC, COLOR, YELLO		PRODUCT SPEC UL486A								FINISH TIN PLATE PER MIL-T-10727		APPLICATION SPEC -		SIZE A3		CAGE CODE 00779		DRAWING NO C-34072		RESTRICTED TO -										WEIGHT -		CUSTOMER DRAWING		SCALE 4:1		SHEET 1 OF 1		REV L2	
-	-	-																																																																																																																								
25	LOOSE PIECE, BAG	8-34072-5																																																																																																																								
5	LOOSE PIECE, BLS	8-34072-4																																																																																																																								
100	LOOSE PIECE, BOX	8-34072-1																																																																																																																								
1500	ON TAPE, REEL	2-34072-2																																																																																																																								
500	LOOSE PIECE	34072																																																																																																																								
QTY	PACKAGE TYPE	PART NO																																																																																																																								
AMP INCORPORATED CUSTOMER SERVICE SYSTEM		MAX RECOMMENDED OPERATING TEMPERATURE: 90° C [194° F]		THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN M ELLIS 19JUL95		TE TE Connectivity																																																																																																																		
FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS		PRODUCT INFORMATION CENTER 1-800-522-6752		DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:						CHK C PRESNELL 19JUL95																																																																																																														
FOR APPLICATION TOOLING INFORMATION		TOOLING ASSISTANCE CENTER 1-800-722-1111		VOLTAGE RATING: 600V MAX 1000V (FIXTURES OR SIGNS)				APVD S BORTNER 19JUL95		NAME SPLICE, BUTT, PLASTI-GRIP™ WIRE SIZE,12-10 AWG																																																																																																																
FOR ORDER ENTRY		1-800-526-5142		CIRCULAR MIL AREA: 2.62mm²-6.64mm² [5180-13100]		MATERIAL BODY, CU ASTM B 152 SLV, PVC, COLOR, YELLO		PRODUCT SPEC UL486A																																																																																																																		
						FINISH TIN PLATE PER MIL-T-10727		APPLICATION SPEC -		SIZE A3		CAGE CODE 00779		DRAWING NO C-34072		RESTRICTED TO -																																																																																																										
								WEIGHT -		CUSTOMER DRAWING		SCALE 4:1		SHEET 1 OF 1		REV L2																																																																																																										



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.