

### 220 Watts

- Energy Efficiency Level VI
- <0.21 W Standby Power
- 0 °C to 60 °C Operation
- High Power Density
- Low Earth Leakage Current
- ITE Safety Approvals
- 3 Year Warranty



#### Dimensions:

**AHE220:**

7.76 x 3.46 x 1.73" (197.0 x 88.0 x 44 mm)

### Models & Ratings


| Output Power | Output Voltage | Output Current | Total Regulation | Efficiency <sup>(1)</sup> | Model Number              |
|--------------|----------------|----------------|------------------|---------------------------|---------------------------|
| 180 W        | 12.0 V         | 15.0 A         | ±5%              | 90%                       | AHE220PS12 <sup>(2)</sup> |
| 220 W        | 19.0 V         | 11.57 A        |                  | 92%                       | AHE220PS19                |
|              | 24.0 V         | 9.16 A         |                  | 94%                       | AHE220PS24                |

### Notes

1. Typical efficiency measured at 100% load and 230 VAC input.

2. For IEC320-C6, add suffix 'C6' to the end of the part number e.g. AHE220PS12C6.

### Mechanical Details



#### Mains Leads Order Part:

UK - C14 inlet: UK-MAINS-IEC, C6 inlet: UK-MAINS-5  
 European - C14 inlet: EU-MAINS-IEC, C6 inlet: EU-MAINS-5  
 US - C14 inlet: US-MAINS-IEC, C6 inlet: US-MAINS-5

#### Pin Connector

##### AHE220PS12

| Pin   | Function           |
|-------|--------------------|
| 1     | Output +           |
| 2     | Output +           |
| 3     | Return/Input Earth |
| 4     | Return/Input Earth |
| Shell | Return/Input Earth |

##### AHE220PS19/24

| Pin | Function           |
|-----|--------------------|
| 1   | Return/Input Earth |
| 2   | Return/Input Earth |
| 3   | Return/Input Earth |
| 4   | Output +           |
| 5   | Output +           |
| 6   | Output +           |

### Notes

1. Dimensions shown in inches (mm). Tolerance is 0.02 (0.5) maximum, except output cable length.
2. Weight: 2.31 lb (1050 g).
3. Optional output connectors available. Consult sales.

4. Output connector for AHE220PS12 is non locking 4 pin DC power plug and mates with Kycon KPJX-4S or equivalent. Output connector for AHE220PS19/24 is molex Mini-Fit part number 39-01-2060 with 5556 terminals and mates with molex plug 39-01-2066 and 5558 terminals or equivalent.
5. Mains lead length is 76" (1930 mm) approx

### Input

| Characteristic        | Minimum                              | Typical   | Maximum | Units | Notes & Conditions                            |
|-----------------------|--------------------------------------|-----------|---------|-------|---|
| Input Voltage         | 90                                   |           | 264     | VAC   |   |
| Input Frequency       | 47                                   |           | 63      | Hz    |   |
| Input Current         |                                      | 2.34/0.98 |         | A     | Measured at 100/240 VAC                       |
| Inrush Current        |                                      |           | 80/160  | A     | 115/230 VAC, cold start at 25 °C              |
| Power Factor          | 0.9                                  |           |         |       | At 230 VAC and full load, EN61000-3-2 Class A |
| Earth Leakage Current |                                      | 220       | 250     | µA    | 264 VAC, 60 Hz                                |
| No Load Input Power   |                                      |           | 0.21    | W     |   |
| Input Protection      | T3.15A/250 VAC internal fuse in line |           |         |       |   |


### Output

| Characteristic           | Min.                                      | Typ. | Max. | Units   | Notes & Conditions   |
|--------------------------|---|------|------|---------|--|
| Output Voltage           | 12  |      | 24   | VDC     | See Models and Ratings table   |
| Initial Set Accuracy     |   |      | ±2   | %       | At 50% load  |
| Minimum Load             |   |      |      |         | No minimum load required   |
| Start Up Delay           |   |      | 3    | s       |  |
| Start Up Rise Time       |   |      | 40   | ms      |  |
| Hold Up Time             | 10  |      |      | ms      | Full load and 115 VAC  |
| Line Regulation          |   |      | ±0.5 | %       |  |
| Total Regulation         |   |      | ±5   | %       |  |
| Transient Response       |   |      | 4    | %       | Maximum deviation, recovering to less than 1% within 500 µs for 25% step load                    |
| Ripple and Noise         |   |      | 7    | %/pk-pk | Measured with 20 MHz Bandwidth and 10 µF electrolytic in parallel with 0.1 µF ceramic capacitor. |
| Overshoot                |   |      | 5    | %       | At turn on / turn off  |
| Overload Protection      | 115                                       |      | 175  | %       |  |
| Overvoltage Protection   | 112                                       |      | 160  | %       | Recycle mains to reset   |
| Short Circuit Protection | Trip and restart (hiccup), auto resetting |      |      |         |  |
| Thermal Protection       | Measured internally, recycle AC to reset  |      |      |         |  |
| Temperature Coefficient  |   | 0.04 |      | %/°C    |  |

### Environmental

| Characteristic        | Minimum   | Typical | Maximum | Units | Notes & Conditions                                  |
|-----------------------|---|---------|---------|-------|---|
| Operating Temperature | 0   |         | +60     | °C    | Derate from 100% load at 40 °C to 50% load at 60 °C |
| Cooling               | Natural convection  |         |         |       |   |
| Operating Humidity    | 5   |         | 90      | %RH   | Non-condensing                                      |
| Storage Temperature   | -10   |         | +80     | °C    |   |
| Operating Altitude    |   |         | 5000    | m     |   |
| Shock                 | IEC68-2-27, 30 g, 11 ms half sine, 3 times in each of 6 axes        |         |         |       |   |
| Vibration             | IEC68-2-6, 10-500 Hz, 2 g 10 mins/sweep, 60 mins for each of 3 axes |         |         |       |   |

### Derating Curve




### General


| Characteristic  | Minimum | Typical     | Maximum | Units             | Notes & Conditions                        |
|---|---------|-------------|---------|-------------------|---|
| Efficiency  |         | 91          |         | %                 | See Models and Ratings table and curves.  |
| Isolation: Input to Output<br>Input to Ground<br>Output to Ground | 3000    |             |         | VAC               |   |
|   | 1500    |             |         | VAC               |   |
|   |         |             |         | VAC               | Output return is connected to input earth |
| Switching Frequency   | 75      |             | 150     | kHz               |   |
| Power Density   |         | 4.55        |         | W/in <sup>3</sup> |   |
| Mean Time Between Failure   |         | >500        |         | kHrs              | SR332 at 25 °C GB                         |
| Weight  |         | 2.31 (1050) |         | lb (g)            |   |

### Efficiency Curves

#### AHE220PS12



#### AHE220PS24



### EMC: Emissions

| Phenomenon       | Standard    | Test Level | Notes & Conditions   |
|------------------|-------------|------------|----------------------|
| Emissions        | EN55032     | Level B    | Conducted & Radiated |
| Harmonic Current | EN61000-3-2 | Class A    |                      |
| Voltage Flicker  | EN61000-3-3 |            |                      |


### EMC: Immunity

| Phenomenon             | Standard     | Test Level               | Criteria | Notes & Conditions               |
|------------------------|--------------|--------------------------|----------|----------------------------------|
| ESD                    | EN61000-4-2  | ±15 kV Air, ±8kV contact | A        |                                  |
| Radiated               | EN61000-4-3  | 3 V/m                    | A        |                                  |
| EFT/Burst              | EN61000-4-4  | 2                        | A        |                                  |
| Surge                  | EN61000-4-5  | Installation Class 3     | A        |                                  |
| Conducted              | EN61000-4-6  | 3 V                      | A        |                                  |
| Magnetic Fields        | EN61000-4-8  | 3 A/m                    | A        |                                  |
| Dips and Interruptions | EN61000-4-11 | Dip: 30% 500 ms          | A        | High Line with 65% load/Low Line |
|                        |              | Dip: 60% 200 ms          | A/B      |                                  |
|                        |              | Int: 100% 5000 ms        | B        |                                  |
|                        |              | Int: 100% 10 ms          | A        |                                  |

### Safety Approvals

| Safety Agency | Safety Standard                        | Notes & Conditions |
|---------------|--|--------------------|
| UL            | cUL60950-1                             |                    |
| TUV           | EN60950-1                              |                    |
| CB            | IEC60950-1                             |                    |
| CCC           | China Compulsory Certification, GB4943 |                    |
| AU/NZ         | AU/NZ 60950.1                          |                    |

### Mechanical Details



#### Cable Length

PS12 - 37.4" ± 1.97" (950 ± 50mm)  
 PS19/24 - 59.1" ± 1.97" (1500 ± 50mm)

#### Mains Leads Order Part:

UK - C14 inlet: UK-MAINS-IEC, C6 inlet: UK-MAINS-5  
 European - C14 inlet: EU-MAINS-IEC, C6 inlet: EU-MAINS-5  
 US - C14 inlet: US-MAINS-IEC, C6 inlet: US-MAINS-5

#### Pin Connector

##### AHE220PS12

| Pin   | Function           |
|-------|--------------------|
| 1     | Output +           |
| 2     | Output +           |
| 3     | Return/Input Earth |
| 4     | Return/Input Earth |
| Shell | Return/Input Earth |

##### AHE220PS19/24

| Pin | Function           |
|-----|--------------------|
| 1   | Return/Input Earth |
| 2   | Return/Input Earth |
| 3   | Return/Input Earth |
| 4   | Output +           |
| 5   | Output +           |
| 6   | Output +           |

### Notes

- Dimensions shown in inches (mm). Tolerance is 0.02 (0.5) maximum, except output cable length.
- Weight: 2.31 lb (1050 g).
- Optional output connectors available. Consult sales.
- Output connector for AHE220PS12 is non locking 4 pin DC power plug and mates with Kycon KPJX-4S or equivalent. Output connector for AHE220PS19/24/48 is molex Mini-Fit part number 39-01-2060 with 5556 terminals and mates with molex plug 39-01-2066 and 5558 terminals or equivalent.
- Mains lead length is 76" (1930 mm) approx



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.