

1	2	3	4	5	6	7	8																																																																																												
SEK 18 male low profile solder and press-in RoHS compliant				Recommended configuration of plated through holes for press-in termination In addition to the hot-air-level (HAL), other PCB surfaces are getting more important. Due to their different properties – such as mechanical strength and coefficient of friction – we recommend the following configuration of PCB through holes. drilled hole $\varnothing$ finished hole $\varnothing$ plating (e.g. Sn) Cu min. 25 μm <table><tr><td rowspan="3">Tin plated PCB (HAL) acc. to EN 60352-5</td><td>Drilled hole $\varnothing$</td><td>1,15-0,03 mm</td></tr><tr><td>Cu</td><td>min. 25 μm</td></tr><tr><td>Sn</td><td>max. 15 μm</td></tr><tr><td rowspan="3">Chemical tin plated PCB</td><td>plated hole $\varnothing$</td><td>0,94 - 1,09 mm</td></tr><tr><td>Drilled hole $\varnothing$</td><td>1,15-0,03 mm</td></tr><tr><td>Cu</td><td>min. 25 μm</td></tr><tr><td rowspan="3"></td><td>Sn</td><td>min. 0,8μm</td></tr><tr><td>plated hole $\varnothing$</td><td>1,00 - 1,10 mm</td></tr><tr><td rowspan="4">Gold /Nickel plated PCB</td><td>Drilled hole $\varnothing$</td><td>1,15-0,03 mm</td></tr><tr><td>Cu</td><td>min. 25 μm</td></tr><tr><td>Ni</td><td>3 - 7 μm</td></tr><tr><td>Au</td><td>0,05 - 0,12 μm</td></tr><tr><td rowspan="3"></td><td>plated hole $\varnothing$</td><td>1,00 - 1,10 mm</td></tr><tr><td rowspan="3">Silver plated PCB</td><td>Drilled hole $\varnothing$</td><td>1,15-0,03 mm</td></tr><tr><td>Cu</td><td>min. 25 μm</td></tr><tr><td>Ag</td><td>0,1 - 0,3 μm</td></tr><tr><td rowspan="3"></td><td>plated hole $\varnothing$</td><td>1,00 - 1,10 mm</td></tr><tr><td rowspan="3">Copper plated PCB (OSP)</td><td>Drilled hole $\varnothing$</td><td>1,15-0,03 mm</td></tr><tr><td>Cu</td><td>min. 25 μm</td></tr><tr><td>plated hole $\varnothing$</td><td>1,00 - 1,10 mm</td></tr></table>				Tin plated PCB (HAL) acc. to EN 60352-5	Drilled hole $\varnothing$	1,15-0,03 mm	Cu	min. 25 μ m	Sn	max. 15 μ m	Chemical tin plated PCB	plated hole $\varnothing$	0,94 - 1,09 mm	Drilled hole $\varnothing$	1,15-0,03 mm	Cu	min. 25 μ m		Sn	min. 0,8 μ m	plated hole $\varnothing$	1,00 - 1,10 mm	Gold /Nickel plated PCB	Drilled hole $\varnothing$	1,15-0,03 mm	Cu	min. 25 μ m	Ni	3 - 7 μ m	Au	0,05 - 0,12 μ m		plated hole $\varnothing$	1,00 - 1,10 mm	Silver plated PCB	Drilled hole $\varnothing$	1,15-0,03 mm	Cu	min. 25 μ m	Ag	0,1 - 0,3 μ m		plated hole $\varnothing$	1,00 - 1,10 mm	Copper plated PCB (OSP)	Drilled hole $\varnothing$	1,15-0,03 mm	Cu	min. 25 μ m	plated hole $\varnothing$	1,00 - 1,10 mm																																												
Tin plated PCB (HAL) acc. to EN 60352-5	Drilled hole $\varnothing$	1,15-0,03 mm																																																																																																	
	Cu	min. 25 μ m																																																																																																	
	Sn	max. 15 μ m																																																																																																	
Chemical tin plated PCB	plated hole $\varnothing$	0,94 - 1,09 mm																																																																																																	
	Drilled hole $\varnothing$	1,15-0,03 mm																																																																																																	
	Cu	min. 25 μ m																																																																																																	
	Sn	min. 0,8 μ m																																																																																																	
	plated hole $\varnothing$	1,00 - 1,10 mm																																																																																																	
	Gold /Nickel plated PCB	Drilled hole $\varnothing$	1,15-0,03 mm																																																																																																
Cu		min. 25 μ m																																																																																																	
Ni		3 - 7 μ m																																																																																																	
Au		0,05 - 0,12 μ m																																																																																																	
	plated hole $\varnothing$	1,00 - 1,10 mm																																																																																																	
	Silver plated PCB	Drilled hole $\varnothing$	1,15-0,03 mm																																																																																																
		Cu	min. 25 μ m																																																																																																
Ag		0,1 - 0,3 μ m																																																																																																	
	plated hole $\varnothing$	1,00 - 1,10 mm																																																																																																	
	Copper plated PCB (OSP)	Drilled hole $\varnothing$	1,15-0,03 mm																																																																																																
		Cu	min. 25 μ m																																																																																																
plated hole $\varnothing$		1,00 - 1,10 mm																																																																																																	
General information <table><tr><td>Design</td><td colspan="3">IEC 60603-13</td></tr><tr><td>No. of contacts</td><td colspan="3">6,10,14,16,20,26,30,34,40,50,60,64</td></tr><tr><td>Contact spacing</td><td colspan="3">2,54 mm x 2,54 mm</td></tr><tr><td>Test voltage Ur.m.s</td><td colspan="3">1 kV</td></tr><tr><td>Working voltage</td><td colspan="3">500 V for pollution degree 1</td></tr><tr><td>Working current acc. to IEC 60512-2</td><td colspan="3">See derating diagram</td></tr><tr><td>Contact resistance</td><td colspan="3">max. 20mOhm</td></tr><tr><td>Insulation resistance</td><td colspan="3">min. 10⁹Ohm</td></tr><tr><td>Temperature range</td><td colspan="3">-55°C ... +125°C (solder) -55°C ... +105°C (press-in)</td></tr><tr><td>Termination technology</td><td colspan="3">solder, press-in</td></tr><tr><td>Clearance & creepage distance</td><td colspan="3">min. 0,5 mm clearance min. 0,56 creepage</td></tr><tr><td rowspan="6">Insertion and withdrawal forces</td><td colspan="2">6-pole max. 12N for PL1-2 / 18N for PL3</td><td>; 30-pole max. 60N for PL1-2 / 90N for PL3</td></tr><tr><td colspan="2">10-pole max. 20N for PL1-2 / 30N for PL3</td><td>; 34-poles max. 68N for PL1-2 / 102N for PL3</td></tr><tr><td colspan="2">14-pole max. 28N for PL1-2 / 42 for PL3</td><td>; 40-poles max. 80N for PL1-2 / 120N for PL3</td></tr><tr><td colspan="2">16-pole max. 32N for PL1-2 / 48N for PL3</td><td>; 50-poles max. 100N for PL1-2 / 150N for PL3</td></tr><tr><td colspan="2">20-pole max. 40N for PL1-2 / 60N for PL3</td><td>; 60-poles max. 120N for PL1-2 / 180N for PL3</td></tr><tr><td colspan="2">26-pole max. 52N for PL1-2 / 78N for PL3</td><td>; 64-poles max. 128N for PL1-2 / 192N for PL3</td></tr><tr><td rowspan="4">Mating cycles</td><td colspan="2">S4 surface treatment</td><td>Au over PdNi (min. 0,76 μm)</td></tr><tr><td>PL 1 acc. to IEC 60603-13</td><td>500 mating cycles</td><td>10 days gas test</td></tr><tr><td>PL 2 acc. to IEC 60603-13</td><td>250 mating cycles</td><td>4 days gas test</td></tr><tr><td>PL 3 acc. to IEC 60603-13</td><td>50 mating cycles</td><td>No gas test</td></tr><tr><td>UL file</td><td colspan="3">E 102079</td></tr><tr><td>RoHS – compliant</td><td colspan="3">Yes</td></tr><tr><td>Leadfree</td><td colspan="3">Yes</td></tr><tr><td>Hot plugging</td><td colspan="3">No</td></tr></table>				Design	IEC 60603-13			No. of contacts	6,10,14,16,20,26,30,34,40,50,60,64			Contact spacing	2,54 mm x 2,54 mm			Test voltage Ur.m.s	1 kV			Working voltage	500 V for pollution degree 1			Working current acc. to IEC 60512-2	See derating diagram			Contact resistance	max. 20mOhm			Insulation resistance	min. 10 ⁹ Ohm			Temperature range	-55°C ... +125°C (solder) -55°C ... +105°C (press-in)			Termination technology	solder, press-in			Clearance & creepage distance	min. 0,5 mm clearance min. 0,56 creepage			Insertion and withdrawal forces	6-pole max. 12N for PL1-2 / 18N for PL3		; 30-pole max. 60N for PL1-2 / 90N for PL3	10-pole max. 20N for PL1-2 / 30N for PL3		; 34-poles max. 68N for PL1-2 / 102N for PL3	14-pole max. 28N for PL1-2 / 42 for PL3		; 40-poles max. 80N for PL1-2 / 120N for PL3	16-pole max. 32N for PL1-2 / 48N for PL3		; 50-poles max. 100N for PL1-2 / 150N for PL3	20-pole max. 40N for PL1-2 / 60N for PL3		; 60-poles max. 120N for PL1-2 / 180N for PL3	26-pole max. 52N for PL1-2 / 78N for PL3		; 64-poles max. 128N for PL1-2 / 192N for PL3	Mating cycles	S4 surface treatment		Au over PdNi (min. 0,76 μ m)	PL 1 acc. to IEC 60603-13	500 mating cycles	10 days gas test	PL 2 acc. to IEC 60603-13	250 mating cycles	4 days gas test	PL 3 acc. to IEC 60603-13	50 mating cycles	No gas test	UL file	E 102079			RoHS – compliant	Yes			Leadfree	Yes			Hot plugging	No						
Design	IEC 60603-13																																																																																																		
No. of contacts	6,10,14,16,20,26,30,34,40,50,60,64																																																																																																		
Contact spacing	2,54 mm x 2,54 mm																																																																																																		
Test voltage Ur.m.s	1 kV																																																																																																		
Working voltage	500 V for pollution degree 1																																																																																																		
Working current acc. to IEC 60512-2	See derating diagram																																																																																																		
Contact resistance	max. 20mOhm																																																																																																		
Insulation resistance	min. 10 ⁹ Ohm																																																																																																		
Temperature range	-55°C ... +125°C (solder) -55°C ... +105°C (press-in)																																																																																																		
Termination technology	solder, press-in																																																																																																		
Clearance & creepage distance	min. 0,5 mm clearance min. 0,56 creepage																																																																																																		
Insertion and withdrawal forces	6-pole max. 12N for PL1-2 / 18N for PL3		; 30-pole max. 60N for PL1-2 / 90N for PL3																																																																																																
	10-pole max. 20N for PL1-2 / 30N for PL3		; 34-poles max. 68N for PL1-2 / 102N for PL3																																																																																																
	14-pole max. 28N for PL1-2 / 42 for PL3		; 40-poles max. 80N for PL1-2 / 120N for PL3																																																																																																
	16-pole max. 32N for PL1-2 / 48N for PL3		; 50-poles max. 100N for PL1-2 / 150N for PL3																																																																																																
	20-pole max. 40N for PL1-2 / 60N for PL3		; 60-poles max. 120N for PL1-2 / 180N for PL3																																																																																																
	26-pole max. 52N for PL1-2 / 78N for PL3		; 64-poles max. 128N for PL1-2 / 192N for PL3																																																																																																
Mating cycles	S4 surface treatment		Au over PdNi (min. 0,76 μ m)																																																																																																
	PL 1 acc. to IEC 60603-13	500 mating cycles	10 days gas test																																																																																																
	PL 2 acc. to IEC 60603-13	250 mating cycles	4 days gas test																																																																																																
	PL 3 acc. to IEC 60603-13	50 mating cycles	No gas test																																																																																																
UL file	E 102079																																																																																																		
RoHS – compliant	Yes																																																																																																		
Leadfree	Yes																																																																																																		
Hot plugging	No																																																																																																		
Insulator material <table><tr><td>Material</td><td colspan="3">PBT (thermoplastics, glass fiber reinforcement 30%)</td></tr><tr><td>Color</td><td colspan="3">black (RAL 7001) or grey (RAL 7032) for solder grey (RAL 7053) for press-in</td></tr><tr><td>UL classification</td><td colspan="3">UL94-V0</td></tr><tr><td>Material group acc. IEC 60664-1</td><td colspan="3">IIa (175 < CTI < 400)</td></tr><tr><td>NF F 16-101 classification</td><td colspan="3">I3,F3</td></tr></table>				Material	PBT (thermoplastics, glass fiber reinforcement 30%)			Color	black (RAL 7001) or grey (RAL 7032) for solder grey (RAL 7053) for press-in			UL classification	UL94-V0			Material group acc. IEC 60664-1	IIa (175 < CTI < 400)			NF F 16-101 classification	I3,F3																																																																														
Material	PBT (thermoplastics, glass fiber reinforcement 30%)																																																																																																		
Color	black (RAL 7001) or grey (RAL 7032) for solder grey (RAL 7053) for press-in																																																																																																		
UL classification	UL94-V0																																																																																																		
Material group acc. IEC 60664-1	IIa (175 < CTI < 400)																																																																																																		
NF F 16-101 classification	I3,F3																																																																																																		
Contact material <table><tr><td>Contact material</td><td colspan="3">Copper alloy</td></tr><tr><td>Plating termination zone</td><td colspan="3">Sn over Ni for solder, Ni for press-in</td></tr><tr><td>Plating contact sliding side</td><td colspan="3">Au or Au over PdNi (according to performance level)</td></tr></table>				Contact material	Copper alloy			Plating termination zone	Sn over Ni for solder, Ni for press-in			Plating contact sliding side	Au or Au over PdNi (according to performance level)																																																																																						
Contact material	Copper alloy																																																																																																		
Plating termination zone	Sn over Ni for solder, Ni for press-in																																																																																																		
Plating contact sliding side	Au or Au over PdNi (according to performance level)																																																																																																		
Derating diagram acc to IEC 60512-2 (Current carrying capacity) The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity-curve is valid for continuous, not interrupted current-loaded contacts of connectors when simultaneous power on all contacts is given without exceeding the maximum temperature. Control and test procedures according to DIN IEC 60512. 1) Temperature rise 2) Derating 3) Derating curve at I max x 0.8(IEC 60512-2)																																																																																																			
All Dimensions in mm Original Size DIN A3 All rights reserved Department EC PD – DE HARTING Electronics GmbH D-32339 Espelkamp Scale 1:1 Free size tol. Created by STORCK Inspected by LEHNERT Standardisation HOFFMANN Date 2016-09-05 State Final Release Title SEK 18 male low profile solder and press-in Doc-Key / ECM-Nr. 100554984/UGD/001/F 500000107692 Type DS Number 09181100001 Rev. F Page 1/1																																																																																																			
1	2	3	4	5	6	7	8																																																																																												

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

[09185106321](#) [09185607321](#) [09185645919](#) [09185065322](#) [09185067323](#) [09185067324](#) [09185105322](#)
[09185105324](#) [09185106322](#) [09185106323](#) [09185106329](#) [09185106803](#) [09185107324](#) [09185145323](#) [09185146322](#)
[09185146324](#) [09185146803](#) [09185147324](#) [09185147329](#) [09185165322](#) [09185165323](#) [09185165329](#)
[09185166322](#) [09185166803](#) [09185166813](#) [09185167322](#) [09185167323](#) [09185167324](#) [09185205323](#) [09185206322](#)
[09185206323](#) [09185206329](#) [09185207322](#) [09185207323](#) [09185207324](#) [09185207329](#) [09185265323](#)
[09185265324](#) [09185265329](#) [09185266322](#) [09185266323](#) [09185266329](#) [09185267324](#) [09185345322](#) [09185345324](#)
[09185346322](#) [09185346323](#) [09185347324](#) [09185347329](#) [09185405329](#) [09185406322](#) [09185407322](#)
[09185407329](#) [09185505322](#) [09185506323](#) [09185506324](#) [09185507322](#) [09185507329](#) [09185507803](#) [09185509002](#)
[09185605323](#) [09185605324](#) [09185605329](#) [09185606322](#) [09185606324](#) [09185606329](#) [09185645323](#)
[09185646329](#) [09185647322](#) [09185647323](#) [09185647324](#) [09185066324](#) [09185106324](#) [09185266324](#) [09185067321](#)
[09185105321](#) [09185107321](#) [09185206321](#) [09185266321](#) [09185406321](#) [09185407321](#) [09185505321](#)
[09185506321](#) [09185507324](#) [09185407323](#) [09185146329](#) [09185065324](#) [09185107323](#) [09185166329](#) [09185146323](#)
[09185646323](#) [09185066323](#) [09185607324](#) [09185346329](#) [09185069002](#) [09185349002](#) [09185065329](#)
[09185105323](#) [09185147323](#) [09185166323](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.