


## 1.0A SURFACE MOUNT GLASS PASSIVATED BRIDGE RECTIFIER

### Features

- Glass Passivated Die Construction
- Low Forward Voltage Drop, High Current Capability
- Surge Overload Rating to 50A Peak
- Designed for Surface Mount Application
- UL Listed Under Recognized Component Index, File Number E94661
- **Lead Free Finish, RoHS Compliant (Date Code 0532+)** (Note 3)

### Mechanical Data

- Case: DF-S
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Finish - Tin. Solderable per MIL-STD-202, Method 208 (e3)
- Polarity: As marked on Case
- Marking: Type Number, See Page 3
- Weight: 0.38 grams (approximate)




| DF-S                 |       |       |
|----------------------|-------|-------|
| Dim                  | Min   | Max   |
| A                    | 7.40  | 7.90  |
| B                    | 6.20  | 6.50  |
| C                    | 0.22  | 0.30  |
| D                    | 0.076 | 0.33  |
| E                    | —     | 10.40 |
| G                    | 1.02  | 1.53  |
| H                    | 8.13  | 8.51  |
| J                    | 2.40  | 2.60  |
| K                    | 5.00  | 5.20  |
| L                    | 1.00  | 1.20  |
| All Dimensions in mm |       |       |

### Maximum Ratings and Electrical Characteristics @ T<sub>A</sub> = 25°C unless otherwise specified


Single phase, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.

| Characteristic   | Symbol   | DF 005S     | DF 01S | DF 02S | DF 04S | DF 06S | DF 08S | DF 10S | Unit             |
|--|--|-------------|--------|--------|--------|--------|--------|--------|------------------|
| Peak Repetitive Reverse Voltage<br>Working Peak Reverse Voltage<br>DC Blocking Voltage                           | V <sub>RMM</sub><br>V <sub>RWM</sub><br>V <sub>R</sub> | 50          | 100    | 200    | 400    | 600    | 800    | 1000   | V                |
| RMS Reverse Voltage  | V <sub>RMS</sub>                                       | 35          | 70     | 140    | 280    | 420    | 560    | 700    | V                |
| Average Forward Rectified Current @ T <sub>A</sub> = 40°C  | I <sub>O</sub>   | 1.0         |        |        |        |        |        |        | A                |
| Non-Repetitive Peak Forward Surge Current, 8.3 ms single half-sine-wave superimposed on rated load               | I <sub>FSM</sub>                                       | 50          |        |        |        |        |        |        | A                |
| Forward Voltage (per element) @ I <sub>F</sub> = 1.0A  | V <sub>FM</sub>  | 1.1         |        |        |        |        |        |        | V                |
| Peak Reverse Current at Rated DC Blocking Voltage (per element) @ T <sub>A</sub> = 25°C @ T <sub>A</sub> = 125°C | I <sub>RM</sub>  | 10<br>500   |        |        |        |        |        |        | μA               |
| I <sup>2</sup> t Rating for Fusing (t < 8.3ms)   | I <sup>2</sup> t                                       | 10.4        |        |        |        |        |        |        | A <sup>2</sup> s |
| Typical Total Capacitance (per element) (Note 1)   | C <sub>T</sub>   | 25          |        |        |        |        |        |        | pF               |
| Typical Thermal Resistance, Junction to Ambient (Note 2)   | R <sub>θJA</sub>                                       | 40          |        |        |        |        |        |        | °C/W             |
| Operating and Storage Temperature Range  | T <sub>j</sub> , T <sub>STG</sub>                      | -65 to +150 |        |        |        |        |        |        | °C               |


- Notes: 1. Measured at 1.0 MHz and Applied Reverse Voltage of 4.0V DC.  
2. Thermal resistance, junction to ambient, measured on PC board with 5.0mm<sup>2</sup> (0.03mm thick) land areas.  
3. RoHS revision 13.2.2003. Glass and High Temperature Solder Exemptions Applied, see EU Directive Annex Notes 5 and 7.




$T_A$ : AMBIENT TEMPERATURE ( $^{\circ}C$ )  
Fig. 1 Output Current Derating Curve




$V_F$ : INSTANTANEOUS FORWARD VOLTAGE (V)  
Fig. 2 Typ Forward Characteristics (per element)



NUMBER OF CYCLES AT 60 Hz  
Fig. 3 Max Non-Repetitive Peak Forward Surge Current



$V_R$ : REVERSE VOLTAGE (V)  
Fig. 4 Typical Total Capacitance (per element)



PERCENT OF RATED PEAK REVERSE VOLTAGE (%)  
Fig. 5 Typ Reverse Characteristics (per element)


**Ordering Information** (Note 4)

| Device*        | Packaging    | Shipping                                 |
|----------------|--------------|--|
| DFxS<br>DFxS-T | DF-S<br>DF-S | 50 Per Tube<br>1500/Tape & Reel, 13-inch |

\* x = Device type, e.g. DF005S or DF10S, etc.

Notes: 4. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

**Marking Information**



D|| = Manufacturers' code marking  
 DFxxxS = Product type marking code, ex: DF10S  
 YWW = Date code marking  
 Y = Last digit of year ex: 2 for 2002  
 WW = Week code 01 to 52

**IMPORTANT NOTICE**

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

**LIFE SUPPORT**

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.