


PSM-LWL-KDHEAVY-980/1000

**Polymer fiber cable, duplex 980/1000 µm,
medium-weight version for fixed indoor installation**



Data sheet
100330_en_02

© PHOENIX CONTACT 2012-09-27

1 Description

The **PSM-LWL-KDHEAVY-980/100** fiber optic cable is a medium-weight round cable for fixed indoor installation.

1.1 Properties

- Universal installation cable for fixed indoor installation
- Polyurethane (PUR) outer sheath
- 2.2 mm single wires made from extremely hard-wearing polyamide (PA)
- Halogen-free, ozone and UV resistant

1.2 Structure




Figure 1 Cross section drawing

- 1 PUR outer sheath
- 2 PA sheath
- 3 Fibers
- 4 Separator (aluminum foil)
- 5 Strain relief



Make sure you always use the latest documentation.
It can be downloaded at www.phoenixcontact.net/catalog.



This data sheet is valid for all products listed on the following page:

2 Ordering data

Cables

Description	Type	Order No.	Pcs. / Pkt.
Polymer fiber cable, duplex, 980 µm/1000 µm, medium-weight version for fixed indoor installation, by the meter without plug	PSM-LWL-KDHEAVY-980/1000	2744319	1
Polymer fiber cable , duplex 980/1000 µm, medium-weight version for fixed indoor installation, assembled with plugs (IP20 heads only)	FOC-KDHEAVY-1011/IP20/...	2901553	1
Polymer fiber cable , duplex 980/1000 µm, medium-weight version for fixed indoor installation, assembled with plugs	FOC-KDHEAVY-1011/...	1402188	1

Accessories

Description	Type	Order No.	Pcs. / Pkt.
Fiber optic plug-in connector, SCRJ plug set for polymer fibers, consisting of two duplex quick mounting plugs with bend protection	PSM-SET-SCRJ-DUP/2-POF	2708656	1
Fiber optic plug-in connector , F-SMA plug set, for polymer fibers, consisting of four quick mounting plugs with bend protection	PSM-SET-FSMA/4-KT	2799720	1
Polymer fiber assembly kit , consisting of: stripping blade, stripping pliers, polishing wheels for F-SMA and SCRJ quick mounting plugs, polishing pad, and emery paper	PSM-POF-KONFTOOL	2744131	1
Polymer fiber polishing set , for F-SMA quick mounting plugs	PSM-SET-FSMA-POLISH	2799348	1
Refilling set , for VS-SCRJ-POF-POLISH, consisting of two polishing discs and a polisher	VS-SCRJ-POF-POLISH	1656673	1
Stripping tool , for removing cables (especially fiber optic cables) of Ø 4 mm ... 16 mm	WIREFOX-D 16	1212173	1
Fiber optic measuring case , consisting of an optical power meter, F-SMA and B-FOC adapters, reference fibers, and operating instructions	PSM-FO-POWERMETER	2799539	1
Fiber optic measuring case supplementary set , for devices with SCRJ interface, consisting of one-meter polymer reference fiber (SC Simplex to F-SMA plug), one-meter HCS GI reference fiber (SC Simplex to B-FOC plug), and SCRJ coupling	PSM-FO-POWERMETER SCRJ-SET	2901560	1

3 Technical data

General data	
Cable type	Polymer fiber, 980/1000 µm
Cable abbreviation	J-V11Y 4Y2P 980/1000 160A 10
Cable length	Free input (0.4 ... 100.0 m)
Weight	33 kg/km
Temperature range	
Installation	-5°C ... +50°C
Operation	-20°C ... +70°C
Storage	-40°C ... +80°C
Altitude	5000 m
Fibers	
Type	980/1000 µm, step index profile
Material	PMMA
Attenuation	
At 650 nm	≤ 170 dB/km (monochromatic)
At 660 nm	≤ 230 dB/km (LED)
Bandwidth length product	
At 650 nm	≥ 10 MHz x 100 m
Numerical aperture	0.50

Single wires

Material	Polyamide (PA)
Color	Black and orange
Wire diameter	2.2 mm ±0.07 mm
Stranding	Two single elements wrapped in aluminum foil

Outer sheath

Material	Polyurethane (PUR)
Color	Red
Diameter	6 mm ±0.5 mm
Strain relief elements	Non-metallic, aramide yarn
Imprint	PHOENIX CONTACT FIBER OPTIC CABLE J-V11Y 4Y2P 980/1000 160A 10 HEAVY and running length specification in m, date of manufacture

Mechanical properties according to IEC 60794-1-2

		Cables		Single wires	
Bending radius	Method E11, test type A	Temporary	At least 30 mm	Temporary	At least 30 mm
		Permanent	At least 30 mm	Permanent	At least 20 mm
Tensile strength	Method E1	Temporary	Maximum 600 N	Temporary	Maximum 60 N
		Permanent	Maximum 100 N	Permanent	Maximum 10 N
Lateral strength	Method E3	Temporary	Maximum 200 N/cm		
		Permanent	Maximum 20 N/cm		
Impact strength	Method E4	At least 2 Nm, 10°impacts			
Resistance to abrasion	Method E2, test type A	At least 5000 cycles, 0.45 mm radius of the steel point, 7 N			
Roller change bending test	Method E8			At least 50,000 cycles, r = 20 mm	

Material properties

Resistance to oil	IRM 902 100°C according to DIN VDE 0473-811-2-1
Paint or varnish coating	Free from substances that would ruin a paint or varnish coating according to central standard P-VW 3.10.757 65 0 of VW, Audi, Seat
Halogen-free	According to IEC 60754-2 A1
Resistance to ozone	According to DIN VDE 0472-805, test type B
UV resistance	According to DIN EN ISO 4892-2, method A
Fire load	1.02 MJ/m (0.24 kWh/m)
RoHS conformance	Cable meets EU directive 2002/95/EC



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.