Features

- **Industry Standard Architecture**
  - **Low-cost Easy-to-use Software Tools**
- **High-speed, Electrically Erasable Programmable Logic Devices**
- **CMOS and TTL Compatible Inputs and Outputs**
  - **Input and I/O Pull-up Resistors**
- **Advanced Flash Technology**
  - **Reprogrammable**
  - **100% Tested**
- **High-reliability CMOS Process**
  - **20 year Data Retention**
  - **100 Erase/Write Cycles**
  - **2,000V ESD Protection**
  - **200mA Latchup Immunity**
- **Full Military Temperature Ranges**
- **Dual-in-line and Surface Mount Packages in Standard Pinouts**
- **PCI Compliant**

Figure 0-1. Logic Diagram





Figure 0-2. Pin Configurations

All Pinouts Top View

Pin Name	Function
CLK	Clock
IN	Logic Inputs
I/O	Bidirectional Buffers
*	No Internal Connection
V_{CC}	+5V Supply



High-performance Electrically Erasable Programmable Logic Device

Atmel ATF22V10B

0250M–PLD–7/10

1. Description

The Atmel® ATF22V10B is a high-performance CMOS (electrically erasable) programmable logic device (PLD) which utilizes the Atmel proven electrically erasable Flash memory technology. Speeds down to 7.5ns and power dissipation as low as 10mA are offered. All speed ranges are specified over the full 5V ± 10% range for military and industrial temperature ranges, and 5V ± 5% for commercial temperature ranges.

Several low-power options allow selection of the best solution for various types of power-limited applications. Each of these options significantly reduces total system power and enhances system reliability.

2. Absolute Maximum Ratings*

Temperature Under Bias	-55°C to +125°C
Storage Temperature	-65°C to +150°C
Voltage on Any Pin with Respect to Ground	-2.0V to +7.0V(1)
Voltage on Input Pins with Respect to Ground During Programming	-2.0V to +14.0V(1)
Programming Voltage with Respect to Ground	-2.0V to +14.0V(1)

*NOTICE: Stresses beyond those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Note: 1. Minimum voltage is -0.6V DC, which may undershoot to -2.0V for pulses of less than 20ns. Maximum output pin voltage is V_{CC} + 0.75V DC, which may overshoot to 7.0V for pulses of less than 20ns.

3. DC and AC Operating Conditions

	Commercial	Industrial	Military
Operating Temperature	0°C - 70°C (Ambient)	-40°C - 85°C (Ambient)	-55°C - 125°C (Case)
V_{CC} Power Supply	5V ± 5%	5V ± 10%	5V ± 10%

Note: 1. The shaded devices are obsolete


3.1 DC Characteristics

Symbol	Parameter	Condition			Min	Typ	Max	Units
I_{IL}	Input or I/O Low Leakage Current	$0 \le V_{IN} \le V_{IL}$ (Max)				-35	-100	µA
I_{IH}	Input or I/O High Leakage Current	$3.5 \le V_{IN} \le V_{CC}$					10	µA
I_{CC}	Power Supply Current, Standby	V_{CC} = Max, V_{IN} = Max, Outputs Open	B-7	Com.		85	120	mA
				Ind., Mil.		85	140	mA
I_{CC}	Power Supply Current, Standby	V_{CC} = Max, V_{IN} = Max, Outputs Open	B-10	Com./Ind.		85/85	120/140	mA
				Mil.		85	140	mA
			B-15	Com./Ind.		65/65	90/115	mA
				Mil.		65	115	mA
			B-25	Com.		65	90	mA
				Ind., Mil.		65	115	mA
			BQ-15	Com.		35	55	mA
			BQL-20, -25	Com.		5	10	mA
				Ind., Mil.		5	15	mA
I_{CC2}	Clocked Power Supply Current	V_{CC} = Max, Outputs Open, f = 15MHz	B-7	Com.		90	120	mA
				Mil., Ind.		90	145	mA
			B-10	Com./Ind.		90/90	120/145	mA
				Mil.		90	150	mA
			B-15	Com./Ind.		65/65	90/120	mA
				Mil.		65	150	mA
			B-25	Com.		65	90	mA
				Ind., Mil.		65	120	mA
			BQ-15	Com.		40	60	mA
			BQL-20, -25	Com.		20	50	mA
				Ind., Mil.		20	70	mA
I_{OS}[1]	Output Short Circuit Current	V_{OUT} = 0.5V					-130	mA
V_{IL}	Input Low Voltage				-0.5		0.8	V
V_{IH}	Input High Voltage				2.0		V_{CC} + 0.75	V
V_{OL}	Output Low Voltage	$V_{IN} = V_{IH}$ or V_{IL}, V_{CC} = Min	I_{OL} = 16mA	Com., Ind.			0.5	V
			I_{OL} = 12mA	Mil.			0.5	V
V_{OH}	Output High Voltage	$V_{IN} = V_{IH}$ or V_{IL}, V_{CC} = Min	I_{OH} = -4.0mA		2.4			V

Notes: 1. Not more than one output at a time should be shorted. Duration of short circuit test should not exceed 30 sec

2. The shaded devices are obsolete

4. AC Waveforms[1]




Note: 1. Timing measurement reference is 1.5V. Input AC driving levels are 0.0V and 3.0V, unless otherwise specified

5. AC Characteristics[1]

Symbol	Parameter	-10		-15		Units
		Min	Max	Min	Max	
t_{PD}	Input or Feedback to Combinatorial Output	3	10	3	15	ns
t_{CO}	Clock to Output	2	6.5	2	8	ns
t_{CF}	Clock to Feedback		2.5		2.5	ns
t_S	Input or Feedback Setup Time	4.5		10		ns
t_H	Hold Time	0		0		ns
f_{MAX}	External Feedback $1/(t_S + t_{CO})$	90		55.5		MHz
	Internal Feedback $1/(t_S + t_{CF})$	142		69		MHz
	No Feedback $1/(t_{WH} + t_{WL})$	142		83.3		MHz
t_W	Clock Width (t_{WL} and t_{WH})	3.5		6		ns
t_{EA}	Input or I/O to Output Enable	3	10	3	15	ns
t_{ER}	Input or I/O to Output Disable	3	9	3	15	ns
t_{AP}	Input or I/O to Asynchronous Reset of Register	3	12	3	20	ns
t_{AW}	Asynchronous Reset Width	8		15		ns
t_{AR}	Asynchronous Reset Recovery Time	6		10		ns
t_{SP}	Setup Time, Synchronous Preset	6		10		ns
t_{SPR}	Synchronous Preset to Clock Recovery Time	8		10		ns


Notes: 1. See ordering information for valid part numbers

6. Input Test Waveforms and Measurement Levels



t_R, t_F < 3ns

7. Output Test Loads



* All except -7 which is R2 = 300Ω

8. Pin Capacitance

f = 1MHz, T = 25°C[1]

	Typ	Max	Units	Conditions
C_{IN}	5	8	pF	V_{IN} = 0V
C_{OUT}	6	8	pF	V_{OUT} = 0V

Note: 1. Typical values for nominal supply voltage. This parameter is only sampled and is not 100% tested

9. Power-up Reset

The registers in the Atmel® ATF22V10B are designed to reset during power-up. At a point delayed slightly from V_{CC} crossing V_{RST}, all registers will be reset to the low state. The output state will depend on the polarity of the output buffer.

This feature is critical for state machine initialization. However, due to the asynchronous nature of reset and the uncertainty of how V_{CC} actually rises in the system, the following conditions are required:

1. The V_{CC} rise must be monotonic
2. After reset occurs, all input and feedback setup times must be met before driving the clock pin high
3. The clock must remain stable during t_{PR}

10. Preload of Registered Outputs

The Atmel® ATF22V10B registers are provided with circuitry to allow loading of each register with either a high or a low. This feature will simplify testing since any state can be forced into the registers to control test sequencing. A JEDEC file with preload is generated when a source file with vectors is compiled. Once downloaded, the JEDEC file preload sequence will be done automatically by most of the approved programmers after the programming.

Figure 10-1.




Table 10-1.

Parameter	Description	Typ	Max	Units
t_{PR}	Power-up Reset Time	600	1,000	ns
V_{RST}	Power-up Reset Voltage	3.8	4.5	V

11. Security Fuse Usage

A single fuse is provided to prevent unauthorized copying of the ATF22V10B fuse patterns. Once programmed, fuse verify and preload are inhibited. However, the 64-bit User Signature remains accessible.

The security fuse should be programmed last, as its effect is immediate.

12. Electronic Signature Word

There are 64-bits of programmable memory that are always available to the user, even if the device is secured. These bits can be used for user-specific data.

13. Programming/Erasing

Programming/erasing is performed using standard PLD programmers. See *CMOS PLD Programming Hardware and Software Support* for information on software/programming.

14. Input and I/O Pull-ups

All Atmel® ATF22V10B family members have internal input and I/O pull-up resistors. Therefore, whenever inputs or I/Os are not being driven externally, they will float to V_{CC}. This ensures that all logic array inputs are at known states. These are relatively weak active pull-ups that can easily be overdriven by TTL-compatible drivers (see input and I/O diagrams below).

Figure 14-1. Input Diagram




Figure 14-2. I/O Diagram







Figure 14-3. Functional Logic Diagram Atmel ATF22V10B




SUPPLY CURRENT vs. INPUT FREQUENCY




SUPPLY CURRENT vs. INPUT FREQUENCY




SUPPLY CURRENT vs. SUPPLY VOLTAGE




SUPPLY CURRENT vs. SUPPLY VOLTAGE



SUPPLY CURRENT vs. AMBIENT TEMPERATURE




SUPPLY CURRENT vs. AMBIENT TEMPERATURE




OUTPUT SOURCE CURRENT


vs. SUPPLY VOLTAGE (VOH = 2.4V)





OUTPUT SINK CURRENT


vs. SUPPLY VOLTAGE (VOL = 0.5V)






OUTPUT SOURCE CURRENT
vs. OUTPUT VOLTAGE (VCC = 5V, TA = 25°C)
IOH mA
0
-2
-4
-6
-8
-10
-12
3.5
3.8
4.1
4.4
4.7
5.0
OUTPUT VOLTAGE (v)



OUTPUT SINK CURRENT
vs. OUTPUT VOLTAGE (VCC = 5V, TA = 25°C)
IOL mA
60
50
40
30
20
10
0
0.0
0.2
0.4
0.6
0.8
1.00
OUTPUT VOLTAGE (v)



OUTPUT SOURCE CURRENT
vs. OUTPUT VOLTAGE (VCC = 5V, TA = 25°C)
IOH mA
0
-15
-30
-45
-60
0.0 0.5 1.0 1.5 2.0 2.5 3.0 3.5 4.0 4.5 5.0
OUTPUT VOLTAGE (V)



OUTPUT SINK CURRENT
vs. OUTPUT VOLTAGE (VCC = 5V, TA = 25°C)
IOL mA
150
120
90
60
30
0
0
1
2
3
4
5
OUTPUT VOLTAGE (V)



NORMALIZED tPD
vs. SUPPLY VOLTAGE (TA = 25°C)
NORM TPD
1.30
1.15
1.00
0.85
0.70
ATF22V10B/BQ
ATF22V10BQL
4.50
4.75
5.00
5.25
5.50
SUPPLY VOLTAGE (V)



NORMALIZED tPD
vs. AMBIENT TEMPERATURE (VCC = 5V)
NORM TPD
1.30
1.15
1.00
0.85
0.70
-55
-25
5
35
65
95
125
AMBIENT TEMPERATURE (C)



NORMALIZED tCO
vs. SUPPLY VOLTAGE (TA = 25°C)
NORM TCO
1.30
1.15
1.00
0.85
0.70
ATF22V10B/BQ
ATF22V10BQL
4.50
4.75
5.00
5.25
5.50
SUPPLY VOLTAGE (V)



NORMALIZED tCO
vs. AMBIENT TEMPERATURE (VCC = 5V)
NORM TCO
1.30
1.15
1.00
0.85
0.70
-55
-10
35
80
125
AMBIENT TEMPERATURE (C)



NORMALIZED t_S
vs. SUPPLY VOLTAGE (TA = 25°C)
NORM TS
1.5
1.3
1.1
0.9
0.7
4.0
4.5
5.0
5.5
6.0
SUPPLY VOLTAGE (v)



NORMALIZED t_S
vs. AMBIENT TEMPERATURE (VCC = 5V)
NORM TS
1.30
1.15
1.00
0.85
0.70
-55
-10
35
80
125
AMBIENT TEMPERATURE (C)



DELTA t_{PD} vs. OUTPUT LOADING
(VCC = 4.5V, OUTPUT LOAD = COMMERCIAL)
DELTA TPD ns
12
9
6
3
0
-3
0
100
200
300
400
OUTPUT LOADING (pF)


DELTA t_{CO} vs. OUTPUT LOADING
(VCC = 4.5V, OUTPUT LOAD = COMMERCIAL)
DELTA TCO ns
12
9
6
3
0
-3
0
100
200
300
400
OUTPUT LOADING (pF)


DELTA t_{PD} vs. # OUTPUT SWITCHING
(VCC = 5V, TA = 25°C)
DELTA TPD ns
0.0
-0.1
-0.2
-0.3
-0.4
-0.5
1
2
3
4
5
6
7
8
9
10
OF OUTPUT SWITCHING


DELTA t_{CO} vs. # OUTPUT SWITCHING
(VCC = 5V, TA = 25°C)
DELTA TCO ns
0.0
-0.1
-0.2
-0.3
-0.4
-0.5
1
2
3
4
5
6
7
8
9
10
OF OUTPUT SWITCHING


INPUT CURRENT vs. INPUT VOLTAGE
(VCC = 5V, TA = 25°C)
INPUT CURRENT uA
40
20
0
-20
-40
0
1
2
3
4
5
6
7
8
INPUT VOLTAGE (V)


INPUT CLAMP CURRENT
vs. INPUT VOLTAGE (VCC = 5V, TA = 25°C)
INPUT CURRENT mA
20
0
-20
-40
-60
-80
-1.0
-0.8
-0.6
-0.4
-0.2
0.0
INPUT VOLTAGE (V)

15. Ordering Information

15.1 Atmel ATF22V10B[2] Ordering Detail

t_{PD} (ns)	t_S (ns)	t_{CO} (ns)	Ordering Code	Package	Operation Range
10	4.5	6.5	ATF22V10B-10GM/883 ATF22V10B-10NM/883	24D3 28L	Military/883C (-55°C to 125°C) Class B, Fully Compliant
			5962-89841 06LA 5962-89841 063X	24D3 28L	Military (-55°C to 125°C) Class B, Fully Compliant
15	10	8	ATF22V10B-15GM/883 ATF22V10B-15NM/883	24D3 28L	Military/883C (-55°C to 125°C) Class B, Fully Compliant
			5962-89841 03LA 5962-89841 033X	24D3 28L	Military (-55°C to 125°C) Class B, Fully Compliant

15.2 Atmel ATF22V10BQ(L)[1,2] Ordering Detail


t_{PD} (ns)	t_S (ns)	t_{CO} (ns)	Ordering Code	Package	Operation Range
20	14	12	ATF22V10BQL-20GM/883 ATF22V10BQL-20NM/883	24D3 28L	Military/883C (-55°C to 125°C) Class B, Fully Compliant
			5962-89841 14 LA 5962-89841 14 3X	24D3 28L	Military (-55°C to 125°C) Class B, Fully Compliant
25	15	15	ATF22V10BQL-25GM/883 ATF22V10BQL-25NM/883	24D3 28L	Military/883C (-55°C to 125°C) Class B, Fully Compliant
			5962-89841 13 LA 5962-89841 13 3X	24D3 28L	Military (-55°C to 125°C) Class B, Fully Compliant

Notes: 1. The shaded devices are obsolete
2. Please see DSCC DWG for military parts

16. Packaging Information

24D3

24D3, 24-lead, 0.300"Wide. Non-windowed,
Ceramic Dual Inline Parkage (Cerdip)
Dimensions in Millimeters and (Inches)*
MIL-STD-1835 D-9 CONFIG A (Glass Sealed)




*Controlling dimension: Inches

REV. A 04/11/2001

28L

28L, 28-pad, Non-windowed, Ceramic lid, Leadless Chip Carrier (LCC)
Dimensions in Millimeters and (Inches)*
MIL-STD-1835 C-4



*Controlling dimension: Inches

17. Revision History

Doc. Rev.	Date	Comments
0250M	07/2010	Removed all commerical and industrial grade leaded part offerings

Headquarters

Atmel Corporation
2325 Orchard Parkway
San Jose, CA 95131
USA
Tel: (+1)(408) 441-0311
Fax: (+1)(408) 487-2600
www.atmel.com

International

Atmel Asia Limited
Unit 01-5 & 16, 19/F
BEA Tower, Millennium City 5
418 Kwun Tong Road
Kwun Tong, Kowloon
HONG KONG
Tel: (+852) 2245-6100
Fax: (+852) 2722-1369

Atmel Munich GmbH
Business Campus
Parkring 4
D-85748 Garching b. Munich
GERMANY
Tel: (+49) 89-31970-0
Fax: (+49) 89-3194621

Atmel Japan
9F, Tonetsu Shinkawa Bldg.
1-24-8 Shinkawa
Chuo-ku, Tokyo 104-0033
JAPAN
Tel: (+81) 3-3523-3551
Fax: (+81) 3-3523-7581

Product Contact

Technical Support	*Sales Contact*	*Literature Requests*
pld@atmel.com	www.atmel.com/contacts	www.atmel.com/literature

Disclaimer: The information in this document is provided in connection with Atmel products. No license, express or implied, by estoppel or otherwise, to any intellectual property right is granted by this document or in connection with the sale of Atmel products. **EXCEPT AS SET FORTH IN ATMEL'S TERMS AND CONDITIONS OF SALE LOCATED ON ATMEL'S WEB SITE, ATMEL ASSUMES NO LIABILITY WHATSOEVER AND DISCLAIMS ANY EXPRESS, IMPLIED OR STATUTORY WARRANTY RELATING TO ITS PRODUCTS INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT SHALL ATMEL BE LIABLE FOR ANY DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE, SPECIAL OR INCIDENTAL DAMAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF PROFITS, BUSINESS INTERRUPTION, OR LOSS OF INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT, EVEN IF ATMEL HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.** Atmel makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Atmel does not make any commitment to update the information contained herein. Unless specifically provided otherwise, Atmel products are not suitable for, and shall not be used in, automotive applications. Atmel's products are not intended, authorized, or warranted for use as components in applications intended to support or sustain life.

© 2010 Atmel Corporation. All rights reserved.
Atmel®, Atmel logo and combinations thereof and others are registered trademarks or trademarks of Atmel Corporation or its subsidiaries. Other terms and product names may be trademarks of others.


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.