


NLP65 Medical Series

Single, Dual and Triple output

Total Power: 65 W
Input Voltage: 85 - 264 VAC
of Outputs: Single, Dual, Triple



Special Features

- 85 VAC to 264 VAC universal input range
- Harmonic current correction as standard
- Maximum component height 1.26 inches
- UL, CSA and VDE safety approvals
- Overvoltage and short circuit protection
- 5 x 3 x 1.26 inch (127.0 x 76.2 x 32mm) footprint
- Available RoHS compliant
- 2 year warranty

Safety

- UL60601-1/CAN/CSA-C22.2 No. 60601-1-M90
- VDE License No. 121949 under | EN60601-1/IEC60601-1

Electrical Specifications

| Input | | |
|-----------------------------------|---|---|
| Input voltage range: | Universal input (see Note 2) | 85 - 264 Vac |
| Input frequency range: | | 47 - 63 Hz |
| Input current: (cold start) | 120 Vac 230 Vac | 17 A max. 32 A max |
| Safety ground leakage current: | 264 Vac, 60 Hz | 95 μ A |
| Input current: | 120 Vac 230 Vac | 1.05 A rms 0.51 A rms |
| Input fuse: | | 250 Vac F 3.15 A |
| Output | | |
| Output power: | Natural convection | 65 W max. |
| Total regulation: (line and load) | | See table |
| Rise time: | At turn-on | 1.0 s, max |
| Transient response: | Main output 25% step at 0.1 A/ μ s | 5.0% max. dev., 1ms recovery to 1.0% |
| Temperature coefficient: | | \pm 0.02%/ $^{\circ}$ C |
| Overvoltage protection: | Main outputs | 125%, \pm 10% |
| Short circuit protection: | Cyclic operation | Yes |

EMC Characteristics

| | | |
|----------------------|----------------------|------------------|
| Conducted emissions: | EN55022, FCC part 15 | Level A |
| Radiated emissions: | EN55022, FCC part 15 | Level A |
| ESD air: | EN61000-4-2, level 3 | Perf. criteria 1 |
| ESD contact: | EN61000-4-2, level 4 | Perf. criteria 1 |
| Surge: | EN61000-4-5, level 3 | Perf. criteria 1 |
| Fast transients: | EN61000-4-4, level 3 | Perf. criteria 1 |
| Radiated immunity: | EN61000-4-3, level 3 | Perf. criteria 2 |
| Conducted immunity: | EN61000-4-6, level 3 | Perf. criteria 2 |


General Specifications

| | | |
|--------------------------|-------------------------------|----------------------|
| Hold-up time: | 120 Vac, 60 Hz | 16 ms @ 65 W |
| Efficiency: | 120 Vac, 65 W | 72% typical |
| Isolation voltage: | Input/output Input/chassis | 4000 Vac 1500 Vac |
| Switching frequency: | Fixed | 100 kHz, ± 5 kHz |
| Approvals and standards: | EN60601-1, IEC60601-1 | |
| Weight: | 283 g (10 oz) | |
| MTBF demonstrated: | MIL-HDBK-217F | 150,000 hours |

All specifications are typical at nominal input, full load at 25 °C unless otherwise stated.

Environmental Specifications

| | | |
|-------------------------|--|--|
| Thermal performance: | Operating ambient (See derating curve) | 0° C to +70 °C |
| | Non-operating | -40 °C to +85 °C |
| | 0 °C to 50 °C, ambient, convection cooled | 65 W |
| | 50 °C - 70 °C ambient, convection cooled | Derate to 50% load |
| | Peak (0 °C to 50 °C, 60 s) | See table |
| Relative humidity: | Non-condensing | 5 to 95% RH |
| | Altitude: | Operating 10,000 feet max. Non-operating 30,000 feet max. |
| Vibration (See Note 5): | 5 - 500 Hz | 2.4 G rms approx. |
| Shock | per MIL-STD-810E | 516.4 Part IV |




Ordering Information

| Output Voltage | Output Current | | | Ripple ⁽⁴⁾ | Total Regulation ⁽⁶⁾ | Model Number ^(11, 12) |
|----------------|--------------------|--------|---------------------|-----------------------|---------------------------------|----------------------------------|
| | Max ⁽¹⁾ | Peak | Fan ⁽¹⁰⁾ | | | |
| +5 V | 7 A | 9.1 A | 8 A | 50 mV | ± 2.0% | NLP65-9908J |
| +12 V | 2.5 A | 3.3 A | 3 A | 150 mV | ± 5.0% | |
| -12 V | 0.5 A | 0.81 A | 1 A | 120 mV | ± 5.0% | |
| +5 V | 7 A | 9.1 A | 8 A | 50 mV | ± 2.0% | NLP65-9920J |
| +24 V | 2 A | 2.6 A | 2 A | 240 mV | ± 5.0% | |
| +5 V | 7 A | 9.1 A | 8 A | 50 mV | ± 2.0% | NLP65-9929J |
| +12 V | 2.5 A | 3.3 A | 3 A | 150 mV | ± 5.0% | |
| +12 V | 5.4 A | 7 A | 6.5 A | 120 mV | ± 2.0% | NLP65-9912J |
| +15 V | 4.4 A | 5.7 A | 5.3 A | 150 mV | ± 2.0% | NLP65-9915J |
| +24 V | 2.7 A | 3.5 A | 3.5 A | 240 mV | ± 2.0% | NLP65-9924J |

Notes

- 1 Natural convection cooling. Models NLP65-9929J, and NLP65-9908J must not exceed 62.5 Watts continuous output power with natural convection. Model NLP65-9920J not to exceed 65 Watts continuous output power with natural convection.
- 2 When the input voltage is less than 90 Vac the operating temperature range is 0 °C to +40 °C. The ripple and regulation specifications may not be met.
- 3 Peak output current lasting less than 60 seconds with duty cycle less than 5%. During peak loading, output voltage may exceed total regulation limits.
- 4 Figure is peak-to-peak for convection power rating. Output noise measurements are made across a 20 MHz bandwidth using a 6 inch twisted pair, terminated with a 10 µF electrolytic capacitor and a 0.1 µF ceramic capacitor.
- 5 Three orthogonal axes, random vibration 10 minutes for each axes, 2.4 G rms 5 Hz to 500 Hz.
- 6 To maintain stated regulation then:
For single output units: $I \geq 0.2 \text{ A } I \text{ max.}$
For multiple output units: $0.25 \leq I(A)/I(B) \leq 5$, for $I(A) \geq 0.2 \text{ A } I(A) \text{ max.}$
- 7 For optimum reliability, no part of the heatsink should exceed 120 °C, and no semiconductor case temperature should exceed 130 °C.
- 8 CAUTION: Allow a minimum of 1 second after disconnecting line power when making thermal measurements.
- 9 This product is only for inclusion by professional installers within other equipment and must not be operated as a stand alone product.
- 10 Maximum continuous output power for all multiple output models must not exceed 75 Watts with 20 CFM forced air cooling at 50 °C.
- 11 The 'J' suffix indicates that these parts are Pb-free (RoHS 6/6) compliant.
- 12 NOTICE: Some models do not support all options. Please contact your local Emerson Network Power representative or use the on-line model number search tool at <http://www.Emerson.com/EmbeddedPower> to find a suitable alternative.



Americas

5810 Van Allen Way
Carlsbad, CA 92008
USA
Telephone: +1 760 930 4600
Facsimile: +1 760 930 0698

Europe (UK)

Waterfront Business Park
Merry Hill, Dudley
West Midlands, DY5 1LX
United Kingdom
Telephone: +44 (0) 1384 842 211
Facsimile: +44 (0) 1384 843 355

Asia (HK)

14/F, Lu Plaza
2 Wing Yip Street
Kwun Tong, Kowloon
Hong Kong
Telephone: +852 2176 3333
Facsimile: +852 2176 3888

For global contact, visit:

www.Emerson.com/EmbeddedPower
techsupport.embeddedpower@emerson.com

While every precaution has been taken to ensure accuracy and completeness in this literature, Emerson Network Power assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

| Pin Connections | |
|-----------------|---------------|
| J1 | |
| Pin 1 | AC Line |
| Pin 2 | No Pin |
| Pin 3 | AC Neutral |
| J2 | |
| Pin 1 | Safety Ground |

| Input and Output Connectors | | Mating Connectors |
|-----------------------------|-------------------------------------|--|
| AC (J1) | Molex 26-60-4030 type or equivalent | Molex 09-50-3031 or equivalent with Molex 08-50-0105 or equivalent crimp terminals |
| DC (J3) | Molex 26-60-4060 or equivalent | Molex 09-50-3061 with Molex 2478 phosphor bronze crimp terminals or equivalent. |

| Output Pin Connections | | | |
|------------------------|---------------|--------|--------|
| J3 | SINGLE | DUAL | TRIPLE |
| Pin 1 | No Connection | V (B) | V (B) |
| Pin 2 | V (A) | V (A) | V (A) |
| Pin 3 | V (A) | V (A) | V (A) |
| Pin 4 | Return | Return | Return |
| Pin 5 | Return | Return | Return |
| Pin 6 | No Connection | No Pin | V (C) |

Emerson Network Power.

The global leader in enabling business-critical continuity.

- AC Power
- Connectivity
- DC Power
- Embedded Computing
- Embedded Power
- Monitoring
- Outside Plant
- Power Switching & Controls
- Precision Cooling
- Racks & Integrated Cabinets
- Services
- Surge Protection

EmersonNetworkPower.com

Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co.
©2011 Emerson Electric Co.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.