

## Leaded Varistors

### Automotive Series

#### Construction

- Round varistor element, leaded
- Coating: epoxy resin (D1: phenolic resin), flame-retardant to UL 94 V-0
- Terminals: tinned copper wire

#### Features


- High energy absorption, particularly in case of load dump
- Jump-start strength
- Stable protection level, minimum leakage current
- High resistance to cyclic temperature stress
- PSpice models
- Types for  $T_A = 125\text{ °C}$

#### Taping

- All types available on tape upon request

#### Type designation

Detailed description of coding system on page 39, chapter “General Technical Information”



#### General technical data

|                                               |                                         |                                  |
|-----------------------------------------------|-----------------------------------------|----------------------------------|
| Climatic category                             | 40/85/56 (D1: 40/125/56)                | in accordance with IEC 60068-1   |
| LCT                                           | – 40 °C                                 |                                  |
| UCT                                           | + 85 °C (D1: + 125 °C)                  |                                  |
| Damp heat, steady state<br>(93 % r.h., 40 °C) | 56 days                                 | in accordance with IEC 60068-2-3 |
| Operating temperature                         | – 40 ... + 85 °C<br>(D1: ... + 125 °C)  | in accordance with CECC 42 000   |
| Storage temperature                           | – 40 ... + 125 °C<br>(D1: ... + 150 °C) |                                  |
| Electric strength                             | ≥ 2,5 kV <sub>RMS</sub> (not D1)        | in accordance with CECC 42 000   |
| Insulation resistance                         | ≥ 10 MΩ (not D1)                        | in accordance with CECC 42 000   |
| Response time                                 | < 25 ns                                 |                                  |




## Leaded Varistors

### Automotive Series

**Maximum ratings** ( $T_A = 85\text{ °C}$ ,  $T_A = 125\text{ °C}$  for S...D1)

| Type<br>(untaped)<br>SIOV- | Ordering code   | $V_{RMS}$<br>V | $V_{DC}$<br>V | $i_{max}$<br>8/20 $\mu$ s<br>A | $W_{max}$<br>(2 ms)<br>J | $P_{max}$<br>W | $W_{LD}$<br>(10x)<br>J |
|----------------------------|-----------------|----------------|---------------|--------------------------------|--------------------------|----------------|------------------------|
| 12-V supply systems        |                 |                |               |                                |                          |                |                        |
| S07K14AUTOS2D1             | B72207S1140K201 | 14             | 16            | 250                            | 0,9                      | 0,02           | 12                     |
| S10K14AUTO                 | B72210S1140K102 | 14             | 16            | 500                            | 2,0                      | 0,05           | 25                     |
| S10K14AUTOS5D1             | B72210S1140K501 | 14             | 16            | 500                            | 2,0                      | 0,05           | 25                     |
| S14K14AUTO                 | B72214S1140K102 | 14             | 16            | 1000                           | 4,0                      | 0,10           | 50                     |
| S14K14AUTOS5D1             | B72214S1140K501 | 14             | 16            | 1000                           | 4,0                      | 0,10           | 50                     |
| S20K14AUTO                 | B72220S1140K102 | 14             | 16            | 2000                           | 12,0                     | 0,20           | 100                    |
| S10K17AUTO                 | B72210S1170K102 | 17             | 20            | 500                            | 2,5                      | 0,05           | 25                     |
| S14K17AUTO                 | B72214S1170K102 | 17             | 20            | 1000                           | 5,0                      | 0,10           | 50                     |
| S20K17AUTO                 | B72220S1170K102 | 17             | 20            | 2000                           | 14,0                     | 0,20           | 100                    |
| 24-V supply systems        |                 |                |               |                                |                          |                |                        |
| S20K25AUTO                 | B72220S1250K102 | 25             | 28            | 2000                           | 22,0                     | 0,20           | 100                    |
| S14K30AUTO                 | B72214S1300K102 | 30             | 34            | 1000                           | 9,0                      | 0,10           | 50                     |
| S20K30AUTO                 | B72220S1300K102 | 30             | 34            | 2000                           | 26,0                     | 0,20           | 100                    |



## Leaded Varistors

### Automotive Series

#### Characteristics ( $T_A = 25^\circ\text{C}$ )

| Type<br>(untaped)<br>SIOV- | $V_{\text{Jump}}$<br>(5 min)<br>V | $V_V$<br>(1 mA)<br>V | $\Delta V_V$<br>(1 mA)<br>% | Max. clamping voltage<br>$v$ $i$<br>V      A |  | $C_{\text{typ}}$<br>(1 kHz)<br>nF | Derating<br>curve<br>Page | V/I char-<br>acteristic<br>Page |
|----------------------------|-----------------------------------|----------------------|-----------------------------|----------------------------------------------|--|-----------------------------------|---------------------------|---------------------------------|
|----------------------------|-----------------------------------|----------------------|-----------------------------|----------------------------------------------|--|-----------------------------------|---------------------------|---------------------------------|

#### 12-V supply systems

|                |    |    |          |    |      |      |     |     |
|----------------|----|----|----------|----|------|------|-----|-----|
| S07K14AUTOS2D1 | 25 | 22 | $\pm 10$ | 43 | 2,5  | 2,3  | 246 | 275 |
| S10K14AUTO     | 25 | 22 | $\pm 10$ | 43 | 5,0  | 5,2  | 248 | 276 |
| S10K14AUTOS5D1 | 25 | 22 | $\pm 10$ | 43 | 5,0  | 5,2  | 248 | 276 |
| S14K14AUTO     | 25 | 22 | $\pm 10$ | 43 | 10,0 | 10,0 | 249 | 277 |
| S14K14AUTOS5D1 | 25 | 22 | $\pm 10$ | 43 | 10,0 | 10,0 | 249 | 277 |
| S20K14AUTO     | 25 | 22 | $\pm 10$ | 43 | 20,0 | 19,0 | 251 | 278 |
| S10K17AUTO     | 30 | 27 | $\pm 10$ | 53 | 5,0  | 4,4  | 248 | 276 |
| S14K17AUTO     | 30 | 27 | $\pm 10$ | 53 | 10,0 | 8,2  | 249 | 277 |
| S20K17AUTO     | 30 | 27 | $\pm 10$ | 53 | 20,0 | 15,6 | 251 | 278 |

#### 24-V supply systems


|            |    |    |          |    |      |      |     |     |
|------------|----|----|----------|----|------|------|-----|-----|
| S20K25AUTO | 40 | 39 | $\pm 10$ | 77 | 20,0 | 11,1 | 251 | 278 |
| S14K30AUTO | 45 | 47 | $\pm 10$ | 93 | 10,0 | 5,0  | 249 | 277 |
| S20K30AUTO | 45 | 47 | $\pm 10$ | 93 | 20,0 | 9,4  | 251 | 278 |

#### Notes

- If the maximum loads specified for load dump and jump start are fully utilized, subsequent polarity reversal of the AUTO varistors is inadmissible.
- If the load remains under the maximum ratings, polarity reversal may be admissible.  
Contact EPCOS for consultancy on this kind of problem.
- Load dump or jump start can decrease the varistor voltage in load direction by max. 15 %.
- Load dump: min. time of energy input 40 ms, interval 60 s.

| Characteristics           | Test methods                                                                                                        | Specifications                                                      |
|---------------------------|---------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|
| Fast temperature cycling  | IEC 60068-2-14, test Na,<br>UCT/LCT, dwell time 15 min<br>100 cycles: SIOV-S...AUTO<br>1000 cycles: SIOV-S...AUTOD1 | $ \Delta V/V (1 \text{ mA})  \leq 10 \%$<br>No visible damage       |
| Damp heat, steady state   | Based on IEC 60068-2-3,<br>85 °C, 85 % r.h., $V_{\text{DC}}$ , 1000 h                                               | $ \Delta V/V (1 \text{ mA}) ^{(1)} \leq 10 \%$<br>No visible damage |
| Max. DC operating voltage | MIL STD 202F, method 108A,<br>UCT, $V_{\text{DC}}$ , 1000 h                                                         | $ \Delta V/V (1 \text{ mA}) ^{(1)} \leq 10 \%$<br>No visible damage |

1) Measured in load direction



1) Seating plane in accordance with IEC 60717

VAR0401-Y

## Dimensions

| Type                | $e \pm 1$<br>mm | $a \pm 1$<br>mm | $b_{\max}$<br>mm | $s_{\max}$<br>mm | $h_{\max}$<br>mm | $l_{\min}$<br>mm | $d \pm 0,05$<br>mm |
|---------------------|-----------------|-----------------|------------------|------------------|------------------|------------------|--------------------|
| SIOV-S07K14AUTOS2D1 | 5,0             | 1,3             | 9,0              | 3,5              | 12,5             | 30,0             | 0,6                |
| SIOV-S10K14AUTO     | 7,5             | 1,5             | 13,0             | 5,0              | 16,5             | 30,0             | 0,8                |
| SIOV-S10K14AUTOS5D1 | 7,5             | 1,5             | 12,0             | 4,0              | 16,0             | 30,0             | 0,8                |
| SIOV-S14K14AUTO     | 7,5             | 1,5             | 17,0             | 5,0              | 20,5             | 30,0             | 0,8                |
| SIOV-S14K14AUTOS5D1 | 7,5             | 1,5             | 16,0             | 4,0              | 20,0             | 30,0             | 0,8                |
| SIOV-S20K14AUTO     | 10,0            | 1,6             | 23,0             | 5,4              | 27,5             | 30,0             | 1,0                |
| SIOV-S10K17AUTO     | 7,5             | 1,6             | 13,0             | 5,1              | 16,5             | 30,0             | 0,8                |
| SIOV-S14K17AUTO     | 7,5             | 1,7             | 17,0             | 5,1              | 20,5             | 30,0             | 0,8                |
| SIOV-S20K17AUTO     | 10,0            | 1,6             | 23,0             | 5,6              | 27,5             | 30,0             | 1,0                |
| SIOV-S20K25AUTO     | 10,0            | 2,9             | 23,0             | 6,2              | 27,5             | 30,0             | 1,0                |
| SIOV-S14K30AUTO     | 7,5             | 1,8             | 17,0             | 5,3              | 20,5             | 30,0             | 0,8                |
| SIOV-S20K30AUTO     | 10,0            | 3,2             | 23,0             | 6,5              | 27,5             | 30,0             | 1,0                |

For crimp styles S2 and S5 see page 212

## Weight

| Size | approx.       |
|------|---------------|
| S07  | 0,6 ... 0,8 g |
| S10  | 1,0 ... 2,0 g |
| S14  | 2,0 ... 4,0 g |
| S20  | 3,0 ... 6,0 g |

**Herausgegeben von EPCOS AG****Unternehmenskommunikation, Postfach 80 17 09, 81617 München, DEUTSCHLAND****☎ ++49 89 636 09, FAX (0 89) 636-2 26 89**

© EPCOS AG 2002. Vervielfältigung, Veröffentlichung, Verbreitung und Verwertung dieser Broschüre und ihres Inhalts ohne ausdrückliche Genehmigung der EPCOS AG nicht gestattet.

Bestellungen unterliegen den vom ZVEI empfohlenen Allgemeinen Lieferbedingungen für Erzeugnisse und Leistungen der Elektroindustrie, soweit nichts anderes vereinbart wird.

Diese Broschüre ersetzt die vorige Ausgabe.

Fragen über Technik, Preise und Liefermöglichkeiten richten Sie bitte an den Ihnen nächstgelegenen Vertrieb der EPCOS AG oder an unsere Vertriebsgesellschaften im Ausland. Bauelemente können aufgrund technischer Erfordernisse Gefahrstoffe enthalten. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständige Vertriebsgesellschaft einzuholen.

**Published by EPCOS AG****Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY****☎ ++49 89 636 09, FAX (0 89) 636-2 26 89**

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.