


Fast Switching EmCon Diode

Features:

- 600 V EmCon technology
- Fast recovery
- Soft switching
- Low reverse recovery charge
- Low forward voltage
- 175 °C junction operating temperature
- Easy paralleling
- Pb-free lead plating; RoHS compliant
- Complete product spectrum and PSpice Models:
<http://www.infineon.com/emcon/>



Applications:

- Welding
- Motor drives

Type	V_{RRM}	I_F	$V_{F, T_J=25^\circ C}$	$T_{j,max}$	Marking	Package
IDW100E60	600V	100A	1.65V	175°C	D100E60	PG-TO-247-3

Maximum Ratings

Parameter	Symbol	Value	Unit
Repetitive peak reverse voltage	V_{RRM}	600	V
Continuous forward current	I_F		A
$T_C = 25^\circ C$		150	
$T_C = 90^\circ C$		104	
$T_C = 100^\circ C$		96	
Surge non repetitive forward current	I_{FSM}	400	A
$T_C = 25^\circ C, t_p = 10 \text{ ms, sine halfwave}$			
Maximum repetitive forward current	I_{FRM}	300	A
$T_C = 25^\circ C, t_p \text{ limited by } t_{j,max}, D = 0.5$			
Power dissipation	P_{tot}		W
$T_C = 25^\circ C$		375	
$T_C = 90^\circ C$		212	
$T_C = 100^\circ C$		198	
Operating junction and storage temperature	$T_{j, T_{stg}}$	-55...+175	°C
Soldering temperature 1.6mm (0.063 in.) from case for 10 s	T_S	260	°C

Thermal Resistance

Parameter	Symbol	Conditions	Max. Value	Unit
Characteristic				
Thermal resistance, junction – case	R_{thJC}		0.40	K/W
Thermal resistance, junction – ambient	R_{thJA}		40	

Electrical Characteristic, at $T_j = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	

Static Characteristic

Collector-emitter breakdown voltage	V_{RRM}	$I_R = 0.25\text{mA}$	600	-	-	V
Diode forward voltage	V_F	$I_F = 100\text{A}$ $T_j = 25^\circ\text{C}$ $T_j = 175^\circ\text{C}$	-	1.65	2.0	
Reverse leakage current	I_R	$V_R = 600\text{V}$ $T_j = 25^\circ\text{C}$ $T_j = 175^\circ\text{C}$	-	-	40	μA
			-	-	1000	

Dynamic Electrical Characteristics

Diode reverse recovery time	t_{rr}	$T_j = 25^\circ\text{C}$	-	120	-	ns
Diode reverse recovery charge	Q_{rr}	$V_R = 400\text{V}$,	-	3.6	-	μC
Diode peak reverse recovery current	I_{rr}	$I_F = 100\text{A}$,	-	49.5	-	A
Diode peak rate of fall of reverse recovery current during t_b	dl_{rr}/dt	$dl_F/dt = 1200\text{A}/\mu\text{s}$	-	750	-	$\text{A}/\mu\text{s}$

Diode reverse recovery time	t_{rr}	$T_j = 125^\circ\text{C}$	-	168	-	ns
Diode reverse recovery charge	Q_{rrm}	$V_R = 400\text{V}$,	-	5.8	-	μC
Diode peak reverse recovery current	I_{rr}	$I_F = 100\text{A}$,	-	61.6	-	A
Diode peak rate of fall of reverse recovery current during t_b	dl_{rr}/dt	$dl_F/dt = 1200\text{A}/\mu\text{s}$	-	705	-	$\text{A}/\mu\text{s}$

Diode reverse recovery time	t_{rr}	$T_j = 175^\circ\text{C}$	-	200	-	ns
Diode reverse recovery charge	Q_{rrm}	$V_R = 400\text{V}$,	-	7.8	-	μC
Diode peak reverse recovery current	I_{rr}	$I_F = 100\text{A}$,	-	67.0	-	A
Diode peak rate of fall of reverse recovery current during t_b	dl_{rr}/dt	$dl_F/dt = 1200\text{A}/\mu\text{s}$	-	650	-	$\text{A}/\mu\text{s}$




Figure 1. Power dissipation as a function of case temperature
($T_j \leq 175^\circ\text{C}$)




Figure 2. Diode forward current as a function of case temperature
($T_j \leq 175^\circ\text{C}$)




Figure 3. Typical diode forward current as a function of forward voltage






Figure 4. Typical diode forward voltage as a function of junction temperature




di_f/dt , DIODE CURRENT SLOPE

Figure 5. Typical reverse recovery time as a function of diode current slope
 ($V_R=400V$, $I_F=100A$,
 Dynamic test circuit in Figure E)




di_f/dt , DIODE CURRENT SLOPE

Figure 6. Typical reverse recovery charge as a function of diode current slope
 ($V_R = 400V$, $I_F = 100A$,
 Dynamic test circuit in Figure E)



di_f/dt , DIODE CURRENT SLOPE

Figure 7. Typical reverse recovery current as a function of diode current slope
 ($V_R = 400V$, $I_F = 100A$,
 Dynamic test circuit in Figure E)



di_f/dt , DIODE CURRENT SLOPE

Figure 8. Typical diode peak rate of fall of reverse recovery current as a function of diode current slope
 ($V_R=400V$, $I_F=100A$,
 Dynamic test circuit in Figure E)





Figure 9. Diode transient thermal impedance as a function of pulse width
 ($D=t_p/T$)

T0247-3



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.83	5.21	0.190	0.205
A1	2.27	2.54	0.089	0.100
A2	1.85	2.16	0.073	0.085
b	1.07	1.33	0.042	0.052
b1	1.90	2.41	0.075	0.095
b2	1.90	2.16	0.075	0.085
b3	2.87	3.38	0.113	0.133
b4	2.87	3.13	0.113	0.123
c	0.55	0.68	0.022	0.027
D	20.80	21.10	0.819	0.831
D1	16.25	17.65	0.640	0.695
D2	0.95	1.35	0.037	0.053
E	15.70	16.13	0.618	0.635
E1	13.10	14.15	0.516	0.557
E2	3.68	5.10	0.145	0.201
E3	1.00	2.60	0.039	0.102
e	5.44		0.214	
N	3		3	
L	19.80	20.32	0.780	0.800
L1	4.10	4.47	0.161	0.176
ϕP	3.50	3.70	0.138	0.146
Q	5.49	6.00	0.216	0.236
S	6.04	6.30	0.238	0.248

DOCUMENT NO.
Z8B00003327

SCALE

EUROPEAN PROJECTION

ISSUE DATE
01-10-2009

REVISION
04

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2008 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.