



Quality Products. Service Excellence.

20 Amp Horizontal Rackmount Outlet Strip 1589-RF-RR Series

Front or Rear Mounted Receptacles

Features

- Designed for power distribution from front or rear of the unit.
- 1U horizontal 19" rackmount installation.
- Available with on/off switch or red pilot light to indicate power on.
- Available in black powder coat finish.



Specifications

- Heavy duty 12 gauge wire cord - 12/3 SJT type for extreme temperature ranges and integral molded plug.
- Heavy-duty black receptacles rated for 20A, 125VAC service (NEMA 5-20R, Single T-Slot).
- Plug types available are NEMA 5-20P straight blade or NEMA L5-20P locking type.
- Includes 20 Amp, 125 VAC circuit breaker to prevent accidental overload.
- CSA certified, Standards C22.2 (No. 21-95 and No. 42-99)
- UL/cUL recognized Standard UL1363 file No. E166039 & CSA C22.2 No. 308-14



Accessories

- Mounting Hardware
- Rail Depth Adapter Kit



| On/Off Switch Part No. | Illuminated Light Only Part No. | Overall Dimensions | | | Number of Outlets | | NEMA Type | | Plug Blade Type | Cord Length | Rack Units |
|---------------------------|---------------------------------------|--------------------|-------|-------|-------------------|------|-----------|--------|-----------------------|----------------|---------------|
| | | Height | Width | Depth | Front | Rear | Outlet | Plug | | | |
| 1589H6C1BKRF | 1589T6C1BKRF | 1.72 | 19.00 | 2.66 | 6 | 0 | 5-20R | L5-20P | Locking | 6 ft | 1U |
| 1589H6D1BKRF | 1589T6D1BKRF | 1.72 | 19.00 | 2.66 | 6 | 0 | 5-20R | L5-20P | Locking | 15 ft | 1U |
| 1589H6F1BKRF | 1589T6F1BKRF | 1.72 | 19.00 | 2.66 | 6 | 0 | 5-20R | 5-20P | Straight | 6 ft | 1U |
| 1589H6G1BKRF | 1589T6G1BKRF | 1.72 | 19.00 | 2.66 | 6 | 0 | 5-20R | 5-20P | Straight | 15 ft | 1U |
| 1589H8C1BKRF | 1589T8C1BKRF | 1.72 | 19.00 | 2.66 | 8 | 0 | 5-20R | L5-20P | Locking | 6 ft | 1U |
| 1589H8D1BKRF | 1589T8D1BKRF | 1.72 | 19.00 | 2.66 | 8 | 0 | 5-20R | L5-20P | Locking | 15 ft | 1U |
| 1589H8F1BKRF | 1589T8F1BKRF | 1.72 | 19.00 | 2.66 | 8 | 0 | 5-20R | 5-20P | Straight | 6 ft | 1U |

| On/Off Switch Part No. | Illuminated Light Only Part No. | Overall Dimensions | | | Number of Outlets | | NEMA Type | | Plug Blade Type | Cord Length | Rack Units |
|---------------------------|---------------------------------------|--------------------|-------|-------|-------------------|------|-----------|--------|-----------------------|----------------|---------------|
| | | Height | Width | Depth | Front | Rear | Outlet | Plug | | | |
| 1589H8G1BKRF | 1589T8G1BKRF | 1.72 | 19.00 | 2.66 | 8 | 0 | 5-20R | 5-20P | Straight | 15 ft | 1U |
| 1589H6C1BKRR | 1589T6C1BKRR | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-20R | L5-20P | Locking | 6 ft | 1U |
| 1589H6D1BKRR | 1589T6D1BKRR | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-20R | L5-20P | Locking | 15 ft | 1U |
| 1589H6F1BKRR | 1589T6F1BKRR | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-20R | 5-20P | Straight | 6 ft | 1U |
| 1589H6G1BKRR | 1589T6G1BKRR | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-20R | 5-20P | Straight | 15 ft | 1U |
| 1589H8C1BKRR | 1589T8C1BKRR | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-20R | L5-20P | Locking | 6 ft | 1U |
| 1589H8D1BKRR | 1589T8D1BKRR | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-20R | L5-20P | Locking | 15 ft | 1U |
| 1589H8F1BKRR | 1589T8F1BKRR | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-20R | 5-20P | Straight | 6 ft | 1U |
| 1589H8G1BKRR | 1589T8G1BKRR | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-20R | 5-20P | Straight | 15 ft | 1U |

Data subject to change without notice

© 2020. Hammond Manufacturing Ltd. All rights reserved.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.