

For more Information  
please call

1-800-Belden1



### General Description:

30 AWG stranded (7x38) .012" tinned copper conductor, foam HDPE insulation, tinned copper braid shield (90% coverage), PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

AWG:

| # Coax | AWG | Stranding | Conductor Material | Dia. (mm) |
|--------|-----|-----------|--------------------|-----------|
| 1      | 30  | 7x38      | TC - Tinned Copper | 0.3048    |

Total Number of Conductors: 1

#### Insulation

Insulation Material:

| Insulation Material                    | Dia. (mm) |
|--|-----------|
| FHDPE - Foam High Density Polyethylene | 1.4732    |

#### Outer Shield

Outer Shield Material:

| Type  | Outer Shield Material | Coverage (%) |
|-------|-----------------------|--------------|
| Braid | TC - Tinned Copper    | 90.000       |

#### Outer Jacket

Outer Jacket Material:

| Outer Jacket Material    |
|--------------------------|
| PVC - Polyvinyl Chloride |

#### Overall Cable

Overall Nominal Diameter: 2.464 mm

### Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +60°C

UL Temperature Rating: 60°C (UL AWM Style 1375)

Bulk Cable Weight: 8.929 Kg/Km

Max. Recommended Pulling Tension: 62.275 N

Min. Bend Radius/Minor Axis: 6.350 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

AWM Specification: UL Style 1375 (30 V 60°C)

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MIL Order #39 (China RoHS): Yes

#### Suitability

Suitability - Indoor: Yes

Suitability - Outdoor: Yes

**Plenum/Non-Plenum**

Plenum (Y/N): No

**Electrical Characteristics (Overall)**

**Nom. Characteristic Impedance:**

**Impedance (Ohm)**  
75

**Nom. Inductance:**

**Inductance (µH/m)**  
0.318257

**Nom. Capacitance Conductor to Shield:**

**Capacitance (pF/m)**  
56.7613

**Nominal Velocity of Propagation:**

**VP (%)**  
78

**Nominal Delay:**

**Delay (ns/m)**  
4.2653

**Nom. Conductor DC Resistance:**

**DCR @ 20°C (Ohm/km)**  
328.1

**Nominal Outer Shield DC Resistance:**

**DCR @ 20°C (Ohm/km)**  
38.2236

**Nom. Attenuation:**

| Freq. (MHz) | Attenuation (dB/100m) |
|-------------|-----------------------|
| 1           | 2.2967                |
| 3.6         | 4.2653                |
| 5           | 5.2496                |
| 7           | 6.2339                |
| 9           | 6.8901                |
| 10          | 7.2182                |
| 50          | 16.7331               |
| 70          | 20.0141               |
| 100         | 23.9513               |
| 200         | 34.4505               |
| 400         | 50.8555               |
| 700         | 70.5415               |
| 900         | 81.3688               |
| 1000        | 87.2746               |

**Max. Operating Voltage - UL:**

**Voltage**  
30 V RMS (UL AWM Style 1375)

**Put Ups and Colors:**

| Item #       | Putup  | Ship Weight | Color | Notes | Item Desc             |
|--------------|--------|-------------|-------|-------|-----------------------|
| 9221 010U500 | 500 FT | 4.000 LB    | BLACK |       | 75 OHM MINIATURE COAX |
| 9221 010100  | 100 FT | 1.400 LB    | BLACK |       | 75 OHM MINIATURE COAX |
| 9221 010500  | 500 FT | 4.000 LB    | BLACK |       | 75 OHM MINIATURE COAX |

Revision Number: 1    Revision Date: 10-04-2012

© 2015 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.