


Dual 1 Form A Solid-State Relay



DESCRIPTION

The LH1520 dual 1 form A relays are SPST normally open switches that can replace electromechanical relays in many applications. They are constructed using a GaAlAs LED for actuation control and an integrated monolithic die for the switch output. The die, fabricated in a high-voltage dielectrically isolated technology is comprised of a photodiode array, switch control circuitry, and MOSFET switches. In addition, the LH1520 SSRs employ current limiting circuitry, enabling them to pass lightning surge testing as per ANSI/TIA-968-B and other regulatory surge requirements when overvoltage protection is provided.

FEATURES

- Dual channel (LH1500)
- Current limit protection
- Isolation test voltage 5300 V_{RMS}
- Typical R_{ON} 20 Ω
- Load voltage 350 V
- Load current 150 mA
- High surge capability
- Clean bounce free switching
- Low power consumption
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC



RoHS
COMPLIANT

APPLICATIONS

- General telecom switching
 - On/off hook control
 - Ring delay
 - Dial pulse
 - Ground start
 - Ground fault protection
- Instrumentation
- Industrial controls

AGENCY APPROVALS

- UL1577: file no. E52744 system code H, double protection
- CSA: certification no. 093751
- BSI/BABT: certification no. 7980
- DIN EN: 60747-5-2 (VDE 0884)/60747-5-5 (pending), available with option 1
- FIMKO: approval

| ORDERING INFORMATION | | | | | | | | | | | | |
|----------------------|---|---|---|---|---|----------------------------|--------------------|---|------------------|---|--|--|
| L | H | 1 | 5 | 2 | 0 | A | # | # | T | R | | |
| PART NUMBER | | | | | | ELECTR. VARIATION | PACKAGE CONFIG. | | TAPE AND REEL | | | |
| PACKAGE | | | | | | UL, CSA, BSI, FIMKO | | | | | | |
| SMD-8, tubes | | | | | | LH1520AAC | | | | | | |
| SMD-8, tape and reel | | | | | | LH1520AACTR | | | | | | |
| DIP-8, tubes | | | | | | LH1520AB | | | | | | |



| ABSOLUTE MAXIMUM RATINGS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | |
|--|--|------------|---------------|--------------------|
| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
| INPUT | | | | |
| LED continuous forward current | | I_F | 50 | mA |
| LED reverse voltage | $I_R \leq 10\text{ }\mu\text{A}$ | V_R | 8 | V |
| OUTPUT | | | | |
| DC or peak AC load voltage | $I_L \leq 50\text{ }\mu\text{A}$ | V_L | 350 | V |
| Continuous DC load current, one pole operating | | I_L | 150 | mA |
| Continuous DC load current, two poles operating | | I_L | 110 | mA |
| Peak load current (single shot), form B | $t = 100\text{ ms}$ | I_P | (2) | |
| SSR | | | | |
| Ambient temperature range | | T_{amb} | - 40 to + 85 | $^{\circ}\text{C}$ |
| Storage temperature range | | T_{stg} | - 40 to + 150 | $^{\circ}\text{C}$ |
| Pin soldering temperature (3) | $t = 10\text{ s max.}$ | T_{sld} | 260 | $^{\circ}\text{C}$ |
| Input to output isolation test voltage | $t = 1\text{ s}, I_{ISO} = 10\text{ }\mu\text{A max.}$ | V_{ISO} | 5300 | V_{RMS} |
| Pole-to-pole isolation voltage (S1 to S2) (1) (dry air, dust free, at sea level) | | | 1600 | V |
| Output power dissipation (continuous) | | P_{diss} | 600 | mW |

Notes

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.
- Breakdown occurs between the output pins external to the package.
- Refer to current limit performance application note for a discussion on relay operation during transient currents.
- Refer to reflow profile for soldering conditions for surface mounted devices (SMD). Refer to wave profile for soldering conditions for through hole devices (DIP).

| ELECTRICAL CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | | |
|--|--|------------|------|------|------|---------------|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| INPUT | | | | | | |
| LED forward current, switch turn-on | $I_L = 100\text{ mA}, t = 10\text{ ms}$ | I_{Fon} | | 1 | 2 | mA |
| LED forward current, switch turn-off | $V_L = \pm 300\text{ V}$ | I_{Foff} | 0.2 | 1.1 | | mA |
| LED forward voltage | $I_F = 10\text{ mA}$ | V_F | 1.15 | 1.26 | 1.45 | V |
| OUTPUT | | | | | | |
| On-resistance | $I_F = 5\text{ mA}, I_L = 50\text{ mA}$ | R_{ON} | 12 | 20 | 25 | Ω |
| Off-resistance | $I_F = 0\text{ mA}, V_L = \pm 100\text{ V}$ | R_{OFF} | 0.5 | 300 | | $G\Omega$ |
| Current limit | $I_F = 5\text{ mA}, t = 5\text{ ms}, V_L = \pm 6\text{ V}$ | I_{LMT} | 230 | 270 | 370 | mA |
| Off-state leakage current | $I_F = 0\text{ mA}, V_L = \pm 100\text{ V}$ | I_O | | 0.32 | 200 | nA |
| | $I_F = 0\text{ mA}, V_L = \pm 350\text{ V}$ | I_O | | | 1 | μA |
| Output capacitance | $I_F = 0\text{ mA}, V_L = 1\text{ V}$ | C_O | | 55 | | pF |
| | $I_F = 0\text{ mA}, V_L = 50\text{ V}$ | C_O | | 10 | | pF |
| Pole-to-pole capacitance (S1 to S2) | $I_F = 5\text{ mA}$ | | | 0.5 | | pF |
| Switch offset | $I_F = 5\text{ mA}$ | V_{OS} | | 0.15 | | μV |
| TRANSFER | | | | | | |
| Capacitance (input to output) | $V_{ISO} = 1\text{ V}$ | C_{IO} | | 1.1 | | pF |

Note

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluations. Typical values are for information only and are not part of the testing requirements.

| SWITCHING CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | | |
|---|---|-----------|------|------|------|------|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Turn-on time | $I_F = 5\text{ mA}, I_L = 50\text{ mA}$ | t_{on} | | 1.4 | 2 | ms |
| Turn-off time | $I_F = 5\text{ mA}, I_L = 50\text{ mA}$ | t_{off} | | 0.7 | 2 | ms |



TYPICAL CHARACTERISTICS (T_{amb} = 25 °C, unless otherwise specified)




Fig. 1 - Recommended Operating Conditions




Fig. 4 - LED Reverse Current vs. LED Reverse Voltage




Fig. 2 - LED Voltage vs. Temperature




Fig. 5 - LED Current for Switch Turn-on vs. Temperature




Fig. 3 - LED Forward Current vs. LED Forward Voltage




Fig. 6 - LED Dropout Voltage vs. Temperature




Fig. 7 - Current Limit vs. Temperature




Fig. 10 - Variation in On-resistance vs. LED Current




Fig. 8 - Load Current vs. Load Voltage




Fig. 11 - Switch Capacitance vs. Applied Voltage




Fig. 9 - On-Resistance vs. Temperature






Fig. 12 - Insertion Loss vs. Frequency




ilh1520ab_12

Fig. 13 - Leakage Current vs. Applied Voltage




ilh1520ab_15

Fig. 16 - Switch Breakdown Voltage vs. Temperature




ilh1520ab_13

Fig. 14 - Output Isolation




ilh1520ab_16

Fig. 17 - Switch Offset Voltage vs. Temperature



ilh1520ab_14

Fig. 15 - Switch Breakdown Voltage vs. Load Current



ilh1520ab_17

Fig. 18 - Switch Offset Voltage vs. LED Current




Fig. 19 - Turn-on Time vs. Temperature




Fig. 21 - Turn-on Time vs. LED Current




Fig. 20 - Turn-off Time vs. Temperature









Fig. 22 - Turn-off Time vs. LED Current

PACKAGE DIMENSIONS in millimeters


DIP



i178008



PACKAGE MARKING (example)



Note

- Tape and reel suffix (TR) is not part of the package marking.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.