



LOC	DIST	REVISIONS					
GP	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
			A	PRODUCTION RELEASE	05 JUN 2019	JW	SH




1. MATERIALS:
CAGE ASSEMBLY - NICKEL-SILVER ALLOY PER ASTM B 122
CONNECTOR HOUSING - LCP, BLACK, UL 94V-O RATED
CHICKLET - LCP, BLACK, UL 94V-O RATED
CHICKLET ALIGNMENT CLIP - LCP, BLACK, UL 94V-O RATED
CONTACT - COPPER ALLOY
EMI GASKET - ELASTOMERIC
GASKET FLANGE - STAINLESS STEEL
EMI SPRINGS - PHOSPHOR BRONZE PER ASTM B 103,
0.8µm MIN TIN PER ASTM B 545
LIGHT PIPE - POLYCARBONATE
LIGHT PIPE PLATE- STAINLESS STEEL
2. CONTACT FINISH:
CONFORMS TO THE REQUIREMENTS OF PRODUCT SPECIFICATION 108-2481, BASED ON EIA/ECA-364-1000.01A, (CONTROLLED ENVIRONMENT APPLICATIONS) ON MATING INTERFACE, TIN ON NEEDLE EYE
3. PCB MINIMUM THICKNESS = 1.5mm

4. FOR HOLE SIZE AND PLATINGS, SEE APPLICATION SPECIFICATION 114-13319
5. LIGHT PIPE PAD LAYOUT IS FOR 0805 LOW PROFILE LED PACKAGE WITH A HEIGHT OF 0.8mm
6. DIMENSIONS APPLY FOR EMI SPRINGS ONLY
7. THE ENTIRE AREA OF THE CONNECTOR FOOTPRINT, INDICATED BY THE DASHED LINE, TO BE CONSIDERED THE KEEPOUT AREA FOR COMPONENTS AND SIGNAL TRACES, TOP SIDE ONLY, TOP SIDE TRACES ALLOWED WITHIN CONNECTOR HOLE PATTERN

2347721-1
SCALE 3:1




2347721-5
SCALE 3:1




REVERSED INNER LIGHT PIPES
2-2347721-1, 1-2347721-3
SCALE 4:1


88	EMI SPRING AIRFLOW ENHANCE TYPE	NONE	3-2347721-1
90.75	EMI GASKET AIRFLOW ENHANCE TYPE	NONE	3-2347721-0
88	EMI SPRINGS	REVERSED INNER	2-2347721-1
		REVERSED OUTER	2-2347721-0
		CENTER/REVERSED OUTER	1-2347721-9
90.75	EMI GASKET	REVERSED OUTER	1-2347721-8
		CENTER/REVERSED OUTER	1-2347721-7
88	EMI SPRINGS WITH NICKEL PLATING ONLY	REVERSED INNER	1-2347721-3
		OUTER	1-2347721-2
		INNER	1-2347721-1
		INNER/OUTER	1-2347721-0
88	EMI SPRINGS	NONE	2347721-9
		OUTER	2347721-8
		INNER	2347721-7
		INNER/OUTER	2347721-6
90.75	EMI GASKET	NONE	2347721-5
		OUTER	2347721-4
		INNER	2347721-3
		INNER/OUTER	2347721-2
		NONE	2347721-1
(E)	CAGE TYPE	LIGHT PIPE CONFIGURATION	PART NUMBER




INNER/OUTER LIGHT PIPES
2347721-2, 2347721-6
SCALE 4:1




INNER LIGHT PIPES
2347721-3, 2347721-7
SCALE 4:1



OUTER LIGHT PIPES
2347721-4, 2347721-8
SCALE 4:1



CENTER/REVERSED OUTER
1-2347721-7, 1-2347721-9
SCALE 4:1




REVERSED OUTER
1-2347721-8, 2-2347721-0
SCALE 4:1


THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. WANG 26FEB2019	TE Connectivity	
DIMENSIONS:		CHK S. HAN 26FEB2019		
mm		APVD S. HAN 26FEB2019	NAME RECEPTACLE ASSEMBLY, 2X6, STACKED, SFP56	
		PRODUCT SPEC	SIZE CAGE CODE DRAWING NO	
		108-2481		
		APPLICATION SPEC	RESTRICTED TO	
		114-13319		
MATERIAL SEE NOTES		WEIGHT	A100779C=2347721	
		CUSTOMER DRAWING	SCALE 4:1 SHEET 1 OF 6 REV A	

LOC		DIST		REVISIONS						
GP		00		P	LTR	DESCRIPTION	DATE	DWN	APVD	
				-	-	SEE SHEET 1	-	-	-	


AIRFOLW ENHANCE TYPE



AIR VENTS




AIR VENTS



AIR VENTS

3-2347721-0
EMI GASKET TYPE





AIR VENTS



3-2347721-1
EMI SPRING TYPE


THIS DRAWING IS A CONTROLLED DOCUMENT.				DWN	J. WANG	26FEB2019	 TE Connectivity																
				CHK	S. HAN	26FEB2019																	
				APVD	S. HAN	26FEB2019																	
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME		RECEPTACLE ASSEMBLY, 2X6, STACKED, SFP56																	
mm				PRODUCT SPEC		-																	
		0 PLC ±0.25		108-2481		SIZE																	
		1 PLC ±0.25		APPLICATION SPEC								CAGE CODE											
		2 PLC ±0.25		114-13319														DRAWING NO					
		3 PLC ±0.25																					
4 PLC ±0.25				A1																			
ANGLES ±°										00779													
																C=2347721							
																						SCALE	
				1:1																			
										SHEET													
																2							
																						OF	
				6																			
										REV													
																A							

LOC	DIST	REVISIONS					
GP	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-







2347721-5 THRU 1-2347721-2, 1-2347721-9, 2-2347721-0, 2-2347721-1
EMI SPRINGS ONLY
SCALE 4:1





THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. WANG 26FEB2019	 TE Connectivity	
		CHK S. HAN 26FEB2019		
DIMENSIONS:		APVD S. HAN 26FEB2019	NAME RECEPTACLE ASSEMBLY, 2X6, STACKED, SFP56	
mm		PRODUCT SPEC 108-2481		
		APPLICATION SPEC 114-13319	SIZE A100779C=2347721	
		ANGLES FINISH SEE NOTES		
MATERIAL SEE NOTES		WEIGHT -	CUSTOMER DRAWING	
		SCALE 1:1		
		SHEET 3 OF 6	REV A	

LOC		DIST		REVISIONS					
GP	00	P	LTR	DESCRIPTION	DATE	DWN	APVD		
		-		SEE SHEET 1	-	-	-		






DETAIL A
6X INDIVIDUALLY
SCALE 10:1

THIS DRAWING IS A CONTROLLED DOCUMENT.				DWN	J. WANG	26FEB2019	 TE Connectivity	
DIMENSIONS:				CHK	S. HAN	26FEB2019		
mm				APVD	S. HAN	26FEB2019	NAME	
				TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		
				0 PLC		±0.25		
				1 PLC		±0.25		
				2 PLC		±0.25		
MATERIAL				3 PLC		±0.25		
				4 PLC		±0.25		
SEE NOTES				ANGLES		±°		
				FINISH		±°		
SEE NOTES				APPLICATION SPEC		108-2481		
				CUSTOMER DRAWING		114-13319		
SCALE				WEIGHT		-		
				RESTRICTED TO		-		
SHEET				SIZE		A1		
				CAGE CODE		100779		
OF				DRAWING NO		2347721		
				REV		A		




LOC		DIST		REVISIONS			
GP		P	LTR	DESCRIPTION	DATE	DWN	APVD
		-		SEE SHEET 1	-	-	-




RECOMMENDED PCB LAYOUT
SCALE 5:1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. WANG 26FEB2019	TE Connectivity	
DIMENSIONS: mm		CHK S. HAN 26FEB2019		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD S. HAN 26FEB2019	NAME RECEPTACLE ASSEMBLY, 2X6, STACKED, SFP56	
0 PLC ±0.25 1 PLC ±0.25 2 PLC ±0.25 3 PLC ±0.25 4 PLC ±0.25 ANGLES ±° FINISH ±°		PRODUCT SPEC 108-2481 APPLICATION SPEC 114-13319 WEIGHT -	SIZE A1	
MATERIAL SEE NOTES		CAGE CODE 00779	DRAWING NO. C=2347721	
		CUSTOMER DRAWING	RESTRICTED TO -	
		SCALE 4:1	SHEET 5 OF 6	
			REV A	

LOC		DIST		REVISONS			
GP	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-




DETAIL C
RECOMMENDED PIN AND LIGHT PIPE LAYOUT
SCALE 15:1




DETAIL D
PIN MAP
6 PLACES
SCALE 20:1

PIN MAP LEGEND	
PIN NUMBER	FUNCTION
L1/T1	VEET
L2/T2	TX-FAULT
L3/T3	TX-DISABLE
L4/T4	SDA
L5/T5	SCL
L6/T6	MOD_ABS
L7/T7	RSO
L8/T8	RX_LOS
L9/T9	RS1
L10/T10	VEER
L11/T11	VEER
L12/T12	RD-
L13/T13	RD+
L14/T14	VEER
L15/T15	VCCR
L16/T16	VCCT
L17/T17	VEET
L18/T18	TD+
L19/T19	TD-
L20/T20	VEET



RECOMMENDED BEZEL CUT-OUT DETAIL
SCALE 5:2



RECOMMENDED BEZEL LOCATION WITH EMI GASKET
SCALE 5:2

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. WANG 26FEB2019	 TE Connectivity		
DIMENSIONS:		CHK S. HAN 26FEB2019			
mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD S. HAN 26FEB2019	NAME	RECEPTACLE ASSEMBLY, 2X6, STACKED, SFP56	
		PRODUCT SPEC	-		
	0 PLC ±0.25 1 PLC ±0.25 2 PLC ±0.25 3 PLC ±0.25 4 PLC ±0.25 ANGLES ±°	APPLICATION SPEC	SIZE		
		114-13319	CAGE CODE DRAWING NO		
MATERIAL	FINISH	WEIGHT	A100779	C=2347721	RESTRICTED TO
SEE NOTES	SEE NOTES	-	-		-
CUSTOMER DRAWING		SCALE	4:1	SHEET 6 OF 6	REV A



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.