

# MC74VHC257

## Quad 2-Channel Multiplexer with 3-State Outputs

The MC74VHC257 is an advanced high speed CMOS quad 2-channel multiplexer fabricated with silicon gate CMOS technology. It achieves high speed operation similar to equivalent Bipolar Schottky TTL while maintaining CMOS low power dissipation.

It consists of four 2-input digital multiplexers with common select (S) and enable ( $\overline{OE}$ ) inputs. When ( $\overline{OE}$ ) is held High, selection of data is inhibited and all the outputs go Low.

The select decoding determines whether the A or B inputs get routed to the corresponding Y outputs.

The inputs tolerate voltages up to 7 V, allowing the interface of 5 V systems to 3 V systems.

- High Speed:  $t_{PD} = 4.1 \text{ ns (Typ)}$  at  $V_{CC} = 5.0 \text{ V}$
- Low Power Dissipation:  $I_{CC} = 4.0 \mu\text{A (Max)}$  at  $T_A = 25^\circ\text{C}$
- High Noise Immunity:  $V_{NIH} = V_{NIL} = 28\% V_{CC}$
- Power Down Protection Provided on Inputs
- Balanced Propagation Delays
- Designed for 2.0 V to 5.5 V Operating Range
- Low Noise:  $V_{OLP} = 0.8 \text{ V (Max)}$
- Pin and Function Compatible with Other Standard Logic Families
- Latchup Performance Exceeds 300 mA
- ESD Performance: HBM > 2000 V; Machine Model > 200 V
- Chip Complexity: FETs = 100; Equivalent Gates = 25
- These Devices are Pb-Free and are RoHS Compliant




Figure 1. Pin Assignment




ON Semiconductor™

<http://onsemi.com>



### MARKING DIAGRAMS




SO-16  
D SUFFIX  
CASE 751B



TSSOP-16  
DT SUFFIX  
CASE 948F



EIAJ SO-16  
M SUFFIX  
CASE 966



A = Assembly Location  
L, WL = Wafer Lot  
Y, YY = Year  
W, WW = Work Week  
G or ■ = Pb-Free Package

### ORDERING INFORMATION

| Device          | Package    | Shipping        |
|-----------------|------------|-----------------|
| MC74VHC257DG    | SO-16      | 48 Units/Rail   |
| MC74VHC257DR2G  | SO-16      | 2500 Units/Reel |
| MC74VHC257DTG   | TSSOP-16   | 96 Units/Rail   |
| MC74VHC257DTR2G | TSSOP-16   | 2500 Units/Reel |
| MC74VHC257MG    | EIAJ SO-16 | 50 Units/Rail   |

MC74VHC257




Figure 2. Expanded Logic Diagram




Figure 3. IEC Logic Symbol

FUNCTION TABLE

| Inputs          |     | Outputs<br>$Y0 - Y3$ |
|-----------------|-----|----------------------|
| $\overline{OE}$ | $S$ |                      |
| H               | X   | $Z$                  |
| L               | L   | $A0 - A3$            |
| L               | H   | $B0 - B3$            |

$A0 - A3$ ,  $B0 - B3$  = the levels of the respective Data-Word Inputs.

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high-impedance circuit. For proper operation,  $V_{in}$  and  $V_{out}$  should be constrained to the range  $GND \leq (V_{in} \text{ or } V_{out}) \leq V_{CC}$ . Unused inputs must always be tied to an appropriate logic voltage level (e.g., either GND or  $V_{CC}$ ). Unused outputs must be left open.

# MC74VHC257

## MAXIMUM RATINGS

| Symbol               | Parameter                                                                                                                  | Value                        | Unit |
|----------------------|----------------------------------------------------------------------------------------------------------------------------|------------------------------|------|
| V <sub>CC</sub>      | Positive DC Supply Voltage                                                                                                 | –0.5 to +7.0                 | V    |
| V <sub>IN</sub>      | Digital Input Voltage                                                                                                      | –0.5 to +7.0                 | V    |
| V <sub>OUT</sub>     | DC Output Voltage                                                                                                          | –0.5 to V <sub>CC</sub> +0.5 | V    |
| I <sub>IK</sub>      | Input Diode Current                                                                                                        | –20                          | mA   |
| I <sub>OK</sub>      | Output Diode Current                                                                                                       | ± 20                         | mA   |
| I <sub>OUT</sub>     | DC Output Current, per Pin                                                                                                 | ± 25                         | mA   |
| I <sub>CC</sub>      | DC Supply Current, V <sub>CC</sub> and GND Pins                                                                            | ± 75                         | mA   |
| P <sub>D</sub>       | Power Dissipation in Still Air<br><div>SOIC Package<br/>TSSOP</div>                                                        | 200<br>180                   | mW   |
| T <sub>STG</sub>     | Storage Temperature Range                                                                                                  | –65 to +150                  | °C   |
| V <sub>ESD</sub>     | ESD Withstand Voltage<br><div>Human Body Model (Note 1)<br/>Machine Model (Note 2)<br/>Charged Device Model (Note 3)</div> | >2000<br>>200<br>>2000       | V    |
| I <sub>LATCHUP</sub> | Latchup Performance<br>Above V <sub>CC</sub> and Below GND at 125°C (Note 4)                                               | ± 300                        | mA   |
| θ <sub>JA</sub>      | Thermal Resistance, Junction–to–Ambient<br><div>SOIC Package<br/>TSSOP</div>                                               | 143<br>164                   | °C/W |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1 Tested to EIA/JESD22–A114–A

2 Tested to EIA/JESD22–A115–A

3 Tested to JESD22–C101–A

4 Tested to EIA/JESD78

## RECOMMENDED OPERATING CONDITIONS

| Symbol                          | Characteristics                                | Min                                                                | Max             | Unit |
|---------------------------------|------------------------------------------------|--------------------------------------------------------------------|-----------------|------|
| V <sub>CC</sub>                 | DC Supply Voltage                              | 2.0                                                                | 5.5             | V    |
| V <sub>IN</sub>                 | DC Input Voltage                               | 0                                                                  | 5.5             | V    |
| V <sub>OUT</sub>                | DC Output Voltage                              | 0                                                                  | V <sub>CC</sub> | V    |
| T <sub>A</sub>                  | Operating Temperature Range, all Package Types | –55                                                                | 125             | °C   |
| t <sub>r</sub> , t <sub>f</sub> | Input Rise or Fall Time                        | V <sub>CC</sub> = 3.3 V ± 0.3 V<br>V <sub>CC</sub> = 5.0 V ± 0.5 V | 0<br>100<br>20  | ns/V |

## DEVICE JUNCTION TEMPERATURE VERSUS TIME TO 0.1% BOND FAILURES

| Junction Temperature °C | Time, Hours | Time, Years |
|-------------------------|-------------|-------------|
| 80                      | 1,032,200   | 117.8       |
| 90                      | 419,300     | 47.9        |
| 100                     | 178,700     | 20.4        |
| 110                     | 79,600      | 9.4         |
| 120                     | 37,000      | 4.2         |
| 130                     | 17,800      | 2.0         |
| 140                     | 8,900       | 1.0         |




Figure 4. Failure Rate vs. Time Junction Temperature

# MC74VHC257

## DC CHARACTERISTICS (Voltages Referenced to GND)

| Symbol          | Parameter                                      | Condition                                                                                                  | V <sub>CC</sub><br>(V) | T <sub>A</sub> = 25°C          |                   |                                | T <sub>A</sub> ≤ 85°C          |                                | -55°C ≤ T <sub>A</sub> ≤ 125°C |                                | Unit |
|-----------------|------------------------------------------------|------------------------------------------------------------------------------------------------------------|------------------------|--------------------------------|-------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|------|
|                 |                                                |                                                                                                            |                        | Min                            | Typ               | Max                            | Min                            | Max                            | Min                            | Max                            |      |
| V <sub>IH</sub> | Minimum High-Level Input Voltage               |                                                                                                            | 2.0<br>3.0 to 5.5      | 1.5<br>V <sub>CCX</sub><br>0.7 |                   |                                | 1.5<br>V <sub>CCX</sub><br>0.7 | 1.5<br>V <sub>CCX</sub><br>0.7 | 1.5<br>V <sub>CCX</sub><br>0.7 |                                | V    |
| V <sub>IL</sub> | Maximum Low-Level Input Voltage                |                                                                                                            | 2.0<br>3.0 to 5.5      |                                |                   | 0.5<br>V <sub>CCX</sub><br>0.3 |                                | 0.5<br>V <sub>CCX</sub><br>0.3 |                                | 0.5<br>V <sub>CCX</sub><br>0.3 | V    |
| V <sub>OH</sub> | Maximum High-Level Output Voltage              | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>OH</sub> = -50 μA                           | 2.0<br>3.0<br>4.5      | 1.9<br>2.9<br>4.4              | 2.0<br>3.0<br>4.5 |                                | 1.9<br>2.9<br>4.4              |                                | 1.9<br>2.9<br>4.4              |                                | V    |
|                 |                                                | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>OH</sub> = -4 mA<br>I <sub>OH</sub> = -8 mA | 3.0<br>4.5             | 2.58<br>3.94                   |                   |                                | 2.48<br>3.8                    |                                | 2.34<br>3.66                   |                                |      |
| V <sub>OL</sub> | Maximum Low-Level Output Voltage               | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>OL</sub> = 50 μA                            | 2.0<br>3.0<br>4.5      |                                | 0.0<br>0.0<br>0.0 | 0.1<br>0.1<br>0.1              |                                | 0.1<br>0.1<br>0.1              |                                | 0.1<br>0.1<br>0.1              | V    |
|                 |                                                | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>OH</sub> = 4 mA<br>I <sub>OH</sub> = 8 mA   | 3.0<br>4.5             |                                |                   | 0.36<br>0.36                   |                                | 0.44<br>0.44                   |                                | 0.52<br>0.52                   |      |
| I <sub>IN</sub> | Input Leakage Current                          | V <sub>IN</sub> = 5.5 V or GND                                                                             | 0 to 5.5               |                                |                   | ±0.1                           |                                | ±1.0                           |                                | ±1.0                           | μA   |
| I <sub>OZ</sub> | Maximum 3-State Leakage Current                | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>V <sub>OUT</sub> = V <sub>CC</sub> or GND          | 5.5                    |                                |                   | ±0.25                          |                                | ±2.5                           |                                | ±2.5                           | μA   |
| I <sub>CC</sub> | Maximum Quiescent Supply Current (per package) | V <sub>IN</sub> = V <sub>CC</sub> or GND                                                                   | 5.5                    |                                |                   | 4.0                            |                                | 40.0                           |                                | 40.0                           | μA   |

## AC ELECTRICAL CHARACTERISTICS (Input t<sub>r</sub> = t<sub>f</sub> = 3.0ns)

| Symbol                                 | Parameter                                | Test Conditions                                                                                      | T <sub>A</sub> = 25°C |            |              | T <sub>A</sub> ≤ 85°C |              | -55°C ≤ T <sub>A</sub> ≤ 125°C |              | Unit |
|----------------------------------------|------------------------------------------|------------------------------------------------------------------------------------------------------|-----------------------|------------|--------------|-----------------------|--------------|--------------------------------|--------------|------|
|                                        |                                          |                                                                                                      | Min                   | Typ        | Max          | Min                   | Max          | Min                            | Max          |      |
| t <sub>PLH</sub> ,<br>t <sub>PHL</sub> | Maximum Propagation Delay<br>A or B to Y | V <sub>CC</sub> = 3.3 ± 0.3 V C <sub>L</sub> = 15 pF<br>C <sub>L</sub> = 50 pF                       |                       | 5.8<br>8.3 | 9.3<br>12.8  | 1.0<br>1.0            | 11.0<br>14.5 | 1.0<br>1.0                     | 11.0<br>14.5 | ns   |
|                                        |                                          | V <sub>CC</sub> = 5.0 ± 0.5 V C <sub>L</sub> = 15 pF<br>C <sub>L</sub> = 50 pF                       |                       | 3.6<br>5.1 | 5.9<br>7.9   | 1.0<br>1.0            | 7.0<br>9.0   | 1.0<br>1.0                     | 7.0<br>9.0   |      |
| t <sub>PLH</sub> ,<br>t <sub>PHL</sub> | Maximum Propagation Delay<br>S to Y      | V <sub>CC</sub> = 3.3 ± 0.3 V C <sub>L</sub> = 15 pF<br>C <sub>L</sub> = 50 pF                       |                       | 7.0<br>9.5 | 11.0<br>14.5 | 1.0<br>1.0            | 13.0<br>16.5 | 1.0<br>1.0                     | 13.0<br>16.5 | ns   |
|                                        |                                          | V <sub>CC</sub> = 5.0 ± 0.5 V C <sub>L</sub> = 15 pF<br>C <sub>L</sub> = 50 pF                       |                       | 4.0<br>5.5 | 6.8<br>8.8   | 1.0<br>1.0            | 8.0<br>10.0  | 1.0<br>1.0                     | 8.0<br>10.0  |      |
| t <sub>PZL</sub> ,<br>t <sub>PZH</sub> | Maximum Output Enable Time<br>OE to Y    | V <sub>CC</sub> = 3.3 ± 0.3 V C <sub>L</sub> = 15 pF<br>R <sub>L</sub> = 1 kΩ C <sub>L</sub> = 50 pF |                       | 6.7<br>9.2 | 10.5<br>14.0 | 1.0<br>1.0            | 12.5<br>16.0 | 1.0<br>1.0                     | 12.5<br>16.0 | ns   |
|                                        |                                          | V <sub>CC</sub> = 5.0 ± 0.5 V C <sub>L</sub> = 15 pF<br>R <sub>L</sub> = 1 kΩ C <sub>L</sub> = 50 pF |                       | 3.6<br>5.1 | 6.8<br>8.8   | 1.0<br>1.0            | 8.0<br>10.0  | 1.0<br>1.0                     | 8.0<br>10.0  |      |
| t <sub>PLZ</sub> ,<br>t <sub>PHZ</sub> | Maximum Output Disable Time<br>OE to Y   | V <sub>CC</sub> = 3.3 ± 0.3 V C <sub>L</sub> = 50 pF<br>R <sub>L</sub> = 1 kΩ                        |                       | 12.0       | 15.0         | 1.0                   | 16.0         | 1.0                            | 17.5         | ns   |
|                                        |                                          | V <sub>CC</sub> = 5.0 ± 0.5 V C <sub>L</sub> = 50 pF<br>R <sub>L</sub> = 1 kΩ                        |                       | 5.7        | 13.0         | 1.0                   | 14.0         | 1.0                            | 15.0         |      |
| C <sub>IN</sub>                        | Maximum Input Capacitance                |                                                                                                      |                       | 4          | 10           |                       | 10           |                                | 10           | pF   |

| C <sub>PD</sub> | Power Dissipation Capacitance (Note 5) | Typical @ 25°C, V <sub>CC</sub> = 5.0V | pF |
|-----------------|----------------------------------------|----------------------------------------|----|
|                 |                                        | 20                                     |    |

5. C<sub>PD</sub> is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation: I<sub>CC(OPR)</sub> = C<sub>PD</sub> • V<sub>CC</sub> • f<sub>in</sub> + I<sub>CC</sub>. C<sub>PD</sub> is used to determine the no-load dynamic power consumption; P<sub>D</sub> = C<sub>PD</sub> • V<sub>CC</sub><sup>2</sup> • f<sub>in</sub> + I<sub>CC</sub> • V<sub>CC</sub>.

# MC74VHC257

**NOISE CHARACTERISTICS** (Input  $t_r = t_f = 3.0$  ns,  $C_L = 50$  pF,  $V_{CC} = 5.0$  V)

| Symbol    | Characteristic                           | $T_A = 25^\circ\text{C}$ |      | Unit |
|-----------|------------------------------------------|--------------------------|------|------|
|           |                                          | Typ                      | Max  |      |
| $V_{OLP}$ | Quiet Output Maximum Dynamic $V_{OL}$    | 0.3                      | 0.8  | V    |
| $V_{OLV}$ | Quiet Output Minimum Dynamic $V_{OL}$    | -0.3                     | -0.8 | V    |
| $V_{IHD}$ | Minimum High Level Dynamic Input Voltage |                          | 3.5  | V    |
| $V_{ILD}$ | Maximum Low Level Dynamic Input Voltage  |                          | 1.5  | V    |




Figure 5. Switching Waveform






Figure 6. Switching Waveform



\*Includes all probe and jig capacitance

Figure 7. Test Circuit



\*Includes all probe and jig capacitance

Figure 8. Test Circuit





Figure 9. Input Equivalent Circuit

# MC74VHC257

## PACKAGE DIMENSIONS

SOIC-16  
CASE 751B-05  
ISSUE K




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

| DIM | MILLIMETERS |       | INCHES    |       |
|-----|-------------|-------|-----------|-------|
|     | MIN         | MAX   | MIN       | MAX   |
| A   | 9.80        | 10.00 | 0.386     | 0.393 |
| B   | 3.80        | 4.00  | 0.150     | 0.157 |
| C   | 1.35        | 1.75  | 0.054     | 0.068 |
| D   | 0.35        | 0.49  | 0.014     | 0.019 |
| F   | 0.40        | 1.25  | 0.016     | 0.049 |
| G   | 1.27 BSC    |       | 0.050 BSC |       |
| J   | 0.19        | 0.25  | 0.008     | 0.009 |
| K   | 0.10        | 0.25  | 0.004     | 0.009 |
| M   | 0°          | 7°    | 0°        | 7°    |
| P   | 5.80        | 6.20  | 0.229     | 0.244 |
| R   | 0.25        | 0.50  | 0.010     | 0.019 |


## SOLDERING FOOTPRINT



# MC74VHC257

## PACKAGE DIMENSIONS


TSSOP-16  
CASE 948F-01  
ISSUE B



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  2. CONTROLLING DIMENSION: MILLIMETER.
  3. DIMENSION A DOES NOT INCLUDE MOLD FLASH. PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
  4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
  5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
  6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
  7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-.

|     | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
| DIM | MIN         | MAX  | MIN       | MAX   |
| A   | 4.90        | 5.10 | 0.193     | 0.200 |
| B   | 4.30        | 4.50 | 0.169     | 0.177 |
| C   | ---         | 1.20 | ---       | 0.047 |
| D   | 0.05        | 0.15 | 0.002     | 0.006 |
| F   | 0.50        | 0.75 | 0.020     | 0.030 |
| G   | 0.65 BSC    |      | 0.026 BSC |       |
| H   | 0.18        | 0.28 | 0.007     | 0.011 |
| J   | 0.09        | 0.20 | 0.004     | 0.008 |
| J1  | 0.09        | 0.16 | 0.004     | 0.006 |
| K   | 0.19        | 0.30 | 0.007     | 0.012 |
| K1  | 0.19        | 0.25 | 0.007     | 0.010 |
| L   | 6.40 BSC    |      | 0.252 BSC |       |
| M   | 0°          | 8°   | 0°        | 8°    |



## SOLDERING FOOTPRINT




# MC74VHC257

## PACKAGE DIMENSIONS


SOEIAJ-16  
CASE 966-01  
ISSUE A



DETAIL P



VIEW P



### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS AND ARE MEASURED AT THE PARTING LINE. MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
5. THE LEAD WIDTH DIMENSION (b) DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE LEAD WIDTH DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT. MINIMUM SPACE BETWEEN PROTRUSIONS AND ADJACENT LEAD TO BE 0.46 (0.018).

| DIM            | MILLIMETERS |       | INCHES    |       |
|----------------|-------------|-------|-----------|-------|
|                | MIN         | MAX   | MIN       | MAX   |
| A              | ---         | 2.05  | ---       | 0.081 |
| A <sub>1</sub> | 0.05        | 0.20  | 0.002     | 0.008 |
| b              | 0.35        | 0.50  | 0.014     | 0.020 |
| c              | 0.10        | 0.20  | 0.007     | 0.011 |
| D              | 9.90        | 10.50 | 0.390     | 0.413 |
| E              | 5.10        | 5.45  | 0.201     | 0.215 |
| e              | 1.27 BSC    |       | 0.050 BSC |       |
| H <sub>E</sub> | 7.40        | 8.20  | 0.291     | 0.323 |
| L              | 0.50        | 0.85  | 0.020     | 0.033 |
| L <sub>E</sub> | 1.10        | 1.50  | 0.043     | 0.059 |
| M              | 0°          | 10°   | 0°        | 10°   |
| Q <sub>1</sub> | 0.70        | 0.90  | 0.028     | 0.035 |
| Z              | ---         | 0.78  | ---       | 0.031 |

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada

Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910

Japan Customer Focus Center  
Phone: 81-3-5773-3850

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.