



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to NEX10®

Documents

Assembly instruction 89 B1

Material and plating

Connector parts

Center contact	Brass	Plating	Silver, 3-6 µm
Outer contact	Spring bronze		Silver, 3-6 µm
Body	Brass		White bronze(e.g. Optalloy®)
Dielectric	PTFE		
Gasket	Silicone		

Electrical data

Impedance	50 Ω
Frequency	DC to 20 GHz
Return loss	≥ 36 dB @ DC to 2 GHz ≥ 30 dB @ 2 to 3 GHz ≥ 26 dB @ 3 to 6 GHz
Insertion loss	≤ 0.05 x √ f [GHz] dB
Insulation resistance	≥ 5 GΩ
Center contact resistance	≤ 1.5 mΩ
Outer contact resistance	≤ 1.5 mΩ
Working voltage	500 V rms
RF-leakage	≥ 90 dB @ DC to 3 GHz ≥ 70 dB @ 3 to 6 GHz
Power handling	100 W @ 2.0 GHz and 85°C ambient temperature 50 W @ 2.0 GHz and 105°C ambient temperature
Intermodulation (3 rd order)	≥ 160 dBc (2 x 43 dBm) @ 0.4 – 6.0 GHz

- Limitations are possible due to the used cable type -

Mechanical data

Mating cycles	≥ 100
Retention force of coupling mechanism	> 150N

Environmental data

Temperature range	-55 °C to +125 °C operating temperature
Thermal shock	IEC 61169-1 9.4.4
Vibration	IEC 61169-1 9.3.3 and IEC 60068-2-64
Shock	IEC 61169-1 9.3.14
Degree of protection (mated pair)	IEC 60529, IP68 24h / 1m
RoHS	compliant

Tooling

N/A

Suitable cables

UT 085, RG 405 and similar

Weight

Weight	12.2 g/pce
--------	------------

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
F. Fraunhofer	16.08.17	F. Fraunhofer	12.12.2018	a00	18-s303	S. Huber-Siegl	12.12.2018
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de						Tel. : +49 8684 18-0 Email : info@rosenberger.de	
							Page 2 / 2



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.