



A

6 POS.	6 POS.	7 POS.
DIMA DEL PCB PER PN (PCB LAYOUT FOR PN.S) x-284734-1	DIMA DEL PCB PER PN (PCB LAYOUT FOR PN.S) x-282046-1	DIMA DEL PCB PER PN (PCB LAYOUT FOR PN.S) x-282047-1 and 2293372-7
8 POS.	8 POS.	9 POS.
DIMA DEL PCB PER PN (PCB LAYOUT FOR PN.S) x-284208-1	DIMA DEL PCB PER PN (PCB LAYOUT FOR PN.S) x-284574-1	DIMA DEL PCB PER PN (PCB LAYOUT FOR PN.S) x-282049-1
10 POS.	10 POS.	
DIMA DEL PCB PER PN (PCB LAYOUT FOR PN.S) x-284401-x	DIMA DEL PCB PER PN (PCB LAYOUT FOR PN.S) x-282050-x	
11 POS.	12 POS.	
DIMA DEL PCB PER PN (PCB LAYOUT FOR PN.S) x-282051-x	DIMA DEL PCB PER PN (PCB LAYOUT FOR PN.S) x-282052-x	

CONNECTOR LAYOUT
(3D VIEW FOR REFERENCE TO SHOW THE CONNECTOR
ORIENTATION RESPECT TO PCB CUT OUT DESIGN)



- SUGGESTED SHAPE FOR PCB MATING
SIDE, CAN BE ALSO OBTAINED
BY SCORING PROCESS-

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C.CORDOLA 23JUL1996	TE Connectivity			
DIMENSIONS: mm		CHK G.TURCO 23JUL1996				
		APVD G.TURCO 23JUL1996	NAME MONO-SHAPE, MK1 PCB CONNECTOR 2-12 POS.			
		PRODUCT SPEC	SIZE A2			
		APPLICATION SPEC	CAGE CODE 1			
MATERIAL CONNETTORE NYLON (CONNECTOR NYLON) CONTATTO OTTONE (CONTACT BRASS)		WEIGHT -	DRAWING NO C-282042			
		Customer Drawing	RESTRICTED TO -			
			SCALE NO			
			SHEET 6 OF 8			
			REV 78			

4				3				2				1																											
THIS DRAWING IS UNPUBLISHED.				RELEASED FOR PUBLICATION				LOC				DIST				REVISIONS																							
COPYRIGHT copyright.d8Te-				ALL RIGHTS RESERVED.				-				-				P				LTR				DESCRIPTION				DATE				DWN				APVD			
																				SEE SHEET 1																			
NUMERO DI VIE		CONFIGURAZIONE (VISTA CON USCITA CAVI IN ALTO)		VERSIONE PEZZI IN VASSOIO		REV.		VERSIONE PEZZI SCIOLTI		REV.		POSIZIONE POLARIZ. (INTERVIA)		L (mm)		MARCHIATURA CON BANDA COLORATA																							
NO. OF POS.		(CONFIGURATION) (VIEW WITH CABLE EXIT UP)		ON TRAY PACKAGING VERSION		PART REV.		LOOSE PIECES PACKAGING VERSION		PART REV.		POLARIZ. POSITION (INTERVIA)		L (mm)		STRIP COLOUR																							
2				1-282042-1		U		2-282042-1		U		-		10.8		ARANCIO (ORANGE)																							
2				1-282042-2		U		2-282042-2		U		-		10.8		VERDE (GREEN)																							
2				1-282042-3		U		2-382042-3		U		-		9.9		BLU (BLUE)																							
2				1-282042-4		U		2-282042-4		U		-		10.8		ROSSO (RED)																							
2				1-282042-5		U		2-282042-5		U		-		9.9		NERO (BLACK)																							
2				1-284561-1		V		-		-		-		9.9		VERDE (GREEN)																							
2				1-282042-6		V		-		-		-		9.9		VIOLA (VIOLET)																							
2				1-284561-2		V		-		-		-		9.9		-																							
3				1-282043-2		U		2-282043-2		U		-		14.9		-																							
				1-282043-3		U		2-282043-3		U		-		14.9		NERO (BLACK)																							
3				0-282235-2		U		2-282235-2		U		-		15.8		-																							
				0-282235-3		U		2-282235-3		U		-		15.8		NERO (BLACK)																							
3				1-284546-1		V		-		-		2-3		14.9		BLU (BLUE)																							
4				1-282044-1		V		2-282044-1		V		-		19.9		-																							
				3-282044-1		V		-		-		-		19.9		-																							
5				1-282045-1		U		2-282045-1		U		-		24.9		-																							
5				1-282045-2		U		2-282045-2		U		2-3		24.9		VERDE (GREEN)																							
5				1-282045-3		U		2-382045-3		U		2-3		24.9		BLU (BLUE)																							
5				1-284733-1		U		2-284733-1		U		-		24.9		-																							
5				3-282045-4		I		-		-		1-2		24.9		Orange																							
6				1-282046-1		U		2-282046-1		U		2-3		29.9		-																							
6				1-284734-1		U		2-284734-1		U		2-3		29.9		-																							
7				1-282047-1		U		2-282047-1		U		-		34.9		-																							
8				0-284208-1		U		2-284208-1		U		2-3		39.9		-																							
9				1-282049-1		U		2-282049-1		U		2-3 6-7		44.9		-																							
10				1-282050-1		U		2-282050-1		U		2-3 7-8		49.9		-																							
10				1-284401-1		V		-		-		2-3		49.9		NERO (BLACK)																							
11				1-282051-1		U		2-282051-1		U		2-3 8-9		54.9		-																							
12				1-282052-1		U		2-282052-1		U		2-3 9-10		59.9		-																							

CONNETTORE COMPLETO DI CAVO (TERMINATED CONNECTOR)

LEGENDA (DESCRIPTION)

AMP MONO-SHAPE PCB CONNECTOR

1) PER LE DIMENSIONI DEGLI SCARICHI SUL PCB VEDERE FOGLIO 5 (FOR PCB LAYOUT AND DIMENSIONS SEE SHEET 5)

2) GLI AGGANCI PER DIMA CIRCUITO STAMPATO, SONO SEMPRE RICAVATI SULLA SECONDA E PENULTIMA PARETE DEL BLOCCETTO (INDICATI COME X-Y SUI DETTAGLI DEL DISEGNO) (LOCKING TEETH ARE OBTAINED ON THE SECOND AND THE SECOND-LAST WALL (NAMED "X-Y" ON RELEVANT DWG. DETAILS))

3) MARCHIO DI FABBRICA (LIBERA POSIZIONE) (TRADEMARK) (FREE POSITION)

4) NUMERI DI IDENTIFICAZIONE CAVITA' (CIRCUIT IDENTIFICATION)

5) ADATTO PER SCHEDA CIRCUITO STAMPATO SPESSORE 1.5±0.14 (SUITABLE FOR P.C.B. THK. 1.5±0.14)

6) CODICE NON ANCORA IN PRODUZIONE (PN NOT YET RELEASED FOR PRODUCTION)

12) INCLUDE LA POLARIZZAZIONE DOVE E' ESISTENTE (INCLUDING POLARIZATION KEY, WHEN EXISTING)

15) STATO DI FORNITURA: CONFEZIONAMENTO IN "VASSOI + SCATOLA" (PACKAGING: "ON TRAY PLUS CARTON BOX")

16) CONFEZIONAMENTO IN BOBINA OBSOLETATO (PACKAGING: "ON REEL" OBSOLETE)

17) APPROVAZIONE VDE, FILE No. 3905 (VDE APPROVAL, FILE No. 3905)

18) PROFILO "A" E' VALIDO PER OGNI CONFIGURAZIONE, PROFILO "B" E' AMMESSO SOLO PER I PN IDENTIFICATI IN TABELLA DALLA PRESENTE NOTA (SHAPE "A" VALID FOR EACH CONFIGURATION, SHAPE "B" IS PERMITTED ONLY ON PN WHERE THIS NOTE IS SHOWN ON RELEVANT DRAWING TABLE)

19) OBSOLETE: CIS STREAMLINING PER D.RENAUD/D.SINISI

20) OBSOLETE

21) PA GF, UL-VO GWEPT 750°C NO FLAME, NATURAL PRELIMINARY - NOT YET RELEASED FOR PRODUCTION

2	BLOCCETTO (HOUSING)	NATURALE (NATURAL)	PA 6.6 CARICATO VETRO (POLIAMIDE 6.6 GLASSFIBER FILLED)
1	CONTATTO (CONTACT)	STAGNATO (TIN-PLATED)	OTTONE (BRASS)
ITEM	DENOMINAZIONE (DESCRIPTION)	FINITURA/COLORE (FINISH/COLOUR)	MATERIALE (MATERIAL)

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± 0.3

1 PLC ± 0.3

2 PLC ± 0.3

3 PLC ± 0.3

4 PLC ± 0.3

ANGLES ±2°

MATERIAL: CONNETTORE NYLON (CONNECTOR NYLON), CONTATTO OTTONE (CONTACT BRASS)

FINISH: STAGNATO (TIN PLATED)

DWN: C.CORDOLA 23JUL1996

CHK: G.TURCO 23JUL1996

APVD: G.TURCO 23JUL1996

PRODUCT SPEC: 108-20067

APPLICATION SPEC: 114-20018

WEIGHT: -

Customer Drawing

SCALE: NO

SHEET: 7 OF 8

REV: 78

TE Connectivity

MONO-SHAPE, MK1 PCB CONNECTOR 2-12 POS.

SIZE: A2

CAGE CODE: 1

DRAWING NO: C-282042

RESTRICTED TO: -

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

©

 COPYRIGHT copyright.d8fe-

ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
-	-	P	LTR	DESCRIPTION	DATE	DWN	APVD
				SEE SHEET 1			


21

PA GF, UL-V0 GWEPT 750° C NO FLAME, NATURAL
PRELIMINARY - NOT YET RELEASED FOR PRODUCTION

NO. of POS.	CONFIGURATION (SEE TYP. SECTION ONLY FOR REF.)	ON TRAY PACKAGING VERSION	PART REV.	LOOSE PIECES PACKAGING VERSION	PART REV.	POLARIZ. POSITION (INTERVIA)	"L" (mm)	COLOR CODE
5		2293372-5	I	-	-	1-2	24.9	-
7		2293372-7	I	-	-	-	34.9	-

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm



TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±
1 PLC ±
2 PLC ± 0.3
3 PLC ±
4 PLC ±
ANGLES ±2°

MATERIAL
CONNETTORE NYLON
(CONNECTOR NYLON)
CONTATTO OTTONE
(CONTACT BRASS)

FINISH
STAGNATO
(TIN PLATED)

DWN
C. CORDOLA
23 JUL 1996

CHK
G. TURCO
23 JUL 1996

APVD
G. TURCO
23 JUL 1996

PRODUCT SPEC
108-20067

APPLICATION SPEC
114-20018

WEIGHT
-

Customer Drawing

NAME
MONO-SHAPE, MK I
PCB CONNECTOR 2-12 POS.

SIZE
A2

CAGE CODE
1

DRAWING NO
C-282042

RESTRICTED TO
-

SCALE
NO

SHEET
8

OF
8

REV
Z8

TE Connectivity



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.