SEK 19 male standard connector solder straight

RoHS compliant

General information

Design	IEC 60603-13	
No. of contacts	6,10,14,16,20,24,26,30,34,40,50,60,64	
Contact spacing	2,54 mm x 2,54 mm	
Test voltage Ur.m.s	1 kV	
Working voltage	500 V for pollution degree 1	
Contact resistance	max. 20mOhm	
Insulation resistance	min. 10⁹Ohm	
Working current acc. to IEC 60512-2	See derating diagram	
Temperature range	-55°C ... +125°C	
Termination technology	solder	
Clearance & creepage distance	min. 0,5 mm clearance min. 0,56 creepage	
Insertion and withdrawal forces	6-pole max. 12N for PL1-2 / 18N for PL3	; 30-pole max. 60N for PL1-2 / 90N for PL3
	10-pole max. 20N for PL1-2 / 30N for PL3	; 34-pole max. 68N for PL1-2 / 102N for PL3
	14-pole max. 28N for PL1-2 / 42 for PL3	; 40-pole max. 80N for PL1-2 / 120N for PL3
	16-pole max. 32N for PL1-2 / 48N for PL3	; 50-pole max. 100N for PL1-2 / 150N for PL3
	20-pole max. 40N for PL1-2 / 60N for PL3	; 60-pole max. 120N for PL1-2 / 180N for PL3
	24-pole max. 48N for PL1-2 / 72N for PL3	; 64-pole max. 128N for PL1-2 / 192N for PL3
	26-pole max. 52N for PL1-2 / 78N for PL3	
Mating cycles	S4 surface treatment	Au over PdNi (min. 0,76 µm)
	PL 1 acc. to IEC 60603-13	500 mating cycles 10 days gas test
	PL 2 acc. to IEC 60603-13	250 mating cycles 4 days gas test
	PL 3 acc. to IEC 60603-13	50 mating cycles No gas test
UL file	No	
RoHS - compliant	Yes	
Leadfree	Yes	
Hot plugging	No	

Insulator material

Material	PCT (thermoplastics, glass fiber reinforcement 30%)
Color	Black (RAL 7001) or beige
UL classification	UL94-V0
Material group acc. IEC 60664-1	II (400 < CTI < 600)
NF F 16-101 classification	No

Contact material

Contact material	Copper alloy
Plating termination zone	Sn over Ni
Plating contact sliding side	Au or Au over PdNi (according to performance level)

Derating diagram acc to IEC 60512-2 (Current carrying capacity)

The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals.
The current capacity-curve is valid for continuous, not interrupted current-loaded contacts of connectors when simultaneous power on all contacts is given without exceeding the maximum temperature.
Control and test procedures according to DIN IEC 60512.

1) Temperature rise
2) Derating
3) Derating curve at I max x 0.8(IEC 60512-2)



Soldering instructions

THR (Through Hole Reflow) connectors are designed to be used in a reflow oven. THR connectors can also be used together with SMD (Surface Mount Device) components in a reflow oven. In this process, called as well "Pin in hole intrusive reflow", the connectors are inserted into plated through holes in a comparable way to conventional component mounting. All other components can be assembled on the PCB surface.

The length of the connector contacts should be such that they protrude by no more than 1,5 millimeters after insertion to the PCB. Each contact collects solder on its tip as it penetrates the solder paste in the hole. So if the contact is too long, this solder would no longer be able to reflow back into the plated through hole by capillary action during the soldering process, therefore the quality of the soldered connection would suffer as a result.

Quantity of solder paste

Before the components are assembled, solder paste must be applied to all solder pads (for connecting surface-mount components) and the plated through holes.
To ensure that the plated through holes are completely filled, significantly more solder paste must be applied than traditional solder pads on the PCB.
The following rule of thumb has proved valuable in practice:

Vpaste=2(VH-VP)
in which:
VPaste = Required volume of solder paste
VH= Volume of plated through hole
VP= Volume of the connector termination in the hole

comment: the multiplier "2" compensates for solder paste shrinkage during soldering.
For this purpose, it was assumed that 50% of the paste consists of the actual solder, the other 50% being soldering aids.

Cross section of solder terminations



Packaging material (only for plastic tray)

Material	Polystyrol
Color	Yellow
Standardization	acc. to DIN EN / IEC 61340-5-1 and ANSI / ESD S541-2003

- Safe protection for electronic components against electrostatic charges

All Dimensions in mm Original Size DIN A3	Scale 1:1	Free size tol.		Ref. Sub.	
All rights reserved	Created by STORCK	Inspected by ELLERMANN	Standardisation HOFFMANN	Date 2017-03-01	State Final Release
Department EC PD - DE	Title SEK 19 male standard connector solder straight				Doc-Key / ECM-Nr. 100555060/UGD/001/E 500000116390
HARTING Electronics GmbH D-32339 Espelkamp	Type DS	Number 09191230202		Rev. E	Page 1/1

A3

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

09195105004 09195105014 09195105024 09195106004 09195106014 09195106024 09195107004 09195107014 09195107024 09195145004 09195145014 09195145024 09195146004 09195146014 09195146024 09195147004 09195147014 09195147024 09195165004 09195165014 09195165024 09195166004 09195166014 09195166024 09195167004 09195167014 09195167024 09195205004 09195205014 09195205024 09195206004 09195206014 09195206024 09195207004 09195207014 09195207024 09195265004 09195265014 09195265024 09195266004 09195266014 09195266024 09195267004 09195267014 09195267024 09195345004 09195345014 09195345024 09195346004 09195346014 09195346024 09195347004 09195347014 09195347024 09195405004 09195405014 09195405024 09195406004 09195406014 09195406024 09195407004 09195407014 09195407024 09195505004 09195505014 09195505024 09195506004 09195506014 09195506024 09195507004 09195507014 09195507024 09195605004 09195605014 09195605024 09195606004 09195606014 09195606024 09195607004 09195607014 09195607024 09195645004 09195645014 09195645024 09195646004 09195646014 09195646024 09195647004 09195647014 09195647024 09195065924 09195066914 09195067914 09195106904 09195107914 09195165924 09195166914 09195205904 09195207904 09195265904

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.

Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.