



**OptiMOS™ P3 Small-Signal-Transistor**
**Features**

- P-channel
- Enhancement mode
- Logic level (4.5V rated)
- ESD protected
- Qualified according to AEC Q101
- 100% lead-free; RoHS compliant
- Halogen-free according to IEC61249-2-21


**Product Summary**

|                  |                        |      |            |
|------------------|------------------------|------|------------|
| $V_{DS}$         |                        | -30  | V          |
| $R_{DS(on),max}$ | $V_{GS}=-10\text{ V}$  | 80   | m $\Omega$ |
|                  | $V_{GS}=-4.5\text{ V}$ | 130  |            |
| $I_D$            |                        | -2.0 | A          |

PG-SOT-23



| Type     | Package  | Tape and Reel Information | Marking | Lead Free | Packing |
|----------|----------|---------------------------|---------|-----------|---------|
| BSS308PE | PG-SOT23 | H6327: 3000 pcs/ reel     | YFs     | Yes       | Non dry |

**Maximum ratings, at  $T_j=25\text{ }^\circ\text{C}$ , unless otherwise specified**

| Parameter                           | Symbol            | Conditions   | Value                | Unit              |
|-------------------------------------|-------------------|--|----------------------|-------------------|
| Continuous drain current            | $I_D$             | $T_A=25\text{ }^\circ\text{C}$   | -2.0                 | A                 |
|                                     |                   | $T_A=70\text{ }^\circ\text{C}$   | -1.6                 |                   |
| Pulsed drain current                | $I_{D,pulse}$     | $T_A=25\text{ }^\circ\text{C}$   | -8.0                 |                   |
| Avalanche energy, single pulse      | $E_{AS}$          | $I_D=-2\text{ A}$ , $R_{GS}=25\text{ }\Omega$  | -10.7                | mJ                |
| Reverse diode $dv/dt$               | $dv/dt$           | $I_D=-2\text{ A}$ ,<br>$V_{DS}=-16\text{ V}$ ,<br>$di/dt=-200\text{ A}/\mu\text{s}$ ,<br>$T_{j,max}=150\text{ }^\circ\text{C}$ | 6                    | kV/ $\mu\text{s}$ |
| Gate source voltage                 | $V_{GS}$          |  | $\pm 20$             | V                 |
| Power dissipation <sup>1)</sup>     | $P_{tot}$         | $T_A=25\text{ }^\circ\text{C}$   | 0.5                  | W                 |
| Operating and storage temperature   | $T_j$ , $T_{stg}$ |  | -55 ... 150          | $^\circ\text{C}$  |
| ESD Class                           |                   | JESD22-A114 -HBM   | 2 (2kV to 4kV)       |                   |
| Soldering Temperature               |                   |  | 260 $^\circ\text{C}$ | $^\circ\text{C}$  |
| IEC climatic category; DIN IEC 68-1 |                   |  | 55/150/56            | $^\circ\text{C}$  |

| Parameter | Symbol | Conditions | Values |      |      | Unit |
|-----------|--------|------------|--------|------|------|------|
|           |        |            | min.   | typ. | max. |      |

**Thermal characteristics**

|  |            |                                 |   |   |     |     |
|--|------------|---------------------------------|---|---|-----|-----|
| Thermal resistance, junction - ambient | $R_{thJA}$ | minimal footprint <sup>1)</sup> | - | - | 250 | K/W |
|--|------------|---------------------------------|---|---|-----|-----|

**Electrical characteristics, at  $T_j=25\text{ °C}$ , unless otherwise specified**
**Static characteristics**

|                                  |               |   |      |      |      |           |
|----------------------------------|---------------|---|------|------|------|-----------|
| Drain-source breakdown voltage   | $V_{(BR)DSS}$ | $V_{GS}=0V, I_D=-250\mu A$                  | -30  | -    | -    | V         |
| Gate threshold voltage           | $V_{GS(th)}$  | $V_{DS}=V_{GS}, I_D=-11\mu A$               | -2.0 | -1.5 | -1.0 |           |
| Drain-source leakage current     | $I_{DSS}$     | $V_{DS}=-30V, V_{GS}=0V, T_j=25\text{ °C}$  | -    | -    | -1   | $\mu A$   |
|                                  |               | $V_{DS}=-30V, V_{GS}=0V, T_j=150\text{ °C}$ | -    | -    | -100 |           |
| Gate-source leakage current      | $I_{GSS}$     | $V_{GS}=-20V, V_{DS}=0V$                    | -    | -    | -5   | $\mu A$   |
| Drain-source on-state resistance | $R_{DS(on)}$  | $V_{GS}=-4.5V, I_D=-1.7A$                   | -    | 88   | 130  | $m\Omega$ |
|                                  |               | $V_{GS}=-10V, I_D=-2A$                      | -    | 62   | 80   |           |
| Transconductance                 | $g_{fs}$      | $ V_{DS} >2 I_D R_{DS(on)max}, I_D=-1.6A$   |      | 4.6  | -    | S         |

<sup>1)</sup> Performed on 40mm<sup>2</sup> FR4 PCB. The traces are 1mm wide, 70 $\mu$ m thick and 20mm long; they are present on both sides of the PCB.

| Parameter | Symbol | Conditions | Values |      |      | Unit |
|-----------|--------|------------|--------|------|------|------|
|           |        |            | min.   | typ. | max. |      |

**Dynamic characteristics**

|                              |              |  |   |      |     |    |
|------------------------------|--------------|--|---|------|-----|----|
| Input capacitance            | $C_{iss}$    | $V_{GS}=0\text{ V}, V_{DS}=-15\text{ V},$<br>$f=1\text{ MHz}$                        | - | 376  | 500 | pF |
| Output capacitance           | $C_{oss}$    |  | - | 196  | 261 |    |
| Reverse transfer capacitance | $C_{rss}$    |  | - | 12   | 18  |    |
| Turn-on delay time           | $t_{d(on)}$  | $V_{DD}=-15\text{ V},$<br>$V_{GS}=-10\text{ V},$<br>$I_D=-2\text{ A}, R_G=6\ \Omega$ | - | 5.6  | -   | ns |
| Rise time                    | $t_r$        |  | - | 7.7  | -   |    |
| Turn-off delay time          | $t_{d(off)}$ |  | - | 15.3 | -   |    |
| Fall time                    | $t_f$        |  | - | 2.8  | -   |    |

**Gate Charge Characteristics**


|                       |               |  |   |      |   |    |
|-----------------------|---------------|--|---|------|---|----|
| Gate to source charge | $Q_{gs}$      | $V_{DD}=-15\text{ V}, I_D=-2\text{ A},$<br>$V_{GS}=0\text{ to }-10\text{ V}$ | - | -1.2 | - | nC |
| Gate to drain charge  | $Q_{gd}$      |  | - | -0.6 | - |    |
| Gate charge total     | $Q_g$         |  | - | -5.0 | - |    |
| Gate plateau voltage  | $V_{plateau}$ |  | - | -3.1 | - | V  |

**Reverse Diode**

|                                  |               |   |   |      |      |    |
|----------------------------------|---------------|---|---|------|------|----|
| Diode continuous forward current | $I_S$         | $T_A=25\text{ }^\circ\text{C}$  | - | -    | -0.4 | A  |
| Diode pulse current              | $I_{S,pulse}$ |   | - | -    | -8.4 |    |
| Diode forward voltage            | $V_{SD}$      | $V_{GS}=0\text{ V}, I_F=-2\text{ A},$<br>$T_j=25\text{ }^\circ\text{C}$   | - | -0.8 | -1.1 | V  |
| Reverse recovery time            | $t_{rr}$      | $V_R=10\text{ V}, I_F=-2\text{ A},$<br>$di_F/dt=100\text{ A}/\mu\text{s}$ | - | 14   | -    | ns |
| Reverse recovery charge          | $Q_{rr}$      |   | - | -5.9 | -    |    |


**1 Power dissipation**

$$P_{\text{tot}} = f(T_A)$$



**2 Drain current**


$$I_D = f(T_A); V_{GS} \geq 10 \text{ V}$$



**3 Safe operating area**

$$I_D = f(V_{DS}); T_A = 25 \text{ °C}; D = 0$$


parameter:  $t_p$



**4 Max. transient thermal impedance**

$$Z_{\text{thJA}} = f(t_p)$$


parameter:  $D = t_p / T$



**5 Typ. output characteristics**

$I_D = f(V_{DS}); T_j = 25\text{ °C}$


parameter:  $V_{GS}$



**6 Typ. drain-source on resistance**


$R_{DS(on)} = f(I_D); T_j = 25\text{ °C}$

parameter:  $V_{GS}$




**7 Typ. transfer characteristics**

$I_D = f(V_{GS}); |V_{DS}| > 2|I_D|R_{DS(on)max}$




**8 Typ. forward transconductance**

$g_{fs} = f(I_D); T_j = 25\text{ °C}$



**9 Drain-source on-state resistance**


$R_{DS(on)} = f(T_j); I_D = -2 \text{ A}; V_{GS} = -10 \text{ V}$



**10 Typ. gate threshold voltage**


$V_{GS(th)} = f(T_j); V_{DS} = V_{GS}; I_D = 11 \mu\text{A}$

parameter:  $I_D$



**11 Typ. capacitances**


$C = f(V_{DS}); V_{GS} = 0 \text{ V}; f = 1 \text{ MHz}; T_j = 25^\circ\text{C}$



**12 Forward characteristics of reverse diode**

$I_F = f(V_{SD})$


parameter:  $T_j$



**13 Avalanche characteristics**

$I_{AS}=f(t_{AV}); R_{GS}=25 \Omega$


parameter:  $T_{j(start)}$



**14 Typ. gate charge**


$V_{GS}=f(Q_{gate}); I_D=-2 \text{ A pulsed}$

parameter:  $V_{DD}$



**15 Drain-source breakdown voltage**

$V_{BR(DSS)}=f(T_j); I_D=250 \mu\text{A}$




**16 Gate charge waveforms**




SOT-23


Package Outline:



Footprint:



Packaging:





**Published by**  
**Infineon Technologies AG**  
**81726 Munich, Germany**  
**© 2009 Infineon Technologies AG**  
**All Rights Reserved.**

**Legal Disclaimer**

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

**Information**

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office ([www.infineon.com](http://www.infineon.com)).

**Warnings**

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.