

3.2-3.8kW Single-Phase Metered PDU, 200-240V Outlets (6-C19 & 32-C13) C20/L6-20P Cable 10ft Cord, 0U Vertical

MODEL NUMBER: PDUMV20HV



Description

Tripp Lite single phase Metered PDU / Power Distribution Units offer real-time local reporting of load level in amps via built-in digital display. Enables visual monitoring of PDU load levels to prevent overloads as additional equipment is added. Offers reliable rackmount multi-outlet power distribution from any protected UPS, generator or mains input power source. High quality design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

Features

- 16/20A single phase 200-240V Metered Power Distribution Unit / PDU (Agency derated to 16A continuous)
- Two-digit lighted meter reports combined total output current in amps
- 10ft / 3m detachable input cable with NEMA L6-20P plug
- C20 inlet accepts a variety of 16A international cordsets
- 0U 63.75in / 162cm vertical rackmount format installs using no rack spaces
- 38 total outlets (6 C19, 32 C13)
- Installable cord retention brackets keep vital networking equipment plugged in
- Toolless installation supported in button-mount compatible equipment racks
- Bolt-down installation brackets support installation in other racks and additional surfaces

Highlights

- Metered single phase 16/20A 200-240V 0U 63.75in / 162cm vertical rackmount PDU
- Two-digit meter reports output current in amps
- 10ft / 3m detachable input cable with NEMA L6-20P plug
- C20 inlet accepts a variety of 16A international cordsets
- 38 output receptacles (6 C19, 32 C13) with cord retention brackets
- Toolless button mount and bolt-down bracket installation hardware included

Package Includes

- PDUMV20HV 63.75 inch basic PDU with owner's manual
- Set of 2 bolt-on plug retention brackets and installation hardware
- Set of mounting brackets and installation hardware

Specifications

| OVERVIEW | |
|----------|---------|
| PDU Type | Metered |
| OUTPUT | |



| | |
|--|---|
| Output Capacity Details | 3.3kW (208V input), 3.5kW (220V input), 3.7kW (230V input), 3.8kW (240V input), 3.2kW (200V input); 20A maximum (agency de-rated to 16A continuous) |
| Frequency Compatibility | 50 / 60 Hz |
| Output Receptacles | (32) C13; (6) C19 |
| Output Nominal Voltage | 200-240V nominal, single phase |
| Overload Protection | Outlets are arranged in a single unbreakered load bank |
| Outlet Type | IEC-C13, IEC-C19 |
| Individual Outlet Switching | No |
| INPUT | |
| PDU Input Voltage | 200; 208; 220; 230; 240 |
| Maximum Input Amps | 20 |
| Maximum Input Amps Details | Agency de-rated to 16A continuous |
| Input Connection Type | L6-20P detachable cordset, C20 inlet available |
| PDU Plug Type | NEMA L6-20P; IEC-320 C20 |
| Input Cord Length (ft.) | 10 |
| Input Cord Length (m) | 3.05 |
| Input Phase | Single-Phase |
| USER INTERFACE, ALERTS & CONTROLS | |
| Front Panel LEDs | Includes built-in 2-character LED meter to display whole PDU power consumption |
| Switches | n/a |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 64.5 x 3.5 x 4.75 |
| Shipping Dimensions (hwd / cm) | 163.8 x 8.9 x 12.1 |
| Shipping Weight (lbs.) | 6 |
| Shipping Weight (kg) | 2.8 |
| Unit Dimensions (hwd / in.) | 63.75 x 2.25 x 3.75 |
| Unit Dimensions (hwd / cm) | 162 x 5.7 x 9.5 |
| Unit Weight (lbs.) | 5.2 |
| Unit Weight (kg) | 2.4 |
| Material of Construction | Aluminum |
| Form Factors Supported | 0u vertical installation in equipment racks, plus under-counter and wallmount |
| PDU Form Factor | Vertical (0U) |
| ENVIRONMENTAL | |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|-------------------------------------|---|
| Relative Humidity | 0-95% non-condensing |
| CERTIFICATIONS | |
| Certifications | Tested to UL60950-1 (USA, Canada), NOM (Mexico), CE (IEC 60950) |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.