N-Channel Power MOSFET

700V, 4.5A, 0.9Ω

FEATURES

- Super-Junction technology
- High performance due to small figure-of-merit
- High ruggedness performance
- High commutation performance

APPLICATION

- Power Supply
- Lighting

KEY PERFORMANCE PARAMETERS		
PARAMETER	**VALUE**	**UNIT**
V_{DS}	700	V
$R_{DS(on)}$ (max)	0.9	Ω
Q_g	9.7	nC

Pb-Free RoHS COMPLIANT HALOGEN FREE

ITO-220

TO-251 (IPAK)

TO-252 (DPAK)

Notes: MSL 3 (Moisture Sensitivity Level) for TO-252 (DPAK) per J-STD-020.

ABSOLUTE MAXIMUM RATINGS (T_C = 25°C unless otherwise noted)					
PARAMETER		**SYMBOL**	**IPAK/DPAK**	**ITO-220**	**UNIT**
Drain-Source Voltage		V_{DS}	700		V
Gate-Source Voltage		V_{GS}	±30		V
Continuous Drain Current (Note 1)	T_C = 25°C	I_D	4.5		A
	T_C = 100°C		2.7		
Pulsed Drain Current (Note 2)		I_{DM}	13.5		A
Total Power Dissipation @ T_C = 25°C		P_{DTOT}	50	20	W
Single Pulsed Avalanche Energy (Note 3)		E_{AS}	64		mJ
Single Pulsed Avalanche Current (Note 3)		I_{AS}	1.6		A
Operating Junction and Storage Temperature Range		T_J, T_{STG}	- 55 to +150		°C

THERMAL PERFORMANCE				
PARAMETER	**SYMBOL**	**IPAK/DPAK**	**ITO-220**	**UNIT**
Junction to Case Thermal Resistance	$R_{\Theta JC}$	2.5	6.25	°C/W
Junction to Ambient Thermal Resistance	$R_{\Theta JA}$	62		°C/W

Notes: $R_{\Theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistances. The case thermal reference is defined at the solder mounting surface of the drain pins. $R_{\Theta JA}$ is guaranteed by design while $R_{\Theta CA}$ is determined by the user's board design. $R_{\Theta JA}$ shown below for single device operation on FR-4 PCB in still air.

ELECTRICAL SPECIFICATIONS (T_C = 25°C unless otherwise noted)						
PARAMETER	**CONDITIONS**	**SYMBOL**	**MIN**	**TYP**	**MAX**	**UNIT**
Static (Note 4)						
Drain-Source Breakdown Voltage	V_{GS} = 0V, I_D = 250μA	BV_{DSS}	700	--	--	V
Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 250μA	$V_{GS(TH)}$	2.0	3.1	4.0	V
Gate Body Leakage	V_{GS} = ±30V, V_{DS} = 0V	I_{GSS}	--	--	±100	nA
Zero Gate Voltage Drain Current	V_{DS} = 700V, V_{GS} = 0V	I_{DSS}	--	--	1	μA
Drain-Source On-State Resistance	V_{GS} = 10V, I_D = 1.5A	$R_{DS(on)}$	--	0.83	0.9	Ω
Dynamic (Note 5)						
Total Gate Charge	V_{DS} = 380V, I_D = 2.3A, V_{GS} = 10V	Q_g	--	9.7	--	nC
Gate-Source Charge		Q_{gs}	--	2.9	--	
Gate-Drain Charge		Q_{gd}	--	3.5	--	
Input Capacitance	V_{DS} = 100V, V_{GS} = 0V, f = 1.0MHz	C_{iss}	--	482	--	pF
Output Capacitance		C_{oss}	--	34	--	
Gate Resistance	F = 1MHz, open drain	R_g	--	3.6	--	Ω
Switching (Note 6)						
Turn-On Delay Time	V_{DD} = 380V, R_{GEN} = 40Ω, I_D = 2.3A, V_{GS} = 10V,	$t_{d(on)}$	--	20	--	ns
Turn-On Rise Time		t_r	--	54	--	
Turn-Off Delay Time		$t_{d(off)}$	--	34	--	
Turn-Off Fall Time		t_f	--	48	--	
Source-Drain Diode (Note 4)						
Forward On Voltage	I_S = 4.5A, V_{GS} = 0V	V_{SD}	--	--	1.4	V
Reverse Recovery Time	V_R=200V, I_S = 2.3A dI_F/dt = 100A/μs	t_{rr}	--	176	--	ns
Reverse Recovery Charge		Q_{rr}	--	1.1	--	μC

Notes:

1. Current limited by package
2. Pulse width limited by the maximum junction temperature
3. L = 50mH, I_{AS} = 1.6A, V_{DD} = 50V, R_G = 25Ω, Starting T_J = 25°C
4. Pulse test: PW ≤ 300μs, duty cycle ≤ 2%
5. For DESIGN AID ONLY, not subject to production testing.
6. Switching time is essentially independent of operating temperature.

ORDERING INFORMATION

PART NO.	PACKAGE	PACKING
TSM70N900CI C0G	ITO-220	50pcs / Tube
TSM70N900CH C5G	TO-251 (IPAK)	75pcs / Tube
TSM70N900CP ROG	TO-252 (DPAK)	2,500pcs / 13” Reel

Note:

1. Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
2. Halogen-free according to IEC 61249-2-21 definition

CHARACTERISTICS CURVES

(T_C = 25°C unless otherwise noted)

Output Characteristics

Transfer Characteristics

On-Resistance vs. Drain Current

Gate-Source Voltage vs. Gate Charge

On-Resistance vs. Junction Temperature

Source-Drain Diode Forward Current vs. Voltage

CHARACTERISTICS CURVES

(T_C = 25°C unless otherwise noted)

Capacitance vs. Drain-Source Voltage

BV_{DSS} vs. Junction Temperature

Maximum Safe Operating Area (DPAK/IPAK)

Maximum Safe Operating Area (ITO-220)

ELECTRICAL CHARACTERISTICS CURVES

(T_C = 25°C unless otherwise noted)

PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

ITO-220

MARKING DIAGRAM

G = Halogen Free
Y = Year Code
WW = Week Code (01~52)
F = Factory Code

PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

TO-251

MARKING DIAGRAM

Y = Year Code

M = Month Code for Halogen Free Product

O =Jan	**P** =Feb	**Q** =Mar	**R** =Apr
S =May	**T** =Jun	**U** =Jul	**V** =Aug
W =Sep	**X** =Oct	**Y** =Nov	**Z** =Dec

L = Lot Code (1~9, A~Z)

PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

TO-252

SUGGESTED PAD LAYOUT (Unit: Millimeters)

MARKING DIAGRAM

Y = Year Code
M = Month Code for Halogen Free Product

O =Jan	**P** =Feb	**Q** =Mar	**R** =Apr
S =May	**T** =Jun	**U** =Jul	**V** =Aug
W =Sep	**X** =Oct	**Y** =Nov	**Z** =Dec

L = Lot Code (1~9, A~Z)

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.

Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.