










CPU Cooler *High performance thermal solutions*

Choosing the wrong CPU cooler for a system can lead to serious overheating, resulting in system shutdowns and potential damage to CPUs.

For industrial applications, the following CPU coolers fit the needs of various operating environments, where different levels of cooling are required.


| IEI Special Desktop Core™ CPU Cooler | | | | | |
|--------------------------------------|---|---|---|---|---|
| |  |  |  |  |  |
| Where Used | For spacial models: SPCIE-C2260, PCIE-Q870, PCIE-H810, WSB-H810, KINO-AQ870 | | | | |
| Model Name | CF-1150SA-R10 | CF-1150SB-R11 | CF-1150SC-R20 | CF-1150SE-R10 | CF-1150SF-R10 |
| Description | IEI customized cooler for LGA1150 Intel® CPU, RoHS | | IEI customized cooler for LGA1150 Intel® CPU, 1U chassis compatible, RoHS | IEI customized cooler for LGA1150 Intel® CPU, RoHS | |
| CPU Solution | Intel® Core™ i7/i5 | Intel® Core™ i7/i5 | Intel® Core™ i7/i5 | Intel® Core™ i7/i5 | Intel® Core™ i7/i5 |
| Socket Solution | LGA1150/LGA1151 | LGA1150/LGA1151 | LGA1150/LGA1151 | LGA1150/LGA1151 | LGA1150/LGA1151 |
| Dimensions (mm) | 83 x 83 x 57 | 96 x 82 x 60 | 105 x 80 x 23.7 | 107 x 61 x 60 | 107 x 70 x 35 |
| Material | Al | Al | Cu | Cu | Al |
| Bearing Type | Ball And Sleeve | Two Ball | Two Ball | Two Ball | Two Ball |
| Capability (Watt) | 95W | 65W | 65W | 95W | 54W |
| Fan Speed (RPM) | 4200 | 3500 | 5500 | 4200 | 4500 |
| Noise Level (dBA) | 40 | 41 | 55 | 36 | 39 |
| Life Expectancy (hrs) | 40000 | 50000 | 50000 | 50000 | 50,000 |
| Weight | | 286g | 406g | 812g | 220g |





| Desktop Core™ CPU Cooler | | | | |
|--------------------------|---|---|--|---|
| |  |  |  |  |
| | LGA1355/1356/2011 | | | |
| Model Name | CF-1356A-RS | CF-1356B-RS | CF-2011A-RS | CF-2011B-RS |
| Description | High performance LGA1355/1356/2011 cooler kit | | | |
| CPU Solution | Intel® Xeon® E5-2400 | | Intel® Xeon® processor E5-2600 | |
| Socket Solution | LGA1355/1356 | LGA1355/1356 | LGA2011 | LGA2011 |
| Dimensions (mm) | 89 x 80 x 27 | 89 x 90 x 24 | 89 x 88 x 27.2 | 89 x 88 x 45.1 |
| Material | Copper | | | |
| Bearing Type | Two-ball | Ball and Sleeve | Two-ball | Ball and Sleeve |
| Capability (Watt) | 60W | 95W | 130W | 130W |
| Fan Speed (RPM) | 4500 | 5500 | 5500 | 4500 |
| Noise Level (dBA) | 51 | 42 | 55 | 42 |
| Life Expectancy (hrs) | 50000 | 40000 | 50000 | 40000 |
| Weight | 55g | 50g | 55g | 50g |

CPU Cooler *High performance thermal solutions*





Choosing the wrong CPU cooler for a system can lead to serious overheating, resulting in system shutdowns and potential damage to CPUs.





For industrial applications, the following CPU coolers fit the needs of various operating environments, where different levels of cooling are required.

| Intel® Standard Desktop Core™ CPU Cooler | | | | |
|--|---|---|--|---|
| |  |  |  |  |
| | LGA115X (LGA1150/ LGA1151/ LGA1155/ LGA1156) | | | |
| Model Name | CF-1156A-RS-R11 | CF-1156E-R11 | CF-1156C-RS | CF-1156D-RS |
| Description | High performance LGA1155/LGA1156 cooler kit, 1U chassis compatible | High performance LGA1155/LGA1156 CPU cooler, RoHS | Low power LGA1155/LGA1156 cooler kit, RoHS | |
| CPU Solution | Intel® Core™ i5/i3 | Intel® Xeon®/Core™ i7/i5/i3 | Intel® Core™ i5/i3 | Intel® Core™ i7/i5/i3 |
| Socket Solution | LGA115X (LGA1150/ LGA1151/ LGA1155/ LGA1156) | | | |
| Dimensions (mm) | 89 x 92.6 x 27.4 | 90 x 90 x 64 | 90 x 90 x 33 | 90 x 90 x 33 |
| Material | Cu | Al | Al | Cu+Al |
| Bearing Type | Two-ball | Two-ball | Two-ball | Two-ball |
| Capability (Watt) | 73W | 95W | 45W | 65W |
| Fan Speed (RPM) | 5500 | 5500 | 3000 | 3000 |
| Noise Level (dBA) | 51 | 40.5 | 33.4 | 33.4 |
| Life Expectancy (hrs) | 50000 | 50000 | 50000 | 50000 |
| Weight | 422g | 301g | 192g | 227g |

| Desktop CPU Cooler | | | | |
|-----------------------|---|---|--|---|
| |  |  |  |  |
| | Heat Pipes Inside | | | |
| | LGA775 Cooler | | | Pentium® 4 Cooler |
| Model Name | CF-775A-RS | CF-775B-RS-R11 | CF-520-RS-R11 | CF-478A-RS |
| Description | High performance Two copper pipes LGA 775 CPU cooler, RoHS | High performance 1U LGA 775 CPU cooler, w/ 7010 fan, RoHS | High performance LGA 775 CPU cooler, RoHS | High Performance Copper Socket 478 CPU Cooler, RoHS |
| CPU Solution | Intel® Core™2 Quad | Intel® Core™2 Duo | Intel® Core™2 Duo | Intel® Pentium® 4 |
| Socket Solution | LGA 775 | LGA 775 | LGA 775 | Socket 478 |
| Dimensions (mm) | 92 x 92 x 73 | 80.5 x 81 x 28.2 | 115 x 115 x 67 | 92 x 92 x 67 |
| Material | Cu-Al | Cu | Aluminum Alloy | Cu |
| Bearing Type | Rifle | Two-ball | Two-ball | Rifle |
| Capability (Watt) | 130W | 90W | 115W | 115W |
| Fan Speed (RPM) | 3600 | 4250 | 4500 | 3600 |
| Noise Level (dBA) | 36.6~39.6 | 40 | 47.5~51.5 | 39.6 |
| Life Expectancy (hrs) | 40000 | 50000 | 70000 | 40000 |
| Weight | 492g | 600g | 635g | 390g |

CPU Cooler *High performance thermal solutions*

| | Desktop CPU Cooler | | | CPU cooler |
|-----------------------|---|---|--|---|
| |  |  |  |  |
| | Pentium® 4 Cooler | | Pentium® 3 Cooler | BLOWER |
| Model Name | CF-478B-RS-R11 | CF-514-RS | CF-370A-RS | BF-02-RS |
| Description | High Performance Heat Pipes Socket 478 1U CPU cooler, RoHS | High Performance Skiving Intel® Pentium® 4 CPU cooler, RoHS | High Performance Slim Type Socket 370 CPU cooler, RoHS | Bracket cooling fan, RoHS |
| CPU Solution | Intel® Pentium® 4 | Intel® Pentium® 4 | Intel® Pentium® 3 | Bracket cooling fan |
| Socket Solution | Socket 478 | Socket 478 | Socket 370 | |
| Dimensions (mm) | 89 x 76 x 26 | 83 x 70 x 55 | 50 x 52 x 20 | 112 x 90 x 21 |
| Material | Cu-Al | Aluminum Alloy | Cu-Al | Plastic |
| Bearing Type | Two-ball | Two-ball | Two-ball | One-ball |
| Capability (Watt) | 86W | 86W | 40W | |
| Fan Speed (RPM) | 4800 | 4800 | 5500 | 2800 |
| Noise Level (dBA) | 40 | 42.4 | 32.1 | 28 |
| Life Expectancy (hrs) | 50000 | 50000 | 40000 | 45000 |
| Weight | 25g | 284g | 62g | 107.5g |

| | Mobile Core™ i7 CPU Cooler | | Mobile CPU Cooler | |
|-----------------------|---|---|--|---|
| |  |  |  |  |
| | PGA989 | | Pentium® M Cooler | |
| Model Name | CF-989A-RS-R12 | CF-989B-RS-R11 | CF-479B-RS | CF-518-RS |
| Description | High performance Socket-G (PGA989) smart fan CPU cooler, RoHS | High performance Socket-G (PGA989) CPU cooler, Aluminum, RoHS | High Performance Socket 479, M and P Intel® Pentium® M CPU cooler, RoHS | High Performance Intel® Pentium® M CPU cooler, RoHS |
| CPU Solution | Intel® Core™ i7/i5/i3 | Intel® Core™ i7/i5/i3 | Intel® Pentium® M, Core™2 Duo (Mobile) | Intel® Pentium® M |
| Socket solution | PGA989 | PGA989 | Socket 479 | Socket 479 |
| Dimensions (mm) | 60 x 60 x 27.5 | 60 x 60 x 27.5 | 50 x 50 x 16 | 60 x 60 x 26 |
| Material | Cu | Al | Al | Aluminum Alloy |
| Bearing Type | Two-ball | Two-ball | Two-ball | Two-ball |
| Capability (Watt) | 55W | 50W | 50W | 20W |
| Fan Speed (RPM) | 4800 | 4800 | 5500 | 5000 |
| Noise Level (dBA) | 40 | 40 | 30.1 | 36.1 |
| Life Expectancy (hrs) | 50000 | 50000 | 50000 | 50000 |
| Weight | 255g | 26g | 19g | 116g |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.