





## CPU Cooler *High performance thermal solutions*

Choosing the wrong CPU cooler for a system can lead to serious overheating, resulting in system shutdowns and potential damage to CPUs.

For industrial applications, the following CPU coolers fit the needs of various operating environments, where different levels of cooling are required.




IEI Special Desktop Core™ CPU Cooler					
					
Where Used	For spacial models: SPCIE-C2260, PCIE-Q870, PCIE-H810, WSB-H810, KINO-AQ870				
Model Name	CF-1150SA-R10	CF-1150SB-R11	CF-1150SC-R20	CF-1150SE-R10	CF-1150SF-R10
Description	IEI customized cooler for LGA1150 Intel® CPU, RoHS		IEI customized cooler for LGA1150 Intel® CPU, 1U chassis compatible, RoHS	IEI customized cooler for LGA1150 Intel® CPU, RoHS	
CPU Solution	Intel® Core™ i7/i5	Intel® Core™ i7/i5	Intel® Core™ i7/i5	Intel® Core™ i7/i5	Intel® Core™ i7/i5
Socket Solution	LGA1150/LGA1151	LGA1150/LGA1151	LGA1150/LGA1151	LGA1150/LGA1151	LGA1150/LGA1151
Dimensions (mm)	83 x 83 x 57	96 x 82 x 60	105 x 80 x 23.7	107 x 61 x 60	107 x 70 x 35
Material	Al	Al	Cu	Cu	Al
Bearing Type	Ball And Sleeve	Two Ball	Two Ball	Two Ball	Two Ball
Capability (Watt)	<b>95W</b>	<b>65W</b>	<b>65W</b>	<b>95W</b>	<b>54W</b>
Fan Speed (RPM)	4200	3500	5500	4200	4500
Noise Level (dBA)	40	41	55	36	39
Life Expectancy (hrs)	40000	50000	50000	50000	50,000
Weight		286g	406g	812g	220g





Desktop Core™ CPU Cooler				
				
	LGA1355/1356/2011			
Model Name	CF-1356A-RS	CF-1356B-RS	CF-2011A-RS	CF-2011B-RS
Description	High performance LGA1355/1356/2011 cooler kit			
CPU Solution	Intel® Xeon® E5-2400		Intel® Xeon® processor E5-2600	
Socket Solution	LGA1355/1356	LGA1355/1356	LGA2011	LGA2011
Dimensions (mm)	89 x 80 x 27	89 x 90 x 24	89 x 88 x 27.2	89 x 88 x 45.1
Material	Copper			
Bearing Type	Two-ball	Ball and Sleeve	Two-ball	Ball and Sleeve
Capability (Watt)	<b>60W</b>	<b>95W</b>	<b>130W</b>	<b>130W</b>
Fan Speed (RPM)	4500	5500	5500	4500
Noise Level (dBA)	51	42	55	42
Life Expectancy (hrs)	50000	40000	50000	40000
Weight	55g	50g	55g	50g

## CPU Cooler *High performance thermal solutions*

Choosing the wrong CPU cooler for a system can lead to serious overheating, resulting in system shutdowns and potential damage to CPUs.

For industrial applications, the following CPU coolers fit the needs of various operating environments, where different levels of cooling are required.

Intel® Standard Desktop Core™ CPU Cooler				
				
	LGA115X (LGA1150/ LGA1151/ LGA1155/ LGA1156)			
Model Name	CF-1156A-RS-R11	CF-1156E-R11	CF-1156C-RS	CF-1156D-RS
Description	High performance LGA1155/LGA1156 cooler kit, 1U chassis compatible	High performance LGA1155/LGA1156 CPU cooler, RoHS	Low power LGA1155/LGA1156 cooler kit, RoHS	
CPU Solution	Intel® Core™ i5/i3	Intel® Xeon®/Core™ i7/i5/i3	Intel® Core™ i5/i3	Intel® Core™ i7/i5/i3
Socket Solution	LGA115X (LGA1150/ LGA1151/ LGA1155/ LGA1156)			
Dimensions (mm)	89 x 92.6 x 27.4	90 x 90 x 64	90 x 90 x 33	90 x 90 x 33
Material	Cu	Al	Al	Cu+Al
Bearing Type	Two-ball	Two-ball	Two-ball	Two-ball
Capability (Watt)	<b>73W</b>	<b>95W</b>	<b>45W</b>	<b>65W</b>
Fan Speed (RPM)	5500	5500	3000	3000
Noise Level (dBA)	51	40.5	33.4	33.4
Life Expectancy (hrs)	50000	50000	50000	50000
Weight	422g	301g	192g	227g

Desktop CPU Cooler				
				
	LGA775 Cooler			
Model Name	CF-775A-RS	CF-775B-RS-R11	CF-520-RS-R11	Pentium® 4 Cooler
Description	High performance Two copper pipes LGA 775 CPU cooler, RoHS	High performance 1U LGA 775 CPU cooler, w/ 7010 fan, RoHS	High performance LGA 775 CPU cooler, RoHS	High Performance Copper Socket 478 CPU Cooler, RoHS
CPU Solution	Intel® Core™2 Quad	Intel® Core™2 Duo	Intel® Core™2 Duo	Intel® Pentium® 4
Socket Solution	LGA 775	LGA 775	LGA 775	Socket 478
Dimensions (mm)	92 x 92 x 73	80.5 x 81 x 28.2	115 x 115 x 67	92 x 92 x 67
Material	Cu-Al	Cu	Aluminum Alloy	Cu
Bearing Type	Rifle	Two-ball	Two-ball	Rifle
Capability (Watt)	<b>130W</b>	<b>90W</b>	<b>115W</b>	<b>115W</b>
Fan Speed (RPM)	3600	4250	4500	3600
Noise Level (dBA)	36.6~39.6	40	47.5~51.5	39.6
Life Expectancy (hrs)	40000	50000	70000	40000
Weight	492g	600g	635g	390g

# CPU Cooler *High performance thermal solutions*

	Desktop CPU Cooler			CPU cooler
				
	Pentium® 4 Cooler		Pentium® 3 Cooler	BLOWER
Model Name	CF-478B-RS-R11	CF-514-RS	CF-370A-RS	BF-02-RS
Description	High Performance Heat Pipes Socket 478 1U CPU cooler, RoHS	High Performance Skiving Intel® Pentium® 4 CPU cooler, RoHS	High Performance Slim Type Socket 370 CPU cooler, RoHS	Bracket cooling fan, RoHS
CPU Solution	Intel® Pentium® 4	Intel® Pentium® 4	Intel® Pentium® 3	Bracket cooling fan
Socket Solution	Socket 478	Socket 478	Socket 370	
Dimensions (mm)	89 x 76 x 26	83 x 70 x 55	50 x 52 x 20	112 x 90 x 21
Material	Cu-Al	Aluminum Alloy	Cu-Al	Plastic
Bearing Type	Two-ball	Two-ball	Two-ball	One-ball
Capability (Watt)	<b>86W</b>	<b>86W</b>	<b>40W</b>	
Fan Speed (RPM)	4800	4800	5500	2800
Noise Level (dBA)	40	42.4	32.1	28
Life Expectancy (hrs)	50000	50000	40000	45000
Weight	25g	284g	62g	107.5g

	Mobile Core™ i7 CPU Cooler		Mobile CPU Cooler	
				
	PGA989		Pentium® M Cooler	
Model Name	CF-989A-RS-R12	CF-989B-RS-R11	CF-479B-RS	CF-518-RS
Description	High performance Socket-G (PGA989) smart fan CPU cooler, RoHS	High performance Socket-G (PGA989) CPU cooler, Aluminum, RoHS	High Performance Socket 479, M and P Intel® Pentium® M CPU cooler, RoHS	High Performance Intel® Pentium® M CPU cooler, RoHS
CPU Solution	Intel® Core™ i7/i5/i3	Intel® Core™ i7/i5/i3	Intel® Pentium® M, Core™2 Duo (Mobile)	Intel® Pentium® M
Socket solution	PGA989	PGA989	Socket 479	Socket 479
Dimensions (mm)	60 x 60 x 27.5	60 x 60 x 27.5	50 x 50 x 16	60 x 60 x 26
Material	Cu	Al	Al	Aluminum Alloy
Bearing Type	Two-ball	Two-ball	Two-ball	Two-ball
Capability (Watt)	<b>55W</b>	<b>50W</b>	<b>50W</b>	<b>20W</b>
Fan Speed (RPM)	4800	4800	5500	5000
Noise Level (dBA)	40	40	30.1	36.1
Life Expectancy (hrs)	50000	50000	50000	50000
Weight	255g	26g	19g	116g



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.