
Product SKU: C5776.41.01

Product Description: C5776, Coaxial Cable, RG6/U Type, 18 AWG Solid Copper Clad Steel, 100% FlexfoilÂ® Bonded +95% Aluminum Braid, PVC Jacket - Black - 1000 Ft. Reel

Product Category: Electronics - Coaxial Cable - RG 6/U



Product Construction:

Conductor:	• Copper clad steel per ASTM B-869
Insulation/Core:	• Cellular polyethylene
Shield:	• Aluminum braid • Flexfoil Â® shield
Jacket:	• Premium PVC compound

Product Specification:

No. of Conductors:	• 1
Conductor Size (AWG):	• 18
Jacket Color:	• Black
Insulation Material (in):	• Cellular Polyethylene 0.177
Insulation Material (mm):	• Cellular Polyethylene 4.50
Shield Coverage Nominal Shield DCR:	• 100% FlexfoilÂ® Bonded +95% Aluminum Braid 4.4 Ohm/M
Nominal Outside Diameter (in):	• 0.276
Nominal Outside Diameter (mm):	• 6.78

Nominal Capacitance (pF/ft):	• 16.20
Nominal Capacitance (pF/m):	• 53.15
Velocity of Propagation %:	• 85
Nominal Impedance Ohm:	• 75
Nominal Attenuation MHz/dB per 100 ft:	• 1/0.26 • 10/0.81 • 50/1.46 • 100/2.05 • 200/2.83 • 500/4.53 • 1000/6.59 • 1450/8.10 • 1800/8.80 • 2200/10.10
Standard Packaging:	• 1000' Non-returnable Wood Reels
Standard Package Quantity:	• 1
UPC #:	• 079407740956
Put-up:	• 1000
SCC-14:	• 50079407740955
Cube:	• 1794.8125
Weight Per Unit of Measure:	• .03

Product Information:

Applications:

- CATV
- Drop cable
- FM broadcast
- Local Area Network (LAN)
- MATV
- Suitable for RF signal transmission

Packaging:

- 1000 foot (305 m) Pull-Pac Â® Cartons
- 1000' (305 m) Reels
- 500' (152 m) Spools
- Other put-ups available- consult Customer Service

Technical Specifications

Unit Conversion Factors
Cable Design Equations - Balanced Pair
Insulation and Jacket Properties
Temperature Conversion Chart
Decimal and Unit Conversion Factors
Cable Design Equations - Braid Shield
AWG Conductor Chart
Conduit Capacity Chart
Cable Design Equations - Coaxial Cable
Engineering Prefixes
Coax Connector Cross Reference
Glossary

c UL us LISTED

CAROL BRAND


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.