



features

- Meets IEC60127-4 specifications (7A or less)
- Stable fusing characteristics due to original technology
- Suitable for reflow and flow soldering
- Marking: White body color with black marking
- Products meet EU RoHS requirements

dimensions and construction



| Type | Dimensions inches (mm) | | | |
|---------------------|------------------------|------------------------|------------------------|------------------------|
| | L | W | t | c |
| CCF1F (2410) | .240±.008 (6.1±0.2) | .098±.008 (2.5±0.2) | .098±.008 (2.5±0.2) | .055±.008 (1.4±0.2) |

ordering information

| | | | | | | |
|------------|------------|----------|---|---------------|---------------------------------------|---|
| New Part # | CCF | 1 | F | 1 | T | TE |
| | Type | Style | Fusing Characteristic F: Fast-acting | Rated Current | Termination Surface Material T: Sn | Packaging TE: 4mm pitch plastic embossed BK: Bulk |

applications and ratings

| Part Designation | Current Rating | Voltage Rating | Interrupting Capacity | Fusing Characteristics | | Internal R. (mΩ) Max. | Normal Melting I _t (A; sec.) | Operating Temperature Range |
|------------------|----------------|--------------------------------|--------------------------------------|--------------------------|------------------------------|-----------------------|---|-----------------------------|
| | | | | Rated Current | Fusing Time | | | |
| CCF1F0.4 | 0.4A | UL(c-UL) AC 125V DC 125V | UL(c-UL) AC125V 50A DC125V 50A | UL(c-UL) 100% 200% | 4 hour min. 120 sec. max. | 650 | 0.024 | -55°C to +125°C |
| CCF1F0.5 | 0.5A | | | | | 510 | 0.030 | |
| CCF1F0.63 | 0.63A | | | | | 390 | 0.052 | |
| CCF1F0.8 | 0.8A | | | | | 250 | 0.125 | |
| CCF1F1 | 1A | | | | | 90.4 | 0.156 | |
| CCF1F1.25 | 1.25A | | | | | 75.9 | 0.220 | |
| CCF1F1.6 | 1.6A | | | | | 59.3 | 0.513 | |
| CCF1F2 | 2A | | | | | 42.9 | 0.814 | |
| CCF1F2.5 | 2.5A | | | | | 36.6 | 1.31 | |

For further information on packaging, please refer to Appendix A.

Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.

11/23/14

applications and ratings (continued)

| | Part Designation | Current Rating | Voltage Rating | Interrupting Capacity | Fusing Characteristics | | Internal R. (mΩ) Max. | Normal Melting Pt (A ² , sec.) | Operating Temperature Range |
|----------------|------------------|----------------|--------------------------------|--------------------------------------|--------------------------|------------------------------|-----------------------|---|-----------------------------|
| | | | | | Rated Current | Fusing Time | | | |
| UNDER DEVELOP. | CCF1F3.15 | 3.15A | UL(c-UL) AC 125V DC 125V | UL(c-UL) AC125V 50A DC125V 50A | UL(c-UL) 100% 200% | 4 hour min. 120 sec. max. | 26.0 | 2.37 | -55°C to +125°C |
| | CCF1F4 | 4A | | | | | 20.1 | 3.85 | |
| | CCF1F5 | 5A | | | | | 15.3 | 6.5 | |
| | CCF1F6.3 | 6.3A | | | | | 11.4 | 10.6 | |
| | CCF1F7 | 7A | | | | | 10.6 | 12.8 | |
| | CCF1F8 | 8A | | | | | 9.5 | 17.0 | |
| | CCF1F10 | 10A | 7.5 | 27.7 | | | | | |
| | CCF1F12 | 12A | UL(c-UL) AC 65V DC 65V | UL(c-UL) AC65V 50A DC65V 50A | | | 4.5 | 73.5 | |
| | CCF1F15 | 15A | | | | | 3.5 | 125.5 | |

environmental applications

Derating Curve



Stationary Current: Regard the peak of stationary current waveform as stationary current value when the stationary current is repeated pulse. Normal derating of this product should be 0.7max. as standards.

Deratings by ambient temperatures. When using the products at the temperatures other than normal temperature (25°C ± 5°), temperature adjustment will be required. Please refer the derating coefficient as shown in the figure.

Fusing Characteristics



Performance Characteristics

| Parameter | Requirements Limit | Ref. | Test |
|-------------------------------|---|-------------------|--|
| | | | Test Method |
| Fusing Characteristics | Within specified time. Insulation resistance shall not be less than 0.1MΩ | IEC60127-4 9.2 | Fusing time measured under 2/N (rated current 200%) and 10/N (rated current 1000%) |
| Surface Temperature Rise | Maximum temperature rise 75°C and not fusing (all the rating) | UL248.14 | Surface temperature should be measured by 1.00/N |
| Voltage Drop | Refer to ratings table | IEC60127-4 9.1 | When the fuse-link has carried its rated current for a time sufficient to reach temperature stability |
| Maximum Sustained Dissipation | Refer to ratings table | IEC60127-4 9.5 | At the end of electrify test to 1.25/N the voltage drop across the fuse-link is measured and used for the calculation of the sustained dissipation |
| Bending Test | Shall not exceed the ratings table | IEC60127-4 8.3 | Distance between holding points 90mm, bent by 1mm at rate of 1mm/second |
| Resistance to Soldering Heat | Shall not exceed the ratings table | IEC60127-4 8.7 | 260°C ± 5°C, 10 seconds ± 0.5 seconds. After the solder depth, voltage drop across the fuse-link is measured |
| Load Life | ΔR±10% | ±2% | 70°C ± 2°C, 1000 hours, rated current x 70%, 1.5 hr ON, 0.5 hr OFF cycle |
| Load Life Moisture | ΔR±10% | ±3% | 40°C ± 2°C, 90 - 95% RH, 1000 hours, rated current x 70%, 1.5 hr ON, 0.5 hr OFF cycle |
| Rapid Change of Temperature | ΔR±10% | ±2% | -55°C (30 minutes), +125°C (30 minutes), 100 cycles |

Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.

11/23/14



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.